# \*\*TEKNOS

### according to 1907/2006/EC, Article 31

3608910

Reviewed on: 06/12/2021 Printing date: 06/12/2021

# SECTION 01: Identification of the substance/mixture and of the company undertaking

- 1.1 Product identifier
- Trade name: AC EMAILLACK FM 3021
- Article number / Safety Data Sheet: F30210SDB
- 1.2 Relevant identified uses of the substance or mixture and uses advised against
- Application of the substance / the preparation Coating material
- 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier:
  Teknos AG
  Industriestrasse 7
  LI-9487 Gamprin-Bendern
  T +423 375 94 00
  F +423 375 94 99
- Further information obtainable from:
- Product safety department. e-mail address: li-sdb@teknos.com
- 1.4 Emergency telephone number:
  Swiss Toxicological Information Centre, CH-8032 Zürich Emergency telephone: +41 (0)44 251 51 51 (International)

#### SECTION 02: Hazards identification

- 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02

Flam. Liq. 2 - H225 Highly flammable liquid and vapour.



GHS05

Eye Dam. 1 - H318 Causes serious eye damage.



GHS07

Skin Irrit. 2 - H315 Causes skin irritation. STOT SE 3 - H335-H336 May cause respirato

STOT SE  ${\bf 3}$  - H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

Aquatic Chronic 3 - H412 Harmful to aquatic life with long lasting effects.

- 2.2 Label elements
- Labelling according to Regulation (EC) No 1272/2008
- · Hazard pictograms







GHS02 GHS05

IS05 GHS07

Signal word Danger

- Hazard-determining components of labelling:
   n-butyl acetate / 4-methylpentan-2-one / butan-1-ol / butanol
- Hazard statements

(continued on page 2)



### according to 1907/2006/EC, Article 31

3608910

Reviewed on: 06/12/2021 Printing date: 06/12/2021

#### PRODUCT: AC EMAILLACK FM 3021

(continued of page 1)

H225 Highly flammable liquid and vapour.

H318 Causes serious eye damage.

H335-H336 May cause respiratory irritation. May cause drowsiness or

dizziness.

H315 Causes skin irritation.

H412 Harmful to aquatic life with long lasting effects.

- \* EUH211 Warning! Hazardous respirable droplets may be formed when
- sprayed. Do not breathe spray or mist.
  - · Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233 Keep container tightly closed.

P240 Ground and bond container and receiving equipment.

P302+P352 IF ON SKIN: Wash with plenty of water.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P501 Dispose of contents/container in accordance with local/regional/ national/international regulations.

- · 2.3 Other hazards
- Results of PBT and vPvB assessment
- PBT:

Not applicable.

vPvB:

Not applicable.

### SECTION 03: Composition/information on ingredients

- · 3.2 Chemical characterization: Mixtures
- · Description:

Mixture of substances listed below with nonhazardous additions.

Dangerous components:

	CAS Number		%
*	13463-67-7	titanium dioxide	10,00- 25,00
*		EC number: 236-675-5	
*		Record number 01-2119489379-17	
*		🕸 Carc. 2 - H351	
*	108-65-6	2-methoxy-1-methylethyl acetate	1,00- 5,00
*		EC number: 203-603-9	
*		Record number 01-2119475791-29	
*		substance with a Community workplace	
*		exposure limit.	
*		🏈 Flam. Liq. 3 - H226	
*	123-86-4	n-butyl acetate	10,00- 25,00
*		EC number: 204-658-1	
*		Record number 01-2119485493-29	
*		♦ Flam. Liq. 3 - H226; ♦ STOT SE 3 -	
*		H336	
*	1330-20-7	xylene	1,00- 5,00
*		EC number: 215-535-7	
*		Record number 01-2119488216-32	
*		🏇 Flam. Liq. 3 - H226; ઇ Acute Tox.	
*		4 - H312, Acute Tox. 4 - H332, Skin Irrit. 2	
*		- H315	
*	64742-95-6	Solvent naphtha (petroleum), light arom.	1,00- 5,00
*		EC number: 265-199-0	
*		Record number 01-2119455851-35	
*		Asp. Tox. 1 - H304;  Flam. Liq. 3	
*		- H226; 💠 Acute Tox. 4 - H332, STOT SE 3	
		•	(continued on page 3)

GB

# Page: 3 / 12 MATERIAL SAFETY DATA SHEET



# according to 1907/2006/EC, Article 31

3608910

Reviewed on: 06/12/2021 Printing date: 06/12/2021

		(continued of page 2
	- H335; 🔄 Aquatic Chronic 2 - H411	
21645-51-2	aluminium hydroxide	0,50- 1,00
	EC number: 244-492-7	
	Record number 01-2119529246-39	
	substance with a Community workplace	
	exposure limit.	
95-63-6	1,2,4-trimethylbenzene	1,00- 5,00
	EC number: 202-436-9	
	Record number 01-2119472135-42	
	\delta Flam. Liq. 3 - H226; 🕚 Acute Tox.	
	4 - H332, Skin Irrit. 2 - H315, Eye Irrit. 2	
	- H319, STOT SE 3 - H335; 🧇 Aquatic	
	Chronic 2 - H411	
108-67-8	mesitylene	0,0015- 0,50
-	EC number: 203-604-4	-77
	Record number 01-2119463878-19	
	♦ Flam. Liq. 3 - H226; ♦ STOT SE 3 -	
	H335; 🕸 Aquatic Chronic 2 - H411	
108-88-3	toluene	1,00- 5,00
100-00-3	EC number: 203-625-9	1,00- 5,00
	Record number 01-2119471310-51	
	♦ Flam. Liq. 2 - H225; ♦ Repr. 2 -	
	H361d, STOT RE 2 - H373, Asp. Tox. 1 - H304;  Skin Irrit. 2 - H315, STOT SE 3 - H336	
107-98-2	1-methoxy-2-propanol	1,00- 5,00
	EC number: 203-539-1	
	Record number 01-2119457435-35	
	🊸 Flam. Liq. 3 - H226; 🔱 STOT SE 3 -	
	H336	
78-83-1	butanol	1,00- 5,00
	EC number: 201-148-0	
	Record number 01-2119484609-23	
	< Eye Dam. 1 - H318; 🚸 Flam. Liq. 3	
	- H226; 💠 Skin Irrit. 2 - H315, STOT SE	
	3 - H335-H336	
67-64-1	acetone	5,00- 10,00
	EC number: 200-662-2	, ,
	Record number 01-2119471330-49	
	\delta Flam. Liq. 2 - H225; 🔱 Eye Irrit.	
	2 - H319-EUH066, STOT SE 3 - H336	
71-36-3	butan-1-ol	5,00- 10,00
	EC number: 200-751-6	, , ,
	Record number 01-2119484630-38	
	🧇 Eye Dam. 1 - H318; 🚸 Flam. Liq. 3	
	- H226; 💠 Acute Tox. 4 - H302, Skin	
	Irrit. 2 - H315, STOT SE 3 - H335-H336	
108-10-1	4-methylpentan-2-one	10,00- 25,00
100-10-1	EC number: 203-550-1	10,00- 23,00
	Record number 01-2119473980-30	
	.135574 (1411)351 01 2110-170000 00	(continued on page 4



#### according to 1907/2006/EC, Article 31

3608910

Reviewed on: 06/12/2021 Printing date: 06/12/2021

PRODUCT: AC EMAILLACK FM 3021

(continued of page 3)

🍑 Flam. Liq. 2 - H225; 🔱 Acute Tox.

\* 4 - H332, Eye Irrit. 2 - H319-EUH066, STOT

\* SE 3 - H335

Additional information:

For the wording of the listed risk phrases refer to section 16.

## SECTION 04: First aid measures

- · 4.1 Description of first aid measures
- After inhalation:
  - In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact:
  - Immediately wash with water and soap and rinse thoroughly.
- Immediately rinse with water.
  - · After eye contact:

Rinse opened eye for several minutes under running water. Then consult a doctor.

- · After swallowing:
  - Do not induce vomiting; call for medical help immediately.
- · Information for doctor:
- 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

#### SECTION 05: Firefighting measures

- 5.1 Extinguishing media
- Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· For safety reasons unsuitable extinguishing agents:

Water with full jet

· 5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

- · 5.3 Advice for firefighters
- Protective equipment:

Mouth respiratory protective device.

Do not inhale explosion gases or combustion gases.

Additional information

Cool endangered receptacles with water spray.

Collect contaminated fire fighting water separately. It must not enter the sewage system.

#### SECTION 06: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

• 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Prevent seepage into sewage system, workpits and cellars.

Inform respective authorities in case of seepage into water course or sewage system.

- \* In case of seepage into the ground inform responsible authorities
- In case of gas release or seepage into the ground inform responsible authorities.

Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Use neutralising agent.

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

• 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

(continued on page 5)



#### according to 1907/2006/EC, Article 31

3608910

Reviewed on: 06/12/2021 Printing date: 06/12/2021

> PRODUCT: **AC EMAILLACK FM 3021**

> > (continued of page 4)

See Section 13 for disposal information.

#### SECTION 07: Handling and storage

- · Handling:
- 7.1 Precautions for safe handling
  - Open and handle receptacle with care.

Take note of emission threshold.

Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).

- Information about fire and explosion protection:
  - Keep ignition sources away Do not smoke.
- Protect against electrostatic charges.
- Prevent impact and friction.
  - 7.2 Conditions for safe storage, including any incompatibilities
  - Storage:
  - Requirements to be met by storerooms and receptacles:
    - Store only in the original receptacle.
  - Information about storage in one common storage facility:

Not required.

Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

7.3 Specific end use(s)

No further relevant information available.

#### SECTION 08: Exposure controls/personal protection

· 8.1 Control parameters

• Ingredients with limit values that require monitoring at the workplace:

108-65-6 2-methoxy-1-methylethyl acetate

WEL

Short-term value	548	mg/m3
	100	ppm
Long-term value	274	mg/m3
	50	ppm

Sk

123-86-4 n-butyl acetate

WEL

Short-term value	966	mg/m3
	200	ppm
Long-term value	724	mg/m3
	150	ppm

1330-20-7 xylene

WEL

Short-term value	441	mg/m3
	100	ppm
Long-term value	220	mg/m3
	50	ppm

Sk; BMGV

21645-51-2 aluminium hydroxide

WEL

Long-term value 2 ma/m3 (continued on page 6)

# Page: 6 / 12 MATERIAL SAFETY DATA SHEET



# according to 1907/2006/EC, Article 31

3608910

Reviewed on: 06/12/2021 Printing date: 06/12/2021

				(continued of page
95-63-6		1,2,4-trimethylbenzene		
WEL		l	405	
	Long-term	value	125	mg/m
			25	ррі
100.07.0	ILV			
108-67-8 WEL		mesitylene		
WEL	Long-term	value	125	mg/m
	Long-term	value	25	ppi
	ILV		20	pp.
108-88-3		toluene		
WEL				
	Short-term	value	384	mg/m
			100	ppi
	Long-term	value	191	mg/m
	<b>3</b>		50	ppi
	Sk			
107-98-2		1-methoxy-2-propanol		
WEL		-		
	Short-term	value	560	mg/m
			150	рр
	Long-term	value	375	mg/m
			100	рр
	Sk			
78-83-1		butanol		
WEL				
	Short-term	value	231	mg/m
			75	pp
	Long-term	value	154	mg/m
<b>67.</b> 66. 1			50	pp
67-64-1		acetone		
WEL	Short-term	valuo	3620	
	Siloi t-term	valuc	3620 1500	mg/m ppi
	Long-term	value	1210	mg/n
	Long-term	Tuide	500	pp
71-36-3		butan-1-ol		PP
WEL				
	Short-term	value	154	mg/m
			50	pp
	Sk			• •
108-10-1		4-methylpentan-2-one		
WEL				
	Short-term	value	416	mg/m
			100	pp
	Long-term	value	208	mg/m
			50	pp
المسموان	Sk, BMGV	logical limit velves		
• Ingredie		logical limit values:		
1330-20-	ı	xylene		(continued on page



#### according to 1907/2006/EC, Article 31

3608910

Reviewed on: 06/12/2021 Printing date: 06/12/2021

> PRODUCT: **AC EMAILLACK FM 3021**

> > (continued of page 6)

**BMGV** 

650 mmol/mol creatinine

Medium: urine

Sampling time: post shift Parameter: methyl hippuric acid 4-methylpentan-2-one

108-10-1

**BMGV** 

20 µmol/L Medium: urine

Sampling time: post shift

Parameter: 4-methylpentan-2-one

Additional information:

The lists valid during the making were used as basis.

- 8.2 Exposure controls

  Personal protective equipment:
- General protective and hygienic measures:
  - The usual precautionary measures are to be adhered to when handling chemicals.
- Keep away from foodstuffs, beverages and feed.
  - Immediately remove all soiled and contaminated clothing
- Avoid contact with the skin.

Avoid contact with the eyes and skin.

Do not eat or drink while working.

Be sure to clean skin thoroughly after work and before breaks.

- Respiratory protection: Suitable respiratory protective device recommended.
- Protection of hands: The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation Protective gloves Impervious gloves
- Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

The determined penetration times according to EN 374 part III are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

- Eye protection: Safety glasses Tightly sealed goggles
- Body protection: Protective work clothing

#### SECTION 09: Physical and chemical properties

Q 1 Information on basic physical and chemical properties

9.1 information on basic physical and ch	emicai properties	
Appearance		
Appearance:		
Form:	Liquid	
Colour:	According to product specifica	
Odour:	Characteristic Characteristic	
Odour threshold:	Not determined.	
Change in condition		
Initial boiling point and boiling range:	55 °C	
Flash point:	-19 °C	
Flammability (solid, gas):	Not applicable.	
Ignition temperature:	340 °C	
Decomposition temperature:	Not determined.	
Auto-ignition temperature:	Not determined.	
		(continued on page 8)



#### according to 1907/2006/EC, Article 31

3608910

Reviewed on: 06/12/2021 Printing date: 06/12/2021

PRODUCT:	AC EMAILL	$\Delta CK$	FM 302	1

			(contin	ued of page 7)
Explosive properties:	Not determined.			
Explosion limits:				
Lower:	1 Vol %			
Upper:	9 Vol %			
Vapour pressure:	at 20 °C mbar	8,0000 mbar at	50 °C	55,0000
Density:	1,0000 g/cm3			
Solubility in / Miscibility with				
water:	Not determined.			
Viscosity:				
•	Not determined.			
	at 20 °C			
9.2 Other information	No further relevant in	nformation available.		

### **SECTION 10: Stability and reactivity**

- 10.1 Reactivity
  - No further relevant information available.
- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:
- No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions
- No dangerous reactions known.
- 10.4 Conditions to avoid
- No further relevant information available.
- 10.5 Incompatible materials:
  - No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

#### SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- Acute toxicity
- LD/LC50 values relevant for classification:

#### 13463-67-7 titanium dioxide

Oral, LD50: >20000 mg/kg (rat) Dermal, LD50: >10000 mg/kg (Rabbit) Inhalative, LC50/4h: >6,82 mg/l (rat) Oral, LD50: 8532 mg/kg (rat) Inhalative, LC50/4h: 35,7 mg/l (rat) Oral, LD50: 13100 mg/kg (rat) Dermal, LD50: >5000 mg/kg (Rabbit) Inhalative, LC50/4h: >21 mg/l (rat) Oral, LD50: 4300 mg/kg (rat) Dermal, LD50: 2000 mg/kg (Rabbit) Oral, LD50: >6800 mg/kg (rat) Dermal, LD50: >3400 mg/kg (Rabbit) Inhalative, LC50/4h: >10,2 mg/l (rat) Oral, LD50: >3400 mg/kg (Rabbit) Inhalative, LC50/4h: >10,2 mg/l (rat) Oral, LD50: >3400 mg/kg (Rabbit) Inhalative, LC50/4h: >10,2 mg/l (rat) Oral, LD50: >3400 mg/kg (Rabbit) Inhalative, LC50/4h: >10,2 mg/l (rat) Oral, LD50: >3400 mg/kg (Rabbit) Inhalative, LC50/4h: >10,2 mg/l (rat) Oral, LD50: >3400 mg/kg (Rabbit) Inhalative, LC50/4h: >10,2 mg/l (rat) Oral, LD50: >3400 mg/kg (Rabbit) Inhalative, LC50/4h: >10,2 mg/l (rat) Oral, LD50: >3400 mg/kg (Rabbit) Inhalative, LC50/4h: >10,2 mg/l (rat) Oral, LD50: >3400 mg/kg (Rabbit) Inhalative, LC50/4h: >10,2 mg/l (rat) Oral, LD50: >3400 mg/kg (Rabbit) Inhalative, LC50/4h: >10,2 mg/l (rat) Oral, LD50: >3400 mg/kg (Rabbit) Inhalative, LC50/4h: >10,2 mg/l (rat) Oral, LD50: >3400 mg/kg (Rabbit) Inhalative, LC50/4h: >10,2 mg/l (rat) Oral, LD50: >3400 mg/kg (Rabbit) Inhalative, LC50/4h: >10,2 mg/l (rat) Oral, LD50: >3400 mg/kg (Rabbit) Inhalative, LC50/4h: >10,2 mg/l (rat) Oral, LD50: >3400 mg/kg (Rabbit) Inhalative, LC50/4h: >10,2 mg/l (rat) Oral, LD50: >3400 mg/kg (Rabbit) Inhalative, LC50/4h: >10,2 mg/l (rat) Oral, LD50: >3400 mg/kg (Rabbit) Inhalative, LC50/4h: >10,2 mg/l (rat) Oral, LD50: >3400 mg/kg (Rabbit) Inhalative, LC50/4h: >10,2 mg/l (rat) Oral, LD50: >3400 mg/kg (Rabbit) Inhalative, LC50/4h: >10,2 mg/l (rat) Oral, LD50: >3400 mg/kg (Rabbit) Inhalative, LC50/4h: >10,2 mg/l (rat) Oral, LD50: >3400 mg/kg (Rabbit) Inhalative, LC50/4h: >10,2 mg/l (rat) Oral, LD50: >3400 mg/kg (Rabbit) Inhalative, LC50/4h: >10,2 mg/l (rat) Oral, LD50: >3400 mg/kg (Rabbit) Inhalative, LC50/4h: >10,2 mg/l (rat) Oral, LD50: >3400 mg/kg (rat) Oral, L LD50: 10000 mg/kg (rat) Oral, LD50: 5000 mg/kg (rat) Oral, LD50: >200 mg/kg (rat) Oral, LD50: 5000 mg/kg (rat) Dermal, LD50: 12124 mg/kg (Rabbit) Inhalative, LC50/4h: 5320 mg/l (mouse) Oral, LD50: 5660 mg/kg (rat) Dermal, LD50: 13000 mg/kg (Rabbit) Inhalative, LC50/4h: 6 mg/l (rat) Oral, LD50: 2460 mg/kg (rat) Dermal, LD50: 3400 mg kg (Rabbit) Oral, LD50: 5800 mg/kg (rat) Dermal, LD50: 20000 mg/kg (Rabbit) Oral, LD50: 790 mg/kg (rat) Dermal, LD50: 3400 mg/kg (Rabbit) Inhalative, LC50/4h: 8000 mg/l (rat) Oral, LD50: 2080 mg/kg (rat) Dermal, LD50: 16000 mg/kg (Rabbit) Inhalative, LC50/4h: 8,3-16,6 mg/l (rat)

108-65-6 2-methoxy-1-methylethyl acetate

123-86-4 n-butyl acetate 1330-20-7

64742-95-6

Solvent naphtha (petroleum), light arom. 7631-86-9 silicon dioxide, chemically prepared

95-63-6 1,2,4-trimethylbenzene

50-00-0 formaldehyde 108-88-3 toluene

107-98-2 1-methoxy-2-propanol

78-83-1 butanol

(continued on page 9)



#### according to 1907/2006/EC, Article 31

3608910

Reviewed on: 06/12/2021 Printing date: 06/12/2021

> PRODUCT: **AC EMAILLACK FM 3021**

> > (continued of page 8)

67-64-1 acetone 71-36-3 butan-1-ol

108-10-1 4-methylpentan-2-one

- Primary irritant effect:
- Skin corrosion/irritation
- Irritant to skin and mucous membranes.
  - Serious eye damage/irritation
    - Strong irritant with the danger of severe eye injury.
  - Respiratory or skin sensitisation No sensitising effects known.
  - Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version: Irritant

- 11.2 Information on other hazards
- Endocrine disrupting properties
- None of the ingredients is listed.

#### SECTION 12: Ecological information

- 12.1 Toxicity
- Aquatic toxicity:

No further relevant information available.

12.2 Persistence and degradability

No further relevant information available.

- Behaviour in environmental systems:
- 12.3 Bioaccumulative potential
- No further relevant information available.
- 12.4 Mobility in soil

No further relevant information available.

- Ecotoxical effects:
- Remark:
- Harmful to fish
- Additional ecological information:
- General notes:

Harmful to aquatic organisms

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system. Must not reach sewage water or drainage ditch undiluted or unneutralised.

- Danger to drinking water if even small quantities leak into the ground. 12.5 Results of PBT and vPvB assessment
- PBT:

Not applicable.

vPvB:

Not applicable.

12.6 Other adverse effects

No further relevant information available.

#### SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- European and swiss waste code

0.8

WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS

08 01

wastes from MFSU and removal of paint and varnish

waste paint and varnish containing organic solvents or other hazardous substances

(continued on page 10)



## according to 1907/2006/EC, Article 31

3608910

Reviewed on: 06/12/2021 Printing date: 06/12/2021

PRODUCT: AC EMAILLACK FM 3021

(continued of page 9)

- · Uncleaned packaging:
- · Recommendation:

Disposal must be made according to official regulations.

# **SECTION 14: Transport information**

• 14.1 UN-Number

 ADR
 UN1263

 IMDG
 UN1263

 IATA
 UN1263

• 14.2 UN proper shipping name

ADR 1263 PAINT
IMDG PAINT
IATA PAINT

• 14.3 Transport hazard class(es)

ADR

Class 3 Flammable liquids.

Label



**IMDG** 

Class 3 Flammable liquids.

Label



IATA

Class 3 Flammable liquids.

Label



• 14.4 Packing group

ADR || IMDG || IATA || I

- 14.5 Environmental hazards:
  - Not applicable.
- 14.6 Special precautions for user Warning: Flammable liquids.

Danger code (Kemler): 33

EMS Number: F-E,S-E

- 14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable.
- · Transport/Additional information:

Not applicable.

Excepted quantities (EQ):

(continued on page 11)



#### according to 1907/2006/EC, Article 31

3608910

Reviewed on: 06/12/2021 Printing date: 06/12/2021

PRODUCT: AC EMAILLACK FM 3021

(continued of page 10)

Limited quantities (LQ) Transport category 5L 2

Tunnel restriction code

D/E

IMDG

Limited quantities (LQ)
Excepted quantities (EQ)

5L F2

• UN "Model Regulation": UN 1263 PAINT, 3, II

### **SECTION 15: Regulatory information**

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic
  equipment Annex II
- None of the ingredients is listed.
- REGULATION (EU) 2019/1148
- Annex I RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))
- None of the ingredients is listed.
  - Annex II REPORTABLE EXPLOSIVES PRECURSORS
    - 67-64-1 acetone
  - REGULATION (EC) No 1907/2006 ANNEX XVII
    Conditions of restriction: 3, 40, 48
  - · National regulations:
  - · Technical instructions (air):
  - · Class Share in %

III 17,12 II 3,64 I 0,01

· Waterhazard class:

Water hazard class 2 (Self-assessment): hazardous for water.

15.2 Chemical safety assessment:

A Chemical Safety Assessment has not been carried out.

#### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

EUH066 Repeated exposure may cause skin dryness or cracking.

H225 Highly flammable liquid and vapour. H226 Flammable liquid and vapour.

LI200 Flammable liquid and v

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin. H315 Causes skin irritation.

H318 Causes serious eye damage. H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H351 Suspected of causing cancer.

H361d Suspected of damaging the unborn child.

\* H373 May cause damage to organs through prolonged or repeated exposure.

\* H411 Toxic to aquatic life with long lasting effects.

#### Department issuing MSDS:

Environment protection department.

(continued on page 12)

Page: 12 / 12

#### MATERIAL SAFETY DATA SHEET



### according to 1907/2006/EC, Article 31

3608910

Reviewed on: 06/12/2021 Printing date: 06/12/2021

#### PRODUCT: **AC EMAILLACK FM 3021**

(continued of page 11)

Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement

concerning the International Carriage of Dangerous Goods by Road)

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer

(Regulations Concerning the International Transport of Dangerous Goods by Rail)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

ICAO: International Civil Aviation Organisation
GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative \* Data compared to the previous version altered.