Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2020/878 - Ireland

# **SAFETY DATA SHEET**



ALPOCRYL UV WALZLACK 6385-15 - All variants

#### SECTION 1: Identification of the substance/mixture and of the company/ undertaking

#### 1.1 Product identifier

Product name : ALPOCRYL UV WALZLACK 6385-15 - All variants

**1.2 Relevant identified uses of the substance or mixture and uses advised againstProduct use**: Paint.

#### 1.3 Details of the supplier of the safety data sheet

Teknos Group Oy, Takkatie 3, FI-00370 HELSINKI, FINLAND. Tel. +358 9 506 091. e-mail address of person : Prod-safe@teknos.com responsible for this SDS

#### **National contact**

Teknos Group Oy, Takkatie 3, FI-00370 HELSINKI, FINLAND. Tel. +358 9 506 091.

#### 1.4 Emergency telephone number

#### National advisory body/Poison Centre

Telephone number : National Poisons Information Centre: 01 809 2566

#### **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317 Carc. 1B, H350 Aquatic Chronic 3, H412

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

#### 2.2 Label elements

Hazard pictograms



Signal word	Danger	
Hazard statements	H315 - Causes skin irritation. H317 - May cause an allergic skin reaction. H318 - Causes serious eye damage. H350 - May cause cancer. H412 - Harmful to aquatic life with long lasting effects.	
Precautionary statements		
Prevention	P201 - Obtain special instructions before use. P280 - Wear protective gloves, protective clothing, eye protection, face protecti or hearing protection.	ion,

## **SECTION 2: Hazards identification**

Response	:	P308 + P313 - IF exposed or concerned: Get medical advice or attention. P305 + P351 + P338 + P310 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor.
Storage	1	Not applicable.
Disposal	:	P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.
Hazardous ingredients	:	Contains: Dipropylenglycol diacrylate; Benzophenon and (1-methyl-1,2-ethanediyl)bis [oxy(methyl-2,1-ethanediyl)] diacrylate
Supplemental label elements	:	
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	:	Restricted to professional users.
2.3 Other hazards		
Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII	:	This mixture does not contain any substances that are assessed to be a PBT or a vPvB.
Other hazards which do	:	None known.

#### not result in classification

# **SECTION 3: Composition/information on ingredients**

Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Туре
Dipropylenglycol diacrylate	REACH #: 01-2119484629-21 EC: 260-754-3 CAS: 57472-68-1	≥25 - ≤50	Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317	-	[1]
Ethanol, 2-amino-, reaction products with polyethylene- polypropylene glycol ether with trimethylolpropane (3: 1) acrylate	CAS: 119327-83-2	≥10 - ≤22	Aquatic Chronic 2, H411	-	[1]
Acryllic Hardener	-	≥10 - ≤25	Eye Irrit. 2, H319	-	[1]
Benzophenon	REACH #: 01-2119899704-20 EC: 204-337-6 CAS: 119-61-9 Index: 606-153-00-5	≤5	Carc. 1B, H350 STOT RE 2, H373 Aquatic Chronic 3, H412	-	[1]
hydroxycyclohexyl phenyl ketone	REACH #: 01-2119457404-40 EC: 213-426-9 CAS: 947-19-3	≤5	Aquatic Chronic 3, H412	-	[1]
(1-methyl-1,2-ethanediyl)bis [oxy(methyl-2,1-ethanediyl)] diacrylate	REACH #: 01-2119484613-34 EC: 256-032-2 CAS: 42978-66-5 Index: 607-249-00-X	≤2.9	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 STOT SE 3, H335 Aquatic Chronic 2, H411	STOT SE 3, H335: C ≥ 10%	[1]

# SECTION 3: Composition/information on ingredients See Section 16 for the full text of the H statements declared above.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section. <u>Type</u>

[1] Substance classified with a health or environmental hazard

Occupational exposure limits, if available, are listed in Section 8.

#### **SECTION 4: First aid measures**

4.1 Description of first aid r	
Eye contact	: Get medical attention immediately. Call a poison center or physician. Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician.
Inhalation	: Get medical attention immediately. Call a poison center or physician. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Skin contact	: Get medical attention immediately. Call a poison center or physician. Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	: Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Chemical burns must be treated promptly by a physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.
1.2 Most important symptoi	ms and effects, both acute and delayed
Over-exposure signs/sym	<u>ptoms</u>
Eye contact	: Adverse symptoms may include the following: pain watering redness
Inhalation	: No specific data.
Skin contact	: Adverse symptoms may include the following: pain or irritation redness

blistering may occur

SECTION 4: First aid	measures
Ingestion	: Adverse symptoms may include the following: stomach pains
4.3 Indication of any immedia	ate medical attention and special treatment needed
Notes to physician	<ul> <li>Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.</li> </ul>
Specific treatments	: No specific treatment.
SECTION 5: Firefight	ing measures
5.1 Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
5.2 Special hazards arising fi	rom the substance or mixture
Hazards from the substance or mixture	In a fire or if heated, a pressure increase will occur and the container may burst. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
Hazardous combustion products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide metal oxide/oxides
5.3 Advice for firefighters	
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

#### SECTION 6: Accidental release measures

6.1 Personal precautions, pro	ote	ctive equipment and emergency procedures
For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Do not breathe vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	:	If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
6.2 Environmental precautions	:	Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.
6.3 Methods and material for	СС	ontainment and cleaning up

# Small spill: Stop leak if without risk. Move containers from spill area. Dilute with water and mop<br/>up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry<br/>material and place in an appropriate waste disposal container. Dispose of via a<br/>licensed waste disposal contractor.

SECTION 6: ACCID	ental release measures
Large spill	: Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product.
6.4 Reference to other sections	<ul> <li>See Section 1 for emergency contact information.</li> <li>See Section 8 for information on appropriate personal protective equipment.</li> <li>See Section 13 for additional waste treatment information.</li> </ul>

#### SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

#### 7.1 Precautions for safe handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapour or mist. Do not ingest. Avoid release to the environment. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

#### 7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

7.3 Specific end use(s)	
Recommendations	: Not available.
Industrial sector specific solutions	: Not available.

#### **SECTION 8: Exposure controls/personal protection**

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

#### 8.1 Control parameters

#### **Occupational exposure limits**

Product/ingredient name	Exposure limit values
No exposure limit value known.	
Biological exposure indices	·

Product/ingredient name	Exposure indices
No exposure indices known.	

#### **SECTION 8: Exposure controls/personal protection**

procedures

**Recommended monitoring** : Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

#### **DNELs/DMELs**

Product/ingredient name	Туре	Exposure	Value	Population	Effects
Dipropylenglycol diacrylate	DNEL	Long term Dermal	1.66 mg/	General	Systemic
			kg bw/day	population	
	DNEL	Long term Oral	2.08 mg/	General	Systemic
		Long torm Dormal	kg bw/day	population Workers	Sustamia
	DNEL	Long term Dermal	2.77 mg/ kg bw/day	vvorkers	Systemic
	DNEL	Long term	7.24 mg/m <sup>3</sup>	General	Systemic
	DITE	Inhalation	7.2 T mg/m	population	o yotonno
	DNEL	Long term	24.48 mg/	Workers	Systemic
		Inhalation	m³		
Benzophenon	DNEL	Long term Oral	0.05 mg/	General	Systemic
			kg bw/day	population	
	DNEL	Long term Dermal	0.05 mg/	General	Systemic
	DNEL	Long torm Dormal	kg bw/day	population Workers	Svotomio
	DINEL	Long term Dermal	0.1 mg/kg bw/day	VUIKEIS	Systemic
	DNEL	Long term	0.17 mg/m <sup>3</sup>	General	Systemic
		Inhalation	••••••g,	population	- )
	DNEL	Long term	0.7 mg/m <sup>3</sup>	Workers	Systemic
		Inhalation	_		
hydroxycyclohexyl phenyl ketone	DNEL	Long term Oral	1.5 mg/kg	General	Systemic
			bw/day	population	
	DNEL	Long term Dermal	1.5 mg/kg	General	Systemic
	DNEL	Long term Dermal	bw/day 3 mg/kg	population Workers	Systemic
	DINCL	Long term Derma	bw/day	WUIKEIS	Systemic
	DNEL	Long term	5.22 mg/m <sup>3</sup>	General	Systemic
		Inhalation		population	,
	DNEL	Long term	21.16 mg/	Workers	Systemic
		Inhalation	m³		
(1-methyl-1,2-ethanediyl)bis[oxy	DNEL	Long term Dermal	1.7 mg/kg	Workers	Systemic
(methyl-2,1-ethanediyl)] diacrylate			bw/day		
	DNEL	Long term Inhalation	2.35 mg/m <sup>3</sup>	Workers	Systemic
		Innalation			

#### **PNECs**

No PNECs available

8.2 Exposure controls		
Appropriate engineering controls	:	If user operations generate dust, fumes, gas, vapour or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.
Individual protection measu	res	<u>3</u>
Hygiene measures	:	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

#### **SECTION 8: Exposure controls/personal protection**

Eye/face protection	: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash
	goggles and/or face shield. If inhalation hazards exist, a full-face respirator may be required instead.
Skin protection	
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
	Recommendations : Wear suitable gloves tested to EN374.
	< 1 hour (breakthrough time): Nitrile gloves. thickness > 0.3 mm
	> 8 hours (breakthrough time): 4H / Silver Shield® gloves.
	Wash hands before breaks and immediately after handling the product.
Body protection	<ul> <li>Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.</li> </ul>
Other skin protection	<ul> <li>Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.</li> </ul>
Respiratory protection	: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.
	Filter type: A 2 - P 2
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

#### **SECTION 9: Physical and chemical properties**

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

#### 9.1 Information on basic physical and chemical properties

<u>Appearance</u>	
Physical state	: Liquid.
Colour	: Various
Odour	: Slight
Odour threshold	: Not available.
Melting point/freezing point	: Not available.
Initial boiling point and boiling range	:

Ingredient name		°C	°F	Method
(1-methyl-1,2-ethanediyl)bis[oxy(methyl- 2,1-ethanediyl)] diacrylate		>120	>248	
Flammability	: Not ava	ailable.	•	
Lower and upper explosion limit		Not applicable. Not applicable.		

**Flash point** : Closed cup: >100°C (>212°F) 2

Ingredient name		°C	°F	Method	
Dipropylenglycol diacrylate		240	464	DIN 51794	
Decomposition temperature	: 1	Not available.		L	
рН	: 1	Not applicable.			
Viscosity	: 1	Not available.			
Solubility(ies)	:				
Not available.					
Solubility in water	: 1	Not available.			
Partition coefficient: n-octanol/ water	: 1	Not applicable.			

#### Vapour pressure

	Vapour Pressure at 20°C			Vapour pressure at 50°C		
Ingredient name	mm Hg	kPa	Method	mm Hg	kPa	Method
Dipropylenglycol diacrylate	0.00064	0.000085	OECD 104			
(1-methyl-1,2-ethanediyl)bis[oxy (methyl-2,1-ethanediyl)] diacrylate	0.00003	0.000004	EU A.4			
Relative density	: Not	available.				•
Density	: 1.1	g/cm³				
Vapour density	: Not	available.				
Explosivo proportios	• Not	availahla				

Explosive properties	: Not available.
Oxidising properties	: Not available.
Particle characteristics	
Median particle size	: Not applicable.

\$

SECTION 10: Stability and reactivity				
10.1 Reactivity	: No specific test data related to reactivity available for this product or its ingredients.			
10.2 Chemical stability	: The product is stable.			
10.3 Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.			
10.4 Conditions to avoid	: No specific data.			
10.5 Incompatible materials	: No specific data.			
10.6 Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.			

### **SECTION 11: Toxicological information**

#### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Dipropylenglycol diacrylate Benzophenon	LD50 Oral LD50 Dermal LD50 Oral	Rat Rabbit Rat	4600 mg/kg 3535 mg/kg >10 g/kg	-
(1-methyl-1,2-ethanediyl)bis [oxy(methyl-2,1-ethanediyl)] diacrylate	LD50 Oral	Rat	6200 mg/kg	-

: No previous validation

#### **SECTION 11: Toxicological information**

Conclusion/Summary

: Based on available data, the classification criteria are not met.

#### Acute toxicity estimates

Route	ATE value
Not available.	

#### Irritation/Corrosion

Based as of the same direct to same	Dec. 14	0	0			
Product/ingredient name	Result	Species	Score	Exposure	Observation	
Dipropylenglycol diacrylate	Eyes - Severe irritant	Rabbit	-	100 mg	-	
	Skin - Severe irritant	Rabbit	-	500 mg	-	
(1-methyl-1,2-ethanediyl)bis [oxy(methyl-2,1-ethanediyl)]	Eyes - Severe irritant	Rabbit	-	24 hours 100 uL	-	
diacrylate				u L		
, ,	Skin - Moderate irritant	Rabbit	-	500 mg	-	
Conclusion/Summary	: Causes skin irritation.					
Sensitisation						
Conclusion/Summary	: May cause an allergic skin reaction.					
<u>Mutagenicity</u>						
Conclusion/Summary	: Based on available data, the classification criteria are not met.					
Carcinogenicity						
<b>Conclusion/Summary</b>	: May cause cancer. Risk of cancer depends on duration and level of exposure.					
Reproductive toxicity						
Conclusion/Summary	: Based on available data, the classification criteria are not met.					
Teratogenicity						
Conclusion/Summary	: Based on available data, the classification criteria are not met.					
Specific target organ toxicit	<u>y (single exposure)</u>					

Product/ingredient name	Category	Route of exposure	Target organs
(1-methyl-1,2-ethanediyl)bis[oxy(methyl-2,1-ethanediyl)] diacrylate	Category 3	-	Respiratory tract irritation

#### Specific target organ toxicity (repeated exposure)

Product/ingredient name	Category	Route of exposure	Target organs
Benzophenon	Category 2	-	-

#### Aspiration hazard

Not available.

#### Information on likely routes : Not available.

of exposure

Potential acute health effects

Eye contact	: Causes serious eye damage.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: Causes skin irritation. May cause an allergic skin reaction.
Ingestion	: No known significant effects or critical hazards.

#### Symptoms related to the physical, chemical and toxicological characteristics

Eye contact	: Adverse symptoms may include the following: pain watering redness
Inhalation	: No specific data.

SECTION 11: Toxico	cal information	
Skin contact	dverse symptoms may include the following: ain or irritation edness listering may occur	
Ingestion	dverse symptoms may include the following: tomach pains	
Delayed and immediate effe	well as chronic effects from short and long-term exposure	
<u>Short term exposure</u>		
Potential immediate effects	lot available.	
Potential delayed effects	lot available.	
Long term exposure		
Potential immediate effects	lot available.	
Potential delayed effects	lot available.	
Potential chronic health eff		
Not available.		
Conclusion/Summary	lot available.	
General	Once sensitized, a severe allergic reaction may occur when subsequently o very low levels.	exposed
Carcinogenicity	lay cause cancer. Risk of cancer depends on duration and level of expo	sure.
Mutagenicity	lo known significant effects or critical hazards.	
Reproductive toxicity	lo known significant effects or critical hazards.	

#### 11.2 Information on other hazards

#### **11.2.1 Endocrine disrupting properties**

Not available.

#### **11.2.2 Other information**

Not available.

#### **SECTION 12: Ecological information**

#### 12.1 Toxicity

Product/ingredient name	Result	Species	Exposure	
Benzophenon	Acute LC50 10.89 mg/l Fresh water	Fish - <i>Pimephales promelas</i> - LARVAE	96 hours	
Conclusion/Summary	on/Summary : Harmful to aquatic life with long lasting effects.			

#### 12.2 Persistence and degradability

**Conclusion/Summary** : This product has not been tested for biodegradation.

#### 12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
Dipropylenglycol diacrylate Benzophenon hydroxycyclohexyl phenyl ketone (1-methyl-1,2-ethanediyl)bis [oxy(methyl-2,1-ethanediyl)] diacrylate	0.01 to 0.39 3.18 2.81 2	- 12.02 4 to 12 -	Low Low Low

#### 12.4 Mobility in soil

Date of issue/Date of revision	: 15/03/2024	Date of previous issue	: No previous validation	Version	:1	10/15
ALPOCRYL UV WALZLACK 638	5-15 - All varia	ants		Label No	:5183	8

# **SECTION 12: Ecological information**

Soil/water partition coefficient (Koc)	: Not available.
Mobility	: Not available.

#### 12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

#### 12.6 Endocrine disrupting properties

Not available.

#### 12.7 Other adverse effects

No known significant effects or critical hazards.

#### **SECTION 13: Disposal considerations**

#### **13.1 Waste treatment methods**

#### Product

Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
European waste catalogue (EWC)	: 08.01.11
Packaging	
Methods of disposal	<ul> <li>The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.</li> </ul>
Special precautions	This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

#### **SECTION 14: Transport information**

	ADR/RID	ADN	IMDG	IATA
14.1 UN number or ID number	Not regulated.	9006	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.	-	-
14.3 Transport hazard class(es)	-	9	-	-
14.4 Packing group	-	-	-	-
14.5 Environmental hazards	No.	Yes.	No.	No.

#### **Additional information**

**ADN** 

: The product is only regulated as a dangerous good when transported in tank vessels.

SECTION 14: Transport information				
ΙΑΤΑ	:	The environmentally hazardous substance mark may appear if required by other transportation regulations.		
14.6 Special precautions for user	:	<b>Transport within user's premises:</b> always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.		
14.7 Maritime transport in bulk according to IMO instruments	:	Not relevant/applicable due to nature of the product.		

#### **SECTION 15: Regulatory information**

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture <u>EU Regulation (EC) No. 1907/2006 (REACH)</u>

#### Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

#### Substances of very high concern

None of the components are listed.

# Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Product/ingredient name	%	Designation [Usage]	
ALPOCRYL UV WALZLACK 6385-15	≥90	3	
Benzophenon	≤5	28 28	
Labelling : Restricte	ed to professional	l users.	
Other EU regulations			
Industrial emissions : Not listed (integrated pollution prevention and control) - Air	d		
Industrial emissions : Not listed (integrated pollution prevention and control) - Water	d		
Explosive precursors : Not appl	icable.		
Ozone depleting substances (1005/200	<u>09/EU)</u>		
Not listed.			
Prior Informed Consent (PIC) (649/201 Not listed.	<u>2/EU)</u>		
Persistent Organic Pollutants Not listed.			
Seveso Directive This product is not controlled under the S nternational regulations Chemical Weapon Convention List Sch			
Not listed.			
<u>Iontreal Protocol</u>			
Not listed.			
Stockholm Convention on Persistent O Not listed.	rganic Pollutan	<u>ts</u>	
te of issue/Date of revision : 15/03/20	024 Date of previo	: No previous validation	Version : 1 12/15
POCRYL UV WALZLACK 6385-15 - All v	/ariants		Label No :51838

#### **SECTION 15: Regulatory information**

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

#### **UNECE Aarhus Protocol on POPs and Heavy Metals**

Not listed.

15.2	Chemical	safety
asse	essment	

: This product contains substances for which Chemical Safety Assessments are still required.

#### **SECTION 16: Other information**

✓ Indicates information that has changed from previously issued version.

	5 1 ,
Abbreviations and	: ATE = Acute Toxicity Estimate
acronyms	CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No.
	1272/2008]
	DMEL = Derived Minimal Effect Level
	DNEL = Derived No Effect Level
	EUH statement = CLP-specific Hazard statement
	N/A = Not available
	PBT = Persistent, Bioaccumulative and Toxic
	PNEC = Predicted No Effect Concentration
	RRN = REACH Registration Number
	SGG = Segregation Group
	vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Skin Irrit. 2, H315	Calculation method
Eye Dam. 1, H318	Calculation method
Skin Sens. 1, H317	Calculation method
Carc. 1B, H350	Calculation method
Aquatic Chronic 3, H412	Calculation method

Full text of abbreviated H statements

H315	Causes skin irritation.	
H317	May cause an allergic skin reaction.	
H318	Causes serious eye damage.	
H319	Causes serious eye irritation.	
H335	May cause respiratory irritation.	
H350	May cause cancer.	
H373	May cause damage to organs through prolonged or repeated exposure.	
H411	Toxic to aquatic life with long lasting effects.	
H412	Harmful to aquatic life with long lasting effects.	

#### Full text of classifications [CLP/GHS]

Aquatic Chronic 2	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2
Aquatic Chronic 3	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3
Carc. 1B	CARCINOGENICITY - Category 1B
Eye Dam. 1	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1
Eye Irrit. 2	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2
Skin Sens. 1	SKIN SENSITISATION - Category 1
STOT RE 2	SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 2
STOT SE 3	SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3
Date of issue/ Date of	: 15/03/2024
revision	
Date of previous issue	No previous validation

: 1

ALPOCRYL UV WALZLACK 6385-15

#### Notice to reader

Version

#### **SECTION 16: Other information**

The information in this SDS is based on the present state of our knowledge and on current laws. The product is not to be used for purposes other than those specified under section 1 without first obtaining written handling instructions. It is always the responsibility of the user to take all necessary steps to fulfil the demands set out in the local rules and legislation. The information in this SDS is meant to be a description of the safety requirements for our product. It is not to be considered a guarantee of the product's properties.

Date of issue/Date of revision: 15/03/2024Date of previous issueALPOCRYL UV WALZLACK 6385-15 - All variants

: No previous validation