Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2020/878

# **SAFETY DATA SHEET**



ANTISTAIN AQUA 2901-52 - CLEAN WHITE

### SECTION 1: Identification of the substance/mixture and of the company/ undertaking

#### 1.1 Product identifier Product name

ANTISTAIN AQUA 2901-52 - CLEAN WHITE

**1.2 Relevant identified uses of the substance or mixture and uses advised againstProduct use**: Paint.

### 1.3 Details of the supplier of the safety data sheet

Teknos Group Oy, Takkatie 3, FI-00370 HELSINKI, FINLAND. Tel. +358 9 506 091. e-mail address of person : Prod-safe@teknos.com responsible for this SDS

### **National contact**

Teknos Group Oy, Takkatie 3, FI-00370 HELSINKI, FINLAND. Tel. +358 9 506 091.

### 1.4 Emergency telephone number

National advisory body/Poison Centre
--------------------------------------

Telephone number: In an emergency, call 112

### **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS] Not classified.

The product is not classified as hazardous according to Regulation (EC) 1272/2008 as amended. See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements		
Signal word	:	No signal word.
Hazard statements	:	No known significant effects or critical hazards.
Precautionary statements		
Prevention	1	Not applicable.
Response	1	Not applicable.
Storage	1	Not applicable.
Disposal	1	Not applicable.
Supplemental label elements	:	Contains 1,2-benzisothiazol-3(2H)-one and 2-Methyl-1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction. Safety data sheet available on request. Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist. Contains biocidal products for in-can preservation: BIT and DTBMA and MBIT.
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	:	

### **SECTION 2: Hazards identification**

#### 2.3 Other hazards

Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII Other hazards which do

not result in classification

: This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

: None known.

### **SECTION 3: Composition/information on ingredients**

3.2 Mixtures	: Mixture	I			
Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Туре
utanium dioxide	REACH #: 01-2119489379-17 EC: 236-675-5 CAS: 13463-67-7	≥10 - ≤25	Carc. 2, H351 (inhalation)	-	[1] [*]
2-(2-butoxyethoxy)ethanol	REACH #: 01-2119475104-44 EC: 203-961-6 CAS: 112-34-5 Index: 603-096-00-8	≤3	Eye Irrit. 2, H319	-	[1] [2]
1,2-benzisothiazol-3(2H)- one	EC: 220-120-9 CAS: 2634-33-5 Index: 613-088-00-6	<0.05	Acute Tox. 4, H302 Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Acute 1, H400	ATE [Oral] = 1020 mg/kg Skin Sens. 1, H317: C ≥ 0.05% M [Acute] = 1	[1]
2-Methyl-1,2-benzisothiazol- 3(2H)-one	CAS: 2527-66-4 Index: 613-336-00-3	<0.0015	Acute Tox. 3, H301 Acute Tox. 4, H312 Skin Corr. 1C, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 2, H411 EUH071 See Section 16 for the full text of the H statements declared above.	ATE [Oral] = 175 mg/kg ATE [Dermal] = 1100 mg/kg Skin Sens. 1, H317: C ≥ 0.0015% M [Acute] = 1	[1]

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Туре

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

[\*] The classification as a carcinogen by inhalation applies only to mixtures placed on the market in powder form containing 1% or more of titanium dioxide particles with aerodynamic diameter  $\leq$  10 µm not bound within a matrix.

Occupational exposure limits, if available, are listed in Section 8.

### **SECTION 4: First aid measures**

### 4.1 Description of first aid measures

Eye contact	: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Get medical attention if irritation occurs.
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical attention if symptoms occur.

Date of issue/Date of revision	: 06/01/2025	Date of previous issue	: 05/10/2022	Version : 1.07 2/21
ANTISTAIN AQUA 2901-52	- CLEAN WHITE			Label No :91104

SECTION 4: First aid	
Skin contact	: Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur.
Ingestion	: Wash out mouth with water. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Do not induce vomiting unless directed to do so by medical personnel. Get medical attention if symptoms occur.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training.
4.2 Most important symptor	ns and effects, both acute and delayed
Over-exposure signs/symp	<u>otoms</u>
Eye contact	: No specific data.
Inhalation	: No specific data.
Skin contact	: No specific data.
Ingestion	: No specific data.
4.3 Indication of any immed	iate medical attention and special treatment needed
Notes to physician	<ul> <li>Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.</li> </ul>
Specific treatments	: No specific treatment.
SECTION 5: Firefigh	ting measures
5.1 Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
5.2 Special hazards arising	from the substance or mixture
Hazards from the substance or mixture	: In a fire or if heated, a pressure increase will occur and the container may burst.

Hazardous combustion products       : Decomposition products may include the following material carbon dioxide carbon monoxide metal oxide/oxides
---

5.3 Advice for firefighters		
Special protective actions for fire-fighters	romptly isolate the scene by removing all persons from the vicinity of the intere is a fire. No action shall be taken involving any personal risk or without uitable training.	
Special protective equipment for fire-fighters	ire-fighters should wear appropriate protective equipment and self-contain reathing apparatus (SCBA) with a full face-piece operated in positive pres node. Clothing for fire-fighters (including helmets, protective boots and glo onforming to European standard EN 469 will provide a basic level of protective hemical incidents.	sure oves)

## **SECTION 6: Accidental release measures**

6.1 Personal precautions, protective equipment and emergency procedures				
For non-emergency personnel	: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Put on appropriate personal protective equipment.			
For emergency responders	: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".			

SECTION 6: Accidental release measures			
6.2 Environmental precautions	: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).		
6.3 Methods and materia	for containment and cleaning up		
Small spill	: Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.		
Large spill	: Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Dispose of via a licensed waste disposal contractor. Contain and collect spillage with non-combustible, absorbent material e. g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.		
6.4 Reference to other sections	: See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.		

### SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

#### 7.1 Precautions for safe handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8).
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

### 7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)	
Recommendations	: Not available.
Industrial sector specific solutions	: Not available.

### SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

#### 8.1 Control parameters

#### **Occupational exposure limits**

Product/ingredient	name		Exposure limit	values
(2-butoxyethoxy)ethanol		TWA 8 hours: 10 TWA 8 hours: 67. PEAK 15 minutes:		r shift.
<b>Date of issue/Date of revision</b> ANTISTAIN AQUA 2901-52 - CL	: 06/01/2025 EAN WHITE	Date of previous issue	: 05/10/2022	Version : 1.07 4/21 Label No :91104

2-(2-butoxyethoxy)ethanol	Limit values (Belgium, 12/2023)
	STEL 15 minutes: 15 ppm. TWA 8 hours: 10 ppm. TWA 8 hours: 67.5 mg/m <sup>3</sup> . STEL 15 minutes: 101.2 mg/m <sup>3</sup> .
2-(2-butoxyethoxy)ethanol	Ministry of Labour and Social Policy and the Ministry of Health - Ordinance No 13/2003. (Bulgaria, 4/2024) Limit value 8 hours: 67.5 mg/m <sup>3</sup> . Limit value 15 minutes: 101.2 mg/m <sup>3</sup> . Limit value 15 minutes: 15 ppm. Limit value 8 hours: 10 ppm.
2-(2-butoxyethoxy)ethanol	Ordinance on the protection of workers from exposure to hazardous chemicals at work, exposure limit values (Annex I (Croatia, 12/2023) STELV 15 minutes: 101.2 mg/m <sup>3</sup> . STELV 15 minutes: 15 ppm. ELV 8 hours: 67.5 mg/m <sup>3</sup> . ELV 8 hours: 10 ppm.
2-(2-butoxyethoxy)ethanol	Department of labour inspection (Cyprus, 7/2021) STEL 15 minutes: 15 ppm. STEL 15 minutes: 101.2 mg/m <sup>3</sup> . TWA 8 hours: 10 ppm. TWA 8 hours: 67.5 mg/m <sup>3</sup> .
2-(2-butoxyethoxy)ethanol	Government regulation of Czech Republic PEL/NPK-P (Czech Republic, 12/2023) TWA 8 hours: 67.5 mg/m <sup>3</sup> . TWA 8 hours: 10 ppm. STEL 15 minutes: 101.2 mg/m <sup>3</sup> . STEL 15 minutes: 15 ppm.
2-(2-butoxyethoxy)ethanol	Working Environment Authority (Denmark, 3/2024) TWA 8 hours: 68 mg/m <sup>3</sup> . TWA 8 hours: 10 ppm. STEL 15 minutes: 15 ppm. STEL 15 minutes: 101 mg/m <sup>3</sup> .
2-(2-butoxyethoxy)ethanol	Occupational exposure limits, Regulation No. 293 (Estonia, 4/2024) TWA 8 hours: 10 ppm. TWA 8 hours: 67.5 mg/m <sup>3</sup> .
2-(2-butoxyethoxy)ethanol	<b>EU OEL (Europe, 1/2022)</b> TWA 8 hours: 67.5 mg/m <sup>3</sup> . TWA 8 hours: 10 ppm. STEL 15 minutes: 101.2 mg/m <sup>3</sup> . STEL 15 minutes: 15 ppm.
2-(2-butoxyethoxy)ethanol	Institute of Occupational Health, Ministry of Social Affairs (Finland, 10/2021) TWA 8 hours: 10 ppm. TWA 8 hours: 68 mg/m <sup>3</sup> .
2-(2-butoxyethoxy)ethanol	Ministry of Labor (France, 6/2024) STEL 15 minutes: 101.2 mg/m <sup>3</sup> . Notes: Indicative regulatory limit values (decree of 30-06-2004 modified) STEL 15 minutes: 15 ppm. Notes: Indicative regulatory limit values (decree of 30-06-2004 modified) TWA 8 hours: 67.5 mg/m <sup>3</sup> . Notes: Indicative regulatory limit values (decree of 30-06-2004 modified) TWA 8 hours: 10 ppm. Notes: Indicative regulatory limit values (decree of 30-06-2004 modified)
te of issue/Date of revision : 06/	01/2025 Date of previous issue : 05/10/2022 Version : 1.07 5/21

SECTION 8: Exposure co	ontrols/personal protection
(2-butoxyethoxy)ethanol	TRGS 900 OEL (Germany, 6/2024)TWA 8 hours: 67 mg/m³.PEAK 15 minutes: 100.5 mg/m³.TWA 8 hours: 10 ppm.PEAK 15 minutes: 15 ppm.DFG MAC-values list (Germany, 7/2023) Develop C.TWA 8 hours: 67 mg/m³.PEAK 15 minutes: 100.5 mg/m³ 4 times per shift [Interval: 1 hour].TWA 8 hours: 10 ppm.PEAK 15 minutes: 15 ppm 4 times per shift [Interval: 1 hour].
1,2-benzisothiazol-3(2H)-one	DFG MAC-values list (Germany, 7/2023) Skin sensitiser.
₽-(2-butoxyethoxy)ethanol	Presidential Decree 307/1986: Occupational exposure limit values (Greece, 9/2021) STEL 15 minutes: 101.2 mg/m <sup>3</sup> . STEL 15 minutes: 15 ppm. TWA 8 hours: 67.5 mg/m <sup>3</sup> . TWA 8 hours: 10 ppm.
2-(2-butoxyethoxy)ethanol	<b>5/2020. (II. 6.) ITM Decree (Hungary, 12/2023)</b> TWA 8 hours: 67.5 mg/m <sup>3</sup> . PEAK 15 minutes: 101.2 mg/m <sup>3</sup> . PEAK 15 minutes: 15 ppm. TWA 8 hours: 10 ppm.
₽-(2-butoxyethoxy)ethanol	Ministry of Welfare, List of Exposure Limits (Iceland, 11/2023) STEL 15 minutes: 101.2 mg/m <sup>3</sup> . STEL 15 minutes: 15 ppm. TWA 8 hours: 67.5 mg/m <sup>3</sup> . TWA 8 hours: 10 ppm.
2-(2-butoxyethoxy)ethanol	<ul> <li>NAOSH (Ireland, 4/2024) Notes: EU derived Occupational Exposure Limit Values</li> <li>OELV 8 hours: 10 ppm.</li> <li>OELV 15 minutes: 101.2 mg/m<sup>3</sup>.</li> <li>OELV 8 hours: 67.5 mg/m<sup>3</sup>.</li> <li>OELV 15 minutes: 15 ppm.</li> </ul>
₽-(2-butoxyethoxy)ethanol	Legislative Decree No. 81/2008. Title IX. Protection from chemical agents, carcinogens and mutagens (Italy, 6/2020) Limit value 8 hours: 10 ppm. Limit value 8 hours: 67.5 mg/m <sup>3</sup> . Short Term 15 minutes: 15 ppm. Short Term 15 minutes: 101.2 mg/m <sup>3</sup> .
2-(2-butoxyethoxy)ethanol	Ministers Cabinet Regulations Nr.325 - AER (Latvia, 3/2024) STEL 15 minutes: 101.2 mg/m <sup>3</sup> . TWA 8 hours: 10 ppm. STEL 15 minutes: 15 ppm. TWA 8 hours: 67.5 mg/m <sup>3</sup> .
₽-(2-butoxyethoxy)ethanol	Lithuanian Hygiene Standard HN 23 (Lithuania, 1/2024) TWA 8 hours: 67.5 mg/m <sup>3</sup> . TWA 8 hours: 10 ppm. STEL 15 minutes: 101.2 mg/m <sup>3</sup> . STEL 15 minutes: 15 ppm.
2-(2-butoxyethoxy)ethanol	Grand-Duchy Regulation 2016. Chemical agents. Annex I (Luxembourg, 3/2021) STEL 15 minutes: 15 ppm. STEL 15 minutes: 101.2 mg/m <sup>3</sup> . TWA 8 hours: 10 ppm. TWA 8 hours: 67.5 mg/m <sup>3</sup> .
₽-(2-butoxyethoxy)ethanol	EU OEL (Europe, 1/2022) TWA 8 hours: 67.5 mg/m <sup>3</sup> . TWA 8 hours: 10 ppm. STEL 15 minutes: 101.2 mg/m <sup>3</sup> . STEL 15 minutes: 15 ppm.
Date of issue/Date of revision :	06/01/2025 Date of previous issue : 05/10/2022 Version : 1.07 6/21

(2-butoxyethoxy)ethanol	Ministry of Social Affairs and Employment, Legal limit values (Netherlands, 5/2024) Absorbed through skin. TWA 8 hours: 50 mg/m <sup>3</sup> . STEL 15 minutes: 100 mg/m <sup>3</sup> . TWA 8 hours: 7.4 ppm. STEL 15 minutes: 14.8 ppm.
2-(2-butoxyethoxy)ethanol	<b>FOR-2011-12-06-1358 (Norway, 12/2022)</b> TWA 8 hours: 10 ppm. TWA 8 hours: 68 mg/m <sup>3</sup> .
2-(2-butoxyethoxy)ethanol	Regulation of the Minister of Family, Labor and Social Policy of June 12, 2018 on the maximum permissible concentrations and intensities of factors harmful to health in the work environment (Journal of Laws of 2018, item 1286) (Poland, 8/2023) TWA 8 hours: 67 mg/m <sup>3</sup> . STEL 15 minutes: 100 mg/m <sup>3</sup> .
2-(2-butoxyethoxy)ethanol	<b>Portuguese Institute of Quality (Portugal, 11/2014)</b> TWA 8 hours: 10 ppm. Form: Inhalable fraction and vapor.
2-(2-butoxyethoxy)ethanol	HG 1218/2006, Annex 1, with subsequent modifications and additions (Romania, 3/2024) VLA 8 hours: 67.5 mg/m <sup>3</sup> . Short term 15 minutes: 101.2 mg/m <sup>3</sup> . Short term 15 minutes: 15 ppm. VLA 8 hours: 10 ppm.
2-(2-butoxyethoxy)ethanol	Government regulation SR c. 355/2006 (Slovakia, 7/2024) Inhalation sensitiser. TWA 8 hours: 67.5 mg/m <sup>3</sup> . STEL 15 minutes: 101.2 mg/m <sup>3</sup> . TWA 8 hours: 10 ppm. STEL 15 minutes: 15 ppm.
2-(2-butoxyethoxy)ethanol	Regulation on protection of workers from the risks related to exposure to chemical substances at work (Slovenia, 4/2024) TWA 8 hours: 67.5 mg/m <sup>3</sup> . TWA 8 hours: 10 ppm. KTV 15 minutes: 101.2 mg/m <sup>3</sup> 4 times per shift [time between tw exposure events at this concentration must be at least 60 minutes KTV 15 minutes: 15 ppm 4 times per shift [time between two exposure events at this concentration must be at least 60 minutes
2-(2-butoxyethoxy)ethanol	National institute of occupational safety and health (Spain, 1/2024) TWA 8 hours: 67.5 mg/m <sup>3</sup> . TWA 8 hours: 10 ppm. STEL 15 minutes: 15 ppm. STEL 15 minutes: 101.2 mg/m <sup>3</sup> .
2-(2-butoxyethoxy)ethanol	Work environment authority Regulation 2018:1 (Sweden, 11/2022) TWA 8 hours: 10 ppm. TWA 8 hours: 68 mg/m <sup>3</sup> . STEL 15 minutes: 15 ppm. STEL 15 minutes: 101 mg/m <sup>3</sup> .
2-(2-butoxyethoxy)ethanol	<b>SUVA (Switzerland, 1/2024)</b> TWA 8 hours: 67 mg/m <sup>3</sup> . Form: vapour and aerosols. STEL 15 minutes: 101 mg/m <sup>3</sup> . Form: vapour and aerosols. STEL 15 minutes: 15 ppm. Form: vapour and aerosols. TWA 8 hours: 10 ppm. Form: vapour and aerosols.
2-(2-butoxyethoxy)ethanol	EH40/2005 WELs (United Kingdom (UK), 1/2020) TWA 8 hours: 10 ppm. TWA 8 hours: 67.5 mg/m <sup>3</sup> . STEL 15 minutes: 15 ppm. STEL 15 minutes: 101.2 mg/m <sup>3</sup> .

ANTISTAIN AQUA 2901-52 - CLEAN WHITE

## **SECTION 8: Exposure controls/personal protection**

Product/ingredient	name	Exposure indices
No exposure indices known.		
lo exposure indices known.		
ecommended monitoring		Id be made to monitoring standards, such as the following:
rocedures	assessment of e values and mea atmospheres - ( of exposure to c (Workplace atm for the measure	dard EN 689 (Workplace atmospheres - Guidance for the exposure by inhalation to chemical agents for comparison with limi surement strategy) European Standard EN 14042 (Workplace Guide for the application and use of procedures for the assessmer chemical and biological agents) European Standard EN 482 lospheres - General requirements for the performance of procedur ment of chemical agents) Reference to national guidance nethods for the determination of hazardous substances will also be
DNELs/DMELs		
Product/ingredient name		Result

DNEL - General population - Long term - Inhalation 28 μg/m <sup>3</sup>
Effects: Local
DNEL - Workers - Long term - Inhalation
170 μg/m³ <u>Effects</u> : Local
<b>DNEL - General population - Long term - Oral</b> 6.25 mg/kg bw/day <u>Effects</u> : Systemic
<b>DNEL - Workers - Long term - Inhalation</b> 67.5 mg/m³ <u>Effects</u> : Local
<b>DNEL - Workers - Short term - Inhalation</b> 101.2 mg/m³ <u>Effects</u> : Local
<b>DNEL - General population - Long term - Dermal</b> 0.345 mg/kg bw/day <u>Effects</u> : Systemic
<b>DNEL - Workers - Long term - Dermal</b> 0.966 mg/kg bw/day <u>Effects</u> : Systemic
<b>DNEL - General population - Long term - Inhalation</b> 1.2 mg/m <sup>3</sup> <u>Effects</u> : Systemic
<b>DNEL - Workers - Long term - Inhalation</b> 6.81 mg/m <sup>3</sup> <u>Effects</u> : Systemic

8.2 Exposure controls Appropriate engineering controls	: Good general ventilation should be sufficient to control worker exposure to airborne contaminants.	Э	
Individual protection meas			
Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period Appropriate techniques should be used to remove potentially contaminated clothing Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.		
Eye/face protection	Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.		
Skin protection			
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicate this is necessary.		
	Recommendations : Wear suitable gloves tested to EN374.		
	> 8 hours (breakthrough time): Nitrile gloves. thickness > 0.3 mm		
	Not recommended polyvinyl alcohol (PVA) gloves		
Date of issue/Date of revision	: 06/01/2025 Date of previous issue : 05/10/2022 Version : 1.07 9/21		
ANTISTAIN AQUA 2901-52 -	CLEAN WHITE Label No : 104		

### **SECTION 8: Exposure controls/personal protection**

•	
Body protection	<ul> <li>Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.</li> </ul>
Other skin protection	: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.
	Filter type (spray application): A P
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

### **SECTION 9: Physical and chemical properties**

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

#### 9.1 Information on basic physical and chemical properties

Appearance	
Physical state	: Liquid.
Colour	: White.
Odour	: Slight
Odour threshold	: Not available.
Melting point/freezing point	: Not available.
Initial boiling point and boiling range	:

	Ingredient name	°C	°F	Method	
	water	100	212		
	2-(2-butoxyethoxy)ethanol	225 to 227.6	437 to 441.7		
_					

Flammability	: Not available.
Lower and upper explosion limit	: Lower: Not applicable. Upper: Not applicable.
Flash point	: Closed cup: >100°C (>212°F)

2

t

. . .

.....

### Auto-ignition temperature

Ingredient name	°C	°F	Method
2-(2-butoxyethoxy)ethanol	210	410	DIN 51794

Decomposition temperature	÷	Not available.
рН	:	8 to 9
Viscosity	;	Not available.
Solubility(ies)	:	
Not available.		
Solubility in water	:	Not available.
Partition coefficient: n-octanol/	:	Not applicable.

### water Vapour pressure

	Va	Vapour Pressure at 20°C			Vapour pressure at 50°C			
Ingredient name	mm Hg	kPa	Method	mm Hg	kPa	Method		
water	17.5	2.3						
2-(2-butoxyethoxy)ethanol	0.022	0.0029						
te of issue/Date of revision	: 06/01/2	2025 Date of	f previous issue	: 05/10/2022		Version : 1.07 10/21		
NTISTAIN AQUA 2901-52	- CLEAN WHI	TE			La	abel No : <mark>91</mark> 104		

Relative density	: Not available.	
Density	: 1.2 g/cm <sup>3</sup>	
Vapour density	: Not available.	
Particle characteristics		
Median particle size	: Not applicable.	
0.2 Other information		
9.2.1 Information with regar	d to physical hazard classes	
Explosive properties	: Not available.	
Oxidising properties	: Not available.	
9.2.2 Other safety character	stics	
Not applicable.		

	-	-
10.1 Reactivity	1	No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	:	The product is stable.
10.3 Possibility of hazardous reactions	:	Under normal conditions of storage and use, hazardous reactions will not occur.
10.4 Conditions to avoid	:	No specific data.
10.5 Incompatible materials	:	No specific data.
10.6 Hazardous decomposition products	:	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

### **SECTION 11: Toxicological information**

11.1 Information on hazard classes as defined in	Regulation (EC) No 1272/2008
Acute toxicity	
Product/ingredient name	Result
2-(2-butoxyethoxy)ethanol	Rabbit - Dermal - LD50
	2700 mg/kg
	Rat - Oral - LD50
	4500 mg/kg
	<u>Toxic effects</u> : Behavioral - Tetany Lung, Thorax, or Respiration - Dyspnea Liver - Other changes
1,2-benzisothiazol-3(2H)-one	<b>Rat - Oral - LD50</b> 1020 mg/kg

### **Conclusion/Summary [Product]** : Based on available data, the classification criteria are not met.

#### Acute toxicity estimates

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
<ul> <li>2-butoxyethoxy)ethanol</li> <li>1,2-benzisothiazol-3(2H)-one</li> <li>2-Methyl-1,2-benzisothiazol-3(2H)-one</li> </ul>	4500	2700	N/A	N/A	N/A
	1020	N/A	N/A	N/A	N/A
	175	1100	N/A	N/A	N/A

#### **Skin corrosion/irritation**

Date of issue/Date of revision: 06/01/2025ANTISTAIN AQUA 2901-52 - CLEAN WHITE

: 06/01/2025 Date of previous issue

:05/10/2022

SECTION 11: Toxicological	information		
Product/ingredient name	Resu	lt	
titanium dioxide		an - Skin - Mild irritant	
	Durat	ion of treatment/exposure int/concentration applied:	
1,2-benzisothiazol-3(2H)-one	Hum	an - Skin - Mild irritant	
	Durat	ion of treatment/exposure int/concentration applied:	
Conclusion/Summary [Product] :	Based on available	data, the classification crit	teria are not met.
Serious eye damage/eye irritation			
Product/ingredient name	Resu	lt	
2-(2-butoxyethoxy)ethanol	Rabb	it - Eyes - Moderate irrita	ant
	Durat	ion of treatment/exposure int/concentration applied:	: 24 hours
		it - Eyes - Severe irritant int/concentration applied:	
Conclusion/Summary [Product] :	Based on available	data, the classification crit	teria are not met.
Respiratory corrosion/irritation			
Not available.			
Conclusion/Summary [Product] :	Based on available	data, the classification crit	teria are not met.
Respiratory or skin sensitization Not available.			
Skin			
Conclusion/Summary [Product] :	May produce an all	ergic reaction.	
Respiratory			
Conclusion/Summary [Product] :	Based on available	data, the classification crit	teria are not met.
Germ cell mutagenicity			
Not available.			
Conclusion/Summary [Product] :	Based on available	data, the classification crit	teria are not met.
<u>Carcinogenicity</u>			
It has been observed that the carcinoge	nic hazard of this pr	oduct arises when respiral	ble dust is inhaled in quantities
leading to significant impairment of par			· ·
Not available.		-	
Conclusion/Summary [Product] :	Based on available	data, the classification crit	teria are not met.
Reproductive toxicity			
Not available.			
Conclusion/Summary [Product] :	Based on available	data, the classification crit	teria are not met.
Specific target organ toxicity (single Not available.	exposure)		
Date of issue/Date of revision : 06/01	/2025 Date of previou	s issue : 05/10/2022	Version : 1.07 12/21
ANTISTAIN AQUA 2901-52 - CLEAN WH			Label No : 91104

#### Specific target organ toxicity (repeated exposure) Not available.

**Aspiration hazard** Not available. Information on likely routes of exposure Not available. Potential acute health effects Eye contact : No known significant effects or critical hazards. Inhalation : No known significant effects or critical hazards. **Skin contact** : No known significant effects or critical hazards. Ingestion : No known significant effects or critical hazards. Symptoms related to the physical, chemical and toxicological characteristics Eye contact : No specific data. Inhalation : No specific data. **Skin contact** : No specific data. Ingestion : No specific data. Delayed and immediate effects as well as chronic effects from short and long-term exposure Short term exposure **Potential immediate** : Not available. effects **Potential delayed effects** : Not available. Long term exposure **Potential immediate** : Not available. effects **Potential delayed effects** : Not available. **Potential chronic health effects** Not available. **Conclusion/Summary** [Product] : Based on available data, the classification criteria are not met. General : No known significant effects or critical hazards. Carcinogenicity : No known significant effects or critical hazards. **Mutagenicity** : No known significant effects or critical hazards. **Reproductive toxicity** : No known significant effects or critical hazards. 11.2 Information on other hazards 11.2.1 Endocrine disrupting properties Not available. : The product does not meet the criteria to be considered as having endocrine Conclusion/Summary [Product]

### 11.2.2 Other information

Not available.

### **SECTION 12: Ecological information**

#### 12.1 Toxicity

**Product/ingredient name** 

Result

No. 1907/2006 or Regulation (EC) No 1272/2008.

disrupting properties according to the criteria set out in either Regulation (EC)

tanium dioxide	Acute - LC50 - Marine water
	Fish - Mummichog - <i>Fundulus heteroclitus</i> >1000000 µg/l [96 hours]
	Effect: Mortality
	Acute - LC50 - Fresh water
	Crustaceans - Water flea - <i>Ceriodaphnia dubia</i> - Neonate
	<u>Age</u> : <24 hours 3 mg/l [48 hours]
	Effect: Mortality
-(2-butoxyethoxy)ethanol	Acute - LC50 - Fresh water
	Fish - Bluegill - Lepomis macrochirus
	<u>Size</u> : 33 to 75 mm 1300000 μg/l [96 hours]
	Effect: Mortality
,2-benzisothiazol-3(2H)-one	Acute - LC50 - Fresh water
	OECD [Fish, Acute Toxicity Test] Fish - Trout - <i>Onorhynchus Mykiss</i>
	1.9 mg/l [96 hours]
	Acute - EC50
	OECD 202 [Daphnia sp. Acute Immobilization Test and
	Reproduction Test] Daphnia - Daphnia - <i>Daphnia Magna</i>
	3.7 mg/l [48 hours]
	Acute - EC50 - Marine water
	OECD 201 [Alga, Growth Inhibition Test]
	Algae - Algae - <i>Skeletonema Costatum</i> 0.36 mg/l [72 hours]
	Acute - NOEC - Marine water
	OECD 201 [Alga, Growth Inhibition Test] Algae - Algae - <i>Skeletonema Costatum</i>
	0.15 mg/l [72 hours]
2-Methyl-1,2-benzisothiazol-3(2H)-one	Acute - EC50 - Fresh water
	US EPA Daphnia - Water flea - <i>Daphnia magna</i>
	Age: <24 hours
	0.92 ppm [48 hours]
	Effect: Intoxication
	<b>Acute - EC50 - Fresh water</b> US EPA
	Algae - Green algae - <i>Pseudokirchneriella subcapitata</i>
	0.22 ppm [96 hours]
	Effect: Population
	<b>Acute - LC50 - Fresh water</b> US EPA
	Fish - Rainbow trout, donaldson trout - Oncorhynchus myk
	Juvenile (Fledgling, Hatchling, Weanling)
	0.24 ppm [96 hours] <u>Effect</u> : Mortality
	Chronic - NOEC
	US EPA Fish - Fathead minnow - <i>Pimephales promelas</i>

Conclusion/Summary [Product] : Not available.

### **SECTION 12: Ecological information**

### 12.2 Persistence and degradability

### **Product/ingredient name**

1,2-benzisothiazol-3(2H)-one

Result EU 24% [28 days]

### Conclusion/Summary [Product] : Not available.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
7,2-benzisothiazol-3(2H)-one	-	-	Inherent
2.3 Bioaccumulative potentia	al	•	•
Product/ingredient name	LogPow	BCF	Potential
2-(2-butoxyethoxy)ethanol 1,2-benzisothiazol-3(2H)-one	1 -	- 3.2	Low Low

### 12.4 Mobility in soil

### Soil/water partition coefficient

Product/ingredient name	logKoc	Кос
<ul> <li>2-(2-butoxyethoxy)ethanol</li> <li>1,2-benzisothiazol-3(2H)-one</li> <li>2-Methyl-1,2-benzisothiazol-3(2H)-one</li> </ul>	1.56 1.86 1.72	36.5981 73.142 52.5063

### Results of PMT and vPvM assessment

Product/ingredient name	PMT	Р	М	Т	vPvM	vP	vM
1,2-benzisothiazol-3(2H)-one 2-Methyl-1,2-benzisothiazol-		No No No No	No No No No	No No No No	No No No No	No No No No	No No No No
3(2H)-one Mobility	: Not ava	ailable.					

Mobility

**Conclusion/Summary** 

: The product does not meet the criteria to be considered as a PMT or vPvM.

### 12.5 Results of PBT and vPvB assessment Regulation (EC) No. 1907/2006 [REACH]

Product/ingredient name	PBT	Р	В	т	vPvB	vP	vB
Manium dioxide 2-(2-butoxyethoxy)ethanol 1,2-benzisothiazol-3(2H)-one 2-Methyl-1,2-benzisothiazol- 3(2H)-one	No No No No	No No No	No No No	No No No	No No No No	No No No No	No No No No

#### Regulation (EC) No. 1272/2008 [CLP]

Product/ingredient name	PBT	Р	В	т	vPvB	vP	vB	
Manium dioxide 2-(2-butoxyethoxy)ethanol 1,2-benzisothiazol-3(2H)-one 2-Methyl-1,2-benzisothiazol- 3(2H)-one		No No No	No No No No	No No No	No No No No	No No No No	No No No No	

**Conclusion/Summary Regulation (EC) No. 1272/2008** [CLP]

: The product does not meet the criteria to be considered as a PBT or vPvB.

#### 12.6 Endocrine disrupting properties

Not available.

### **SECTION 12: Ecological information**

Conclusion/Summary [Product] : The prodist disruption

: The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

#### 12.7 Other adverse effects

No known significant effects or critical hazards.

### **SECTION 13: Disposal considerations**

13.1 Waste treatment methods	
Product	
Methods of disposal :	The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
European waste : catalogue (EWC)	080112, 200128
Packaging	
Methods of disposal :	The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.
Special precautions :	This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

### **SECTION 14: Transport information**

	ADR/RID	ADN	IMDG	ΙΑΤΑ
14.1 UN number or ID number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-	-
14.3 Transport hazard class(es)	-	-	-	-
14.4 Packing group	-	-	-	-
14.5 Environmental hazards	No.	No.	No.	No.

14.6 Special precautions for user

: **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Maritime transport in bulk according to IMO instruments : Not relevant/applicable due to nature of the product.

### **SECTION 15: Regulatory information**

# 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture <u>EU Regulation (EC) No. 1907/2006 (REACH)</u>

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

## Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

_	%	Designation [Usage]	
2-(2-butoxyethoxy)ethanol	≤3	55 [Consumer paint]	
Labelling :			
ther EU regulations			
Industrial emissions : Not listed (integrated pollution prevention and control) - Air	1		
Industrial emissions : Not listed (integrated pollution prevention and control) - Water	ł		
Explosive precursors : Not appli	cable.		
Ozone depleting substances (EU 2024) Not listed.	<u>/590)</u>		
Prior Informed Consent (PIC) (649/2012 Not listed.	<u>2/EU)</u>		
Persistent Organic Pollutants Not listed.			
Seveso Directive			
This product is not controlled under the S	eveso Direc	tive.	
	eveso Direc	tive.	
This product is not controlled under the S lational regulations Austria		tive.	
This product is not controlled under the S ational regulations		tive.	
This product is not controlled under the S lational regulations Austria Limitation of the use of : Permitted organic solvents Belgium	d.	tive.	
This product is not controlled under the S lational regulations Austria Limitation of the use of : Permitted organic solvents Belgium	d.	tive.	
This product is not controlled under the S ational regulations Austria Limitation of the use of : Permitted organic solvents	d.	tive.	Status
This product is not controlled under the S lational regulations Austria Limitation of the use of : Permitted organic solvents Belgium Book VI carcinogenic agents annex VI.	d.	tive.	Status Listed Listed
This product is not controlled under the S ational regulations Austria Limitation of the use of : Permitted organic solvents Belgium Book VI carcinogenic agents annex VI. Ingredient name Silice Styrène	d.	tive.	Listed
This product is not controlled under the S ational regulations Austria Limitation of the use of : Permitted organic solvents Belgium Book VI carcinogenic agents annex VI. Ingredient name	d.	tive.	Listed
This product is not controlled under the S ational regulations Austria Limitation of the use of : Permitted organic solvents Belgium Book VI carcinogenic agents annex VI. Ingredient name Stirce Styrène Czech Republic	d.	tive.	Listed
This product is not controlled under the S ational regulations Austria Limitation of the use of : Permitted organic solvents Belgium Book VI carcinogenic agents annex VI. Ingredient name Stice Styrène Czech Republic Storage code : IV Denmark	d.	tive.	Listed
This product is not controlled under the S ational regulations Austria Limitation of the use of : Permitted organic solvents Belgium Book VI carcinogenic agents annex VI. Ingredient name Silice Styrène Czech Republic Storage code : IV Denmark Fire class :  M-1	d.	tive.	Listed
This product is not controlled under the S ational regulations Austria Limitation of the use of : Permitted organic solvents Belgium Book VI carcinogenic agents annex VI. Ingredient name Silice Styrène Czech Republic Storage code : IV Denmark	d.	tive.	Listed

 Date of issue/Date of revision
 : 06/01/2025
 Date of previous issue
 : 05/10/2022
 Version
 : 1.07
 17/21

 ANTISTAIN AQUA 2901-52 - CLEAN WHITE
 Label No : 104
 Label No : 104
 Label No : 104

## **SECTION 15: Regulatory information**

-	ory information
Protection based on MAL	: According to the regulations on work involving coded products, the following stipulations apply to the use of personal protective equipment:
	<b>General:</b> Gloves must be worn for all work that may result in soiling. Apron/ coveralls/protective clothing must be worn when soiling is so great that regular work clothes do not adequately protect skin against contact with the product. A face shield must be worn in work involving spattering if a full mask is not required. In this case, other recommended use of eye protection is not required.
	In all spraying operations in which there is return spray, the following must be worn: respiratory protection and arm protectors/apron/coveralls/protective clothing as appropriate or as instructed.
	MAL-code: 00-1 <b>Application:</b> When spraying in existing* spray booths, if the operator is outside the spray zone.
	- Arm protectors must be worn.
	During all spraying where atomisation occurs in cabins or spray booths where the operator is inside the spray zone and during spraying outside a closed facility, cabin or booth.
	- Full mask with combined filter, coveralls and hood must be worn.
	<b>Drying:</b> Items for drying/drying ovens that are temporarily placed on such things as rack trolleys, etc, must be equipped with a mechanical exhaust system to prevent fumes from wet items from passing through workers' inhalation zone.
	<b>Polishing:</b> When polishing treated surfaces, a mask with dust filter must be worn. When machine grinding, eye protection must be worn. Work gloves must always be worn.
	<b>Caution</b> The regulations contain other stipulations in addition to the above.
	*See Regulations.
Restrictions on use	: Not to be used by professional users below 18 years of age. See the National Working Environment Authorities Executive Order regarding Young People At Work.
List of undesirable substances	Not listed
Carcinogenic waste	<ul> <li>Waste containers must be labeled: Contains a substance or substances regulated by Danish working environment legislation on cancer risks.</li> </ul>
<u>Finland</u> France	
	: 2-(2-butoxyethoxy)ethanol RG 84
Reinforced medical surveillance	<ul> <li>Act of July 11, 1977 determining the list of activities which require reinforced medical surveillance: not applicable</li> </ul>
<u>Germany</u>	
Storage class (TRGS 510) Hazardous incident ordinan	
	<u>ce</u> under the Germany Hazardous Incident Ordinance.
•	: 1
Technical instruction on air	quality control (TA Luft)

### **SECTION 15: Regulatory information**

Number [Class]	Description	%		
<b>5</b> .2.1	Total dust	47.3		
5.2.4 [11]	Gaseous inorganic substances	0.015		
5.2.5	Organic substances	4.1		
5.2.5 [I]	Organic substances	3.2		
5.2.7.2	Poorly degradable, easily accumulating and highly toxic organic substances	0.021		

AOX

: The product contains organically bound halogens and can contribute to the AOX value in waste water.

Italy

```
D.Lgs. 152/06
```

: Not determined.

**Netherlands** 

Ministry of Social Affairs and Employment (SZW) - Carcinogenic substances and processes, mutagenic or reprotoxic substances

Ingredient name	Carcinogen		Reproductive toxicity - Fertility	Reproductive toxicity - Development	Harmful via breastfeeding
͡sīlica, crystalline (NL- carcinogen specific)	Listed	-	-	-	-

Water Discharge Policy (ABM)

:  $\mathbb{Z}(1)$  Non biodegradable substances with hazardous properties for humans and the environment (carcinogenicity/ mutagenicity/ reprotoxicity/ bioacumulative potential/ toxicity or persistence). Decontamination effort: Z

### Norway

Sweden

Switzerland

**VOC content** : Exempt.

**International regulations** 

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

### **Montreal Protocol**

Not listed.

### **Stockholm Convention on Persistent Organic Pollutants**

Not listed.

### **Rotterdam Convention on Prior Informed Consent (PIC)**

Not listed.

### **UNECE Aarhus Protocol on POPs and Heavy Metals**

Not listed.

#### **15.2 Chemical safety** : Not applicable.

assessment

### **SECTION 16: Other information**

Indicates information that has changed from previously issued version.

Abbreviations and	: ATE = Acute Toxicity Estimate
acronyms	CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
	DMEL = Derived Minimal Effect Level
	DNEL = Derived No Effect Level
	EUH statement = CLP-specific Hazard statement
	N/A = Not available
	PBT = Persistent, Bioaccumulative and Toxic
	PNEC = Predicted No Effect Concentration
	RRN = REACH Registration Number

### **SECTION 16: Other information**

SGG = Segregation Group

vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Not classified.

#### Full text of abbreviated H statements

<b>H</b> 301	Toxic if swallowed.
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H351	Suspected of causing cancer.
H400	Very toxic to aquatic life.
H411	Toxic to aquatic life with long lasting effects.
EUH071	Corrosive to the respiratory tract.

#### Full text of classifications [CLP/GHS]

Acute Tox. 3	ACUTE TOXICITY - Category 3
Acute Tox. 4	ACUTE TOXICITY - Category 4
Aquatic Acute 1	SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1
Aquatic Chronic 2	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2
Carc. 2	CARCINOGENICITY - Category 2
Eye Dam. 1	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1
Eye Irrit. 2	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2
Skin Corr. 1C	SKIN CORROSION/IRRITATION - Category 1C
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2
Skin Sens. 1	SKIN SENSITISATION - Category 1
Skin Sens. 1A	SKIN SENSITISATION - Category 1A
Date of issue/ Date of	: 06/01/2025
revision	
Date of previous issue	e : 05/10/2022
Version	: 1.07

ANTISTAIN AQUA 2901-52\_CLEAN V

#### Notice to reader

The information in this SDS is based on the present state of our knowledge and on current laws. The product is not to be used for purposes other than those specified under section 1 without first obtaining written handling instructions. It is always the responsibility of the user to take all necessary steps to fulfil the demands set out in the local rules and legislation. The information in this SDS is meant to be a description of the safety requirements for our product. It is not to be considered a guarantee of the product's properties.