

# SAFETY DATA SHEET



GLANZÖL 1410-80 - FARBLOS-INCOLORE-COLOURLESS

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

**Product name** : GLANZÖL 1410-80 - FARBLOS-INCOLORE-COLOURLESS

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Product use** : Paint.

### 1.3 Details of the supplier of the safety data sheet

Teknos Group Oy, Takkatie 3, FI-00370 HELSINKI, FINLAND. Tel. +358 9 506 091.

**e-mail address of person responsible for this SDS** : Prod-safe@teknos.com

#### National contact

Teknos Group Oy, Takkatie 3, FI-00370 HELSINKI, FINLAND. Tel. +358 9 506 091.

### 1.4 Emergency telephone number

#### National advisory body/Poison Centre

**Telephone number** : In an emergency, call 112

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

**Product definition** : Mixture

#### Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Flam. Liq. 3, H226

Repr. 1B, H360D

STOT SE 3, H336

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

### 2.2 Label elements

**Hazard pictograms** :



**Signal word** : Danger

**Hazard statements** : H226 - Flammable liquid and vapour.  
H336 - May cause drowsiness or dizziness.  
H360D - May damage the unborn child.

#### Precautionary statements

**Prevention** : P201 - Obtain special instructions before use.  
P280 - Wear protective gloves, protective clothing, eye protection, face protection, or hearing protection.  
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

**Response** : P308 + P313 - IF exposed or concerned: Get medical advice or attention.

**Storage** : P403 + P233 - Store in a well-ventilated place. Keep container tightly closed.

## SECTION 2: Hazards identification

<b>Disposal</b>	: P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.
<b>Hazardous ingredients</b>	: Contains: Naphtha (petroleum), hydrotreated heavy; 2-ethylhexanoic acid, zirconium salt and 2-ethylhexanoic acid, manganese salt
<b>Supplemental label elements</b>	:
<b>Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles</b>	: Restricted to professional users.

### 2.3 Other hazards

<b>Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII</b>	: This mixture does not contain any substances that are assessed to be a PBT or a vPvB.
<b>Other hazards which do not result in classification</b>	: None known.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures : Mixture

Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Type
Naphtha (petroleum), hydrotreated heavy	EC: 265-150-3 CAS: 64742-48-9 Index: 649-327-00-6	≥25 - ≤50	Flam. Liq. 3, H226 STOT SE 3, H336 Asp. Tox. 1, H304 EUH066	-	[1]
Distillates (petroleum), hydrotreated light	EC: 265-149-8	≥10 - ≤25	Asp. Tox. 1, H304	-	[1]
2-ethylhexanoic acid, zirconium salt	REACH #: 01-2119979088-21 EC: 245-018-1 CAS: 22464-99-9 Index: 607-230-00-6	<0.3	Repr. 1B, H360D	-	[1]
2-ethylhexanoic acid, manganese salt	REACH #: 01-2119979087-23 EC: 240-085-3 CAS: 15956-58-8 Index: 607-230-00-6	<0.3	Eye Irrit. 2, H319 Repr. 1B, H360D STOT RE 2, H373 Aquatic Chronic 2, H411 <b>See Section 16 for the full text of the H statements declared above.</b>	-	[1] [2]

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

#### Type

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention if irritation occurs.
- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Skin contact** : Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. If necessary, call a poison center or physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

### 4.2 Most important symptoms and effects, both acute and delayed

#### Over-exposure signs/symptoms

- Eye contact** : No specific data.
- Inhalation** : Adverse symptoms may include the following:  
nausea or vomiting  
headache  
drowsiness/fatigue  
dizziness/vertigo  
unconsciousness  
reduced foetal weight  
increase in foetal deaths  
skeletal malformations
- Skin contact** : Adverse symptoms may include the following:  
reduced foetal weight  
increase in foetal deaths  
skeletal malformations
- Ingestion** : Adverse symptoms may include the following:  
reduced foetal weight  
increase in foetal deaths  
skeletal malformations

### 4.3 Indication of any immediate medical attention and special treatment needed

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

- Suitable extinguishing media** : Use dry chemical, CO<sub>2</sub>, water spray (fog) or foam.
- Unsuitable extinguishing media** : Do not use water jet.

### 5.2 Special hazards arising from the substance or mixture

- Hazards from the substance or mixture** : Flammable liquid and vapour. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion.
- Hazardous combustion products** : No specific data.

### 5.3 Advice for firefighters

- Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

### 6.2 Environmental precautions

- : Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

### 6.3 Methods and material for containment and cleaning up

- Small spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

### 6.4 Reference to other sections

- : See Section 1 for emergency contact information.  
See Section 8 for information on appropriate personal protective equipment.  
See Section 13 for additional waste treatment information.

## SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

### 7.1 Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapour or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

### 7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidising materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

#### Seveso Directive - Reporting thresholds

##### Danger criteria

Category	Notification and MAPP threshold	Safety report threshold
P5c	5000 tonnes	50000 tonnes

### 7.3 Specific end use(s)

- Recommendations** : Not available.
- Industrial sector specific solutions** : Not available.

## SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

### 8.1 Control parameters

#### Occupational exposure limits

Product/ingredient name	Exposure limit values
2-ethylhexanoic acid, zirconium salt	<b>Regulation on Limit Values - MAC (Austria, 4/2021) [Zirkonverbindungen]</b> TWA 8 hours: 5 mg/m <sup>3</sup> (measured as Zr). Form: Inhalable fraction.
2-ethylhexanoic acid, manganese salt	<b>Regulation on Limit Values - MAC (Austria, 4/2021) [Mangan und seine anorganischen Verbindungen einschließlich Trimangantetroxid]</b> TWA 8 hours: 0.2 mg/m <sup>3</sup> (measured as Mn). Form: Inhalable fraction. PEAK 15 minutes: 1.6 mg/m <sup>3</sup> (measured as Mn), 4 times per shift. Form: Inhalable fraction.

Date of issue/Date of revision : 10/01/2025 Date of previous issue : 20/12/2024 Version : 1.02 5/26

GLANZÖL 1410-80 - FARBLOS-INCOLORE-COLOURLESS

Label No : 01172


## SECTION 8: Exposure controls/personal protection

<p>Distillates (petroleum), hydrotreated light</p> <p>2-ethylhexanoic acid, zirconium salt</p>	<p>PEAK 15 minutes: 0.16 mg/m<sup>3</sup> (measured as Mn), 4 times per shift. Form: Respirable fraction. TWA 8 hours: 0.05 mg/m<sup>3</sup> (measured as Mn). Form: Respirable fraction.</p> <p><b>Limit values (Belgium, 12/2023)</b> Absorbed through skin. TWA 8 hours: 200 mg/m<sup>3</sup> (total hydrocarbon vapour).</p>
<p>2-ethylhexanoic acid, manganese salt</p>	<p><b>Limit values (Belgium, 12/2023) [Zirkonium (en verbindingen)]</b> TWA 8 hours: 5 mg/m<sup>3</sup> (as Zr). STEL 15 minutes: 10 mg/m<sup>3</sup> (as Zr).</p>
<p>2-ethylhexanoic acid, zirconium salt</p>	<p><b>Limit values (Belgium, 12/2023) [Mangaan, en -verbindingen]</b> TWA 8 hours: 0.2 mg/m<sup>3</sup> (as Mn). <b>Limit values (Belgium, 12/2023) [Mangaan, en anorganische verbindingen]</b> TWA 8 hours: 0.05 mg/m<sup>3</sup> (as Mn). Form: Respirable fraction.</p>
<p>2-ethylhexanoic acid, manganese salt</p>	<p><b>Ministry of Labour and Social Policy and the Ministry of Health - Ordinance No 13/2003. (Bulgaria, 4/2024) [Manganese oxide and inorganic compounds]</b> Limit value 8 hours: 0.05 mg/m<sup>3</sup> (as Manganese). Form: Respirable fraction. Limit value 8 hours: 0.2 mg/m<sup>3</sup> (as Manganese). Form: Inhalable fraction.</p>
<p>2-ethylhexanoic acid, zirconium salt</p>	<p><b>Ordinance on the protection of workers from exposure to hazardous chemicals at work, exposure limit values (Annex I) (Croatia, 12/2023) [cirkonijevi spojevi]</b> STELV 15 minutes: 10 mg/m<sup>3</sup> (as Zr). ELV 8 hours: 5 mg/m<sup>3</sup> (as Zr).</p>
<p>2-ethylhexanoic acid, manganese salt</p>	<p><b>Ordinance on the protection of workers from exposure to hazardous chemicals at work, exposure limit values (Annex I) (Croatia, 12/2023) [mangan i anorganski spojevi mangana]</b> ELV 8 hours: 0.05 mg/m<sup>3</sup> (as Mn). Form: respiratory dust, a fraction that can reach the lungs by inhalation and inhalable fraction. ELV 8 hours: 0.2 mg/m<sup>3</sup> (as Mn). Form: total dust, inhalable particles and the fraction that can reach the lungs by inhalation.</p>
<p>2-ethylhexanoic acid, manganese salt</p>	<p><b>Department of labour inspection (Cyprus, 7/2021) [Μαγγάνιο και ανόργανες ενώσεις του μαγγανίου]</b> TWA 8 hours: 0.05 mg/m<sup>3</sup> (as Mn). Form: Respirable fraction. TWA 8 hours: 0.2 mg/m<sup>3</sup> (as Mn). Form: Inhalable fraction..</p>
<p>2-ethylhexanoic acid, manganese salt</p>	<p><b>Government regulation of Czech Republic PEL/NPK-P (Czech Republic, 12/2023) [mangan a jeho anorganické sloučeniny]</b> TWA 8 hours: 0.05 mg/m<sup>3</sup> (as Mn). Form: aerosol, respirable fraction.. STEL 15 minutes: 0.1 mg/m<sup>3</sup> (as Mn). Form: aerosol, respirable fraction.. STEL 15 minutes: 0.4 mg/m<sup>3</sup> (as Mn). Form: aerosol, inhalable fraction.. TWA 8 hours: 0.2 mg/m<sup>3</sup> (as Mn). Form: aerosol, inhalable fraction..</p>
<p>2-ethylhexanoic acid, zirconium salt</p>	<p><b>Working Environment Authority (Denmark, 3/2024) [zirkoniumforbindelser]</b> TWA 8 hours: 5 mg/m<sup>3</sup> (calculated as Zr). STEL 15 minutes: 10 mg/m<sup>3</sup> (calculated as Zr).</p>
<p>2-ethylhexanoic acid, manganese salt</p>	<p><b>Working Environment Authority (Denmark, 3/2024) [uorganiske manganforbindelser]</b> TWA 8 hours: 0.2 mg/m<sup>3</sup> (calculated as Mn). Form: inhalable. TWA 8 hours: 0.05 mg/m<sup>3</sup> (calculated as Mn). Form: Respirable fraction.</p>

## SECTION 8: Exposure controls/personal protection

2-ethylhexanoic acid, manganese salt	<p><b>Occupational exposure limits, Regulation No. 293 (Estonia, 4/2024) [mangaan ja mangaani anorgaanilised ühendid]</b>  TWA 8 hours: 0.05 mg/m<sup>3</sup> (calculated for manganese). Form: Respirable dust.  TWA 8 hours: 0.2 mg/m<sup>3</sup> (calculated for manganese). Form: Total dust.</p>
2-ethylhexanoic acid, manganese salt	<p><b>EU OEL (Europe, 1/2022) [Manganese and inorganic manganese compounds]</b>  TWA 8 hours: 0.05 mg/m<sup>3</sup> ((as manganese)). Form: Respirable fraction.  TWA 8 hours: 0.2 mg/m<sup>3</sup> ((as manganese)). Form: Inhalable fraction.</p>
linseed-oil	<p><b>Institute of Occupational Health, Ministry of Social Affairs (Finland, 10/2021) [Öljysumu]</b>  TWA 8 hours: 5 mg/m<sup>3</sup>. Form: Mist.</p>
2-ethylhexanoic acid, zirconium salt	<p><b>Institute of Occupational Health, Ministry of Social Affairs (Finland, 10/2021) [Zirkonium ja sen yhdisteet]</b>  TWA 8 hours: 1 mg/m<sup>3</sup> (calculated as Zr).</p>
2-ethylhexanoic acid, manganese salt	<p><b>Institute of Occupational Health, Ministry of Social Affairs (Finland, 10/2021) [Mangaani ja sen epäorgaaniset yhdisteet]</b>  TWA 8 hours: 0.2 mg/m<sup>3</sup> (calculated as Mn). Form: inhalable dust.  TWA 8 hours: 0.02 mg/m<sup>3</sup> (calculated as Mn). Form: Respirable dust.</p>
2-ethylhexanoic acid, manganese salt	<p><b>Ministry of Labor (France, 6/2024) [manganèse et ses composés]</b>  TWA 8 hours: 0.2 mg/m<sup>3</sup> (as Mn). Form: Inhalable fraction. Notes: Indicative regulatory limit values (decree of 30-06-2004 modified)  TWA 8 hours: 0.05 mg/m<sup>3</sup> (as Mn). Form: Respirable fraction. Notes: Indicative regulatory limit values (decree of 30-06-2004 modified)</p>
1-naphtha (petroleum), hydrotreated heavy	<p><b>DFG MAC-values list (Germany, 7/2023) Develop D.</b>  TWA 8 hours: 50 ppm.  TWA 8 hours: 300 mg/m<sup>3</sup>.  PEAK 15 minutes: 100 ppm 4 times per shift [Interval: 1 hour].  PEAK 15 minutes: 600 mg/m<sup>3</sup> 4 times per shift [Interval: 1 hour].</p>
Distillates (petroleum), hydrotreated light	<p><b>TRGS 900 OEL (Germany, 6/2024)</b>  TWA 8 hours: 300 mg/m<sup>3</sup>.  <b>DFG MAC-values list (Germany, 7/2023) Carc 3B, Develop C.</b>  TWA 8 hours: 5 mg/m<sup>3</sup>. Form: aerosol.  TWA 8 hours: 350 mg/m<sup>3</sup>. Form: vapour.  TWA 8 hours: 50 ppm. Form: vapour.  PEAK 15 minutes: 20 mg/m<sup>3</sup> 4 times per shift [Interval: 1 hour]. Form: aerosol.  PEAK 15 minutes: 100 ppm 4 times per shift [Interval: 1 hour]. Form: vapour.  PEAK 15 minutes: 700 mg/m<sup>3</sup> 4 times per shift [Interval: 1 hour]. Form: vapour.</p>
Linseed-oil	<p><b>TRGS 900 OEL (Germany, 6/2024) [Triglyceride]</b>  PEAK 15 minutes: 20 mg/m<sup>3</sup>. Form: Respirable fraction.  TWA 8 hours: 5 mg/m<sup>3</sup>. Form: Respirable fraction.</p>
2-ethylhexanoic acid, manganese salt	<p><b>TRGS 900 OEL (Germany, 6/2024) [Mangan und seine anorganischen Verbindungen]</b>  TWA 8 hours: 0.2 mg/m<sup>3</sup>. Form: Inhalable fraction.  PEAK 15 minutes: 0.16 mg/m<sup>3</sup>. Form: Respirable fraction.  PEAK 15 minutes: 1.6 mg/m<sup>3</sup>. Form: Inhalable fraction.  TWA 8 hours: 0.02 mg/m<sup>3</sup>. Form: Respirable fraction.  <b>DFG MAC-values list (Germany, 7/2023) [Manganese and its inorganic compounds] Develop C.</b>  TWA 8 hours: 0.02 mg/m<sup>3</sup>. Form: respirable fraction.  PEAK 15 minutes: 0.16 mg/m<sup>3</sup> 4 times per shift [Interval: 1 hour]. Form: respirable fraction.  PEAK 15 minutes: 1.6 mg/m<sup>3</sup> 4 times per shift [Interval: 1 hour].</p>


## SECTION 8: Exposure controls/personal protection

 2-ethylhexanoic acid, zirconium salt


2-ethylhexanoic acid, manganese salt

 2-ethylhexanoic acid, zirconium salt


2-ethylhexanoic acid, manganese salt


 2-ethylhexanoic acid, zirconium salt

2-ethylhexanoic acid, manganese salt

 2-ethylhexanoic acid, zirconium salt

2-ethylhexanoic acid, manganese salt

 2-ethylhexanoic acid, manganese salt

 2-ethylhexanoic acid, manganese salt

 Inseed-oil

2-ethylhexanoic acid, manganese salt

Form: inhalable fraction.

TWA 8 hours: 0.2 mg/m<sup>3</sup>. Form: inhalable fraction.

**Presidential Decree 307/1986: Occupational exposure limit values (Greece, 9/2021) [Ζιρκόνιο και ενώσεις του]**

TWA 8 hours: 5 mg/m<sup>3</sup>.

STEL 15 minutes: 10 mg/m<sup>3</sup>.

**Presidential Decree 307/1986: Occupational exposure limit values (Greece, 9/2021) [μαγγάνιο και ενώσεις του]**

TWA 8 hours: 0.2 mg/m<sup>3</sup> (as manganese). Form: Inhalable fraction.

TWA 8 hours: 0.05 mg/m<sup>3</sup> (as manganese). Form: Respirable fraction.

**5/2020. (II. 6.) ITM Decree (Hungary, 12/2023) [CIRKÓNÍUM VEGYÜLETEI]**

TWA 8 hours: 5 mg/m<sup>3</sup> (as Zr).

PEAK 15 minutes: 20 mg/m<sup>3</sup> (as Zr).

**EU OEL (Europe, 1/2022) [Manganese and inorganic manganese compounds]**

TWA 8 hours: 0.05 mg/m<sup>3</sup> ((as manganese)). Form: Respirable fraction.

TWA 8 hours: 0.2 mg/m<sup>3</sup> ((as manganese)). Form: Inhalable fraction.

**Ministry of Welfare, List of Exposure Limits (Iceland, 11/2023) [Sirkóníumsambönd]**

TWA 8 hours: 5 mg/m<sup>3</sup> (as Zr).

**Ministry of Welfare, List of Exposure Limits (Iceland, 11/2023) [mangan og ólifræn mangansambönd]**

TWA 8 hours: 0.2 mg/m<sup>3</sup> (as Mn). Form: percentage of inhaled air.

TWA 8 hours: 0.05 mg/m<sup>3</sup> (as Mn). Form: percentage of exhaled air..

**NAOSH (Ireland, 4/2024) [zirconium compounds] Notes:** Advisory Occupational Exposure Limit Values (OELVs)

OELV 8 hours: 5 mg/m<sup>3</sup> (as Zr).

OELV 15 minutes: 10 mg/m<sup>3</sup> (as Zr).

**NAOSH (Ireland, 4/2024) [manganese and inorganic manganese compounds] Notes:** EU derived Occupational Exposure Limit Values

OELV 8 hours: 0.2 mg/m<sup>3</sup> (as Mn). Form: Inhalable fraction.

OELV 8 hours: 0.05 mg/m<sup>3</sup> (as Mn). Form: respirable fraction.

**Legislative Decree No. 81/2008. Title IX. Protection from chemical agents, carcinogens and mutagens (Italy, 6/2020) [Manganese e composti inorganici del manganese]**

Limit value 8 hours: 0.05 mg/m<sup>3</sup> (as Mn). Form: respirable fraction.

Limit value 8 hours: 0.2 mg/m<sup>3</sup> (as Mn). Form: inhalable fraction.

**Ministers Cabinet Regulations Nr.325 - AER (Latvia, 3/2024) [mangāns un tā neorganiskie savienojumi]**

TWA 8 hours: 0.05 mg/m<sup>3</sup> (as manganese). Form: respirable fraction.

TWA 8 hours: 0.2 mg/m<sup>3</sup> (as manganese). Form: Inhalable fraction.

**Lithuanian Hygiene Standard HN 23 (Lithuania, 1/2024) [tepalo rūkas, įskaitant dūmus]**

TWA 8 hours: 1 mg/m<sup>3</sup>. Form: Mist.

STEL 15 minutes: 3 mg/m<sup>3</sup>. Form: Mist.

**Lithuanian Hygiene Standard HN 23 (Lithuania, 1/2024) [manganas ir neorganiniai jo junginiai]**

TWA 8 hours: 0.05 mg/m<sup>3</sup> (as Mn). Form: Respirable fraction.





TWA 8 hours: 0.2 mg/m<sup>3</sup> (as Mn). Form: Inhalable fraction.



## SECTION 8: Exposure controls/personal protection

2-ethylhexanoic acid, manganese salt	<p><b>Grand-Duchy Regulation 2016. Chemical agents. Annex I (Luxembourg, 3/2021) [manganèse et ses composés inorganiques]</b>  TWA 8 hours: 0.05 mg/m<sup>3</sup> (as manganese). Form: respirable fraction.  TWA 8 hours: 0.2 mg/m<sup>3</sup> (as manganese). Form: inhalable fraction.</p>
2-ethylhexanoic acid, manganese salt	<p><b>EU OEL (Europe, 1/2022) [Manganese and inorganic manganese compounds]</b>  TWA 8 hours: 0.05 mg/m<sup>3</sup> ((as manganese)). Form: Respirable fraction.  TWA 8 hours: 0.2 mg/m<sup>3</sup> ((as manganese)). Form: Inhalable fraction.</p>
2-ethylhexanoic acid, manganese salt	<p><b>Ministry of Social Affairs and Employment, Legal limit values (Netherlands, 5/2024) [mangaan en anorganische mangaanverbindingen]</b>  STEL 15 minutes: 0.05 mg/m<sup>3</sup> (as manganese). Form: respirable.  TWA 8 hours: 0.2 mg/m<sup>3</sup> (as manganese). Form: inhalable.</p>
2-ethylhexanoic acid, zirconium salt	<p><b>FOR-2011-12-06-1358 (Norway, 12/2022) [zirkoniumforbindelser]</b>  TWA 8 hours: 5 mg/m<sup>3</sup> (calculated as Zr).</p>
2-ethylhexanoic acid, manganese salt	<p><b>FOR-2011-12-06-1358 (Norway, 12/2022) [mangan og uorganiske manganforbindelser]</b>  TWA 8 hours: 0.2 mg/m<sup>3</sup> (calculated as Mn). Form: Inhalable fraction.  TWA 8 hours: 0.05 mg/m<sup>3</sup> (calculated as Mn). Form: Respirable fraction.</p>
Naphtha (petroleum), hydrotreated heavy	<p><b>Regulation of the Minister of Family, Labor and Social Policy of June 12, 2018 on the maximum permissible concentrations and intensities of factors harmful to health in the work environment (Journal of Laws of 2018, item 1286) (Poland, 8/2023) [benzin to varnish]</b>  TWA 8 hours: 300 mg/m<sup>3</sup>.  STEL 15 minutes: 900 mg/m<sup>3</sup>.</p>
2-ethylhexanoic acid, zirconium salt	<p><b>Regulation of the Minister of Family, Labor and Social Policy of June 12, 2018 on the maximum permissible concentrations and intensities of factors harmful to health in the work environment (Journal of Laws of 2018, item 1286) (Poland, 8/2023) [zirconium and compounds]</b>  TWA 8 hours: 5 mg/m<sup>3</sup> (calculated as Zr).  STEL 15 minutes: 10 mg/m<sup>3</sup> (calculated as Zr).</p>
2-ethylhexanoic acid, manganese salt	<p><b>Regulation of the Minister of Family, Labor and Social Policy of June 12, 2018 on the maximum permissible concentrations and intensities of factors harmful to health in the work environment (Journal of Laws of 2018, item 1286) (Poland, 8/2023) [manganese and inorganic compounds]</b>  TWA 8 hours: 0.2 mg/m<sup>3</sup> (calculated as Mn). Form: Inhalable fraction.  TWA 8 hours: 0.05 mg/m<sup>3</sup> (calculated as Mn). Form: Respirable fraction.</p>
Distillates (petroleum), hydrotreated light	<p><b>Portuguese Institute of Quality (Portugal, 11/2014) [queroseno/"jet fuels" na forma de vapor] A3.</b> Absorbed through skin.  TWA 8 hours: 200 mg/m<sup>3</sup> (expressed as total hydrocarbons).  Form: Vapour.</p>
2-ethylhexanoic acid, zirconium salt	<p><b>Portuguese Institute of Quality (Portugal, 11/2014) [zircónio e compostos] A4.</b>  TWA 8 hours: 5 mg/m<sup>3</sup> (expressed as Zr).  STEL 15 minutes: 10 mg/m<sup>3</sup> (expressed as Zr).</p>
2-ethylhexanoic acid, manganese salt	<p><b>Portuguese Institute of Quality (Portugal, 11/2014) [manganês e compostos inorgânicos] A4.</b></p>

## SECTION 8: Exposure controls/personal protection

<p> 2-ethylhexanoic acid, zirconium salt</p>	<p>TWA 8 hours: 0.02 mg/m<sup>3</sup> (expressed as Mn). Form: Respirable fraction. TWA 8 hours: 0.1 mg/m<sup>3</sup> (expressed as Mn). Form: Inhalable fraction.</p>
<p>2-ethylhexanoic acid, manganese salt</p>	<p><b>HG 1218/2006, Annex 1, with subsequent modifications and additions (Romania, 3/2024) [Zirconiu și compuși]</b> VLA 8 hours: 5 mg/m<sup>3</sup> (expressed as Zr). Short term 15 minutes: 10 mg/m<sup>3</sup> (expressed as Zr). <b>HG 1218/2006, Annex 1, with subsequent modifications and additions (Romania, 3/2024) [mangan și compuși anorganici de mangan]</b> VLA 8 hours: 0.05 mg/m<sup>3</sup> (expressed in Mn). Form: Respirable fraction. VLA 8 hours: 0.2 mg/m<sup>3</sup> (expressed in Mn). Form: Inhalable fraction.</p>
<p> 2-ethylhexanoic acid, zirconium salt</p> <p>2-ethylhexanoic acid, manganese salt</p>	<p><b>Government regulation SR c. 355/2006 (Slovakia, 7/2024) [zirkón a jeho zlúčeniny]</b> Inhalation sensitiser. TWA 8 hours: 1 mg/m<sup>3</sup> (Zirconium and its compounds, as Zr). <b>Government regulation SR c. 355/2006 (Slovakia, 7/2024) [mangán a jeho anorganické zlúčeniny]</b> Inhalation sensitiser. TWA 8 hours: 0.2 mg/m<sup>3</sup> (Manganese and its inorganic compounds, as manganese). Form: Inhalable fraction. TWA 8 hours: 0.05 mg/m<sup>3</sup> (Manganese and its inorganic compounds, as manganese). Form: Respirable fraction.</p>
<p> 2-ethylhexanoic acid, zirconium salt</p> <p>2-ethylhexanoic acid, manganese salt</p>	<p><b>Regulation on protection of workers from the risks related to exposure to chemical substances at work (Slovenia, 4/2024) [cirkonij, v vodi netopne cirkonijeve spojine]</b> TWA 8 hours: 1 mg/m<sup>3</sup>. Form: Inhalable fraction. KTV 15 minutes: 1 mg/m<sup>3</sup> 4 times per shift [time between two exposure events at this concentration must be at least 60 minutes]. Form: Inhalable fraction. <b>Regulation on protection of workers from the risks related to exposure to chemical substances at work (Slovenia, 4/2024) [mangan in anorganske manganove spojine]</b> TWA 8 hours: 0.2 mg/m<sup>3</sup> ((calculated as Manganese)). Form: Inhalable fraction. KTV 15 minutes: 1.6 mg/m<sup>3</sup> ((calculated as Manganese)), 4 times per shift [time between two exposure events at this concentration must be at least 60 minutes]. Form: Inhalable fraction. KTV 15 minutes: 0.4 mg/m<sup>3</sup> ((calculated as Manganese)), 4 times per shift [time between two exposure events at this concentration must be at least 60 minutes]. Form: Respirable fraction. TWA 8 hours: 0.05 mg/m<sup>3</sup> ((calculated as Manganese)). Form: Respirable fraction.</p>
<p> 2-ethylhexanoic acid, zirconium salt</p> <p>2-ethylhexanoic acid, manganese salt</p>	<p><b>National institute of occupational safety and health (Spain, 1/2024) [compuestos de circonio]</b> TWA 8 hours: 5 mg/m<sup>3</sup> (as Zr). STEL 15 minutes: 10 mg/m<sup>3</sup> (as Zr). <b>National institute of occupational safety and health (Spain, 1/2024) [manganeso elemental y compuestos inorgánicos]</b> TWA 8 hours: 0.2 mg/m<sup>3</sup> (as Mn). Form: Inhalable fraction. TWA 8 hours: 0.05 mg/m<sup>3</sup> (as Mn). Form: Respirable fraction.</p>
<p> Inseed-oil</p> <p>2-ethylhexanoic acid, manganese salt</p>	<p><b>Work environment authority Regulation 2018:1 (Sweden, 11/2022) [oil mist, incl. oil fumes]</b> TWA 8 hours: 1 mg/m<sup>3</sup>. Form: mist and fume. STEL 15 minutes: 3 mg/m<sup>3</sup>. Form: mist and fume. <b>Work environment authority Regulation 2018:1 (Sweden, 11/2022) [inorganic compounds of manganese]</b> TWA 8 hours: 0.2 mg/m<sup>3</sup> (as Mn). Form: inhalable fraction. TWA 8 hours: 0.05 mg/m<sup>3</sup> (as Mn). Form: respirable fraction.</p>

## SECTION 8: Exposure controls/personal protection

Naphtha (petroleum), hydrotreated heavy	<b>SUVA (Switzerland, 1/2024)</b> STEL 15 minutes: 600 mg/m <sup>3</sup> . STEL 15 minutes: 100 ppm. TWA 8 hours: 50 ppm. TWA 8 hours: 300 mg/m <sup>3</sup> .
Distillates (petroleum), hydrotreated light	<b>SUVA (Switzerland, 1/2024) [Destillate (Erdöl), mit Wasserstoff behandelte, leichte]</b> TWA 8 hours: 350 mg/m <sup>3</sup> . STEL 15 minutes: 700 mg/m <sup>3</sup> . TWA 8 hours: 50 ppm. STEL 15 minutes: 100 ppm. TWA 8 hours: 5 mg/m <sup>3</sup> . Form: Inhalable fraction.
Linseed-oil	<b>SUVA (Switzerland, 1/2024) [Triglyceride]</b> STEL 15 minutes: 20 mg/m <sup>3</sup> . Form: Inhalable fraction. TWA 8 hours: 5 mg/m <sup>3</sup> . Form: Inhalable fraction.
2-ethylhexanoic acid, zirconium salt	<b>SUVA (Switzerland, 1/2024) [zirkonium und seine unlöslichen Verbindungen]</b> TWA 8 hours: 5 mg/m <sup>3</sup> (calculated as Zr). Form: Inhalable fraction. STEL 15 minutes: 10 mg/m <sup>3</sup> (calculated as Zr). Form: Inhalable fraction.
2-ethylhexanoic acid, manganese salt	<b>SUVA (Switzerland, 1/2024) [Mangan und seine anorganischen Verbindungen]</b> TWA 8 hours: 0.2 mg/m <sup>3</sup> (calculated as Mn). Form: Inhalable fraction. TWA 8 hours: 0.1 mg/m <sup>3</sup> (calculated as Mn). Form: Respirable fraction.
2-ethylhexanoic acid, zirconium salt	<b>EH40/2005 WELs (United Kingdom (UK), 1/2020) [zirconium compounds]</b> STEL 15 minutes: 10 mg/m <sup>3</sup> (as Zr). TWA 8 hours: 5 mg/m <sup>3</sup> (as Zr).
2-ethylhexanoic acid, manganese salt	<b>EH40/2005 WELs (United Kingdom (UK), 1/2020) [manganese and its inorganic compounds]</b> TWA 8 hours: 0.2 mg/m <sup>3</sup> (as Mn). Form: Inhalable fraction. TWA 8 hours: 0.05 mg/m <sup>3</sup> (as Mn). Form: Respirable fraction.

### Biological exposure indices

Product/ingredient name	Exposure indices
2-ethylhexanoic acid, manganese salt	<b>VGU BEI (Austria, 9/2020) [manganese or its compounds]</b> BEI Fitness: 20 µg/l, manganese [in blood]. Sampling time: one year.
No exposure indices known.	
No exposure indices known.	
No exposure indices known.	
No exposure indices known.	
No exposure indices known.	
No exposure indices known.	
No exposure indices known.	
No exposure indices known.	
No exposure indices known.	
No exposure indices known.	

## SECTION 8: Exposure controls/personal protection

ethylhexanoic acid, manganese salt

### DFG BEI-values list (Germany, 7/2023) [Manganese and its inorganic compounds]

BEI: See Section XII.2: Substances for which no BAT values are currently be derived, but documentaries in the "work Medico-toxicological justifications for BAT values, EKA and BLW", manganese [in blood]. Sampling time: end of exposure or end of shift / for long-term exposures: at the end of the shift after several shifts.

BEI: 15 µg/l, manganese [in blood]. Sampling time: end of exposure or end of shift / for long-term exposures: at the end of the shift after several shifts.

No exposure indices known.

No exposure indices known.

No exposure indices known.

No exposure indices known.

No exposure indices known.

No exposure indices known.

No exposure indices known.

No exposure indices known.

No exposure indices known.

No exposure indices known.

No exposure indices known.

No exposure indices known.

No exposure indices known.

ethylhexanoic acid, manganese salt

### HG 1218/2006, Annex 2, with subsequent modifications and additions (Romania, 3/2024) [Manganese compounds]

OBLV: 10 µg/l, manganese [in urine]. Sampling time: end of shift.

No exposure indices known.

No exposure indices known.

No exposure indices known.

No exposure indices known.

No exposure indices known.

No exposure indices known.

**Recommended monitoring procedures** : Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

### DNELs/DMELs

#### Product/ingredient name

Naphtha (petroleum), hydrotreated heavy

#### Result

**DNEL - General population - Long term - Inhalation**

0.41 mg/m<sup>3</sup>

Effects: Systemic

**DNEL - Workers - Long term - Inhalation**

1.9 mg/m<sup>3</sup>

Effects: Systemic

**DNEL - General population - Long term - Inhalation**

## SECTION 8: Exposure controls/personal protection

178.57 mg/m<sup>3</sup>

Effects: Local

**DNEL - General population - Short term - Inhalation**

640 mg/m<sup>3</sup>

Effects: Local

**DNEL - Workers - Long term - Inhalation**

837.5 mg/m<sup>3</sup>

Effects: Local

**DNEL - Workers - Short term - Inhalation**

1066.67 mg/m<sup>3</sup>

Effects: Local

**DNEL - General population - Short term - Inhalation**

1152 mg/m<sup>3</sup>

Effects: Systemic

**DNEL - Workers - Short term - Inhalation**

1286.4 mg/m<sup>3</sup>

Effects: Systemic

2-ethylhexanoic acid, zirconium salt

**DNEL - General population - Long term - Inhalation**

0.58 mg/m<sup>3</sup>

Effects: Systemic

**DNEL - Workers - Long term - Inhalation**

2.351 mg/m<sup>3</sup>

Effects: Systemic

**DNEL - General population - Long term - Oral**

0.167 mg/kg bw/day

Effects: Systemic

**DNEL - General population - Long term - Dermal**

0.167 mg/kg bw/day

Effects: Systemic

**DNEL - Workers - Long term - Dermal**

0.333 mg/kg bw/day

Effects: Systemic

**DNEL - General population - Long term - Inhalation**

0.7 mg/m<sup>3</sup>

Effects: Local

**DNEL - Workers - Long term - Inhalation**

2.82 mg/m<sup>3</sup>

Effects: Local

2-ethylhexanoic acid, manganese salt

**DNEL - General population - Long term - Inhalation**

0.024 mg/m<sup>3</sup>

Effects: Local

**DNEL - General population - Long term - Inhalation**

0.024 mg/m<sup>3</sup>

Effects: Systemic

**DNEL - General population - Long term - Oral**

0.167 mg/kg bw/day

Effects: Systemic

**DNEL - General population - Long term - Dermal**

0.167 mg/kg bw/day

Effects: Systemic

## SECTION 8: Exposure controls/personal protection

### **DNEL - Workers - Long term - Dermal**

0.333 mg/kg bw/day

Effects: Systemic

### **DNEL - Workers - Long term - Inhalation**

0.83 mg/m<sup>3</sup>

Effects: Local

### **DNEL - Workers - Long term - Inhalation**

0.83 mg/m<sup>3</sup>

Effects: Systemic

### **PNECs**

Not available.

## **8.2 Exposure controls**

### **Appropriate engineering controls**

: Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

### **Individual protection measures**

#### **Hygiene measures**

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

#### **Eye/face protection**

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.

### **Skin protection**

#### **Hand protection**

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Recommendations : Wear suitable gloves tested to EN374.

< 1 hour (breakthrough time): Nitrile gloves. thickness > 0.3 mm

1 - 4 hours (breakthrough time): 4H / Silver Shield® gloves.

#### **Body protection**

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves. Refer to European Standard EN 1149 for further information on material and design requirements and test methods.

#### **Other skin protection**

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

## SECTION 8: Exposure controls/personal protection

- Respiratory protection** : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.  
Filter type: A  
Filter type (spray application): A P
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

## SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

### 9.1 Information on basic physical and chemical properties

#### Appearance

- Physical state** : Liquid.  
**Colour** : Colourless.  
**Odour** : Slight  
**Odour threshold** : Not available.  
**Melting point/freezing point** : Not available.  
**Initial boiling point and boiling range** :

Ingredient name	°C	°F	Method
Distillates (petroleum), hydrotreated light	90 to 300	194 to 572	ASTM D 86
Naphtha (petroleum), hydrotreated heavy	155 to 217	311 to 422.6	

- Flammability** : Not available.  
**Lower and upper explosion limit** : Lower: Not applicable.  
Upper: Not applicable.  
**Flash point** : Closed cup: 40°C (104°F)  
**Auto-ignition temperature** :

Ingredient name	°C	°F	Method
Distillates (petroleum), hydrotreated light	>220	>428	
Naphtha (petroleum), hydrotreated heavy	280 to 470	536 to 878	

- Decomposition temperature** : Not available.  
**pH** : Not applicable.  
**Viscosity** : Not available.  
**Solubility(ies)** :  
Not available.

- Solubility in water** : Not available.  
**Partition coefficient: n-octanol/ water** : Not applicable.

- Vapour pressure** :

Ingredient name	Vapour Pressure at 20°C			Vapour pressure at 50°C		
	mm Hg	kPa	Method	mm Hg	kPa	Method
Naphtha (petroleum), hydrotreated heavy	0.75006 to 2.25018	0.1 to 0.3				
Distillates (petroleum), hydrotreated light	0.22502 to 0.45004	0.03 to 0.06				

- Relative density** : Not available.  
**Density** : 1 g/cm<sup>3</sup>

## SECTION 9: Physical and chemical properties

Vapour density : Not available.

### Particle characteristics

Median particle size : Not applicable.

## 9.2 Other information

### 9.2.1 Information with regard to physical hazard classes

Explosive properties : Not available.

Oxidising properties : Not available.

### 9.2.2 Other safety characteristics

Not applicable.

## SECTION 10: Stability and reactivity

10.1 Reactivity : No specific test data related to reactivity available for this product or its ingredients.

10.2 Chemical stability : The product is stable.

10.3 Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will not occur.

10.4 Conditions to avoid : Avoid all possible sources of ignition (spark or flame). Do not pressurise, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.

10.5 Incompatible materials : Reactive or incompatible with the following materials:  
oxidising materials

10.6 Hazardous decomposition products : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute toxicity

##### Product/ingredient name

Naphtha (petroleum), hydrotreated heavy

##### Result

Rat - Oral - LD50

>6 g/kg

Rat - Inhalation - LC50 Vapour

8500 mg/m<sup>3</sup> [4 hours]

Toxic effects: Lung, Thorax, or Respiration - Other changes

2-ethylhexanoic acid, zirconium salt

Rabbit - Dermal - LD50

>5 g/kg

Rat - Oral - LD50

>5 g/kg

Toxic effects: Behavioral - Somnolence (general depressed activity)

Conclusion/Summary [Product] : Not available.

#### Acute toxicity estimates

N/A

#### Skin corrosion/irritation

Not available.



## SECTION 11: Toxicological information

**Conclusion/Summary [Product]** : Not available.

### Serious eye damage/eye irritation

Not available.

**Conclusion/Summary [Product]** : Not available.

### Respiratory corrosion/irritation

Not available.

**Conclusion/Summary [Product]** : Not available.

### Respiratory or skin sensitization

Not available.

### Skin

**Conclusion/Summary [Product]** : Not available.

### Respiratory

**Conclusion/Summary [Product]** : Not available.

### Germ cell mutagenicity

Not available.

**Conclusion/Summary [Product]** : Not available.

### Carcinogenicity

Not available.

**Conclusion/Summary [Product]** : Not available.

### Reproductive toxicity

Not available.

**Conclusion/Summary [Product]** : Not available.

### Specific target organ toxicity (single exposure)

#### **Product/ingredient name**

Naphtha (petroleum), hydrotreated heavy

#### **Result**

STOT SE 3, H336 (Narcotic effects)

### Specific target organ toxicity (repeated exposure)

#### **Product/ingredient name**

2-ethylhexanoic acid, manganese salt

#### **Result**

STOT RE 2, H373

### Aspiration hazard

#### **Product/ingredient name**

Naphtha (petroleum), hydrotreated heavy  
Distillates (petroleum), hydrotreated light

#### **Result**

ASPIRATION HAZARD - Category 1  
ASPIRATION HAZARD - Category 1

### Information on likely routes of exposure

Not available.

### Potential acute health effects

**Eye contact** : No known significant effects or critical hazards.

## SECTION 11: Toxicological information

- Inhalation** : Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness.
- Skin contact** : No known significant effects or critical hazards.
- Ingestion** : Can cause central nervous system (CNS) depression.

### Symptoms related to the physical, chemical and toxicological characteristics

- Eye contact** : No specific data.
- Inhalation** : Adverse symptoms may include the following:  
nausea or vomiting  
headache  
drowsiness/fatigue  
dizziness/vertigo  
unconsciousness  
reduced foetal weight  
increase in foetal deaths  
skeletal malformations
- Skin contact** : Adverse symptoms may include the following:  
reduced foetal weight  
increase in foetal deaths  
skeletal malformations
- Ingestion** : Adverse symptoms may include the following:  
reduced foetal weight  
increase in foetal deaths  
skeletal malformations

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

#### Short term exposure

- Potential immediate effects** : Not available.
- Potential delayed effects** : Not available.

#### Long term exposure

- Potential immediate effects** : Not available.
- Potential delayed effects** : Not available.

### Potential chronic health effects

Not available.

- Conclusion/Summary [Product]** : Not available.
- General** : No known significant effects or critical hazards.
- Carcinogenicity** : No known significant effects or critical hazards.
- Mutagenicity** : No known significant effects or critical hazards.
- Reproductive toxicity** : May damage the unborn child.

## 11.2 Information on other hazards

### 11.2.1 Endocrine disrupting properties

Not available.

- Conclusion/Summary [Product]** : The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

### 11.2.2 Other information

Not available.

## SECTION 12: Ecological information

### 12.1 Toxicity

Not available.

**Conclusion/Summary [Product]** : Not available.

### 12.2 Persistence and degradability

Not available.

**Conclusion/Summary [Product]** : Not available.

### 12.3 Bioaccumulative potential

Product/ingredient name	LogP <sub>ow</sub>	BCF	Potential
Naphtha (petroleum), hydrotreated heavy	-	10 to 2500	High
2-ethylhexanoic acid, zirconium salt	-	2.96	Low
2-ethylhexanoic acid, manganese salt	-	2.96	Low

### 12.4 Mobility in soil

#### Soil/water partition coefficient

Not available.

#### Results of PMT and vPvM assessment

Product/ingredient name	PMT	P	M	T	vPvM	vP	vM
Naphtha (petroleum), hydrotreated heavy	No	No	No	No	No	No	No
Distillates (petroleum), hydrotreated light	No	No	No	No	No	No	No
2-ethylhexanoic acid, zirconium salt	No	No	No	No	No	No	No
2-ethylhexanoic acid, manganese salt	No	No	No	No	No	No	No

**Mobility** : Not available.

**Conclusion/Summary** : The product does not meet the criteria to be considered as a PMT or vPvM.

### 12.5 Results of PBT and vPvB assessment

#### Regulation (EC) No. 1907/2006 [REACH]

Product/ingredient name	PBT	P	B	T	vPvB	vP	vB
Naphtha (petroleum), hydrotreated heavy	No	No	No	No	No	No	No
Distillates (petroleum), hydrotreated light	No	No	No	No	No	No	No
2-ethylhexanoic acid, zirconium salt	No	No	No	No	No	No	No
2-ethylhexanoic acid, manganese salt	No	No	No	No	No	No	No

#### Regulation (EC) No. 1272/2008 [CLP]

Product/ingredient name	PBT	P	B	T	vPvB	vP	vB
Naphtha (petroleum), hydrotreated heavy	No	No	No	No	No	No	No
Distillates (petroleum), hydrotreated light	No	No	No	No	No	No	No
2-ethylhexanoic acid, zirconium salt	No	No	No	No	No	No	No
2-ethylhexanoic acid, manganese salt	No	No	No	No	No	No	No

## SECTION 12: Ecological information

**Conclusion/Summary Regulation (EC) No. 1272/2008 [CLP]** : The product does not meet the criteria to be considered as a PBT or vPvB.

### 12.6 Endocrine disrupting properties

Not available.

**Conclusion/Summary [Product]** : The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

### 12.7 Other adverse effects

No known significant effects or critical hazards.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

#### Product





**Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

#### Packaging

**Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

**Special precautions** : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapour from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

## SECTION 14: Transport information

	ADR/RID	ADN	IMDG	IATA
<b>14.1 UN number or ID number</b>	UN1263	UN1263	UN1263	UN1263
<b>14.2 UN proper shipping name</b>	(Naphtha (petroleum), hydrotreated heavy, Distillates (petroleum), hydrotreated light)	(Naphtha (petroleum), hydrotreated heavy, Distillates (petroleum), hydrotreated light)	(Naphtha (petroleum), hydrotreated heavy, Distillates (petroleum), hydrotreated light)	(Naphtha (petroleum), hydrotreated heavy, Distillates (petroleum), hydrotreated light)
<b>14.3 Transport hazard class(es)</b>	3 	3 	3 	3 
<b>14.4 Packing group</b>	III	III	III	III
<b>14.5 Environmental hazards</b>	No.	No.	No.	No.

#### Additional information

**ADR/RID** : **Tunnel code** (D/E)

**Date of issue/Date of revision** : 10/01/2025 **Date of previous issue** : 20/12/2024

**Version** : 1.02 20/26

GLANZÖL 1410-80 - FARBLOS-INCOLORE-COLOURLESS

**Label No** : 01172

## SECTION 14: Transport information

**14.6 Special precautions for user** : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

**14.7 Maritime transport in bulk according to IMO instruments** : Not relevant/applicable due to nature of the product.

## SECTION 15: Regulatory information

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

### EU Regulation (EC) No. 1907/2006 (REACH)

#### Annex XIV - List of substances subject to authorisation

##### Annex XIV

None of the components are listed.

##### Substances of very high concern

None of the components are listed.

#### Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Product/ingredient name	%	Designation [Usage]
GLANZÖL 1410-80	≥90	3 30

**Labelling** : Restricted to professional users.

#### Other EU regulations

**Industrial emissions (integrated pollution prevention and control) - Air** : Not listed

**Industrial emissions (integrated pollution prevention and control) - Water** : Not listed

**Explosive precursors** : Not applicable.

#### Ozone depleting substances (EU 2024/590)

Not listed.

#### Prior Informed Consent (PIC) (649/2012/EU)

Not listed.

#### Persistent Organic Pollutants

Not listed.

#### Seveso Directive

This product is controlled under the Seveso Directive.

#### Danger criteria

##### Category

P5c

#### National regulations

##### Austria

**VbF class** : Category 3

**Limitation of the use of organic solvents** : Permitted.

##### Belgium

## SECTION 15: Regulatory information

### Czech Republic

**Storage code** : II

### Denmark

**Fire class** : II-1

**MAL-code** : 1-1

**Protection based on MAL** : **According to the regulations on work involving coded products, the following stipulations apply to the use of personal protective equipment:**

**General:** Gloves must be worn for all work that may result in soiling. Apron/coveralls/protective clothing must be worn when soiling is so great that regular work clothes do not adequately protect skin against contact with the product. A face shield must be worn in work involving spattering if a full mask is not required. In this case, other recommended use of eye protection is not required.

In all spraying operations in which there is return spray, the following must be worn: respiratory protection and arm protectors/apron/coveralls/protective clothing as appropriate or as instructed.

MAL-code: 1-1

**Application:** During downtimes, cleaning and repair in closed facilities, spray booths or cabins, if there is a risk of contact with wet paint or organic solvents.

- Gas filter mask must be worn.

When spraying in existing\* spray booths, if the operator is outside the spray zone.

- Full mask with combined filter and arm protectors must be worn.

During non-atomising spraying in existing\* facilities of the combined-cabin, spray-cabin and spray-booth type where the operator is working inside the spray zone.

- Air-supplied half mask and eye protection must be worn.

During all spraying where atomisation occurs in cabins or spray booths where the operator is inside the spray zone and during spraying outside a closed facility, cabin or booth.

- Air-supplied half mask, eye protection, coveralls and hood must be worn.

**Drying:** Items for drying/drying ovens that are temporarily placed on such things as rack trolleys, etc, must be equipped with a mechanical exhaust system to prevent fumes from wet items from passing through workers' inhalation zone.

**Polishing:** When polishing treated surfaces, a mask with dust filter must be worn. When machine grinding, eye protection must be worn. Work gloves must always be worn.

**Caution** The regulations contain other stipulations in addition to the above.

\*See Regulations.

**Restrictions on use** : Not to be used by professional users below 18 years of age. See the National Working Environment Authorities Executive Order regarding Young People At Work.

**List of undesirable substances** : Not listed

### Finland

### France

**Social Security Code, Articles L 461-1 to L 461-7** : Naphtha (petroleum), hydrotreated heavy RG 84  
Distillates (petroleum), hydrotreated light RG 84

## SECTION 15: Regulatory information

**Reinforced medical surveillance** : Act of July 11, 1977 determining the list of activities which require reinforced medical surveillance: not applicable

### Germany

**Storage class (TRGS 510)** : 3

### Hazardous incident ordinance

This product is controlled under the Germany Hazardous Incident Ordinance.

### Danger criteria

Category	Reference number
P5c	1.2.5.3

**Hazard class for water** : 3

### Technical instruction on air quality control (TA Luft)

Number [Class]	Description	%
5.2.2 [III]	Dusty inorganic substances	0.15
5.2.5	Organic substances	99.6
5.2.5 [I]	Organic substances	28.2
5.2.7.1.3	Reproductive toxic substances	0.2

### Italy

**D.Lgs. 152/06** : Not determined.

### Netherlands

**Ministry of Social Affairs and Employment (SZW) - Carcinogenic substances and processes, mutagenic or reprotoxic substances**

Ingredient name	Carcinogen	Mutagen	Reproductive toxicity - Fertility	Reproductive toxicity - Development	Harmful via breastfeeding
Naphtha (petroleum), hydrotreated heavy	Listed	Listed	-	-	-
complexe derivatives of oil and charcoal hydrocarbon, C9-C11, n-alkane, iso-alkane, cyclic, containing <2% of aromatics, < 0,1% of benzene, < 1% of n-hexane and < 0,5 % of aromatic hydrocarbons	Listed	-	-	-	-
2-ethylhexanoic acid and salts excluding substances specifically listed in Annex VI of CLP	-	-	-	Development 1B	-
Naphtha (petroleum), hydrodesulfurized heavy	Listed	Listed	-	-	-
2-ethylhexanoic acid, manganese salt	-	-	Fertility 2	Development 1B	-

**Water Discharge Policy (ABM)** : Z(1) Non biodegradable substances with hazardous properties for humans and the environment (carcinogenicity/ mutagenicity/ reprotoxicity/ bioacumulative potential/ toxicity or persistence). Decontamination effort: Z

### Norway

### Sweden

**Flammable liquid class (SRVFS 2005:10)** : 2b

### Switzerland

**VOC content** :  VOC (w/w): 47.4%

### International regulations

## SECTION 15: Regulatory information

### Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

### Montreal Protocol

Not listed.

### Stockholm Convention on Persistent Organic Pollutants

Not listed.

### Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

### UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

**15.2 Chemical safety assessment** : This product contains substances for which Chemical Safety Assessments are still required.

## SECTION 16: Other information

✔ Indicates information that has changed from previously issued version.

**Abbreviations and acronyms** : ATE = Acute Toxicity Estimate  
CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]  
DMEL = Derived Minimal Effect Level  
DNEL = Derived No Effect Level  
EUH statement = CLP-specific Hazard statement  
N/A = Not available  
PBT = Persistent, Bioaccumulative and Toxic  
PNEC = Predicted No Effect Concentration  
RRN = REACH Registration Number  
SGG = Segregation Group  
vPvB = Very Persistent and Very Bioaccumulative

### Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Flam. Liq. 3, H226 Repr. 1B, H360D STOT SE 3, H336	On basis of test data Calculation method - Notes 11/12 summation process Calculation method

### Full text of abbreviated H statements

H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H360D	May damage the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

### Full text of classifications [CLP/GHS]

Aquatic Chronic 2	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2
Asp. Tox. 1	ASPIRATION HAZARD - Category 1
Eye Irrit. 2	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2
Flam. Liq. 3	FLAMMABLE LIQUIDS - Category 3
Repr. 1B	REPRODUCTIVE TOXICITY - Category 1B
STOT RE 2	SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 2
STOT SE 3	SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3

**Date of issue/ Date of revision** : 10/01/2025

**Date of previous issue** : 20/12/2024



## SECTION 16: Other information

Version

: 1.02

GLANZÖL 1410-80\_FARBLOS-INCOLORE-  
COLOURLESS

FARBLOS-INCOLORE-COLOURLESS

### Notice to reader

The information in this SDS is based on the present state of our knowledge and on current laws. The product is not to be used for purposes other than those specified under section 1 without first obtaining written handling instructions. It is always the responsibility of the user to take all necessary steps to fulfil the demands set out in the local rules and legislation. The information in this SDS is meant to be a description of the safety requirements for our product. It is not to be considered a guarantee of the product's properties.

*Date of issue*/*Date of revision*

: 10/01/2025

*Date of previous issue*

: 20/12/2024

*Version* : 1.02 25/26

GLANZÖL 1410-80 - FARBLOS-INCOLORE-COLOURLESS

**Label No** : 01172

