# according to 2001/58 EC



3207816

Reviewed on: 30/06/2021 Printing date: 01/07/2021

# 01 Identification of the hazardous chemical and of the supplier

- · Product identifier
- · Trade name:

HYDROFÜLLER 6335-00

· Article number / Safety Data Sheet: 633350

- · Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

Teknos AG

Industriestrasse 7

LI-9487 Gamprin-Bendern

T +423 375 94 00

F +423 375 94 99

- Further information obtainable from:
  - Product safety department. e-mail address: li-sdb@teknos.com
- Emergency telephone number:

Swiss Toxicological Information Centre, CH-8032 Zürich Emergency telephone: +41 (0)44 251 51 51 (International)

# 02 Hazard identification

Classification of the substance or mixture

Void

- Label elements
- GHS label elements
- Hazard pictograms

Void

Signal word

Void

- Hazard-determining components of labelling:
- titanium dioxide / 2-butoxyethanol
- Hazard statements

Void

# 03 Composition and information of the ingredients of the hazardous chemical

- Chemical characterization: Mixtures
- Description:

Mixture of substances listed below with nonhazardous additions.

· Dangerous components:

**CAS Number** 111-76-2 1,00- 5,00

EC number: 203-905-0

2-butoxyethanol

Record number 01-2119475108-36 Acute Tox. 4 - H302, Acute Tox. 4 -H312, Acute Tox. 4 - H332, Skin Irrit. 2 -

H315, Eye Irrit. 2 - H319

13463-67-7 titanium dioxide 10,00-25,00

EC number: 236-675-5

Record number 01-2119489379-17

Additional information:

For the wording of the listed risk phrases refer to section 16.

MAL

# according to 2001/58 EC



3207816

Reviewed on: 30/06/2021 Printing date: 01/07/2021

PRODUCT: HYDROFÜLLER 6335-00

(continued of page 1)

#### 04 First-aid measures

· After inhalation:

Supply fresh air; consult doctor in case of complaints.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

· After eye contact:

Rinse opened eye for several minutes under running water.

· After swallowing:

Do not induce vomiting; call for medical help immediately.

# 05 Fire-fighting measures

· Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

· Protective equipment:

Mouth respiratory protective device.

Do not inhale explosion gases or combustion gases.

· Additional information

Cool endangered receptacles with water spray.

Collect contaminated fire fighting water separately. It must not enter the sewage system.

#### 06 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

In case of seepage into the ground inform responsible authorities.

Dilute with plenty of water.

In case of gas release or seepage into the ground inform responsible authorities.

Do not allow to enter sewers/ surface or ground water.

Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

# 07 Handling and storage

- Handling:
- Precautions for safe handling

Open and handle receptacle with care.

Information about fire - and explosion protection:

Prevent impact and friction.

- Storage:
- Requirements to be met by storerooms and receptacles:

Store only in the original receptacle.

Information about storage in one common storage facility:

Not required.

Further information about storage conditions:

Protect from frost.

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

Specific end use(s)

No further relevant information available.

# according to 2001/58 EC



3207816

Reviewed on: 30/06/2021 Printing date: 01/07/2021

PRODUCT: HYDROFÜLLER 6335-00

(continued of page 2)

#### 08 Exposure controls and personal protection

· Ingredients with limit values that require monitoring at the workplace:

111-76-2 2-butoxyethanol

**PEL** 

 Long-term value
 96.7
 mg/m3

 20
 ppm

(kulit)

Additional information:

The lists valid during the making were used as basis.

- · Personal protective equipment:
- · General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Do not eat or drink while working.

Be sure to clean skin thoroughly after work and before breaks.

- Respiratory protection: Suitable respiratory protective device recommended. Use suitable respiratory protective device in case of insufficient ventilation.
- Protection of hands: The glove material has to be impermeable and resistant to the product/ the substance/ the
  preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the
  preparation/ the chemical mixture. Selection of the glove material on consideration of the penetration times, rates
  of diffusion and the degradation Impervious gloves
- · Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

The determined penetration times according to EN 374 part III are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

- Eye protection: Safety glasses
- · Body protection: Protective work clothing

#### 09 Physical and chemical properties

Appearance	
Appearance:	
Form:	Liquid
Colour:	According to product specifica
Odour:	Characteristic Characteristic
Odour threshold:	Not determined.
Change in condition	
Melting point/freezing point:	0 °C
Initial boiling point and boiling range:	Undetermined.
Flash point:	Not applicable.
Flammability (solid, gas):	Not applicable.
Ignition temperature:	Undetermined.
Decomposition temperature:	Not determined.
Auto-ignition temperature:	Not determined.
Explosive properties:	Not determined.
Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
Vapour pressure:	at 20 °C 23,0000 mbar
Density:	1,4200 g/cm3
Solubility in / Miscibility with	
	(continued on page

(continued on page 4)

# \*\*\* TEKNOS

#### according to 2001/58 EC

3207816

Reviewed on: 30/06/2021 Printing date: 01/07/2021

PRODUCT: HYDROFÜLLER 6335-00

(continued of page 3)

water:	Not determined.	(commerce or page o)
Viscosity:		
	Not determined.	
	20 - 25 s DIN 6 mm	
Other information	No further relevant information available.	

# 10 Stability and reactivity

- Thermal decomposition / conditions to be avoided:
  - No decomposition if used according to specifications.
- · Incompatible materials:
- No further relevant information available.
- · Hazardous decomposition products:

No dangerous decomposition products known.

# 11 Toxicological information

- Acute toxicity
- · LD/LC50 values relevant for classification:

#### 111-76-2 2-butoxyethanol

Oral, LD50: 1746 mg/kg (rat) Oral, LD50: 1414 mg/kg (guinea Pig) Dermal, LD50: 2000 mg/kg (rat) Dermal, LD50: 1000 mg/kg (Rabbit) Dermal, LD50: 2000 mg/kg (guinea Pig) Oral, LD50: 790 mg/kg (rat) Dermal, LD50: 3400 mg/kg (Rabbit) Inhalative, LC50/4h: 8000 mg/l (rat) Oral, LD50: 10000 mg/kg (rat) Oral, LD50: >20000 mg/kg (rat) Dermal, LD50: >10000 mg/kg (Rabbit) Inhalative, LC50/4h: >6,82 mg/l (rat) Oral, LD50: 2000 mg/kg (rat) Dermal, LD50: 1370 mg/kg (Rabbit) Inhalative, LC50/4h: 3,25 mg/l (mouse)

71-36-3 butan-1-ol

7631-86-9 silicon dioxide, chemically prepared

13463-67-7 titanium dioxide 108-01-0 2-dimethylaminoethanol

- Primary irritant effect:
- Skin corrosion/irritation

No irritant effect.

· Serious eye damage/irritation

No irritating effect.

- Respiratory or skin sensitisation
- No sensitising effects known.
- Additional toxicological information:

The product can cause deformations.

The product is not subject to classification according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version.

# 12 Ecological information

Aquatic toxicity:

No further relevant information available.

· Persistence and degradability

No further relevant information available.

- Behaviour in environmental systems:
- Bioaccumulative potential

No further relevant information available.

- · Additional ecological information:
- General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

MAL

# according to 2001/58 EC



3207816

Reviewed on: 30/06/2021 Printing date: 01/07/2021

PRODUCT: HYDROFÜLLER 6335-00

(continued of page 4)

### 13 Disposal information

- · Uncleaned packaging:
- Recommendation:
- Disposal must be made according to official regulations.
- · Recommended cleansing agents:

Water, if necessary together with cleansing agents.

# 14 Transportation information

UN-Number

ADR Void
IMDG Void
IATA Void

• UN proper shipping name

ADR Void IMDG Void IATA Void

Transport hazard class(es)

ADR

**Class** Void

IMDG

**Class** Void

IATA

**Class** Void

Packing group

ADR Void IMDG Void IATA Void

- · Environmental hazards:
  - Not applicable.
- Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable.
- · Transport/Additional information:

Not applicable.

#### 15 Regulatory information

- · National regulations:
- · Information about limitation of use:

The above-mentioned manufacturer's information on the handling of isoc yanates is contained in the safety data sheet of the product. The Euro pean Committee of Paint, Printing Ink and Artists 'Colours Manufacture rs' Associations (CEPE) provides the following information on coatings isocyanates: Ready-to-use paints containing isocyanates may have an ir ritant effect on mucous membranes - especially on breathing organs - a nd cause hypersensitivity reactions. Inhalation of vapour or spray mis t may cause sensitisation. When handling paints containing isocyanates , all precautions required for solvent-containing paints must be follo wed. Vapour and spray mist in particular should not be inhaled. Person s who are allergic, asthmatic, or prone to respiratory ailments should not work with isocyanate-containing paints.

- Technical instructions (air):
- Class Share in %

3,83

· Waterhazard class:

Water hazard class 1 (Self-assessment): slightly hazardous for water.

(continued on page 6)

Page: 6 / 6

#### MATERIAL SAFETY DATA SHEET

# \*\*\* TEKNOS

# according to 2001/58 EC

3207816

Reviewed on: 30/06/2021 Printing date: 01/07/2021

PRODUCT: HYDROFÜLLER 6335-00

(continued of page 5)

· EHS reference list

111-76-2 2-butoxyethanol

# 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H302 Harmful if swallowed. H312 Harmful if in contact with skin.

H315 Causes skin irritation.
H319 Causes serious eye irritation.

H332 Harmful if inhaled.

#### Department issuing MSDS:

Environment protection department.

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association ICAO: International Civil Aviation Organisation

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

\* Data compared to the previous version altered.