

Reviewed on: 23/08/2021 Printing date: 23/08/2021

	tifier	
• Trade name: HYDROFILL F	PREMIUM 6338-00 1C AND 2C	
Article numbe     633380	r / Safety Data Sheet:	
<ul> <li>Details of the</li> <li>Manufacturer/ Teknos AG Industriestrass LI-9487 Gamp T +423 375 94 F +423 375 94</li> </ul>	se 7 brin-Bendern 4 00	
<ul><li>Product safety</li><li>Emergency te</li></ul>	nation obtainable from: y department. e-mail address: li-sdb@teknos.com elephone number: ogical Information Centre, CH-8032 Zürich Emergency telepho	one: +41 (0)44 251 51 51 (Internationa
Hazard ide	ntification	
<ul> <li>Classification Void</li> <li>Label elementi</li> <li>GHS label ele</li> <li>Hazard pictog Void</li> </ul>	ments	
<ul> <li>Signal word Void</li> </ul>		
	nining components of labelling: de / 2-butoxyethanol	
<ul> <li>Hazard staten Void</li> </ul>	nents	
Hazard staten     Void		
Hazard staten     Void	on and information of the ingredients of the ingredients of the second s	ne hazardous chemical
<ul> <li>Hazard staten Void</li> <li>Compositi</li> <li>Chemical cha Description:</li> </ul>		ne hazardous chemical
<ul> <li>Hazard staten Void</li> <li>Compositi</li> <li>Chemical cha Description: Mixture of sub</li> </ul>	on and information of the ingredients of the aracterization: Mixtures betances listed below with nonhazardous additions.	ne hazardous chemical
<ul> <li>Hazard staten Void</li> <li>Compositi</li> <li>Chemical cha Description:</li> </ul>	on and information of the ingredients of the aracterization: Mixtures betances listed below with nonhazardous additions.	ne hazardous chemical %
<ul> <li>Hazard staten Void</li> <li>Compositi</li> <li>Chemical cha Description: Mixture of sub</li> <li>Dangerous cc</li> </ul>	on and information of the ingredients of the aracterization: Mixtures astances listed below with nonhazardous additions. amponents: 2-butoxyethanol EC number: 203-905-0 Record number 01-2119475108-36	
<ul> <li>Hazard staten Void</li> <li>Compositi</li> <li>Chemical cha Description: Mixture of sub</li> <li>Dangerous co CAS Number</li> </ul>	on and information of the ingredients of the aracterization: Mixtures astances listed below with nonhazardous additions. amponents: 2-butoxyethanol EC number: 203-905-0 Record number 01-2119475108-36	%
<ul> <li>Hazard staten Void</li> <li>Compositi</li> <li>Chemical cha Description: Mixture of sub</li> <li>Dangerous co CAS Number</li> </ul>	On and information of the ingredients of the aracterization: Mixtures         aracterization: Mixtures         bistances listed below with nonhazardous additions.         omponents:         2-butoxyethanol         EC number: 203-905-0         Record number       01-2119475108-36         ①       Acute Tox. 4 - H302, Acute Tox. 4 -         H312, Acute Tox. 4 - H332, Skin Irrit. 2 -         H315, Eye Irrit. 2 - H319         titanium dioxide	%
<ul> <li>Hazard staten Void</li> <li>Compositi</li> <li>Chemical cha</li> <li>Description: Mixture of sub</li> <li>Dangerous cci CAS Number 111-76-2</li> </ul>	On and information of the ingredients of the ingredients.         aracterization: Mixtures         bistances listed below with nonhazardous additions.         omponents:         2-butoxyethanol         EC number: 203-905-0         Record number       01-2119475108-36         ①       Acute Tox. 4 - H302, Acute Tox. 4 -         H312, Acute Tox. 4 - H332, Skin Irrit. 2 -         H315, Eye Irrit. 2 - H319	% 1,00- 5,00



(continued of page 1)

#### 3912717

Reviewed on: 23/08/2021 Printing date: 23/08/2021

#### PRODUCT : HYDROFILL PREMIUM 6338-00 1C AND 2C

### 04 First-aid measures

- After inhalation:
- Supply fresh air; consult doctor in case of complaints.
- After skin contact:
- Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing:
- Do not induce vomiting; call for medical help immediately.

### 05 Fire-fighting measures

- Suitable extinguishing agents: CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- Special hazards arising from the substance or mixture
- Formation of toxic gases is possible during heating or in case of fire.
  Protective equipment: Mouth respiratory protective device. Do not inhale explosion gases or combustion gases.
- Additional information
   Cool endangered receptacles with water spray.
   Collect contaminated fire fighting water separately. It must not enter the sewage system.

### 06 Accidental release measures

- Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away. Ensure adequate ventilation
- Environmental precautions: Do not allow product to reach sewage system or any water course.
- Inform respective authorities in case of seepage into water course or sewage system.
- In case of seepage into the ground inform responsible authorities.
- Dilute with plenty of water.
  - In case of gas release or seepage into the ground inform responsible authorities.
  - Do not allow to enter sewers/ surface or ground water.
  - Methods and material for containment and cleaning up:
  - Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
  - Reference to other sections
     See Section 7 for information on safe handling.
     See Section 8 for information on personal protection equipment.
     See Section 13 for disposal information.

# 07 Handling and storage

#### • Handling:

- Precautions for safe handling
- Open and handle receptacle with care.
- Information about fire and explosion protection:
- Prevent impact and friction.
  - Storage:
  - Requirements to be met by storerooms and receptacles: Store only in the original receptacle.
  - Information about storage in one common storage facility: Not required.
- Further information about storage conditions:
- Protect from frost.
- Store in cool, dry conditions in well sealed receptacles.
- Protect from heat and direct sunlight.
- Specific end use(s)
  - No further relevant information available.

\*



Reviewed on: 23/08/2021 Printing date: 23/08/2021

		(continued of page 2
Exposure controls and	personal protection	
<ul> <li>Ingredients with limit values t</li> </ul>	that require monitoring at the workplace:	
111-76-2 2-butoxyeth	hanol	
PEL		
Long-term value	96.7	mg/m3
C C	20	ppm
(kulit)	-	
Additional information:		
The lists valid during the making	g were used as basis.	
<ul> <li>Personal protective equipment</li> </ul>		
General protective and hygienic		
	res are to be adhered to when handling chemic	cals.
Do not eat or drink while working Be sure to clean skin thoroughly		
Bespiratory protection: Suitable	e respiratory protective device recommended. L	lse suitable respiratory protective
device in case of insufficient ver		
	material has to be impermeable and resistant t	
	ts no recommendation to the glove material ca	
	re. Selection of the glove material on considera	ation of the penetration times, rates
<ul><li>of diffusion and the degradation</li><li>Material of gloves</li></ul>	Impervious gioves	
	oves does not only depend on the material, but	also on further marks of quality an
varies from manufacturer to ma	nufacturer. As the product is a preparation of s	several substances, the resistance
the glove material can not be ca	alculated in advance and has therefore to be ch	necked prior to the application.
<ul> <li>Penetration time of glove materi</li> </ul>		
	as to be found out by the manufacturer of the p	protective gloves and has to be
observed.		-
observed. The determined penetration time	es according to EN 374 part III are not perform	ned under practical conditions.
observed. The determined penetration time		ned under practical conditions.

# 09 Physical and chemical properties

Appearance:	
Form:	Liquid
Colour:	According to product specifica
Odour:	Characteristic Characteristic
Odour threshold:	Not determined.
Change in condition	
Melting point/freezing point:	0° 0
Initial boiling point and boiling range:	Undetermined.
Flash point:	Not applicable.
Flammability (solid, gas):	Not applicable.
Ignition temperature:	Undetermined.
Decomposition temperature:	Not determined.
Auto-ignition temperature:	Not determined.
Explosive properties:	Not determined.
Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
Vapour pressure:	at 20 °C 23,0000 mbar
Density:	1,3600 g/cm3
Solubility in / Miscibility with	

\*



Reviewed on: 23/08/2021 Printing date: 23/08/2021

PRODUCT : HYDROFILL	PREMIUM 6338-00 1C AND 2C	
		(continued of page 3)
water:	Not determined.	
Viscosity:		
	Not determined.	
	at 23 °C 37 - 42 s	
Other information	No further relevant information available.	

## 10 Stability and reactivity

Thermal decomposition / conditions to be avoided:

- No decomposition if used according to specifications.
- Incompatible materials:

No further relevant information available.

Hazardous decomposition products:

No dangerous decomposition products known.

# 11 Toxicological information

#### Acute toxicity

- LD/LC50 values relevant for classification:
- 111-76-2 2-butoxyethanol

Oral, LD50: 1746 mg/kg (rat) Oral, LD50: 1414 mg/kg (guinea Pig) Dermal, LD50: 2000 mg/kg (rat) Dermal, LD50: 1000 mg/kg (Rabbit) Dermal, LD50: 2000 mg/kg (guinea Pig) Oral, LD50: 790 mg/kg (rat) Dermal, LD50: 3400 mg kg (Rabbit) Inhalative, LC50/4h: 8000 mg/l (rat) Oral, LD50: 10000 mg/kg (rat) Oral, LD50: >20000 mg/kg (rat) Dermal, LD50: >10000 mg/kg (rat) Oral, LD50: >20000 mg/kg (rat) Dermal, LD50: >10000 mg/kg (rat) Oral, LD50: 2000 mg/kg (rat) Dermal, LD50: 20000 mg/k

71-36-3 butan-1-ol

7631-86-9 silicon dioxide, chemically prepared
--

#### 13463-67-7 titanium dioxide

57-55-6 Propylene glycol

- Primary irritant effect:
- Skin corrosion/irritation
- No irritant effect.
- Serious eye damage/irritation
- No irritating effect. Respiratory or skin sensitisation
- No sensitising effects known.
- Additional toxicological information: The product is not subject to classification according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version.

# 12 Ecological information

- Aquatic toxicity:
- No further relevant information available.
- Persistence and degradability
- No further relevant information available. *Behaviour in environmental systems:*
- Bioaccumulative potential
- No further relevant information available.
- Additional ecological information:
- General notes:
   Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water
   Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

(continued on page 5)



Reviewed on: 23/08/2021 Printing date: 23/08/2021

#### PRODUCT : HYDROFILL PREMIUM 6338-00 1C AND 2C

#### (continued of page 4)

# 13 Disposal information

#### Uncleaned packaging:

Recommendation:

Disposal must be made according to official regulations.

Recommended cleansing agents:

Water, if necessary together with cleansing agents.

UN-Number ADR	Void	
IMDG	Void	
ΙΑΤΑ	Void	
UN proper shippin		
ADR	Void	
IMDG	Void	
ΙΑΤΑ	Void	
<ul> <li>Transport hazard of ADR</li> </ul>	lass(es)	
Class	Void	
IMDG		
Class	Void	
ΙΑΤΑ		
Class	Void	
<ul> <li>Packing group</li> </ul>		
ADR	Void	
IMDG	Void	
ΙΑΤΑ	Void	
<ul> <li>Environmental haz Not applicable.</li> <li>Transport in bulk a Not applicable.</li> </ul>	ards: according to Annex II of MARPOL73/78 and the IBC C	Code

### 15 Regulatory information

#### • National regulations:

• Information about limitation of use:

The above-mentioned manufacturer's information on the handling of isoc yanates is contained in the safety data sheet of the product. The Euro pean Committee of Paint, Printing Ink and Artists 'Colours Manufacture rs' Associations (CEPE) provides the following information on coatings isocyanates: Ready-to-use paints containing isocyanates may have an ir ritant effect on mucous membranes - especially on breathing organs - a nd cause hypersensitivity reactions. Inhalation of vapour or spray mist may cause sensitisation. When handling paints containing isocyanates , all precautions required for solvent-containing paints must be follo wed. Vapour and spray mist in particular should not be inhaled. Person s who are allergic, asthmatic, or prone to respiratory ailments should not work with isocyanate-containing paints.

- Technical instructions (air):
- Class Share in %

T	3,64
III	0,23

- - Waterhazard class:

\*

\*



\_

### 3912717

Reviewed on: 23/08/2021 Printing date: 23/08/2021

	Water baz	zard class 1 (Self-assessment): slightly hazardous for water.	(continued of page 5)
	<ul> <li>EHS refer</li> </ul>		
	111-76-		
		-	
P			
	<u>16</u> Other In	nformation	
		ation is based on our present knowledge. However, this shall not constit	ute a guarantee for any specific
	<ul> <li>Product feature</li> <li>Relevant product feature</li> </ul>	ures and shall not establish a legally valid contractual relationship.	
	H302	Harmful if swallowed.	
	H312	Harmful if in contact with skin.	
	H315	Causes skin irritation.	
	H317	May cause allergic skin reaction.	
	H319	Causes serious eye irritation.	
	H332	Harmful if inhaled.	
	Environme • Abbreviati ADR: Acco concerning RID: Règli (Regulatio IMDG: Inte IATA: Inte ICAO: Inte GHS: Glob	ent issuing MSDS: ent protection department. tions and acronyms: cord européen sur le transport des marchandises dangereuses par Rout ig the International Carriage of Dangerous Goods by Road) lement international concernant le transport des marchandises dangere ons Concerning the International Transport of Dangerous Goods by Rail ternational Maritime Code for Dangerous Goods ernational Air Transport Association ernational Civil Aviation Organisation bally Harmonised System of Classification and Labelling of Chemicals European Inventory of Existing Commercial Chemical Substances	euses par chemin de fer
	ELINCS: E	European Inventory of Existing Commercial Chemical Substances European List of Notified Chemical Substances	
		emical Abstracts Service (division of the American Chemical Society)	
		thal concentration, 50 percent	
		thal dose, 50 percent mpared to the previous version altered.	