# **TEKNOS**

# according to 1907/2006/EC, Article 31

2929414

Reviewed on: 29/08/2022 Printing date: 29/08/2022

# SECTION 01: Identification of the substance/mixture and of the company undertaking

- 1.1 Product identifier
- · Trade name:

HYDROPUR 2K DECKLACK 7590

- Article number / Safety Data Sheet:
- 1.2 Relevant identified uses of the substance or mixture and uses advised against
- Application of the substance / the preparation Coating material
- · 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

Teknos AG

Industriestrasse 7

LI-9487 Gamprin-Bendern

T +423 375 94 00

F +423 375 94 99

- Further information obtainable from:
  - Product safety department. e-mail address: li-sdb@teknos.com
- 1.4 Emergency telephone number:

Swiss Toxicological Information Centre, CH-8032 Zürich Emergency telephone: +41 (0)44 251 51 51 (International)

# SECTION 02: Hazards identification

- · 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008
- Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting
- - · 2.2 Label elements
  - Labelling according to Regulation (EC) No 1272/2008
- Hazard pictograms
  - Void
- Signal word
  - Void
- · Hazard statements
- H412 Harmful to aquatic life with long lasting effects.
- EUH208 Contains BENZOTRIAZOL DERIVATIVES Index no. 607-176-00-3, 1,2- benzisothiazol-3(2H)-one, Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate, reaction mass of: 5-chloro-2-methyl-4- isothiazolin-3-one [EC no. 247-500-7] and 2- methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3: 1), Methyl1,2,2,6,6-pentamethyl-4-piperidyl. May produce an allergic reaction.
- Precautionary statements
- P273 Avoid release to the environment.
- P501 Dispose of contents/container in accordance with local/regional/ national/international regulations.
  - · 2.3 Other hazards
  - Results of PBT and vPvB assessment
  - PBT:

Not applicable.

vPvB:

Not applicable.

# SECTION 03: Composition/information on ingredients

- 3.2 Chemical characterization: Mixtures

Mixture of substances listed below with nonhazardous additions.

· Dangerous components:

**CAS Number** 64742-95-6

Solvent naphtha (petroleum), light arom.

1,00- 5,00

(continued on page 2)

# Page: 2 / 10 MATERIAL SAFETY DATA SHEET



# according to 1907/2006/EC, Article 31

2929414

Reviewed on: 29/08/2022 Printing date: 29/08/2022

PRODUCT :	HYDROPUR 2K DECKLACK 7590	(continued of page 1
	EC number: 265-199-0	(continued of page 1)
	Record number 01-2119455851-35	
	♦ Asp. Tox. 1 - H304; ♦ Flam. Liq. 3	
	- H226; Acute Tox. 4 - H332, STOT SE 3	
	- H335; Aquatic Chronic 2 - H411	
	·	
5131-66-8	3-butoxypropan-2-ol	1,00- 5,00
	EC number: 225-878-4	
	Record number 01-2119475527-28	
	Skin Irrit. 2 - H315, Eye Irrit. 2 -	
	H319	
108-01-0	2-dimethylaminoethanol	0,0015- 0,50
	EC number: 203-542-8	
	Record number 01-2119492298-24	
	Skin Corr. 1B - H314; 🏵 Flam. Liq.	
	3 - H226; 🔱 Acute Tox. 4 - H302, Acute	
	Tox. 4 - H312, Acute Tox. 4 - H332;	
	STOT SE 3; H335: C >= 5 %	
34590-94-8	Dipropylene glycol monomethyl ether	1,00- 5,00
	EC number: 252-104-2	
	Record number 01-2119450011-60	
	substance with a Community workplace	
	exposure limit.	
55965-84-9	reaction mass of: 5-chloro-2-methyl-4-	0,00-0,0015
	isothiazolin-3-one [EC no. 247-500-7] and 2-	
	methyl-2H-isothiazol-3-one [EC no. 220-239-	
	6] (3: 1)	
	Skin Corr. 1C - H314, Eye Dam. 1 -	
	H318; Acute Tox. 3 - H301, Acute Tox.	
	2 - H310, Acute Tox. 2 - H330; 🗘 Skin	
	Sens. 1A - H317; 锋 Aquatic Acute 1 -	
	H400 (M=100), Aquatic Chronic 1 - H410	
	(M=100);	
	Skin Corr. 1C; H314: C >= 0,6 %, Skin Irrit.	
	2; H315: 0,06 <= C < 0,6 %, Eye Dam. 1;	
	H318: C >= 0,6 %, Eye Irrit. 2; H319: 0,06	
	<= C < 0,6 %, Skin Sens. 1A; H317: C >= 0,	
	0015 %	
2634-33-5	1,2-benzisothiazol-3(2H)-one	0,0015- 0,50
	EC number: 220-120-9	
	Eye Dam. 1 - H318;	
	- H302, Skin Irrit. 2 - H315, Skin Sens. 1 -	
	H317; 🅸 Aquatic Acute 1 - H400;	
	Skin Sens. 1; H317: C >= 0,05 %	
111-76-2	2-butoxyethanol	1,00- 5,00
	-	(continued on page 3



# according to 1907/2006/EC, Article 31

#### 2929414

Reviewed on: 29/08/2022 Printing date: 29/08/2022

	PRODUCT:	HYDROPUR 2K DECKLACK 7590	
			(continued of page 2)
*		EC number: 203-905-0	
*		Record number 01-2119475108-36	
*		Acute Tox. 3 - H311; 🗘 Acute Tox.	
*		4 - H302, Acute Tox. 4 - H332, Skin Irrit. 2	
*		- H315, Eye Irrit. 2 - H319	
*	41556-26-7	Bis(1,2,2,6,6-pentamethyl-4-piperidyl)	0,50- 1,00
*		sebacate	
*		Record number 01-2119491304-40	
*		Skin Sens. 1 - H317; 🅸 Aquatic	
*		Acute 1 - H400, Aquatic Chronic 1 - H410	
*	82919-37-7	Methyl1,2,2,6,6-pentamethyl-4-piperidyl	0,0015- 0,50
*		EC number: 280-060-4	
*		Record number 01-2119976378-19	
*		Skin Sens. 1 - H317; 🍄 Aquatic	
*		Acute 1 - H400, Aquatic Chronic 1 - H410	
*		BENZOTRIAZOL DERIVATIVES Index no. 607-176-	0,0015- 0,50
*		00-3	
*		EC number: 400-830-7	
*		Record number 01-0000015075-76	
*		Skin Sens. 1 - H317; 🍄 Aquatic	
*		Chronic 2 - H411	
*	57-55-6	Propylene glycol	0,50- 1,00
*		EC number: 200-338-0	
*		Record number 01-2119456809-23	
*		Acute Tox. 4 - H302	
*	<ul> <li>Additional i For the wor</li> </ul>	information: ding of the listed risk phrases refer to section 16.	

# SECTION 04: First aid measures

- 4.1 Description of first aid measures
- After inhalation:
  - Supply fresh air; consult doctor in case of complaints.
  - After skin contact:
  - Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:
- Rinse opened eye for several minutes under running water.
- After swallowing:
- Do not induce vomiting; call for medical help immediately.
- Information for doctor:
- 4.2 Most important symptoms and effects, both acute and delayed
   No forth acute and delayed
  - No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

GB

# **TEKNOS**

### according to 1907/2006/EC, Article 31

2929414

Reviewed on: 29/08/2022 Printing date: 29/08/2022

PRODUCT: HYDROPUR 2K DECKLACK 7590

(continued of page 3)

### **SECTION 05: Firefighting measures**

- 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

• 5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

- 5.3 Advice for firefighters
- · Protective equipment:

Mouth respiratory protective device.

Do not inhale explosion gases or combustion gases.

· Additional information

Cool endangered receptacles with water spray.

Collect contaminated fire fighting water separately. It must not enter the sewage system.

# SECTION 06: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

In case of seepage into the ground inform responsible authorities.

Dilute with plenty of water.

In case of gas release or seepage into the ground inform responsible authorities.

Do not allow to enter sewers/surface or ground water.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

• 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

# SECTION 07: Handling and storage

- · Handling:
- 7.1 Precautions for safe handling
- Open and handle receptacle with care.
- Information about fire and explosion protection:
  - Prevent impact and friction.
  - 7.2 Conditions for safe storage, including any incompatibilities
  - · Storage:
  - · Requirements to be met by storerooms and receptacles:

Store only in the original receptacle.

Information about storage in one common storage facility:

Not required.

Further information about storage conditions:

Protect from frost.

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

• 7.3 Specific end use(s)

No further relevant information available.

GB

# according to 1907/2006/EC, Article 31

2929414

Reviewed on: 29/08/2022 Printing date: 29/08/2022

> PRODUCT: **HYDROPUR 2K DECKLACK 7590**

> > (continued of page 4)

#### SECTION 08: Exposure controls/personal protection

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

108-01-0 2-dimethylaminoethanol

WEL

Short-term value 22 mg/m3 6 ppm 7.4 Long-term value mg/m3

ppm

34590-94-8 Dipropylene glycol monomethyl ether

WEL

308 mg/m3 Long-term value 50

ppm

111-76-2 2-butoxyethanol

WEL

Short-term value 246 mg/m3 50 ppm Long-term value 123 mg/m3

> 25 ppm

Sk, BMGV

57-55-6 Propylene glycol

WEL

474\* 10\*\* Long-term value mg/m3 150\* ppm

\*total vapour and particulates \*\*particulates

· Ingredients with biological limit values:

111-76-2 2-butoxyethanol

**BMGV** 

240 mmol/mol creatinine

Medium: urine

Sampling time: post shift Parameter: butoxyacetic acid

Additional information:

The lists valid during the making were used as basis.

- 8.2 Exposure controls
- Personal protective equipment:
- General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Do not eat or drink while working.

Be sure to clean skin thoroughly after work and before breaks.

- Respiratory protection: Suitable respiratory protective device recommended. Use suitable respiratory protective device in case of insufficient ventilation.
  - Protection of hands: The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation Impervious gloves
  - Material of gloves

(continued on page 6)



# according to 1907/2006/EC, Article 31

2929414

Reviewed on: 29/08/2022 Printing date: 29/08/2022

#### PRODUCT: HYDROPUR 2K DECKLACK 7590

(continued of page 5)

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

The determined penetration times according to EN 374 part III are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

• Eye protection: Safety glasses

· Body protection: Protective work clothing

# SECTION 09: Physical and chemical properties

9.1 Information on basic physical and ch	emical properties		
Appearance			
Appearance:			
Form:	Liquid According to product specifica		
Colour:			
Odour:	Characteristic Characteristic		
Odour threshold:	Not determined. at 20 °C 8,0		
pH-value:			
Change in condition			
Melting point/freezing point:	0 °C		
Initial boiling point and boiling range:	Undetermined.		
Flash point:	Not applicable.		
Flammability (solid, gas):	Not applicable.		
Ignition temperature:	Undetermined.		
Decomposition temperature:	Not determined.  Not determined.		
Auto-ignition temperature:			
Explosive properties:	Not determined.		
Explosion limits:			
Lower:	Not determined.		
Upper:	Not determined.		
Vapour pressure:	at 20 °C 23,0000 mbar		
Density:	1,0400 g/cm3		
Solubility in / Miscibility with			
water:	Not determined.		
Viscosity:			
	Not determined.		
•	at 23 °C 120 - 150 s DIN 6 mm		
9.2 Other information	No further relevant information available.		

GB

# \*\*\* TEKNOS

# according to 1907/2006/EC, Article 31

2929414

Reviewed on: 29/08/2022 Printing date: 29/08/2022

PRODUCT: HYDROPUR 2K DECKLACK 7590

(continued of page 6)

# SECTION 10: Stability and reactivity

- 10.1 Reactivity
- No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions
- No dangerous reactions known.
- 10.4 Conditions to avoid
- No further relevant information available.
- 10.5 Incompatible materials:
- No further relevant information available.
- · 10.6 Hazardous decomposition products:

No dangerous decomposition products known.

# SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- Acute toxicity
- · LD/LC50 values relevant for classification:

#### 64742-95-6 Solvent naphtha (petroleum), light arom.

Oral, LD50: >6800 mg/kg (rat) Dermal, LD50: >3400 mg/kg (Rabbit) Inhalative, LC50/4h: >10,2 mg/l (rat)

#### 108-01-0 2-dimethylaminoethanol

Oral, LD50: 2000 mg/kg (rat)
Dermal, LD50: 1370 mg/kg (Rabbit)
Inhalative, LC50/4h: 3,25 mg/l (mouse)

# 102-71-6 Triethanolamine

Oral, LD50: 8000 mg/kg (rat)

#### 34590-94-8 Dipropylene glycol monomethyl ether

Oral, LD50: 5135 mg/kg (rat) Dermal, LD50: >19000 mg/kg (Rabbit)

# 7631-86-9 silicon dioxide, chemically prepared

Oral, LD50: 10000 mg/kg (rat)

### 111-76-2 2-butoxyethanol

Oral, LD50: 1746 mg/kg (rat)
Oral, LD50: 1414 mg/kg (guinea Pig)
Dermal, LD50: 2000 mg/kg (rat)
Dermal, LD50: 1000 mg/kg (Rabbit)
Dermal, LD50: 2000 mg/kg (guinea Pig)

#### 13463-41-7 Pyrithione zinc

Oral, LD50: 221 mg/kg (ATE) Inhalative, LC50/4h: 0,14 mg/l (ATE)

# 67-63-0 propan-2-ol

Oral, LD50: 5045 mg/kg (rat)

# Dermal, LD50: 12800 mg/kg (Rabbit) Inhalative, LC50/4h: 30 mg/l (rat)

# 57-55-6 Propylene glycol

Oral, LD50: 2000 mg/kg (rat)

Dermal, LD50: 20800 mg/kg (Rabbit)

- Primary irritant effect:
- · Skin corrosion/irritation

No irritant effect.

- Serious eye damage/irritation
   No irritation affect
  - No irritating effect.
- Respiratory or skin sensitisation
  - No sensitising effects known.
  - 11.2 Information on other hazards
  - Endocrine disrupting properties

(continued on page 8)



# according to 1907/2006/EC, Article 31

2929414

Reviewed on: 29/08/2022 Printing date: 29/08/2022

PRODUCT: HYDROPUR 2K DECKLACK 7590

(continued of page 7)

None of the ingredients is listed.

# **SECTION 12: Ecological information**

- 12.1 Toxicity
- · Aquatic toxicity:

No further relevant information available.

12.2 Persistence and degradability

No further relevant information available.

- · Behaviour in environmental systems:
- 12.3 Bioaccumulative potential
- No further relevant information available.
- 12.4 Mobility in soil

No further relevant information available.

- · Ecotoxical effects:
- · Remark:

Harmful to fish

- · Additional ecological information:
- · General notes:

Harmful to aquatic organisms

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- 12.5 Results of PBT and vPvB assessment
- PBT:
- Not applicable.
- vPvB:
- Not applicable.
- 12.6 Other adverse effects

No further relevant information available.

# **SECTION 13: Disposal considerations**

- · 13.1 Waste treatment methods
- European and swiss waste code

08

WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS

08 01

wastes from MFSU and removal of paint and varnish

08 01 19

aqueous suspensions containing paint or varnish containing organic solvents or other hazardous substances

- · Uncleaned packaging:
- Recommendation:

Disposal must be made according to official regulations.

• Recommended cleansing agents:

Water, if necessary together with cleansing agents.

# **SECTION 14: Transport information**

• 14.1 UN-Number

ADR Void

IMDG Void

IATA Void

• 14.2 UN proper shipping name

ADR Void

IMDG Void

(continued on page 9)



### according to 1907/2006/EC, Article 31

2929414

Reviewed on: 29/08/2022 Printing date: 29/08/2022

> PRODUCT: **HYDROPUR 2K DECKLACK 7590**

> > (continued of page 8)

IATA Void · 14.3 Transport hazard class(es)

**ADR** 

Class

Void

**IMDG** 

Class

Void

Void

IATA

Class

· 14.4 Packing group

ADR Void **IMDG** Void IATA Void

• 14.5 Environmental hazards:

Not applicable.

- 14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable.
- · Transport/Additional information: Not applicable.

# SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
  DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment - Annex II
- None of the ingredients is listed.
- REGULATION (EU) 2019/1148
- · Annex I RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))
- None of the ingredients is listed.
- Annex II REPORTABLE EXPLOSIVES PRECURSORS
  - None of the ingredients is listed.
  - REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3, 40
  - National regulations:
  - Technical instructions (air):
  - Class Share in %

2,95 Ι 0,58

· Waterhazard class:

Water hazard class 1 (Self-assessment): slightly hazardous for water.

15.2 Chemical safety assessment:

A Chemical Safety Assessment has not been carried out.

# **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H226 Flammable liquid and vapour.

H301 Toxic if swallowed. H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H310 Fatal in contact with skin. H311 Toxic in contact with skin.

(continued on page 10)

Page: 10 / 10

# MATERIAL SAFETY DATA SHEET



# according to 1907/2006/EC, Article 31

2929414

Reviewed on: 29/08/2022 Printing date: 29/08/2022

	PRODUCT:	HYDROPUR 2K DECKLACK 7590	
			(continued of page 9)
*	H312	Harmful in contact with skin.	, , ,
*	H314	Causes severe skin burns and eye damage.	
*	H315	Causes skin irritation.	
*	H317	May cause an allergic skin reaction.	
*	H318	Causes serious eye damage.	
*	H319	Causes serious eye irritation.	
*	H330	Fatal if inhaled.	
*	H332	Harmful if inhaled.	
*	H335	May cause respiratory irritation.	
*	H400	Very toxic to aquatic life.	
*	H410	Very toxic to aquatic life with long lasting effects.	
*	H411	Toxic to aquatic life with long lasting effects.	

#### · Department issuing MSDS:

Environment protection department.

Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association ICAO: International Civil Aviation Organisation

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative \* Data compared to the previous version altered.