according to 2001/58 EC



2929213

Reviewed on: 30/06/2021 Printing date: 01/07/2021

01 Identification of the substance/mixture and of the company/undertaking

- · Product identifier
- · Trade name: HYDROPUR 2K DECKLACK 7590
- Article number / Safety Data Sheet: 759000
- · Details of the supplier of the safety data sheet
- Manufacturer/Supplier:
- Teknos AG
- Industriestrasse 7

LI-9487 Gamprin-Bendern

T +423 375 94 00

F +423 375 94 99

- Further information obtainable from:
 - Product safety department. e-mail address: li-sdb@teknos.com
- Emergency telephone number:
- Swiss Toxicological Information Centre, CH-8032 Zürich Emergency telephone: +41 (0)44 251 51 51 (International)

02 Hazards identification

Classification of the substance or mixture



GHS07

Skin Sensitizer - Category 1 - H317 May cause an allergic skin

H402 Harmful to aquatic life.

Aquatic Chronic 3 - H412 Harmful to aquatic life with long lasting effects.

- Label elements
- GHS label elements
- Hazard pictograms



GHS07

- Signal word Warning
- Hazard-determining components of labelling:

2-butoxyethanol / Solvent naphtha (petroleum), light arom. / Bis(1,2, 2,6,6-pentamethyl-4-piperidyl)sebacate

Hazard statements

H317 May cause an allergic skin reaction.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P272 Contaminated work clothing should not be allowed out of the workplace.

P273 Avoid release to the environment.

P280 Wear protective gloves.

P302+P352 IF ON SKIN: Wash with plenty of water.

P501 Dispose of contents/container in accordance with local/regional/ national/international regulations.

CDN

**TEKNOS

according to 2001/58 EC

2929213

Reviewed on: 30/06/2021 Printing date: 01/07/2021

PRODUCT: HYDROPUR 2K DECKLACK 7590

Composition	on/information on ingredients	(continued of page
	racterization: Mixtures	
 Description: Mixture of subs 	tances listed below with nonhazardous additions.	
Dangerous con	nponents:	
CAS Number	•	%
64742-95-6	Solvent naphtha (petroleum), light arom.	1,00- 5,00
	EC number: 265-199-0	
	Record number 01-2119455851-35	
	Aspiration Hazard - Category 1 - H304;	
	Acute Toxicity (Inhalation) - Category	
	4 - H332, Specific Target Organ Toxicity -	
	Single Exposure - Category 3 - H335; Flammable Liquids - Category 4 - H227;	
E101 CC 0	Aquatic Chronic 2 - H411; H401	1,00- 5,00
5131-66-8	3-butoxypropan-2-ol EC number: 225-878-4	1,00- 5,00
	Record number 01-2119475527-28	
	Skin Irritation - Category 2 - H315,	
	Eye Irritation - Category 2A - H319;	
	Flammable Liquids - Category 4 - H227	
108-01-0	2-dimethylaminoethanol	0,00- 0,50
	EC number: 203-542-8	
	Record number 01-2119492298-24	
	Skin Corrosion - Category 1B - H314;	
	Flammable Liquids - Category 3 - H226;	
	Acute Toxicity (Oral) - Category 4 -	
	H302, Acute Toxicity (Dermal) - Category 4 -	
	H312, Acute Toxicity (Inhalation) - Category	
	4 - H332	
102-71-6	Triethanolamine EC number: 203-049-8	0,50- 1,00
	Record number 01-2119486482-31	
34590-94-8	Dipropylene glycol monomethyl ether	1,00- 5,00
	EC number: 252-104-2	, ,
	Record number 01-2119450011-60	
	Flammable Liquids - Category 4 - H227	
55965-84-9	reaction mass of: 5-chloro-2-methyl-4-	0,00- 0,50
	isothiazolin-3-one [EC no. 247-500-7] and 2-	
	methyl-2H-isothiazol-3-one [EC no. 220-239-	
	6] (3: 1) ♦ Skin Corrosion - Category 1B - H314;	
	Acute Toxicity (Oral) - Category 3 -	
	H301, Acute Toxicity (Dermal) - Category 3 - H311, Acute Toxicity (Inhalation) - Category	
	3 - H331; Skin Sensitizer - Category 1	
	- H317; Aquatic Acute 1 - H400,	
	Aquatic Chronic 1 - H410	
111-76-2	2-butoxyethanol	1,00- 5,00
· · · · · -		(continued on page

according to 2001/58 EC



2929213

Reviewed on: 30/06/2021 Printing date: 01/07/2021

PRODUCT:	HYDROPUR 2K DECKLACK 7590	
	EC number: 203-905-0 Record number 01-2119475108-36 Acute Toxicity (Oral) - Category 4 -	(continued of page 2)
	H302, Acute Toxicity (Dermal) - Category 4 - H312, Acute Toxicity (Inhalation) - Category 4 - H332, Skin Irritation - Category 2 - H315, Eye Irritation - Category 2A - H319; Flammable Liquids - Category 4 - H227	
41556-26-7	Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate Record number 01-2119491304-40 ❖ Skin Sensitizer - Category 1 - H317; ❖ Aquatic Acute 1 - H400, Aquatic Chronic 1 - H410; Flammable Liquids - Category 4 - H227	0,50- 1,00
82919-37-7	Methyl1,2,2,6,6-pentamethyl-4-piperidyl EC number: 280-060-4 Record number 01-2119976378-19 ◆ Skin Sensitizer - Category 1 - H317; Aquatic Acute 1 - H400, Aquatic Chronic 1 - H410	0,00- 0,50
	BENZOTRIAZOL DERIVATIVES Index no. 607-176-00-3 EC number: 400-830-7 Record number 01-0000015075-76 Skin Sensitizer - Category 1 - H317; Aquatic Chronic 2 - H411	0,00- 0,50
57-55-6	Propylene glycol EC number: 200-338-0 Record number 01-2119456809-23 Acute Toxicity (Oral) - Category 4 -	0,50- 1,00

04 First aid measures

· After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

After skin contact:

Immediately wash with water and soap and rinse thoroughly.

After eye contact:

Rinse opened eye for several minutes under running water.

· After swallowing:

Do not induce vomiting; call for medical help immediately.

CDN

according to 2001/58 EC



2929213

Reviewed on: 30/06/2021 Printing date: 01/07/2021

PRODUCT: HYDROPUR 2K DECKLACK 7590

(continued of page 3)

05 Firefighting measures

· Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

Protective equipment:

Mouth respiratory protective device.

Do not inhale explosion gases or combustion gases.

· Additional information

Cool endangered receptacles with water spray.

Collect contaminated fire fighting water separately. It must not enter the sewage system.

06 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

· Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

07 Handling and storage

- · Handling:
- Precautions for safe handling

Prevent formation of aerosols.

· Information about fire - and explosion protection:

No special measures required.

Storage:

Requirements to be met by storerooms and receptacles:

Store only in the original receptacle.

Information about storage in one common storage facility:

Not required.

Further information about storage conditions:

Protect from frost.

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

Specific end use(s)

No further relevant information available.

08 Exposure controls/personal protection

· Ingredients with limit values that require monitoring at the workplace:

108-01-0 2-dimethylaminoethanol

E۷

Short-term value	22	mg/m3
	6	ppm
Long-term value	11	mg/m3
	3	ppm (continued on page 5)

TEKNOS

according to 2001/58 EC

2929213

Reviewed on: 30/06/2021 Printing date: 01/07/2021

PRODUCT:	HYDROPUR 2K DECKLACK 7590
----------	----------------------------------

ODOOI	i i i i bi o i i z i b	LONLAGIC 7550	
			(continued of page 4)
102-71-6 Triethanolamine		ine	
EL			
	Long-term value	5	mg/m3
EV			
Long-term value		3.1	mg/m3
		0.5	ppm
34590-94-8 Dipropylene glyce		glycol monomethyl ether	
EL			
	Short-term value	150	ppm
	Long-term value	100	ppm
	Skin		
EV			
	Short-term value	910	mg/m3
		150	ppm
	Long-term value	605	mg/m3
		100	ppm
111-76-2	2-butoxyetha	nol	
EL			
	Long-term value	20	ppm
EV			
	Long-term value	20	ppm
	Skin		
57-55-6	Propylene gly	ycol	
EV			
	Long-term value	155* 10**	mg/m3
		50*	ppm
	*vanour and aerosol·**a	erosol only	

*vapour and aerosol;**aerosol only

Additional information:

The lists valid during the making were used as basis.

- · Personal protective equipment:
- General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Immediately remove all soiled and contaminated clothing

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

Do not eat or drink while working.

Be sure to clean skin thoroughly after work and before breaks.

- Respiratory protection: In case of brief exposure or low pollution use respiratory filter device. In case of intensive
 or longer exposure use self-contained respiratory protective device. Suitable respiratory protective device
 recommended. Use suitable respiratory protective device in case of insufficient ventilation.
- Protection of hands: The glove material has to be impermeable and resistant to the product/ the substance/ the
 preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the
 preparation/ the chemical mixture. Selection of the glove material on consideration of the penetration times, rates
 of diffusion and the degradation Protective gloves Impervious gloves
- Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

The determined penetration times according to EN 374 part III are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

- Eye protection: Safety glasses
- · Body protection: Protective work clothing

according to 2001/58 EC



2929213

Reviewed on: 30/06/2021 Printing date: 01/07/2021

PRODUCT: HYDROPUR 2K DECKLACK 7590

(continued of page 5)

09 Physical and chemical properties

Appearance: Form:

Form: Liquid

Colour:According to product specificaOdour:Characteristic Characteristic

Undetermined.

Not determined.

Odour threshold: Not determined.

Change in condition

Melting point/freezing point: 0 °C

Initial boiling point and boiling range:

Flash point: Not applicable.
Flammability (solid, gas): Not applicable.
Ignition temperature: Undetermined.
Decomposition temperature: Not determined.
Auto-ignition temperature: Not determined.

Explosive properties:

Explosion limits:

Lower: Not determined.

Upper: Not determined.

Vapour pressure: at 20 °C 23,0000 mbar

Density: 1,0300 g/cm3

Solubility in / Miscibility with

water: Not determined.

Viscosity:

Not determined.

. at 23 °C 60 - 70 s

Other information No further relevant information available.

10 Stability and reactivity

- Thermal decomposition / conditions to be avoided:
- No decomposition if used according to specifications.
- · Incompatible materials:
 - No further relevant information available.
- · Hazardous decomposition products:

No dangerous decomposition products known.

11 Toxicological information

- Acute toxicity
- LD/LC50 values relevant for classification:

64742-95-6 Solvent naphtha (petroleum), light arom.

Oral, LD50: >6800 mg/kg (rat) Dermal, LD50: >3400 mg/kg (Rabbit) Inhalative, LC50/4h: >10,2 mg/l (rat) Oral, LD50: 2000 mg/kg (rat) Dermal, LD50: 1370 mg/kg (Rabbit) Inhalative, LC50/4h: 3,25 mg/l (mouse) Oral, LD50: 8000 mg/kg (rat) Oral, LD50: 5135 mg/kg (rat) Dermal, LD50: >19000 mg/kg (Rabbit) Oral, LD50: 10000 mg/kg (rat) Oral, LD50: 1746 mg/kg (rat) Oral, LD50: 1414 mg/kg (guinea Pig) Dermal, LD50: 2000 mg/kg (rat) Dermal, LD50: 1000 mg/kg (Rabbit) Dermal, LD50: 1000 mg/kg (Rabbit) Dermal, LD50: 1000 mg/kg (Rabbit) Dermal, LD50: 2000 mg/kg (guinea Pig) Oral, LD50: 5045 mg/kg (rat) Dermal, LD50: 12800 mg/kg (Rabbit) Inhalative, LC50/4h: 30 mg/l (rat) Oral, LD50: 2000 mg/kg (rat) Dermal, LD50: 20800 mg/kg (Rabbit)

108-01-0 2-dimethylaminoethanol

102-71-6 Triethanolamine

34590-94-8 Dipropylene glycol monomethyl ether

(continued on page 7)

according to 2001/58 EC



2929213

Reviewed on: 30/06/2021 Printing date: 01/07/2021

PRODUCT: HYDROPUR 2K DECKLACK 7590

(continued of page 6)

7631-86-9 silicon dioxide, chemically prepared

111-76-2 2-butoxyethanol 67-63-0 propan-2-ol 57-55-6 Propylene glycol

• Primary irritant effect:

 Skin corrosion/irritation No irritant effect.

Serious eye damage/irritation

No irritating effect.

· Respiratory or skin sensitisation

Sensitisation possible through skin contact.

· Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Irritant

12 Ecological information

· Aquatic toxicity:

No further relevant information available.

· Persistence and degradability

No further relevant information available.

Behaviour in environmental systems:

Bioaccumulative potential

No further relevant information available.

• Ecotoxical effects:

Remark:

Harmful to fish

· Additional ecological information:

· General notes:

Harmful to aquatic organisms

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

13 Disposal considerations

- · Uncleaned packaging:
- Recommendation:

Disposal must be made according to official regulations.

Recommended cleansing agents:

Water, if necessary together with cleansing agents.

14 Transport information

UN-Number

TDG Void
IMDG Void
IATA Void

• UN proper shipping name

TDG Void
IMDG Void
IATA Void

Transport hazard class(es)
 TDG (Transport dangerous goods):
 TDG class: Void

IMDG

Class Void

(continued on page 8)

according to 2001/58 EC



2929213

Reviewed on: 30/06/2021 Printing date: 01/07/2021

PRODUCT: HYDROPUR 2K DECKLACK 7590

(continued of page 7)

IATA

Class Void

Packing group

TDG Void
IMDG Void
IATA Void

- · Environmental hazards:
 - Not applicable
- Transport in bulk according to Annex II of MARPOL73/78 and the IBC Not applicable.
- · Transport/Additional information:

Not applicable.

15 Regulatory information

- · National regulations:
- · Classification according to VbF:

_

- Technical instructions (air):
- Class Share in %

I 2,98 III 0,58

· Waterhazard class:

Water hazard class 1 (Self-assessment): slightly hazardous for water.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H226 Flammable liquid and vapour.

H227 Combustible liquid. H301 Toxic if swallowed. H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H311 Toxic in contact with skin.
H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.

H331 Toxic if inhaled.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H400 Very toxic to aquatic life.
H401 Toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.
H411 Toxic to aquatic life with long lasting effects.

Department issuing MSDS:

Environment protection department.

Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association ICAO: International Civil Aviation Organisation

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

(continued on page 9)

Page: 9/9

MATERIAL SAFETY DATA SHEET

₹ TEKNOS

according to 2001/58 EC

2929213

Reviewed on: 30/06/2021 Printing date: 01/07/2021

PRODUCT: **HYDROPUR 2K DECKLACK 7590**

(continued of page 8)

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VbF: Verordnung über brennbare Flüssigkeiten, Österreich (Ordinance on the storage of combustible liquids,

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

* Data compared to the previous version altered.