

SAFETY DATA SHEET



OW COMBI 2315-05

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : OW COMBI 2315-05

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Paint.

1.3 Details of the supplier of the safety data sheet

Teknos Group Oy, Takkatie 3, FI-00370 HELSINKI, FINLAND. Tel. +358 9 506 091.

e-mail address of person responsible for this SDS : Prod-safe@teknos.com

National contact

Teknos Group Oy, Takkatie 3, FI-00370 HELSINKI, FINLAND. Tel. +358 9 506 091.

1.4 Emergency telephone number

National advisory body/Poison Centre

Telephone number : In an emergency, call 112

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Flam. Liq. 2, H225
Skin Irrit. 2, H315
Eye Dam. 1, H318
Repr. 2, H361d
STOT SE 3, H336
STOT RE 2, H373

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Hazard pictograms :



Signal word : Danger

Hazard statements :

- H225 - Highly flammable liquid and vapour.
- H315 - Causes skin irritation.
- H318 - Causes serious eye damage.
- H336 - May cause drowsiness or dizziness.
- H361d - Suspected of damaging the unborn child.
- H373 - May cause damage to organs through prolonged or repeated exposure.

Precautionary statements

SECTION 2: Hazards identification

| | |
|---|---|
| Prevention | : P280 - Wear protective gloves, protective clothing, eye protection, face protection, or hearing protection. P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P260 - Do not breathe vapour. |
| Response | : P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. |
| Storage | : P403 + P233 - Store in a well-ventilated place. Keep container tightly closed. |
| Disposal | : P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations. |
| Hazardous ingredients | : Contains: n-Butyl acetate; Toluene and iso-butanol |
| Supplemental label elements | : |
| Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles | : |

2.3 Other hazards

| | |
|--|---|
| Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII | : This mixture does not contain any substances that are assessed to be a PBT or a vPvB. |
| Other hazards which do not result in classification | : None known. |

SECTION 3: Composition/information on ingredients

3.2 Mixtures : Mixture

| Product/ingredient name | Identifiers | % | Classification | Specific Conc. Limits, M-factors and ATEs | Type |
|-------------------------|--|-----------|--|---|---------|
| n-Butyl acetate | REACH #: 01-2119485493-29 EC: 204-658-1 CAS: 123-86-4 Index: 607-025-00-1 | ≥10 - ≤25 | Flam. Liq. 3, H226 STOT SE 3, H336 EUH066 | - | [1] [2] |
| acetone | REACH #: 01-2119471330-49 EC: 200-662-2 CAS: 67-64-1 Index: 606-001-00-8 | ≥10 - <25 | Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336 EUH066 | EUH066: C ≥ 25% | [1] [2] |
| Toluene | REACH #: 01-2119471310-51 EC: 203-625-9 CAS: 108-88-3 Index: 601-021-00-3 | ≥10 - ≤25 | Flam. Liq. 2, H225 Skin Irrit. 2, H315 Repr. 2, H361d STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304 | - | [1] [2] |
| Xylene | REACH #: 01-2119488216-32 EC: 215-535-7 CAS: 1330-20-7 Index: 601-022-00-9 | <10 | Flam. Liq. 3, H226 Acute Tox. 4, H312 Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 STOT RE 2, H373 (oral, inhalation) Asp. Tox. 1, H304 | ATE [Dermal] = 1100 mg/kg ATE [Inhalation (vapours)] = 11 mg/ l | [1] [2] |

SECTION 3: Composition/information on ingredients

| | | | | | |
|---------------------|--|------|--|---|---------|
| Ethyl acetate | REACH #: 01-2119475103-46 EC: 205-500-4 CAS: 141-78-6 Index: 607-022-00-5 | ≤10 | Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336 EUH066 | - | [1] [2] |
| iso-butanol | REACH #: 01-2119484609-23 EC: 201-148-0 CAS: 78-83-1 Index: 603-108-00-1 | ≤8.4 | Flam. Liq. 3, H226 Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H335 STOT SE 3, H336 | - | [1] |
| Propan-2-ol | REACH #: 01-2119457558-25 EC: 200-661-7 CAS: 67-63-0 Index: 603-117-00-0 | ≤5 | Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336 | - | [1] |
| Ethylbenzene | REACH #: 01-2119489370-35 EC: 202-849-4 CAS: 100-41-4 Index: 601-023-00-4 | ≤3 | Flam. Liq. 2, H225 Acute Tox. 4, H332 STOT RE 2, H373 (hearing organs) (oral, inhalation) Asp. Tox. 1, H304 | ATE [Inhalation (vapours)] = 11 mg/l | [1] [2] |
| 1-Ethoxy-2-propanol | REACH #: 01-2119462792-32 EC: 216-374-5 CAS: 1569-02-4 Index: 603-177-00-8 | ≤3 | Flam. Liq. 3, H226 STOT SE 3, H336 See Section 16 for the full text of the H statements declared above. | - | [1] |

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

Eye contact

- : Get medical attention immediately. Call a poison center or physician. Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician.

Inhalation

- : Get medical attention immediately. Call a poison center or physician. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

SECTION 4: First aid measures

- Skin contact** : Get medical attention immediately. Call a poison center or physician. Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Chemical burns must be treated promptly by a physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:
pain
watering
redness
- Inhalation** : Adverse symptoms may include the following:
nausea or vomiting
headache
drowsiness/fatigue
dizziness/vertigo
unconsciousness
reduced foetal weight
increase in foetal deaths
skeletal malformations
- Skin contact** : Adverse symptoms may include the following:
pain or irritation
redness
blistering may occur
reduced foetal weight
increase in foetal deaths
skeletal malformations
- Ingestion** : Adverse symptoms may include the following:
stomach pains
reduced foetal weight
increase in foetal deaths
skeletal malformations

4.3 Indication of any immediate medical attention and special treatment needed

- Notes to physician** : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Specific treatments** : No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media** : Use dry chemical, CO₂, water spray (fog) or foam.
- Unsuitable extinguishing media** : Do not use water jet.

5.2 Special hazards arising from the substance or mixture

- Hazards from the substance or mixture** : Highly flammable liquid and vapour. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion.
- Hazardous combustion products** : Decomposition products may include the following materials:
carbon dioxide
carbon monoxide
nitrogen oxides
metal oxide/oxides

5.3 Advice for firefighters

- Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Do not breathe vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions

- : Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

6.3 Methods and material for containment and cleaning up

- Small spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product.

SECTION 6: Accidental release measures

6.4 Reference to other sections : See Section 1 for emergency contact information.
See Section 8 for information on appropriate personal protective equipment.
See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapour or mist. Do not ingest. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Eliminate all ignition sources. Separate from oxidising materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

Seveso Directive - Reporting thresholds

Danger criteria

| Category | Notification and MAPP threshold | Safety report threshold |
|----------|---------------------------------|-------------------------|
| P5c | 5000 tonne | 50000 tonne |

7.3 Specific end use(s)

Recommendations : Not available.

Industrial sector specific solutions : Not available.

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

8.1 Control parameters

Occupational exposure limits

SECTION 8: Exposure controls/personal protection

| Product/ingredient name | Exposure limit values |
|-------------------------|---|
| n-Butyl acetate | <p>Regulation on Limit Values - MAC (Austria, 4/2021). [Butyl acetate (all isomers except tert-butyl acetate)] CEIL: 480 mg/m³ 15 minutes. CEIL: 100 ppm 15 minutes. TWA: 241 mg/m³ 8 hours. TWA: 50 ppm 8 hours.</p> |
| acetone | <p>Regulation on Limit Values - MAC (Austria, 4/2021). TWA: 500 ppm 8 hours. TWA: 1200 mg/m³ 8 hours. PEAK: 2000 ppm, 4 times per shift, 15 minutes. PEAK: 4800 mg/m³, 4 times per shift, 15 minutes.</p> |
| Toluene | <p>Regulation on Limit Values - MAC (Austria, 4/2021). Absorbed through skin. TWA: 50 ppm 8 hours. TWA: 190 mg/m³ 8 hours. PEAK: 100 ppm, 4 times per shift, 15 minutes. PEAK: 380 mg/m³, 4 times per shift, 15 minutes.</p> |
| Xylene | <p>Regulation on Limit Values - MAC (Austria, 4/2021). [Xylenes (all isomers)] PEAK: 442 mg/m³, 4 times per shift, 15 minutes. TWA: 50 ppm 8 hours. PEAK: 100 ppm, 4 times per shift, 15 minutes. TWA: 221 mg/m³ 8 hours.</p> |
| Ethyl acetate | <p>Regulation on Limit Values - MAC (Austria, 4/2021). TWA: 200 ppm 8 hours. TWA: 734 mg/m³ 8 hours. PEAK: 1468 mg/m³, 4 times per shift, 15 minutes. PEAK: 400 ppm, 4 times per shift, 15 minutes.</p> |
| iso-butanol | <p>Regulation on Limit Values - MAC (Austria, 4/2021). [Butanol (all isomers except 2-methyl-2-propanol)] PEAK: 200 ppm, 4 times per shift, 15 minutes. TWA: 150 mg/m³ 8 hours. TWA: 50 ppm 8 hours. PEAK: 600 mg/m³, 4 times per shift, 15 minutes.</p> |
| Propan-2-ol | <p>Regulation on Limit Values - MAC (Austria, 4/2021). TWA: 200 ppm 8 hours. TWA: 500 mg/m³ 8 hours. PEAK: 800 ppm, 4 times per shift, 15 minutes. PEAK: 2000 mg/m³, 4 times per shift, 15 minutes.</p> |
| Ethylbenzene | <p>Regulation on Limit Values - MAC (Austria, 4/2021). Absorbed through skin. TWA: 100 ppm 8 hours. TWA: 440 mg/m³ 8 hours. CEIL: 200 ppm, 8 times per shift, 5 minutes. CEIL: 880 mg/m³, 8 times per shift, 5 minutes.</p> |
| 1-Ethoxy-2-propanol | <p>Regulation on Limit Values - MAC (Austria, 4/2021). STEL: 880 mg/m³ 15 minutes. STEL: 200 ppm 15 minutes. TWA: 220 mg/m³ 8 hours. TWA: 50 ppm 8 hours.</p> |
| n-Butyl acetate | <p>Limit values (Belgium, 5/2021). [butyl acetate, all isomers] STEL: 712 mg/m³ 15 minutes. STEL: 150 ppm 15 minutes. TWA: 238 mg/m³ 8 hours. TWA: 50 ppm 8 hours.</p> |
| acetone | <p>Limit values (Belgium, 5/2021). TWA: 246 ppm 8 hours. TWA: 594 mg/m³ 8 hours. STEL: 492 ppm 15 minutes. STEL: 1187 mg/m³ 15 minutes.</p> |
| Toluene | <p>Limit values (Belgium, 5/2021). Absorbed through skin. TWA: 20 ppm 8 hours. TWA: 77 mg/m³ 8 hours.</p> |

SECTION 8: Exposure controls/personal protection

| | |
|-----------------|--|
| Xylene | <p>STEL: 100 ppm 15 minutes. STEL: 384 mg/m³ 15 minutes.</p> <p>Limit values (Belgium, 5/2021). [Xylene] Absorbed through skin.</p> <p>TWA: 50 ppm 8 hours. TWA: 221 mg/m³ 8 hours. STEL: 100 ppm 15 minutes. STEL: 442 mg/m³ 15 minutes.</p> |
| Ethyl acetate | <p>Limit values (Belgium, 5/2021).</p> <p>TWA: 200 ppm 8 hours. TWA: 734 mg/m³ 8 hours. STEL: 1468 mg/m³ 15 minutes. STEL: 400 ppm 15 minutes.</p> |
| iso-butanol | <p>Limit values (Belgium, 5/2021).</p> <p>TWA: 50 ppm 8 hours. TWA: 154 mg/m³ 8 hours.</p> |
| Propan-2-ol | <p>Limit values (Belgium, 5/2021).</p> <p>TWA: 200 ppm 8 hours. TWA: 500 mg/m³ 8 hours. STEL: 400 ppm 15 minutes. STEL: 1000 mg/m³ 15 minutes.</p> |
| Ethylbenzene | <p>Limit values (Belgium, 5/2021). Absorbed through skin.</p> <p>TWA: 20 ppm 8 hours. TWA: 87 mg/m³ 8 hours. STEL: 125 ppm 15 minutes. STEL: 551 mg/m³ 15 minutes.</p> |
| n-Butyl acetate | <p>Ministry of Labour and Social Policy and the Ministry of Health - Ordinance No 13/2003. (Bulgaria, 6/2021).</p> <p>Limit value 8 hours: 241 mg/m³ 8 hours. Limit value 15 min: 723 mg/m³ 15 minutes. Limit value 15 min: 150 ppm 15 minutes. Limit value 8 hours: 50 ppm 8 hours.</p> |
| acetone | <p>Ministry of Labour and Social Policy and the Ministry of Health - Ordinance No 13/2003. (Bulgaria, 6/2021).</p> <p>Limit value 8 hours: 600 mg/m³ 8 hours. Limit value 15 min: 1400 mg/m³ 15 minutes.</p> |
| Toluene | <p>Ministry of Labour and Social Policy and the Ministry of Health - Ordinance No 13/2003. (Bulgaria, 6/2021). Absorbed through skin.</p> <p>Limit value 15 min: 384 mg/m³ 15 minutes. Limit value 8 hours: 192 mg/m³ 8 hours. Limit value 15 min: 100 ppm 15 minutes. Limit value 8 hours: 50 ppm 8 hours.</p> |
| Xylene | <p>Ministry of Labour and Social Policy and the Ministry of Health - Ordinance No 13/2003. (Bulgaria, 6/2021). [Xylene (mixture of isomers), pure] Absorbed through skin.</p> <p>Limit value 8 hours: 221 mg/m³ 8 hours. Limit value 15 min: 442 mg/m³ 15 minutes. Limit value 15 min: 100 ppm 15 minutes. Limit value 8 hours: 50 ppm 8 hours.</p> |
| Ethyl acetate | <p>Ministry of Labour and Social Policy and the Ministry of Health - Ordinance No 13/2003. (Bulgaria, 6/2021).</p> <p>Limit value 8 hours: 734 mg/m³ 8 hours. Limit value 15 min: 400 ppm 15 minutes. Limit value 15 min: 1468 mg/m³ 15 minutes. Limit value 8 hours: 200 ppm 8 hours.</p> |
| Propan-2-ol | <p>Ministry of Labour and Social Policy and the Ministry of Health - Ordinance No 13/2003. (Bulgaria, 6/2021).</p> <p>Limit value 8 hours: 980 mg/m³ 8 hours. Limit value 15 min: 1225 mg/m³ 15 minutes.</p> |
| Ethylbenzene | <p>Ministry of Labour and Social Policy and the Ministry of Health - Ordinance No 13/2003. (Bulgaria, 6/2021). Absorbed through skin.</p> <p>Limit value 8 hours: 435 mg/m³ 8 hours. Limit value 15 min: 545 mg/m³ 15 minutes.</p> |

SECTION 8: Exposure controls/personal protection

| | |
|-----------------|---|
| n-Butyl acetate | <p>Ministry of Economy, Labour and Entrepreneurship ELV/ STELV (Croatia, 1/2021). STELV: 723 mg/m³ 15 minutes. STELV: 150 ppm 15 minutes. ELV: 241 mg/m³ 8 hours. ELV: 50 ppm 8 hours.</p> |
| acetone | <p>Ministry of Economy, Labour and Entrepreneurship ELV/ STELV (Croatia, 1/2021). ELV: 1210 mg/m³ 8 hours. ELV: 500 ppm 8 hours.</p> |
| Toluene | <p>Ministry of Economy, Labour and Entrepreneurship ELV/ STELV (Croatia, 1/2021). Absorbed through skin. STELV: 384 mg/m³ 15 minutes. STELV: 100 ppm 15 minutes. ELV: 192 mg/m³ 8 hours. ELV: 50 ppm 8 hours.</p> |
| Xylene | <p>Ministry of Economy, Labour and Entrepreneurship ELV/ STELV (Croatia, 1/2021). [xylene (all isomers)] Absorbed through skin. STELV: 442 mg/m³ 15 minutes. STELV: 100 ppm 15 minutes. ELV: 221 mg/m³ 8 hours. ELV: 50 ppm 8 hours.</p> |
| Ethyl acetate | <p>Ministry of Economy, Labour and Entrepreneurship ELV/ STELV (Croatia, 1/2021). STELV: 400 ppm 15 minutes. ELV: 200 ppm 8 hours. STELV: 1468 mg/m³ 15 minutes. ELV: 734 mg/m³ 8 hours.</p> |
| iso-butanol | <p>Ministry of Economy, Labour and Entrepreneurship ELV/ STELV (Croatia, 1/2021). Absorbed through skin. STELV: 231 mg/m³ 15 minutes. STELV: 75 ppm 15 minutes. ELV: 154 mg/m³ 8 hours. ELV: 50 ppm 8 hours.</p> |
| Propan-2-ol | <p>Ministry of Economy, Labour and Entrepreneurship ELV/ STELV (Croatia, 1/2021). STELV: 1250 mg/m³ 15 minutes. STELV: 500 ppm 15 minutes. ELV: 999 mg/m³ 8 hours. ELV: 400 ppm 8 hours.</p> |
| Ethylbenzene | <p>Ministry of Economy, Labour and Entrepreneurship ELV/ STELV (Croatia, 1/2021). Absorbed through skin. STELV: 884 mg/m³ 15 minutes. STELV: 200 ppm 15 minutes. ELV: 442 mg/m³ 8 hours. ELV: 100 ppm 8 hours.</p> |
| n-Butyl acetate | <p>Department of labour inspection (Cyprus, 7/2021). STEL: 150 ppm 15 minutes. STEL: 723 mg/m³ 15 minutes. TWA: 50 ppm 8 hours. TWA: 241 mg/m³ 8 hours.</p> |
| acetone | <p>Department of labour inspection (Cyprus, 7/2021). Absorbed through skin. TWA: 500 ppm 8 hours. TWA: 1210 mg/m³ 8 hours.</p> |
| Toluene | <p>Department of labour inspection (Cyprus, 7/2021). Absorbed through skin. STEL: 100 ppm 15 minutes. STEL: 384 mg/m³ 15 minutes. TWA: 50 ppm 8 hours. TWA: 192 mg/m³ 8 hours.</p> |
| Xylene | <p>Department of labour inspection (Cyprus, 7/2021). [Xylene, mixed isomers] Absorbed through skin.</p> |

SECTION 8: Exposure controls/personal protection

| | |
|-----------------|---|
| Ethyl acetate | <p>STEL: 100 ppm 15 minutes. STEL: 442 mg/m³ 15 minutes. TWA: 50 ppm 8 hours. TWA: 221 mg/m³ 8 hours.</p> <p>Department of labour inspection (Cyprus, 7/2021). STEL: 400 ppm 15 minutes. STEL: 1468 mg/m³ 15 minutes. TWA: 200 ppm 8 hours. TWA: 734 mg/m³ 8 hours.</p> |
| Ethylbenzene | <p>Department of labour inspection (Cyprus, 7/2021). Absorbed through skin. STEL: 884 mg/m³ 15 minutes. TWA: 100 ppm 8 hours. TWA: 442 mg/m³ 8 hours. STEL: 200 ppm 15 minutes.</p> |
| n-Butyl acetate | <p>Government regulation of Czech Republic PEL/NPK-P (Czech Republic, 10/2022). TWA: 241 mg/m³ 8 hours. STEL: 723 mg/m³ 15 minutes. STEL: 149.661 ppm 15 minutes. TWA: 49.887 ppm 8 hours.</p> |
| acetone | <p>Government regulation of Czech Republic PEL/NPK-P (Czech Republic, 10/2022). TWA: 800 mg/m³ 8 hours. STEL: 1500 mg/m³ 15 minutes. STEL: 621 ppm 15 minutes. TWA: 331.2 ppm 8 hours.</p> |
| Toluene | <p>Government regulation of Czech Republic PEL/NPK-P (Czech Republic, 10/2022). Absorbed through skin. TWA: 192 mg/m³ 8 hours. TWA: 50.112 ppm 8 hours. STEL: 384 mg/m³ 15 minutes. STEL: 100.224 ppm 15 minutes.</p> |
| Xylene | <p>Government regulation of Czech Republic PEL/NPK-P (Czech Republic, 10/2022). [xylene, technical mixture of isomers and all isomers] Absorbed through skin. TWA: 200 mg/m³ 8 hours. TWA: 45.4 ppm 8 hours. STEL: 400 mg/m³ 15 minutes. STEL: 90.8 ppm 15 minutes.</p> |
| Ethyl acetate | <p>Government regulation of Czech Republic PEL/NPK-P (Czech Republic, 10/2022). TWA: 700 mg/m³ 8 hours. TWA: 191.1 ppm 8 hours. STEL: 900 mg/m³ 15 minutes. STEL: 245.7 ppm 15 minutes.</p> |
| iso-butanol | <p>Government regulation of Czech Republic PEL/NPK-P (Czech Republic, 10/2022). [Butanol (all isomers)] Absorbed through skin. TWA: 300 mg/m³ 8 hours. TWA: 97.5 ppm 8 hours. STEL: 600 mg/m³ 15 minutes. STEL: 195 ppm 15 minutes.</p> |
| Propan-2-ol | <p>Government regulation of Czech Republic PEL/NPK-P (Czech Republic, 10/2022). Absorbed through skin. TWA: 500 mg/m³ 8 hours. TWA: 200 ppm 8 hours. STEL: 1000 mg/m³ 15 minutes. STEL: 400 ppm 15 minutes.</p> |
| Ethylbenzene | <p>Government regulation of Czech Republic PEL/NPK-P (Czech Republic, 10/2022). Absorbed through skin. TWA: 200 mg/m³ 8 hours. TWA: 45.4 ppm 8 hours. STEL: 500 mg/m³ 15 minutes. STEL: 113.5 ppm 15 minutes.</p> |

SECTION 8: Exposure controls/personal protection

| | |
|---------------------|--|
| 1-Ethoxy-2-propanol | Government regulation of Czech Republic PEL/NPK-P (Czech Republic, 10/2022). STEL: 550 mg/m ³ 15 minutes. TWA: 270 mg/m ³ 8 hours. TWA: 62.37 ppm 8 hours. STEL: 127.05 ppm 15 minutes. |
| n-Butyl acetate | Working Environment Authority (Denmark, 6/2022). [Butyl acetate, all isomers] TWA: 50 ppm 8 hours. TWA: 241 mg/m ³ 8 hours. STEL: 723 mg/m ³ 15 minutes. STEL: 150 ppm 15 minutes. |
| acetone | Working Environment Authority (Denmark, 6/2022). TWA: 250 ppm 8 hours. TWA: 600 mg/m ³ 8 hours. STEL: 1200 mg/m ³ 15 minutes. STEL: 500 ppm 15 minutes. |
| Toluene | Working Environment Authority (Denmark, 6/2022). Absorbed through skin. TWA: 25 ppm 8 hours. TWA: 94 mg/m ³ 8 hours. STEL: 384 mg/m ³ 15 minutes. STEL: 100 ppm 15 minutes. |
| Xylene | Working Environment Authority (Denmark, 6/2022). [Xylenes, all isomers] Absorbed through skin. TWA: 25 ppm 8 hours. TWA: 109 mg/m ³ 8 hours. STEL: 442 mg/m ³ 15 minutes. STEL: 100 ppm 15 minutes. |
| Ethyl acetate | Working Environment Authority (Denmark, 6/2022). TWA: 150 ppm 8 hours. TWA: 540 mg/m ³ 8 hours. STEL: 1468 mg/m ³ 15 minutes. STEL: 400 ppm 15 minutes. |
| iso-butanol | Working Environment Authority (Denmark, 6/2022). [Butanol, all isomers] Absorbed through skin. CEIL: 50 ppm CEIL: 150 mg/m ³ |
| Propan-2-ol | Working Environment Authority (Denmark, 6/2022). Absorbed through skin. TWA: 200 ppm 8 hours. TWA: 490 mg/m ³ 8 hours. STEL: 980 mg/m ³ 15 minutes. STEL: 400 ppm 15 minutes. |
| Ethylbenzene | Working Environment Authority (Denmark, 6/2022). Absorbed through skin. Carcinogen. TWA: 50 ppm 8 hours. TWA: 217 mg/m ³ 8 hours. STEL: 434 mg/m ³ 15 minutes. STEL: 100 ppm 15 minutes. |
| n-Butyl acetate | Occupational exposure limits, Regulation No. 293 (Estonia, 12/2022). STEL: 150 ppm 15 minutes. STEL: 723 mg/m ³ 15 minutes. TWA: 50 ppm 8 hours. TWA: 241 mg/m ³ 8 hours. |
| acetone | Occupational exposure limits, Regulation No. 293 (Estonia, 12/2022). TWA: 1210 mg/m ³ 8 hours. TWA: 500 ppm 8 hours. |
| Toluene | Occupational exposure limits, Regulation No. 293 (Estonia, 12/2022). Absorbed through skin. TWA: 192 mg/m ³ 8 hours. TWA: 50 ppm 8 hours. |

SECTION 8: Exposure controls/personal protection

| | |
|-----------------|---|
| Xylene | <p>STEL: 384 mg/m³ 15 minutes. STEL: 100 ppm 15 minutes. Occupational exposure limits, Regulation No. 293 (Estonia, 12/2022). [Xylenes] Absorbed through skin. TWA: 50 ppm 8 hours. STEL: 100 ppm 15 minutes. STEL: 450 mg/m³ 15 minutes. TWA: 200 mg/m³ 8 hours.</p> |
| Ethyl acetate | <p>Occupational exposure limits, Regulation No. 293 (Estonia, 12/2022). TWA: 500 mg/m³ 8 hours. TWA: 150 ppm 8 hours. STEL: 1100 mg/m³ 15 minutes. STEL: 300 ppm 15 minutes.</p> |
| iso-butanol | <p>Occupational exposure limits, Regulation No. 293 (Estonia, 12/2022). TWA: 150 mg/m³ 8 hours. TWA: 50 ppm 8 hours.</p> |
| Propan-2-ol | <p>Occupational exposure limits, Regulation No. 293 (Estonia, 12/2022). TWA: 350 mg/m³ 8 hours. TWA: 150 ppm 8 hours. STEL: 600 mg/m³ 15 minutes. STEL: 250 ppm 15 minutes.</p> |
| Ethylbenzene | <p>Occupational exposure limits, Regulation No. 293 (Estonia, 12/2022). Absorbed through skin. Skin sensitiser. TWA: 442 mg/m³ 8 hours. TWA: 100 ppm 8 hours. STEL: 884 mg/m³ 15 minutes. STEL: 200 ppm 15 minutes.</p> |
| n-Butyl acetate | <p>EU OEL (Europe, 1/2022). Notes: list of indicative occupational exposure limit values STEL: 150 ppm 15 minutes. STEL: 723 mg/m³ 15 minutes. TWA: 241 mg/m³ 8 hours. TWA: 50 ppm 8 hours.</p> |
| acetone | <p>EU OEL (Europe, 1/2022). Notes: list of indicative occupational exposure limit values TWA: 500 ppm 8 hours. TWA: 1210 mg/m³ 8 hours.</p> |
| Toluene | <p>EU OEL (Europe, 1/2022). Absorbed through skin. Notes: list of indicative occupational exposure limit values TWA: 192 mg/m³ 8 hours. TWA: 50 ppm 8 hours. STEL: 384 mg/m³ 15 minutes. STEL: 100 ppm 15 minutes.</p> |
| Xylene | <p>EU OEL (Europe, 1/2022). [xylene, mixed isomers pure] Absorbed through skin. Notes: list of indicative occupational exposure limit values TWA: 50 ppm 8 hours. TWA: 221 mg/m³ 8 hours. STEL: 100 ppm 15 minutes. STEL: 442 mg/m³ 15 minutes.</p> |
| Ethyl acetate | <p>EU OEL (Europe, 1/2022). Notes: list of indicative occupational exposure limit values STEL: 400 ppm 15 minutes. STEL: 1468 mg/m³ 15 minutes. TWA: 200 ppm 8 hours. TWA: 734 mg/m³ 8 hours.</p> |
| Ethylbenzene | <p>EU OEL (Europe, 1/2022). Absorbed through skin. Notes: list of indicative occupational exposure limit values TWA: 100 ppm 8 hours. TWA: 442 mg/m³ 8 hours. STEL: 200 ppm 15 minutes. STEL: 884 mg/m³ 15 minutes.</p> |

SECTION 8: Exposure controls/personal protection

| | |
|-----------------|---|
| n-Butyl acetate | Institute of Occupational Health, Ministry of Social Affairs (Finland, 10/2021). TWA: 150 ppm 8 hours. TWA: 720 mg/m ³ 8 hours. STEL: 200 ppm 15 minutes. STEL: 960 mg/m ³ 15 minutes. |
| acetone | Institute of Occupational Health, Ministry of Social Affairs (Finland, 10/2021). TWA: 500 ppm 8 hours. TWA: 1200 mg/m ³ 8 hours. STEL: 630 ppm 15 minutes. STEL: 1500 mg/m ³ 15 minutes. |
| Toluene | Institute of Occupational Health, Ministry of Social Affairs (Finland, 10/2021). Absorbed through skin. Ototoxicant. TWA: 25 ppm 8 hours. TWA: 81 mg/m ³ 8 hours. STEL: 100 ppm 15 minutes. STEL: 380 mg/m ³ 15 minutes. |
| Xylene | Institute of Occupational Health, Ministry of Social Affairs (Finland, 10/2021). [Xylenes] Absorbed through skin. STEL: 440 mg/m ³ 15 minutes. TWA: 220 mg/m ³ 8 hours. TWA: 50 ppm 8 hours. STEL: 100 ppm 15 minutes. |
| Ethyl acetate | Institute of Occupational Health, Ministry of Social Affairs (Finland, 10/2021). TWA: 200 ppm 8 hours. TWA: 730 mg/m ³ 8 hours. STEL: 400 ppm 15 minutes. STEL: 1470 mg/m ³ 15 minutes. |
| iso-butanol | Institute of Occupational Health, Ministry of Social Affairs (Finland, 10/2021). [Butanols] Absorbed through skin. TWA: 50 ppm 8 hours. TWA: 150 mg/m ³ 8 hours. STEL: 75 ppm 15 minutes. STEL: 230 mg/m ³ 15 minutes. |
| Propan-2-ol | Institute of Occupational Health, Ministry of Social Affairs (Finland, 10/2021). TWA: 200 ppm 8 hours. TWA: 500 mg/m ³ 8 hours. STEL: 250 ppm 15 minutes. STEL: 620 mg/m ³ 15 minutes. |
| Ethylbenzene | Institute of Occupational Health, Ministry of Social Affairs (Finland, 10/2021). Absorbed through skin. TWA: 50 ppm 8 hours. TWA: 220 mg/m ³ 8 hours. STEL: 200 ppm 15 minutes. STEL: 880 mg/m ³ 15 minutes. |
| n-Butyl acetate | Ministry of Labor (France, 10/2022). Notes: Binding regulatory limit values (article R. 4412-149 of the Labor Code) TWA: 50 ppm 8 hours. TWA: 241 mg/m ³ 8 hours. STEL: 150 ppm 15 minutes. STEL: 723 mg/m ³ 15 minutes. |
| acetone | Ministry of Labor (France, 10/2022). Notes: Binding regulatory limit values (article R. 4412-149 of the Labor Code) TWA: 500 ppm 8 hours. TWA: 1210 mg/m ³ 8 hours. STEL: 2420 mg/m ³ 15 minutes. STEL: 1000 ppm 15 minutes. |
| Toluene | Ministry of Labor (France, 10/2022). Absorbed through skin. Notes: Binding regulatory limit values (article R. 4412-149 of the Labor Code) TWA: 20 ppm 8 hours. |

SECTION 8: Exposure controls/personal protection

| | |
|-----------------|--|
| Xylene | <p>TWA: 76.8 mg/m³ 8 hours. STEL: 100 ppm 15 minutes. STEL: 384 mg/m³ 15 minutes.</p> <p>Ministry of Labor (France, 10/2022). [xylenes, mixed isomers, pure] Absorbed through skin. Notes: Binding regulatory limit values (article R. 4412-149 of the Labor Code)</p> <p>STEL: 442 mg/m³ 15 minutes. STEL: 100 ppm 15 minutes. TWA: 221 mg/m³ 8 hours. TWA: 50 ppm 8 hours.</p> |
| Ethyl acetate | <p>Ministry of Labor (France, 10/2022). Notes: Binding regulatory limit values (article R. 4412-149 of the Labor Code)</p> <p>TWA: 200 ppm 8 hours. TWA: 734 mg/m³ 8 hours. STEL: 1468 mg/m³ 15 minutes. STEL: 400 ppm 15 minutes.</p> |
| iso-butanol | <p>Ministry of Labor (France, 10/2022). Notes: Permissible limit values (circulars)</p> <p>TWA: 50 ppm 8 hours. TWA: 150 mg/m³ 8 hours.</p> |
| Propan-2-ol | <p>Ministry of Labor (France, 10/2022). Notes: Permissible limit values (circulars)</p> <p>STEL: 400 ppm 15 minutes. STEL: 980 mg/m³ 15 minutes.</p> |
| Ethylbenzene | <p>Ministry of Labor (France, 10/2022). Absorbed through skin. Notes: Binding regulatory limit values (article R. 4412-149 of the Labor Code)</p> <p>TWA: 20 ppm 8 hours. TWA: 88.4 mg/m³ 8 hours. STEL: 442 mg/m³ 15 minutes. STEL: 100 ppm 15 minutes.</p> |
| n-Butyl acetate | <p>DFG MAC-values list (Germany, 7/2022).</p> <p>TWA: 100 ppm 8 hours. PEAK: 200 ppm, 4 times per shift, 15 minutes. TWA: 480 mg/m³ 8 hours. PEAK: 960 mg/m³, 4 times per shift, 15 minutes.</p> <p>TRGS 900 OEL (Germany, 6/2022).</p> <p>TWA: 300 mg/m³ 8 hours. TWA: 62 ppm 8 hours. PEAK: 600 mg/m³ 15 minutes. PEAK: 124 ppm 15 minutes.</p> |
| acetone | <p>TRGS 900 OEL (Germany, 6/2022).</p> <p>TWA: 1200 mg/m³ 8 hours. PEAK: 2400 mg/m³ 15 minutes. TWA: 500 ppm 8 hours. PEAK: 1000 ppm 15 minutes.</p> <p>DFG MAC-values list (Germany, 7/2022).</p> <p>TWA: 500 ppm 8 hours. PEAK: 1000 ppm, 4 times per shift, 15 minutes. TWA: 1200 mg/m³ 8 hours. PEAK: 2400 mg/m³, 4 times per shift, 15 minutes.</p> |
| Toluene | <p>TRGS 900 OEL (Germany, 6/2022). Absorbed through skin.</p> <p>TWA: 190 mg/m³ 8 hours. PEAK: 380 mg/m³ 15 minutes. TWA: 50 ppm 8 hours. PEAK: 100 ppm 15 minutes.</p> <p>DFG MAC-values list (Germany, 7/2022). Absorbed through skin.</p> <p>TWA: 50 ppm 8 hours. PEAK: 100 ppm, 4 times per shift, 15 minutes. TWA: 190 mg/m³ 8 hours. PEAK: 380 mg/m³, 4 times per shift, 15 minutes.</p> |
| Xylene | <p>TRGS 900 OEL (Germany, 6/2022). [xylene] Absorbed through skin.</p> <p>TWA: 220 mg/m³ 8 hours.</p> |

SECTION 8: Exposure controls/personal protection

Ethyl acetate

PEAK: 440 mg/m³ 15 minutes.
TWA: 50 ppm 8 hours.
PEAK: 100 ppm 15 minutes.
DFG MAC-values list (Germany, 7/2022). [Xylene (all isomers)]
Absorbed through skin.
TWA: 50 ppm 8 hours.
PEAK: 100 ppm, 4 times per shift, 15 minutes.
TWA: 220 mg/m³ 8 hours.
PEAK: 440 mg/m³, 4 times per shift, 15 minutes.
TRGS 900 OEL (Germany, 6/2022).
TWA: 730 mg/m³ 8 hours.
PEAK: 1460 mg/m³ 15 minutes.
TWA: 200 ppm 8 hours.
PEAK: 400 ppm 15 minutes.

iso-butanol

DFG MAC-values list (Germany, 7/2022).
TWA: 200 ppm 8 hours.
PEAK: 400 ppm, 4 times per shift, 15 minutes.
TWA: 750 mg/m³ 8 hours.
PEAK: 1500 mg/m³, 4 times per shift, 15 minutes.
TRGS 900 OEL (Germany, 6/2022).
TWA: 310 mg/m³ 8 hours.
PEAK: 310 mg/m³ 15 minutes.
TWA: 100 ppm 8 hours.
PEAK: 100 ppm 15 minutes.

Propan-2-ol

DFG MAC-values list (Germany, 7/2022).
TWA: 100 ppm 8 hours.
PEAK: 100 ppm, 4 times per shift, 15 minutes.
TWA: 310 mg/m³ 8 hours.
PEAK: 310 mg/m³, 4 times per shift, 15 minutes.
TRGS 900 OEL (Germany, 6/2022).
TWA: 500 mg/m³ 8 hours.
PEAK: 1000 mg/m³ 15 minutes.
TWA: 200 ppm 8 hours.
PEAK: 400 ppm 15 minutes.

Ethylbenzene

DFG MAC-values list (Germany, 7/2022).
TWA: 200 ppm 8 hours.
PEAK: 400 ppm, 4 times per shift, 15 minutes.
TWA: 500 mg/m³ 8 hours.
PEAK: 1000 mg/m³, 4 times per shift, 15 minutes.
TRGS 900 OEL (Germany, 6/2022). Absorbed through skin.
TWA: 88 mg/m³ 8 hours.
PEAK: 176 mg/m³ 15 minutes.
TWA: 20 ppm 8 hours.
PEAK: 40 ppm 15 minutes.

1-Ethoxy-2-propanol

DFG MAC-values list (Germany, 7/2022). Absorbed through skin.
PEAK: 40 ppm, 4 times per shift, 15 minutes.
PEAK: 176 mg/m³, 4 times per shift, 15 minutes.
TWA: 88 mg/m³ 8 hours.
TWA: 20 ppm 8 hours.
DFG MAC-values list (Germany, 7/2022). Absorbed through skin.
TWA: 86 mg/m³ 8 hours.
PEAK: 172 mg/m³, 4 times per shift, 15 minutes.
TWA: 20 ppm 8 hours.
PEAK: 40 ppm, 4 times per shift, 15 minutes.
TRGS 900 OEL (Germany, 6/2022). Absorbed through skin.
TWA: 86 mg/m³ 8 hours.
PEAK: 172 mg/m³ 15 minutes.
TWA: 20 ppm 8 hours.
PEAK: 40 ppm 15 minutes.

SECTION 8: Exposure controls/personal protection

| | |
|-----------------|---|
| n-Butyl acetate | <p>Presidential Decree 307/1986: Occupational exposure limit values (Greece, 9/2021). TWA: 50 ppm 8 hours. TWA: 241 mg/m³ 8 hours. STEL: 150 ppm 15 minutes. STEL: 723 mg/m³ 15 minutes.</p> |
| acetone | <p>Presidential Decree 307/1986: Occupational exposure limit values (Greece, 9/2021). TWA: 1780 mg/m³ 8 hours. STEL: 3560 mg/m³ 15 minutes.</p> |
| Toluene | <p>Presidential Decree 307/1986: Occupational exposure limit values (Greece, 9/2021). Absorbed through skin. TWA: 50 ppm 8 hours. TWA: 192 mg/m³ 8 hours. STEL: 100 ppm 15 minutes. STEL: 384 mg/m³ 15 minutes.</p> |
| Xylene | <p>Presidential Decree 307/1986: Occupational exposure limit values (Greece, 9/2021). [Xylenes (all isomers)] Absorbed through skin. TWA: 100 ppm 8 hours. TWA: 435 mg/m³ 8 hours. STEL: 150 ppm 15 minutes. STEL: 650 mg/m³ 15 minutes.</p> |
| Ethyl acetate | <p>Presidential Decree 307/1986: Occupational exposure limit values (Greece, 9/2021). TWA: 200 ppm 8 hours. TWA: 734 mg/m³ 8 hours. STEL: 1468 mg/m³ 15 minutes. STEL: 400 ppm 15 minutes.</p> |
| iso-butanol | <p>Presidential Decree 307/1986: Occupational exposure limit values (Greece, 9/2021). TWA: 100 ppm 8 hours. TWA: 300 mg/m³ 8 hours. STEL: 100 ppm 15 minutes. STEL: 300 mg/m³ 15 minutes.</p> |
| Propan-2-ol | <p>Presidential Decree 307/1986: Occupational exposure limit values (Greece, 9/2021). TWA: 400 ppm 8 hours. TWA: 980 mg/m³ 8 hours. STEL: 500 ppm 15 minutes. STEL: 1225 mg/m³ 15 minutes.</p> |
| Ethylbenzene | <p>Presidential Decree 307/1986: Occupational exposure limit values (Greece, 9/2021). TWA: 100 ppm 8 hours. TWA: 435 mg/m³ 8 hours. STEL: 125 ppm 15 minutes. STEL: 545 mg/m³ 15 minutes.</p> |
| n-Butyl acetate | <p>5/2020. (II. 6.) ITM Decree (Hungary, 12/2022). Skin sensitiser. Inhalation sensitiser. TWA: 241 mg/m³ 8 hours. PEAK: 723 mg/m³ 15 minutes. PEAK: 150 ppm 15 minutes. TWA: 50 ppm 8 hours.</p> |
| acetone | <p>5/2020. (II. 6.) ITM Decree (Hungary, 12/2022). Skin sensitiser. Inhalation sensitiser. TWA: 1210 mg/m³ 8 hours. TWA: 500 ppm 8 hours.</p> |
| Toluene | <p>5/2020. (II. 6.) ITM Decree (Hungary, 12/2022). Absorbed through skin. Skin sensitiser. Inhalation sensitiser. TWA: 192 mg/m³ 8 hours. PEAK: 384 mg/m³ 15 minutes. PEAK: 100 ppm 15 minutes. TWA: 50 ppm 8 hours.</p> |
| Xylene | <p>5/2020. (II. 6.) ITM Decree (Hungary, 12/2022). [xylene, mixture</p> |

SECTION 8: Exposure controls/personal protection

| | |
|-----------------|--|
| Ethyl acetate | <p>of isomers] Absorbed through skin. TWA: 221 mg/m³ 8 hours. PEAK: 442 mg/m³ 15 minutes. PEAK: 100 ppm 15 minutes. TWA: 50 ppm 8 hours. 5/2020. (II. 6.) ITM Decree (Hungary, 12/2022). Skin sensitiser. Inhalation sensitiser. TWA: 734 mg/m³ 8 hours. PEAK: 1468 mg/m³ 15 minutes. PEAK: 400 ppm 15 minutes. TWA: 200 ppm 8 hours.</p> |
| Propan-2-ol | <p>5/2020. (II. 6.) ITM Decree (Hungary, 12/2022). Absorbed through skin. Skin sensitiser. Inhalation sensitiser. TWA: 500 mg/m³ 8 hours. PEAK: 1000 mg/m³ 15 minutes. PEAK: 400 ppm 15 minutes. TWA: 200 ppm 8 hours.</p> |
| Ethylbenzene | <p>5/2020. (II. 6.) ITM Decree (Hungary, 12/2022). Absorbed through skin. Skin sensitiser. Inhalation sensitiser. TWA: 442 mg/m³ 8 hours. PEAK: 884 mg/m³ 15 minutes. PEAK: 200 ppm 15 minutes. TWA: 100 ppm 8 hours.</p> |
| n-Butyl acetate | <p>Ministry of Welfare, List of Exposure Limits (Iceland, 5/2021). [butyl acetate, all isomers] TWA: 241 mg/m³ 8 hours. TWA: 50 ppm 8 hours. STEL: 723 mg/m³ 15 minutes. STEL: 150 ppm 15 minutes.</p> |
| acetone | <p>Ministry of Welfare, List of Exposure Limits (Iceland, 5/2021). TWA: 600 mg/m³ 8 hours. TWA: 250 ppm 8 hours.</p> |
| Toluene | <p>Ministry of Welfare, List of Exposure Limits (Iceland, 5/2021). Absorbed through skin. STEL: 188 mg/m³ 15 minutes. STEL: 50 ppm 15 minutes. TWA: 94 mg/m³ 8 hours. TWA: 25 ppm 8 hours.</p> |
| Xylene | <p>Ministry of Welfare, List of Exposure Limits (Iceland, 5/2021). [xylene, all isomers] Absorbed through skin. STEL: 442 mg/m³ 15 minutes. STEL: 100 ppm 15 minutes. TWA: 109 mg/m³ 8 hours. TWA: 25 ppm 8 hours.</p> |
| Ethyl acetate | <p>Ministry of Welfare, List of Exposure Limits (Iceland, 5/2021). TWA: 540 mg/m³ 8 hours. TWA: 150 ppm 8 hours.</p> |
| iso-butanol | <p>Ministry of Welfare, List of Exposure Limits (Iceland, 5/2021). [butanol, all isomers, except n-butanol] Absorbed through skin. STEL: 150 mg/m³ 15 minutes. STEL: 50 ppm 15 minutes.</p> |
| Ethylbenzene | <p>Ministry of Welfare, List of Exposure Limits (Iceland, 5/2021). Absorbed through skin. STEL: 884 mg/m³ 15 minutes. STEL: 200 ppm 15 minutes. TWA: 200 mg/m³ 8 hours. TWA: 50 ppm 8 hours.</p> |

SECTION 8: Exposure controls/personal protection

| | |
|-----------------|--|
| n-Butyl acetate | <p>NAOSH (Ireland, 5/2021). Notes: EU derived Occupational Exposure Limit Values</p> <p>OELV-8hr: 50 ppm 8 hours. OELV-8hr: 241 mg/m³ 8 hours. OELV-15min: 150 ppm 15 minutes. OELV-15min: 723 mg/m³ 15 minutes.</p> |
| acetone | <p>NAOSH (Ireland, 5/2021). Notes: EU derived Occupational Exposure Limit Values</p> <p>OELV-8hr: 500 ppm 8 hours. OELV-8hr: 1210 mg/m³ 8 hours.</p> |
| Toluene | <p>NAOSH (Ireland, 5/2021). Absorbed through skin. Notes: EU derived Occupational Exposure Limit Values</p> <p>OELV-8hr: 50 ppm 8 hours. OELV-8hr: 192 mg/m³ 8 hours. OELV-15min: 100 ppm 15 minutes. OELV-15min: 384 mg/m³ 15 minutes.</p> |
| Xylene | <p>NAOSH (Ireland, 5/2021). [xylene mixed isomers] Absorbed through skin. Notes: EU derived Occupational Exposure Limit Values</p> <p>OELV-8hr: 50 ppm 8 hours. OELV-8hr: 221 mg/m³ 8 hours. OELV-15min: 100 ppm 15 minutes. OELV-15min: 442 mg/m³ 15 minutes.</p> |
| Ethyl acetate | <p>NAOSH (Ireland, 5/2021). Notes: EU derived Occupational Exposure Limit Values</p> <p>OELV-8hr: 200 ppm 8 hours. OELV-15min: 400 ppm 15 minutes. OELV-15min: 1468 mg/m³ 15 minutes. OELV-8hr: 734 mg/m³ 8 hours.</p> |
| iso-butanol | <p>NAOSH (Ireland, 5/2021). Notes: Advisory Occupational Exposure Limit Values (OELVs)</p> <p>OELV-8hr: 50 ppm 8 hours. OELV-8hr: 150 mg/m³ 8 hours. OELV-15min: 75 ppm 15 minutes. OELV-15min: 225 mg/m³ 15 minutes.</p> |
| Propan-2-ol | <p>NAOSH (Ireland, 5/2021). Absorbed through skin. Notes: Advisory Occupational Exposure Limit Values (OELVs)</p> <p>OELV-8hr: 200 ppm 8 hours. OELV-15min: 400 ppm 15 minutes.</p> |
| Ethylbenzene | <p>NAOSH (Ireland, 5/2021). Absorbed through skin. Notes: EU derived Occupational Exposure Limit Values</p> <p>OELV-8hr: 100 ppm 8 hours. OELV-8hr: 442 mg/m³ 8 hours. OELV-15min: 200 ppm 15 minutes. OELV-15min: 884 mg/m³ 15 minutes.</p> |
| n-Butyl acetate | <p>EU OEL (Europe, 1/2022). Notes: list of indicative occupational exposure limit values</p> <p>STEL: 150 ppm 15 minutes. STEL: 723 mg/m³ 15 minutes. TWA: 241 mg/m³ 8 hours. TWA: 50 ppm 8 hours.</p> |
| acetone | <p>Legislative Decree No. 819/2008. Title IX. Protection from chemical agents, carcinogens and mutagens (Italy, 6/2020).</p> <p>8 hours: 500 ppm 8 hours. 8 hours: 1210 mg/m³ 8 hours.</p> |
| Toluene | <p>Legislative Decree No. 819/2008. Title IX. Protection from chemical agents, carcinogens and mutagens (Italy, 6/2020). Absorbed through skin.</p> <p>8 hours: 50 ppm 8 hours. 8 hours: 192 mg/m³ 8 hours.</p> |
| Xylene | <p>Legislative Decree No. 819/2008. Title IX. Protection from chemical agents, carcinogens and mutagens (Italy, 6/2020). [Xylenes, mixed isomers, pure] Absorbed through skin.</p> <p>8 hours: 50 ppm 8 hours.</p> |

SECTION 8: Exposure controls/personal protection

| | |
|-----------------|---|
| Ethyl acetate | <p>8 hours: 221 mg/m³ 8 hours. Short Term: 100 ppm 15 minutes. Short Term: 442 mg/m³ 15 minutes.</p> <p>Legislative Decree No. 819/2008. Title IX. Protection from chemical agents, carcinogens and mutagens (Italy, 6/2020). Short Term: 400 ppm 15 minutes. Short Term: 1468 mg/m³ 15 minutes. 8 hours: 200 ppm 8 hours. 8 hours: 734 mg/m³ 8 hours.</p> |
| Ethylbenzene | <p>Legislative Decree No. 819/2008. Title IX. Protection from chemical agents, carcinogens and mutagens (Italy, 6/2020). Absorbed through skin. 8 hours: 100 ppm 8 hours. 8 hours: 442 mg/m³ 8 hours. Short Term: 200 ppm 15 minutes. Short Term: 884 mg/m³ 15 minutes.</p> |
| n-Butyl acetate | <p>Ministers Cabinet Regulations Nr.325 - AER (Latvia, 2/2021). TWA: 241 mg/m³ 8 hours. STEL: 150 ppm 15 minutes. STEL: 723 mg/m³ 15 minutes. TWA: 50 ppm 8 hours.</p> |
| acetone | <p>Ministers Cabinet Regulations Nr.325 - AER (Latvia, 2/2021). TWA: 1210 mg/m³ 8 hours. TWA: 500 ppm 8 hours.</p> |
| Toluene | <p>Ministers Cabinet Regulations Nr.325 - AER (Latvia, 2/2021). Absorbed through skin. TWA: 50 mg/m³ 8 hours. STEL: 150 mg/m³ 15 minutes. TWA: 14 ppm 8 hours. STEL: 40 ppm 15 minutes.</p> |
| Xylene | <p>Ministers Cabinet Regulations Nr.325 - AER (Latvia, 2/2021). [Xylenes] Absorbed through skin. TWA: 221 mg/m³ 8 hours. TWA: 50 ppm 8 hours. STEL: 100 ppm 15 minutes. STEL: 442 mg/m³ 15 minutes.</p> |
| Ethyl acetate | <p>Ministers Cabinet Regulations Nr.325 - AER (Latvia, 2/2021). TWA: 200 mg/m³ 8 hours. STEL: 400 ppm 15 minutes. STEL: 1468 mg/m³ 15 minutes. TWA: 54 ppm 8 hours.</p> |
| iso-butanol | <p>Ministers Cabinet Regulations Nr.325 - AER (Latvia, 2/2021). [Butylalcohol] TWA: 10 mg/m³ 8 hours.</p> |
| Propan-2-ol | <p>Ministers Cabinet Regulations Nr.325 - AER (Latvia, 2/2021). TWA: 350 mg/m³ 8 hours. STEL: 600 mg/m³ 15 minutes.</p> |
| Ethylbenzene | <p>Ministers Cabinet Regulations Nr.325 - AER (Latvia, 2/2021). Absorbed through skin. TWA: 442 mg/m³ 8 hours. TWA: 100 ppm 8 hours. STEL: 200 ppm 15 minutes. STEL: 884 mg/m³ 15 minutes.</p> |
| n-Butyl acetate | <p>Lithuanian Hygiene Standard HN 23 (Lithuania, 7/2022). TWA: 241 mg/m³ 8 hours. TWA: 50 ppm 8 hours. STEL: 723 mg/m³ 15 minutes. STEL: 150 ppm 15 minutes.</p> |
| acetone | <p>Lithuanian Hygiene Standard HN 23 (Lithuania, 7/2022). TWA: 1210 mg/m³ 8 hours. TWA: 500 ppm 8 hours. STEL: 2420 mg/m³ 15 minutes. STEL: 1000 ppm 15 minutes.</p> |
| Toluene | <p>Lithuanian Hygiene Standard HN 23 (Lithuania, 7/2022).</p> |

SECTION 8: Exposure controls/personal protection

| | |
|-----------------|--|
| Xylene | <p>Absorbed through skin. TWA: 192 mg/m³ 8 hours. TWA: 50 ppm 8 hours. STEL: 384 mg/m³ 15 minutes. STEL: 100 ppm 15 minutes.</p> <p>Lithuanian Hygiene Standard HN 23 (Lithuania, 7/2022). [xylene, mixed isomers, pure] Absorbed through skin. STEL: 442 mg/m³ 15 minutes. TWA: 50 ppm 8 hours. STEL: 100 ppm 15 minutes. TWA: 221 mg/m³ 8 hours.</p> |
| Ethyl acetate | <p>Lithuanian Hygiene Standard HN 23 (Lithuania, 7/2022). TWA: 500 mg/m³ 8 hours. TWA: 150 ppm 8 hours. CEIL: 1100 mg/m³ CEIL: 300 ppm</p> |
| iso-butanol | <p>Lithuanian Hygiene Standard HN 23 (Lithuania, 7/2022). Absorbed through skin. TWA: 10 mg/m³ 8 hours.</p> |
| Propan-2-ol | <p>Lithuanian Hygiene Standard HN 23 (Lithuania, 7/2022). TWA: 350 mg/m³ 8 hours. TWA: 150 ppm 8 hours. STEL: 600 mg/m³ 15 minutes. STEL: 250 ppm 15 minutes.</p> |
| Ethylbenzene | <p>Lithuanian Hygiene Standard HN 23 (Lithuania, 7/2022). Absorbed through skin. TWA: 442 mg/m³ 8 hours. TWA: 100 ppm 8 hours. STEL: 884 mg/m³ 15 minutes. STEL: 200 ppm 15 minutes.</p> |
| n-Butyl acetate | <p>Grand-Duchy Regulation 2016. Chemical agents. Annex I (Luxembourg, 3/2021). STEL: 150 ppm 15 minutes. STEL: 723 mg/m³ 15 minutes. TWA: 50 ppm 8 hours. TWA: 241 mg/m³ 8 hours.</p> |
| acetone | <p>Grand-Duchy Regulation 2016. Chemical agents. Annex I (Luxembourg, 3/2021). TWA: 500 ppm 8 hours. TWA: 1210 mg/m³ 8 hours.</p> |
| Toluene | <p>Grand-Duchy Regulation 2016. Chemical agents. Annex I (Luxembourg, 3/2021). Absorbed through skin. STEL: 100 ppm 15 minutes. STEL: 384 mg/m³ 15 minutes. TWA: 50 ppm 8 hours. TWA: 192 mg/m³ 8 hours.</p> |
| Xylene | <p>Grand-Duchy Regulation 2016. Chemical agents. Annex I (Luxembourg, 3/2021). [xylenes, mixed isomers, pure] Absorbed through skin. TWA: 50 ppm 8 hours. TWA: 221 mg/m³ 8 hours. STEL: 100 ppm 15 minutes. STEL: 442 mg/m³ 15 minutes.</p> |
| Ethyl acetate | <p>Grand-Duchy Regulation 2016. Chemical agents. Annex I (Luxembourg, 3/2021). STEL: 400 ppm 15 minutes. STEL: 1468 mg/m³ 15 minutes. TWA: 200 ppm 8 hours. TWA: 734 mg/m³ 8 hours.</p> |
| Ethylbenzene | <p>Grand-Duchy Regulation 2016. Chemical agents. Annex I (Luxembourg, 3/2021). Absorbed through skin. TWA: 100 ppm 8 hours. TWA: 442 mg/m³ 8 hours. STEL: 200 ppm 15 minutes. STEL: 884 mg/m³ 15 minutes.</p> |

SECTION 8: Exposure controls/personal protection

| | |
|-----------------|--|
| n-Butyl acetate | EU OEL (Europe, 1/2022). Notes: list of indicative occupational exposure limit values STEL: 150 ppm 15 minutes. STEL: 723 mg/m ³ 15 minutes. TWA: 241 mg/m ³ 8 hours. TWA: 50 ppm 8 hours. |
| acetone | EU OEL (Europe, 1/2022). Notes: list of indicative occupational exposure limit values TWA: 500 ppm 8 hours. TWA: 1210 mg/m ³ 8 hours. |
| Toluene | EU OEL (Europe, 1/2022). Absorbed through skin. Notes: list of indicative occupational exposure limit values TWA: 192 mg/m ³ 8 hours. TWA: 50 ppm 8 hours. STEL: 384 mg/m ³ 15 minutes. STEL: 100 ppm 15 minutes. |
| Xylene | EU OEL (Europe, 1/2022). [xylene, mixed isomers pure] Absorbed through skin. Notes: list of indicative occupational exposure limit values TWA: 50 ppm 8 hours. TWA: 221 mg/m ³ 8 hours. STEL: 100 ppm 15 minutes. STEL: 442 mg/m ³ 15 minutes. |
| Ethyl acetate | EU OEL (Europe, 1/2022). Notes: list of indicative occupational exposure limit values STEL: 400 ppm 15 minutes. STEL: 1468 mg/m ³ 15 minutes. TWA: 200 ppm 8 hours. TWA: 734 mg/m ³ 8 hours. |
| Ethylbenzene | EU OEL (Europe, 1/2022). Absorbed through skin. Notes: list of indicative occupational exposure limit values TWA: 100 ppm 8 hours. TWA: 442 mg/m ³ 8 hours. STEL: 200 ppm 15 minutes. STEL: 884 mg/m ³ 15 minutes. |
| n-Butyl acetate | Ministry of Social Affairs and Employment, Legal limit values (Netherlands, 12/2022). OEL, 8-h TWA: 241 mg/m ³ 8 hours. STEL, 15-min: 723 mg/m ³ 15 minutes. STEL, 15-min: 150 ppm 15 minutes. OEL, 8-h TWA: 50 ppm 8 hours. |
| acetone | Ministry of Social Affairs and Employment, Legal limit values (Netherlands, 12/2022). STEL, 15-min: 2420 mg/m ³ 15 minutes. OEL, 8-h TWA: 1210 mg/m ³ 8 hours. OEL, 8-h TWA: 500 ppm 8 hours. STEL, 15-min: 1000 ppm 15 minutes. |
| Toluene | Ministry of Social Affairs and Employment, Legal limit values (Netherlands, 12/2022). OEL, 8-h TWA: 150 mg/m ³ 8 hours. STEL, 15-min: 384 mg/m ³ 15 minutes. STEL, 15-min: 100 ppm 15 minutes. OEL, 8-h TWA: 39 ppm 8 hours. |
| Xylene | Ministry of Social Affairs and Employment, Legal limit values (Netherlands, 12/2022). [xylenes (all isomers)] Absorbed through skin. OEL, 8-h TWA: 210 mg/m ³ 8 hours. STEL, 15-min: 442 mg/m ³ 15 minutes. STEL, 15-min: 100 ppm 15 minutes. OEL, 8-h TWA: 47.5 ppm 8 hours. |
| Ethyl acetate | Ministry of Social Affairs and Employment, Legal limit values (Netherlands, 12/2022). STEL, 15-min: 1468 mg/m ³ 15 minutes. OEL, 8-h TWA: 734 mg/m ³ 8 hours. |

SECTION 8: Exposure controls/personal protection

| | |
|-----------------|---|
| Ethylbenzene | <p>STEL, 15-min: 400 ppm 15 minutes. OEL, 8-h TWA: 200 ppm 8 hours. Ministry of Social Affairs and Employment, Legal limit values (Netherlands, 12/2022). Absorbed through skin. OEL, 8-h TWA: 215 mg/m³ 8 hours. STEL, 15-min: 430 mg/m³ 15 minutes. STEL, 15-min: 97.3 ppm 15 minutes. OEL, 8-h TWA: 48.6 ppm 8 hours.</p> |
| n-Butyl acetate | <p>FOR-2011-12-06-1358 (Norway, 12/2022). STEL: 723 mg/m³ 15 minutes. STEL: 150 ppm 15 minutes. FOR-2011-12-06-1358 (Norway, 12/2022). Notes: indicative limit value TWA: 241 mg/m³ 8 hours. TWA: 50 ppm 8 hours.</p> |
| acetone | <p>FOR-2011-12-06-1358 (Norway, 12/2022). Notes: indicative limit value TWA: 125 ppm 8 hours. TWA: 295 mg/m³ 8 hours.</p> |
| Toluene | <p>FOR-2011-12-06-1358 (Norway, 12/2022). Absorbed through skin. Notes: indicative limit value TWA: 25 ppm 8 hours. TWA: 94 mg/m³ 8 hours.</p> |
| Xylene | <p>FOR-2011-12-06-1358 (Norway, 12/2022). [Xylene, all isomers] Absorbed through skin. Notes: indicative limit value TWA: 25 ppm 8 hours. TWA: 108 mg/m³ 8 hours.</p> |
| Ethyl acetate | <p>FOR-2011-12-06-1358 (Norway, 12/2022). Notes: indicative limit value TWA: 200 ppm 8 hours. TWA: 734 mg/m³ 8 hours. FOR-2011-12-06-1358 (Norway, 12/2022). STEL: 1468 mg/m³ 15 minutes. STEL: 400 ppm 15 minutes.</p> |
| iso-butanol | <p>FOR-2011-12-06-1358 (Norway, 12/2022). Absorbed through skin. CEIL: 75 mg/m³ CEIL: 25 ppm</p> |
| Propan-2-ol | <p>FOR-2011-12-06-1358 (Norway, 12/2022). TWA: 100 ppm 8 hours. TWA: 245 mg/m³ 8 hours.</p> |
| Ethylbenzene | <p>FOR-2011-12-06-1358 (Norway, 12/2022). Absorbed through skin. Carcinogen. Notes: indicative limit value TWA: 5 ppm 8 hours. TWA: 20 mg/m³ 8 hours.</p> |
| n-Butyl acetate | <p>Regulation of the Minister of Family, Labor and Social Policy of 18 February 2021, regarding the highest permissible concentrations and values of agents harmful to health in the work environment (Journal of Laws 2021, item 325) (Poland, 2/2021). TWA: 240 mg/m³ 8 hours. STEL: 720 mg/m³ 15 minutes.</p> |
| acetone | <p>Regulation of the Minister of Family, Labor and Social Policy of 18 February 2021, regarding the highest permissible concentrations and values of agents harmful to health in the work environment (Journal of Laws 2021, item 325) (Poland, 2/2021). TWA: 600 mg/m³ 8 hours. STEL: 1800 mg/m³ 15 minutes.</p> |
| Toluene | <p>Regulation of the Minister of Family, Labor and Social Policy of 18 February 2021, regarding the highest permissible concentrations and values of agents harmful to health in the work environment (Journal of Laws 2021, item 325) (Poland, 2/2021). Absorbed through skin.</p> |

SECTION 8: Exposure controls/personal protection

| | |
|-----------------|---|
| Xylene | <p>TWA: 100 mg/m³ 8 hours. STEL: 200 mg/m³ 15 minutes.</p> <p>Regulation of the Minister of Family, Labor and Social Policy of 18 February 2021, regarding the highest permissible concentrations and values of agents harmful to health in the work environment (Journal of Laws 2021, item 325) (Poland, 2/2021). [xylene – mixed isomers (1,2-, 1,3-, 1,4-)] Absorbed through skin.</p> |
| Ethyl acetate | <p>TWA: 100 mg/m³ 8 hours. STEL: 200 mg/m³ 15 minutes.</p> <p>Regulation of the Minister of Family, Labor and Social Policy of 18 February 2021, regarding the highest permissible concentrations and values of agents harmful to health in the work environment (Journal of Laws 2021, item 325) (Poland, 2/2021).</p> |
| iso-butanol | <p>TWA: 734 mg/m³ 8 hours. STEL: 1468 mg/m³ 15 minutes.</p> <p>Regulation of the Minister of Family, Labor and Social Policy of 18 February 2021, regarding the highest permissible concentrations and values of agents harmful to health in the work environment (Journal of Laws 2021, item 325) (Poland, 2/2021). Absorbed through skin.</p> |
| Propan-2-ol | <p>TWA: 100 mg/m³ 8 hours. STEL: 200 mg/m³ 15 minutes.</p> <p>Regulation of the Minister of Family, Labor and Social Policy of 18 February 2021, regarding the highest permissible concentrations and values of agents harmful to health in the work environment (Journal of Laws 2021, item 325) (Poland, 2/2021). Absorbed through skin.</p> |
| Ethylbenzene | <p>TWA: 900 mg/m³ 8 hours. STEL: 1200 mg/m³ 15 minutes.</p> <p>Regulation of the Minister of Family, Labor and Social Policy of 18 February 2021, regarding the highest permissible concentrations and values of agents harmful to health in the work environment (Journal of Laws 2021, item 325) (Poland, 2/2021). Absorbed through skin.</p> |
| n-Butyl acetate | <p>TWA: 200 mg/m³ 8 hours. STEL: 400 mg/m³ 15 minutes.</p> <p>Portuguese Institute of Quality (Portugal, 11/2014).</p> |
| acetone | <p>TWA: 150 ppm 8 hours. STEL: 200 ppm 15 minutes.</p> <p>Portuguese Institute of Quality (Portugal, 11/2014).</p> |
| Toluene | <p>TWA: 500 ppm 8 hours. STEL: 750 ppm 15 minutes.</p> <p>Portuguese Institute of Quality (Portugal, 11/2014). Absorbed through skin.</p> |
| Xylene | <p>TWA: 20 ppm 8 hours.</p> <p>Portuguese Institute of Quality (Portugal, 11/2014). [Xylene]</p> |
| Ethyl acetate | <p>TWA: 100 ppm 8 hours. STEL: 150 ppm 15 minutes.</p> <p>Portuguese Institute of Quality (Portugal, 11/2014).</p> |
| iso-butanol | <p>TWA: 400 ppm 8 hours.</p> <p>Portuguese Institute of Quality (Portugal, 11/2014).</p> |
| Propan-2-ol | <p>TWA: 50 ppm 8 hours.</p> <p>Portuguese Institute of Quality (Portugal, 11/2014).</p> |
| Ethylbenzene | <p>TWA: 200 ppm 8 hours. STEL: 400 ppm 15 minutes.</p> <p>Portuguese Institute of Quality (Portugal, 11/2014).</p> |
| | <p>TWA: 20 ppm 8 hours.</p> |

SECTION 8: Exposure controls/personal protection

| | |
|-----------------|--|
| n-Butyl acetate | <p>HG 1218/2006, Annex 1, with subsequent modifications and additions (Romania, 3/2021). VLA: 241 mg/m³ 8 hours. VLA: 50 ppm 8 hours. Short term: 723 mg/m³ 15 minutes. Short term: 150 ppm 15 minutes.</p> |
| acetone | <p>HG 1218/2006, Annex 1, with subsequent modifications and additions (Romania, 3/2021). VLA: 1210 mg/m³ 8 hours. VLA: 500 ppm 8 hours.</p> |
| Toluene | <p>HG 1218/2006, Annex 1, with subsequent modifications and additions (Romania, 3/2021). Absorbed through skin. VLA: 192 mg/m³ 8 hours. VLA: 50 ppm 8 hours. Short term: 384 mg/m³ 15 minutes. Short term: 100 ppm 15 minutes.</p> |
| Xylene | <p>HG 1218/2006, Annex 1, with subsequent modifications and additions (Romania, 3/2021). [Xylene] Absorbed through skin. VLA: 221 mg/m³ 8 hours. VLA: 50 ppm 8 hours. Short term: 442 mg/m³ 15 minutes. Short term: 100 ppm 15 minutes.</p> |
| Ethyl acetate | <p>HG 1218/2006, Annex 1, with subsequent modifications and additions (Romania, 3/2021). VLA: 734 mg/m³ 8 hours. VLA: 200 ppm 8 hours. Short term: 1468 mg/m³ 15 minutes. Short term: 400 ppm 15 minutes.</p> |
| iso-butanol | <p>HG 1218/2006, Annex 1, with subsequent modifications and additions (Romania, 3/2021). VLA: 100 mg/m³ 8 hours. VLA: 33 ppm 8 hours. Short term: 200 mg/m³ 15 minutes. Short term: 66 ppm 15 minutes.</p> |
| Propan-2-ol | <p>HG 1218/2006, Annex 1, with subsequent modifications and additions (Romania, 3/2021). VLA: 200 mg/m³ 8 hours. VLA: 81 ppm 8 hours. Short term: 500 mg/m³ 15 minutes. Short term: 203 ppm 15 minutes.</p> |
| Ethylbenzene | <p>HG 1218/2006, Annex 1, with subsequent modifications and additions (Romania, 3/2021). Absorbed through skin. VLA: 442 mg/m³ 8 hours. VLA: 100 ppm 8 hours. Short term: 884 mg/m³ 15 minutes. Short term: 200 ppm 15 minutes.</p> |
| n-Butyl acetate | <p>Government regulation SR c. 355/2006 (Slovakia, 9/2020). [Butyl acetates] TWA: 241 mg/m³, (Butyl acetates) 8 hours. TWA: 50 ppm, (Butyl acetates) 8 hours. STEL: 723 mg/m³, (Butyl acetates) 15 minutes. STEL: 150 ppm, (Butyl acetates) 15 minutes.</p> |
| acetone | <p>Government regulation SR c. 355/2006 (Slovakia, 9/2020). TWA: 1210 mg/m³ 8 hours. TWA: 500 ppm 8 hours.</p> |
| Toluene | <p>Government regulation SR c. 355/2006 (Slovakia, 9/2020). Absorbed through skin. TWA: 192 mg/m³ 8 hours. TWA: 50 ppm 8 hours. STEL: 384 mg/m³ 15 minutes. STEL: 100 ppm 15 minutes.</p> |
| Xylene | <p>Government regulation SR c. 355/2006 (Slovakia, 9/2020). [xylene, mixed isomers] Absorbed through skin. TWA: 221 mg/m³, (xylene, mixed isomers) 8 hours.</p> |

SECTION 8: Exposure controls/personal protection

| | |
|-----------------|---|
| Ethyl acetate | <p>TWA: 50 ppm, (xylene, mixed isomers) 8 hours. STEL: 442 mg/m³, (xylene, mixed isomers) 15 minutes. STEL: 100 ppm, (xylene, mixed isomers) 15 minutes. Government regulation SR c. 355/2006 (Slovakia, 9/2020). TWA: 734 mg/m³ 8 hours. TWA: 200 ppm 8 hours. STEL: 1468 mg/m³ 15 minutes. STEL: 400 ppm 15 minutes.</p> |
| iso-butanol | <p>Government regulation SR c. 355/2006 (Slovakia, 9/2020). [Butyl alcohols] TWA: 310 mg/m³, (Butyl alcohols) 8 hours. TWA: 100 ppm, (Butyl alcohols) 8 hours.</p> |
| Propan-2-ol | <p>Government regulation SR c. 355/2006 (Slovakia, 9/2020). TWA: 500 mg/m³ 8 hours. TWA: 200 ppm 8 hours. STEL: 1000 mg/m³ 15 minutes. STEL: 400 ppm 15 minutes.</p> |
| Ethylbenzene | <p>Government regulation SR c. 355/2006 (Slovakia, 9/2020). Absorbed through skin. TWA: 442 mg/m³ 8 hours. TWA: 100 ppm 8 hours. STEL: 884 mg/m³ 15 minutes. STEL: 200 ppm 15 minutes.</p> |
| n-Butyl acetate | <p>Regulation on protection of workers from the risks related to exposure to chemical substances at work (Slovenia, 5/2021). TWA: 241 mg/m³ 8 hours. TWA: 50 ppm 8 hours. KTV: 723 mg/m³, 4 times per shift, 15 minutes. KTV: 150 ppm, 4 times per shift, 15 minutes.</p> |
| acetone | <p>Regulation on protection of workers from the risks related to exposure to chemical substances at work (Slovenia, 5/2021). TWA: 1210 mg/m³ 8 hours. TWA: 500 ppm 8 hours. KTV: 1000 ppm, 4 times per shift, 15 minutes. KTV: 2420 mg/m³, 4 times per shift, 15 minutes.</p> |
| Toluene | <p>Regulation on protection of workers from the risks related to exposure to chemical substances at work (Slovenia, 5/2021). Absorbed through skin. TWA: 192 mg/m³ 8 hours. TWA: 50 ppm 8 hours. KTV: 384 mg/m³, 4 times per shift, 15 minutes. KTV: 100 ppm, 4 times per shift, 15 minutes.</p> |
| Xylene | <p>Regulation on protection of workers from the risks related to exposure to chemical substances at work (Slovenia, 5/2021). [xylene (mixture of isomers)] Absorbed through skin. TWA: 221 mg/m³ 8 hours. TWA: 50 ppm 8 hours. KTV: 442 mg/m³, 4 times per shift, 15 minutes. KTV: 100 ppm, 4 times per shift, 15 minutes.</p> |
| Ethyl acetate | <p>Regulation on protection of workers from the risks related to exposure to chemical substances at work (Slovenia, 5/2021). TWA: 734 mg/m³ 8 hours. TWA: 200 ppm 8 hours. KTV: 1468 mg/m³, 4 times per shift, 15 minutes. KTV: 400 ppm, 4 times per shift, 15 minutes.</p> |
| iso-butanol | <p>Regulation on protection of workers from the risks related to exposure to chemical substances at work (Slovenia, 5/2021). TWA: 310 mg/m³ 8 hours. TWA: 100 ppm 8 hours. KTV: 310 mg/m³, 4 times per shift, 15 minutes. KTV: 100 ppm, 4 times per shift, 15 minutes.</p> |
| Propan-2-ol | <p>Regulation on protection of workers from the risks related to exposure to chemical substances at work (Slovenia, 5/2021). TWA: 500 mg/m³ 8 hours. TWA: 200 ppm 8 hours.</p> |

SECTION 8: Exposure controls/personal protection

| | |
|---------------------|--|
| Ethylbenzene | <p>KTV: 1000 mg/m³, 4 times per shift, 15 minutes. KTV: 400 ppm, 4 times per shift, 15 minutes. Regulation on protection of workers from the risks related to exposure to chemical substances at work (Slovenia, 5/2021). Absorbed through skin. TWA: 442 mg/m³ 8 hours. TWA: 100 ppm 8 hours. KTV: 884 mg/m³, 4 times per shift, 15 minutes. KTV: 200 ppm, 4 times per shift, 15 minutes.</p> |
| 1-Ethoxy-2-propanol | <p>Regulation on protection of workers from the risks related to exposure to chemical substances at work (Slovenia, 5/2021). Absorbed through skin. KTV: 100 ppm, 4 times per shift, 15 minutes. TWA: 50 ppm 8 hours. KTV: 440 mg/m³, 4 times per shift, 15 minutes. TWA: 220 mg/m³ 8 hours.</p> |
| n-Butyl acetate | <p>National institute of occupational safety and health (Spain, 4/2022). TWA: 50 ppm 8 hours. TWA: 241 mg/m³ 8 hours. STEL: 150 ppm 15 minutes. STEL: 723 mg/m³ 15 minutes.</p> |
| acetone | <p>National institute of occupational safety and health (Spain, 4/2022). TWA: 500 ppm 8 hours. TWA: 1210 mg/m³ 8 hours.</p> |
| Toluene | <p>National institute of occupational safety and health (Spain, 4/2022). Absorbed through skin. TWA: 50 ppm 8 hours. TWA: 192 mg/m³ 8 hours. STEL: 100 ppm 15 minutes. STEL: 384 mg/m³ 15 minutes.</p> |
| Xylene | <p>National institute of occupational safety and health (Spain, 4/2022). [Xylene, mixture of isomers] Absorbed through skin. TWA: 50 ppm 8 hours. TWA: 221 mg/m³ 8 hours. STEL: 100 ppm 15 minutes. STEL: 442 mg/m³ 15 minutes.</p> |
| Ethyl acetate | <p>National institute of occupational safety and health (Spain, 4/2022). TWA: 200 ppm 8 hours. TWA: 734 mg/m³ 8 hours. STEL: 1468 mg/m³ 15 minutes. STEL: 400 ppm 15 minutes.</p> |
| iso-butanol | <p>National institute of occupational safety and health (Spain, 4/2022). TWA: 50 ppm 8 hours. TWA: 154 mg/m³ 8 hours.</p> |
| Propan-2-ol | <p>National institute of occupational safety and health (Spain, 4/2022). TWA: 200 ppm 8 hours. TWA: 500 mg/m³ 8 hours. STEL: 400 ppm 15 minutes. STEL: 1000 mg/m³ 15 minutes.</p> |
| Ethylbenzene | <p>National institute of occupational safety and health (Spain, 4/2022). Absorbed through skin. TWA: 100 ppm 8 hours. TWA: 441 mg/m³ 8 hours. STEL: 200 ppm 15 minutes. STEL: 884 mg/m³ 15 minutes.</p> |

SECTION 8: Exposure controls/personal protection

| | |
|-----------------|---|
| n-Butyl acetate | <p>Work environment authority Regulation 2018:1 (Sweden, 9/2021). [butyl acetate] TWA: 50 ppm 8 hours. TWA: 241 mg/m³ 8 hours. STEL: 150 ppm 15 minutes. STEL: 723 mg/m³ 15 minutes.</p> |
| acetone | <p>Work environment authority Regulation 2018:1 (Sweden, 9/2021). TWA: 250 ppm 8 hours. TWA: 600 mg/m³ 8 hours. STEL: 500 ppm 15 minutes. STEL: 1200 mg/m³ 15 minutes.</p> |
| Toluene | <p>Work environment authority Regulation 2018:1 (Sweden, 9/2021). Absorbed through skin. Ototoxicant. TWA: 50 ppm 8 hours. TWA: 192 mg/m³ 8 hours. STEL: 100 ppm 15 minutes. STEL: 384 mg/m³ 15 minutes.</p> |
| Xylene | <p>Work environment authority Regulation 2018:1 (Sweden, 9/2021). [xylene] Absorbed through skin. TWA: 50 ppm 8 hours. TWA: 221 mg/m³ 8 hours. STEL: 100 ppm 15 minutes. STEL: 442 mg/m³ 15 minutes.</p> |
| Ethyl acetate | <p>Work environment authority Regulation 2018:1 (Sweden, 9/2021). TWA: 150 ppm 8 hours. TWA: 550 mg/m³ 8 hours. STEL: 300 ppm 15 minutes. STEL: 1100 mg/m³ 15 minutes.</p> |
| iso-butanol | <p>Work environment authority Regulation 2018:1 (Sweden, 9/2021). Absorbed through skin. TWA: 50 ppm 8 hours. TWA: 150 mg/m³ 8 hours. STEL: 75 ppm 15 minutes. STEL: 250 mg/m³ 15 minutes.</p> |
| Propan-2-ol | <p>Work environment authority Regulation 2018:1 (Sweden, 9/2021). TWA: 150 ppm 8 hours. TWA: 350 mg/m³ 8 hours. STEL: 250 ppm 15 minutes. STEL: 600 mg/m³ 15 minutes.</p> |
| Ethylbenzene | <p>Work environment authority Regulation 2018:1 (Sweden, 9/2021). Absorbed through skin. TWA: 50 ppm 8 hours. TWA: 220 mg/m³ 8 hours. STEL: 200 ppm 15 minutes. STEL: 884 mg/m³ 15 minutes.</p> |
| n-Butyl acetate | <p>SUVA (Switzerland, 1/2023). TWA: 50 ppm 8 hours. TWA: 240 mg/m³ 8 hours. STEL: 150 ppm 15 minutes. STEL: 720 mg/m³ 15 minutes.</p> |
| acetone | <p>SUVA (Switzerland, 1/2023). TWA: 500 ppm 8 hours. TWA: 1200 mg/m³ 8 hours. STEL: 1000 ppm 15 minutes. STEL: 2400 mg/m³ 15 minutes.</p> |
| Toluene | <p>SUVA (Switzerland, 1/2023). Absorbed through skin. TWA: 50 ppm 8 hours. TWA: 190 mg/m³ 8 hours. STEL: 200 ppm 15 minutes. STEL: 760 mg/m³ 15 minutes.</p> |
| Xylene | <p>SUVA (Switzerland, 1/2023). [Xylenes (all isomers)] Absorbed through skin.</p> |

SECTION 8: Exposure controls/personal protection

| | |
|---------------------|--|
| Ethyl acetate | <p>TWA: 50 ppm 8 hours. TWA: 220 mg/m³ 8 hours. STEL: 100 ppm 15 minutes. STEL: 440 mg/m³ 15 minutes.</p> <p>SUVA (Switzerland, 1/2023). STEL: 400 ppm 15 minutes. STEL: 1460 mg/m³ 15 minutes. TWA: 200 ppm 8 hours. TWA: 730 mg/m³ 8 hours.</p> |
| iso-butanol | <p>SUVA (Switzerland, 1/2023). TWA: 50 ppm 8 hours. TWA: 150 mg/m³ 8 hours. STEL: 50 ppm 15 minutes. STEL: 150 mg/m³ 15 minutes.</p> |
| Propan-2-ol | <p>SUVA (Switzerland, 1/2023). TWA: 200 ppm 8 hours. TWA: 500 mg/m³ 8 hours. STEL: 400 ppm 15 minutes. STEL: 1000 mg/m³ 15 minutes.</p> |
| Ethylbenzene | <p>SUVA (Switzerland, 1/2023). Absorbed through skin. TWA: 50 ppm 8 hours. TWA: 220 mg/m³ 8 hours. STEL: 50 ppm 15 minutes. STEL: 220 mg/m³ 15 minutes.</p> |
| 1-Ethoxy-2-propanol | <p>SUVA (Switzerland, 1/2023). Absorbed through skin. STEL: 100 ppm 15 minutes. STEL: 440 mg/m³ 15 minutes. TWA: 50 ppm 8 hours. TWA: 220 mg/m³ 8 hours.</p> |
| n-Butyl acetate | <p>EH40/2005 WELs (United Kingdom (UK), 1/2020). STEL: 966 mg/m³ 15 minutes. STEL: 200 ppm 15 minutes. TWA: 724 mg/m³ 8 hours. TWA: 150 ppm 8 hours.</p> |
| acetone | <p>EH40/2005 WELs (United Kingdom (UK), 1/2020). STEL: 3620 mg/m³ 15 minutes. STEL: 1500 ppm 15 minutes. TWA: 500 ppm 8 hours. TWA: 1210 mg/m³ 8 hours.</p> |
| Toluene | <p>EH40/2005 WELs (United Kingdom (UK), 1/2020). Absorbed through skin. STEL: 384 mg/m³ 15 minutes. TWA: 191 mg/m³ 8 hours. TWA: 50 ppm 8 hours. STEL: 100 ppm 15 minutes.</p> |
| Xylene | <p>EH40/2005 WELs (United Kingdom (UK), 1/2020). [xylene, o-,m-, p- or mixed isomers] Absorbed through skin. STEL: 441 mg/m³ 15 minutes. TWA: 50 ppm 8 hours. TWA: 220 mg/m³ 8 hours. STEL: 100 ppm 15 minutes.</p> |
| Ethyl acetate | <p>EH40/2005 WELs (United Kingdom (UK), 1/2020). STEL: 400 ppm 15 minutes. TWA: 200 ppm 8 hours. STEL: 1468 mg/m³ 15 minutes. TWA: 734 mg/m³ 8 hours.</p> |
| iso-butanol | <p>EH40/2005 WELs (United Kingdom (UK), 1/2020). STEL: 231 mg/m³ 15 minutes. STEL: 75 ppm 15 minutes. TWA: 154 mg/m³ 8 hours. TWA: 50 ppm 8 hours.</p> |
| Propan-2-ol | <p>EH40/2005 WELs (United Kingdom (UK), 1/2020). STEL: 1250 mg/m³ 15 minutes. STEL: 500 ppm 15 minutes. TWA: 999 mg/m³ 8 hours.</p> |

SECTION 8: Exposure controls/personal protection

| | |
|----------------------|--|
| Ethylbenzene | TWA: 400 ppm 8 hours. EH40/2005 WELs (United Kingdom (UK), 1/2020). Absorbed through skin. STEL: 552 mg/m ³ 15 minutes. STEL: 125 ppm 15 minutes. TWA: 100 ppm 8 hours. |
| 1-Methoxy 2-propanol | TWA: 441 mg/m ³ 8 hours. EH40/2005 WELs (United Kingdom (UK), 1/2020). Absorbed through skin. STEL: 560 mg/m ³ 15 minutes. STEL: 150 ppm 15 minutes. TWA: 375 mg/m ³ 8 hours. TWA: 100 ppm 8 hours. |

Biological exposure indices

| Product/ingredient name | Exposure indices |
|----------------------------|---|
| Toluene | VGU BEI (Austria, 9/2020) BEI Fitness: 250 µg/l, toluene [in blood]. Sampling time: one year. BEI Fitness: 0.8 mg/l, o-cresol [in urine]. Sampling time: one year. BEI Fitness: 130000 /µl, platelets (non-pathological differential blood count) [in blood]. Sampling time: one year. BEI Fitness: 150000 /µl, platelets [in blood]. Sampling time: one year. BEI Fitness: 3700 to 13000 /µl, leukocytes (non-pathological differential blood count) [in blood]. Sampling time: one year. BEI Fitness: 4000 to 13000 /µl, leukocytes [in blood]. Sampling time: one year. BEI Fitness - men: 3.8 million/µl, erythrocytes [in blood]. Sampling time: one year. BEI Fitness - women: 3.2 million/µl, erythrocytes [in blood]. Sampling time: one year. BEI Fitness - men: 12 g/dl, hemoglobin [in blood]. Sampling time: one year. BEI Fitness - women: 10 g/dl, hemoglobin [in blood]. Sampling time: one year. |
| Xylene | VGU BEI (Austria, 9/2020) [xylenes] BEI Fitness: 1000 µg/l, xylene [in blood]. Sampling time: one year. BEI Fitness: 1.5 g/l, methylhippuric acid [in urine]. Sampling time: one year. |
| No exposure indices known. | |
| acetone | Ministry of Labour and Social Policy and the Ministry of Health - Ordinance No 13/2003. (Bulgaria, 6/2021) BLV: 80 mg/l, acetone [in urine]. Sampling time: after the end of the exposure or the end of the work shift. |
| Toluene | Ministry of Labour and Social Policy and the Ministry of Health - Ordinance No 13/2003. (Bulgaria, 6/2021) BLV: 1.6 mmol/mmol creatinine, hippuric acid [in urine]. Sampling time: after the end of the exposure or the end of the work shift. |
| Ethylbenzene | Ministry of Labour and Social Policy and the Ministry of Health - Ordinance No 13/2003. (Bulgaria, 6/2021) Notes: significant skin resorption possible BLV: 2000 mg/g creatinine, mandelic acid and phenylglyoxylic acid – in total [in urine]. Sampling time: after the end of the exposure or the end of the work shift. |

SECTION 8: Exposure controls/personal protection

| | |
|--------------|---|
| acetone | <p>Ministry of Economy, Labour and Entrepreneurship ILV/STEL (Croatia, 10/2018)</p> <p>BEI: 20 mg/g creatinine, acetone [in urine]. Sampling time: at the end of the work shift.</p> <p>BEI: 39 mmol/mol creatinine, acetone [in urine]. Sampling time: at the end of the work shift.</p> <p>BEI: 20 mg/l, acetone [in blood]. Sampling time: at the end of the work shift.</p> <p>BEI: 0.34 mmol/l, acetone [in blood]. Sampling time: at the end of the work shift.</p> |
| Toluene | <p>Ministry of Economy, Labour and Entrepreneurship ILV/STEL (Croatia, 10/2018)</p> <p>BEI: 20 ppm, toluene [in end exhaled air]. Sampling time: during exposure.</p> <p>BEI: 0.83 µmol/l, toluene [in end exhaled air]. Sampling time: during exposure.</p> <p>BEI: 1 mg/l, toluene [in blood]. Sampling time: at the end of the work shift.</p> <p>BEI: 10.85 µmol/l, toluene [in blood]. Sampling time: at the end of the work shift.</p> <p>BEI: 1.05 mmol/mol creatinine, o-cresol [in urine]. Sampling time: at the end of the work shift.</p> <p>BEI: 1 mg/g creatinine, o-cresol [in urine]. Sampling time: at the end of the work shift.</p> <p>BEI: 1.58 mol/mol creatinine, hippuric acid [in urine]. Sampling time: at the end of the work shift.</p> <p>BEI: 2.5 g/g creatinine, hippuric acid [in urine]. Sampling time: at the end of the work shift.</p> |
| Xylene | <p>Ministry of Economy, Labour and Entrepreneurship ILV/STEL (Croatia, 10/2018) [xylene]</p> <p>BEI: 1.5 mg/l, xylene [in blood]. Sampling time: at the end of the work shift.</p> <p>BEI: 14.13 µmol/l, xylene [in blood]. Sampling time: at the end of the work shift.</p> <p>BEI: 0.88 mol/mol creatinine, methylhippuric acid [in urine]. Sampling time: at the end of the work shift.</p> <p>BEI: 1.5 g/g creatinine, methylhippuric acid [in urine]. Sampling time: at the end of the work shift.</p> |
| Propan-2-ol | <p>Ministry of Economy, Labour and Entrepreneurship ILV/STEL (Croatia, 10/2018)</p> <p>BEI: 50 mg/l, acetone [in urine]. Sampling time: at the end of the work shift.</p> <p>BEI: 50 mg/l, acetone [in blood]. Sampling time: at the end of the work shift.</p> <p>BEI: 0.86 µmol/l, acetone [in urine]. Sampling time: at the end of the work shift.</p> <p>BEI: 0.86 µmol/l, acetone [in blood]. Sampling time: at the end of the work shift.</p> |
| Ethylbenzene | <p>Ministry of Economy, Labour and Entrepreneurship ILV/STEL (Croatia, 10/2018)</p> <p>BEI: 1.5 mg/l, ethylbenzene [in blood]. Sampling time: during exposure.</p> <p>BEI: 14.1 µmol/l, ethylbenzene [in blood]. Sampling time: during exposure.</p> <p>BEI: 1.12 mol/mol creatinine, almond acid [in urine]. Sampling time: at the end of the work shift and at the end of the working week.</p> <p>BEI: 1.5 g/g creatinine, almond acid [in urine]. Sampling time: at the end of the work shift and at the end of the working week.</p> |

SECTION 8: Exposure controls/personal protection

No exposure indices known.

Toluene

Government regulation of Czech Republic Limit Values of Biological Exposure Tests (Czech Republic, 9/2015)

Biological limit values: 1000 µmol/mmol creatinine, hippuric acid [in urine]. Sampling time: end of the shift.

Biological limit values: 1600 mg/g, hippuric acid [in urine]. Sampling time: end of the shift.

Biological limit values: 1.6 µmol/mmol creatinine, o-kresol (after hydrolysis) [in urine]. Sampling time: end of the shift.

Biological limit values: 1.5 mg/g creatinine, o-kresol (after hydrolysis) [in urine]. Sampling time: end of the shift.

Xylene

Government regulation of Czech Republic Limit Values of Biological Exposure Tests (Czech Republic, 9/2015) [Xylene]

Biological limit values: 820 µmol/mmol creatinine, methylhippuric acid [in urine]. Sampling time: end of the shift.

Biological limit values: 1400 mg/g creatinine, methylhippuric acid [in urine]. Sampling time: end of the shift.

Ethylbenzene

Government regulation of Czech Republic Limit Values of Biological Exposure Tests (Czech Republic, 9/2015)

Biological limit values: 1100 µmol/mmol creatinine, almond acid [in urine]. Sampling time: end of the shift.

Biological limit values: 1500 mg/g creatinine, almond acid [in urine]. Sampling time: end of the shift.

No exposure indices known.

No exposure indices known.

No exposure indices known.

Toluene

Institute of Occupational Health, Ministry of Social Affairs (Finland, 9/2020)

BEI: 500 nmol/l, toluene [in blood]. Sampling time: the morning after the working day.

Xylene

Institute of Occupational Health, Ministry of Social Affairs (Finland, 9/2020) [Xylene]

BEI: 5 mmol/l, methylhippuric acid [in urine]. Sampling time: at the end of the work shift.

Ethylbenzene

Institute of Occupational Health, Ministry of Social Affairs (Finland, 9/2020)

BEI: 5.2 mmol/l, mandelic acid [in urine]. Sampling time: after work shift at the end of the working week or exposure period.

No exposure indices known.

acetone

DFG BEI-values list (Germany, 7/2022)

BEI: 50 mg/l, acetone [in urine]. Sampling time: end of exposure or end of shift.

TRGS 903 - BEI Values (Germany, 2/2022)

BEI: 80 mg/l, acetone [in urine]. Sampling time: end of exposure or end of shift.

Toluene

DFG BEI-values list (Germany, 7/2022) Notes: danger from percutaneous absorption (see p. 211 and p. 228).

BEI: 600 µg/l, toluene [in blood]. Sampling time: immediately after exposure.

BEI: 1.5 mg/l, o-cresol (after hydrolysis) [in urine]. Sampling time: end of exposure or end of shift / for long-term exposures: at the end of the shift after several shifts.

BEI: 75 µg/l, toluene [in urine]. Sampling time: end of exposure or end of shift.

TRGS 903 - BEI Values (Germany, 2/2022)

BEI: 600 µg/l, toluene [in whole blood]. Sampling time:

SECTION 8: Exposure controls/personal protection

| | |
|---------------------------------------|---|
| Xylene | <p>immediately after exposure. BEI: 1.5 mg/l, o-cresol (after hydrolysis) [in urine]. Sampling time: end of exposure or end of shift; for long-term exposures: at the end of shift after several shifts. BEI: 75 µg/l, toluene [in urine]. Sampling time: end of exposure or end of shift.</p> <p>DFG BEI-values list (Germany, 7/2022) [Xylene (all isomers)] Notes: danger from percutaneous absorption (see p. 211 and p. 228). BEI: 2000 mg/l, methylhippuric acid (toluric acid) (all isomers) [in urine]. Sampling time: end of exposure or end of shift. TRGS 903 - BEI Values (Germany, 2/2022) [Xylene (all isomers)] BEI: 2000 mg/l, methylhippuric acid [in urine]. Sampling time: end of exposure or end of shift.</p> |
| Propan-2-ol | <p>DFG BEI-values list (Germany, 7/2022) BEI: 25 mg/l, acetone [in blood]. Sampling time: end of exposure or end of shift. BEI: 25 mg/l, acetone [in urine]. Sampling time: end of exposure or end of shift. TRGS 903 - BEI Values (Germany, 2/2022) BEI: 25 mg/l, acetone [in whole blood]. Sampling time: end of exposure or end of shift. BEI: 25 mg/l, acetone [in urine]. Sampling time: end of exposure or end of shift.</p> |
| Ethylbenzene | <p>DFG BEI-values list (Germany, 7/2022) Notes: danger from percutaneous absorption (see p. 211 and p. 228). BEI: 250 mg/g creatinine, mandelic acid plus phenyl glyoxylic acid [in urine]. Sampling time: end of exposure or end of shift. TRGS 903 - BEI Values (Germany, 2/2022) BEI: 250 mg/g creatinine, mandelic acid plus phenylglyoxylic acid [in urine]. Sampling time: end of exposure or end of shift.</p> |
| 1-Ethoxy-2-propanol | <p>DFG BEI-values list (Germany, 7/2022) Notes: danger from percutaneous absorption (see p. 211 and p. 228). BEI: See Section XII.2: Substances for which no BAT values are currently be derived, but documentaries in the "work Medico-toxicological justifications for BAT values, EKA and BLW", 1-ethoxy-2-propanol [in urine]. Sampling time: end of exposure or end of shift.</p> |
| No exposure indices known. acetone | <p>5/2020. (II. 6.) ITM Decree (Hungary, 12/2022) BEI: 1380 µmol/l, acetone [in urine]. Sampling time: at the end of the shift. BEI: 80 mg/l, acetone [in urine]. Sampling time: at the end of the shift.</p> |
| Toluene | <p>5/2020. (II. 6.) ITM Decree (Hungary, 12/2022) BEI: 1 mg/g creatinine, o-cresol [in urine]. Sampling time: at the end of the shift. BEI: 1 µmol/mmol creatinine, o-cresol [in urine]. Sampling time: at the end of the shift.</p> |
| Xylene | <p>5/2020. (II. 6.) ITM Decree (Hungary, 12/2022) [xylene] BEI: 1500 mg/g creatinine, methylhippuric acid [in urine]. Sampling time: at the end of the shift. BEI: 860 µmol/mmol creatinine, methylhippuric acid [in urine]. Sampling time: at the end of the shift.</p> |
| Propan-2-ol | <p>5/2020. (II. 6.) ITM Decree (Hungary, 12/2022) BEI: 430 µmol/l, acetone [in urine]. Sampling time: at the end of</p> |

SECTION 8: Exposure controls/personal protection

| | |
|---------------------------------------|--|
| Ethylbenzene | <p>the shift. BEI: 25 mg/l, acetone [in urine]. Sampling time: at the end of the shift.</p> <p>5/2020. (II. 6.) ITM Decree (Hungary, 12/2022) BEI: 1500 mg/g creatinine, mandelic acid [in urine]. Sampling time: at the end of the working week; at the end of the shift. BEI: 1110 µmol/mmol creatinine, mandelic acid [in urine]. Sampling time: at the end of the working week; at the end of the shift.</p> |
| No exposure indices known. acetone | <p>NAOSH (Ireland, 1/2011) BMGV: 50 mg/l, acetone [in urine]. Sampling time: end of shift - As soon as possible after exposure ceases.</p> |
| Toluene | <p>NAOSH (Ireland, 1/2011) BMGV: 0.3 mg/g creatinine, o-cresol [in urine]. Sampling time: end of shift - As soon as possible after exposure ceases. BMGV: 0.03 mg/l, toluene [in urine]. Sampling time: end of shift - As soon as possible after exposure ceases. BMGV: 0.02 mg/l, toluene [in blood]. Sampling time: prior to last shift of workweek.</p> |
| Xylene | <p>NAOSH (Ireland, 1/2011) [Xylene] BMGV: 1.5 g/g creatinine, methylhippuric acids [in urine]. Sampling time: end of shift - As soon as possible after exposure ceases.</p> |
| Propan-2-ol | <p>NAOSH (Ireland, 1/2011) BMGV: 40 mg/l, acetone [in urine]. Sampling time: end of shift at end of workweek.</p> |
| Ethylbenzene | <p>NAOSH (Ireland, 1/2011) BMGV: Semi-quantitative, the biological analyte is an indicator of exposure to the substance but the quantitative interpretation of the measurement is ambiguous. These analytes should be used as a screening test if a quantitative test is not practical; or as a confirmatory test if the quantitative test is not specific and the origin of the determinant is in question., ethylbenzene [in endexhaled air]. Sampling time: not critical. BMGV: 0.7 g/g creatinine [Semi-quantitative, the biological analyte is an indicator of exposure to the substance but the quantitative interpretation of the measurement is ambiguous. These analytes should be used as a screening test if a quantitative test is not practical; or as a confirmatory test if the quantitative test is not specific and the origin of the determinant is in question.], mandelic acid and phenylglyoxylic acid [in urine]. Sampling time: end of shift at end of workweek.</p> |
| No exposure indices known. | |
| Toluene | <p>Minister Cabinet Regulations No.325 - BEI (Latvia, 7/2018) BEI: 0.05 mg/l, toluene [in blood]. BEI: 1.6 g/g creatinine, hippuric acid [in urine]. Sampling time: end of the shift.</p> |
| No exposure indices known. | |
| No exposure indices known. | |
| No exposure indices known. | |
| No exposure indices known. | |
| No exposure indices known. | |
| No exposure indices known. | |

SECTION 8: Exposure controls/personal protection

| | |
|--------------|--|
| acetone | Portuguese Institute of Quality (Portugal, 11/2014) BEI: 50 mg/l, acetone [in urine]. Sampling time: end of shift. |
| Toluene | Portuguese Institute of Quality (Portugal, 11/2014) BEI: 0.3 mg/g creatinine, o-cresol [in urine]. Sampling time: end of shift. BEI: 0.03 mg/l, toluene [in urine]. Sampling time: end of shift. BEI: 0.02 mg/l, toluene [in blood]. Sampling time: end of shift at the end of the workweek. |
| Xylene | Portuguese Institute of Quality (Portugal, 11/2014) [Xylenes] BEI: 1.5 g/g creatinine, (o, m, p) -methyl-boronic acids [in urine]. Sampling time: end of shift. |
| Propan-2-ol | Portuguese Institute of Quality (Portugal, 11/2014) BEI: 40 mg/l, acetone [in urine]. Sampling time: end of shift at the end of the workweek. |
| Ethylbenzene | Portuguese Institute of Quality (Portugal, 11/2014) BEI: 0.7 g/g creatinine, sum of mandelic acid and phenylglyoxylic acid [in urine]. Sampling time: end of shift. |
| acetone | HG 1218/2006, Annex 2, with subsequent modifications and additions (Romania, 3/2020) OBLV: 50 mg/l, acetone [in urine]. Sampling time: end of shift. |
| Toluene | HG 1218/2006, Annex 2, with subsequent modifications and additions (Romania, 3/2020) OBLV: 3 mg/l, o-cresol [in urine]. Sampling time: end of shift. OBLV: 2 g/l, hippuric acid [in urine]. Sampling time: end of shift. |
| Xylene | HG 1218/2006, Annex 2, with subsequent modifications and additions (Romania, 3/2020) [Xylene] OBLV: 3 g/l, methylhippuric acid [in urine]. Sampling time: end of shift. |
| Propan-2-ol | HG 1218/2006, Annex 2, with subsequent modifications and additions (Romania, 3/2020) OBLV: 50 mg/l, acetone [in urine]. Sampling time: end of shift. |
| Ethylbenzene | HG 1218/2006, Annex 2, with subsequent modifications and additions (Romania, 3/2020) OBLV: 1.5 g/g creatinine, mandelic acid [in urine]. Sampling time: end of the week. |
| acetone | Government regulation SR c. 355/2006 (Slovakia, 9/2020) BLV: 103.9 µmol/mmol creatinine, acetone [in urine]. Sampling time: at the end of exposure or work shift. BLV: 53.36 mg/g creatinine, acetone [in urine]. Sampling time: at the end of exposure or work shift. BLV: 1378 µmol/l, acetone [in urine]. Sampling time: at the end of exposure or work shift. BLV: 80 mg/l, acetone [in urine]. Sampling time: at the end of exposure or work shift. |
| Toluene | Government regulation SR c. 355/2006 (Slovakia, 9/2020) BLV: 1010 µmol/mmol creatinine, hippuric acid [in urine]. Sampling time: at the end of exposure or work shift. BLV: 1.08 µmol/mmol creatinine, o-cresol [in urine]. Sampling time: at the end of exposure or work shift; long-term exposure: after several work shifts. BLV: 1600 mg/g creatinine, hippuric acid [in urine]. Sampling time: at the end of exposure or work shift. BLV: 1.03 mg/g creatinine, o-cresol [in urine]. Sampling time: at the end of exposure or work shift; long-term exposure: after several work shifts. |

SECTION 8: Exposure controls/personal protection

| | |
|--------------|---|
| | <p>BLV: 13399 µmol/l, hippuric acid [in urine]. Sampling time: at the end of exposure or work shift.</p> <p>BLV: 14.3 µmol/l, o-cresol [in urine]. Sampling time: at the end of exposure or work shift; long-term exposure: after several work shifts.</p> <p>BLV: 6517 nmol/l, toluene [in blood]. Sampling time: at the end of exposure or work shift.</p> <p>BLV: 2401 mg/l, hippuric acid [in urine]. Sampling time: at the end of exposure or work shift.</p> <p>BLV: 1.5 mg/l, o-cresol [in urine]. Sampling time: at the end of exposure or work shift; long-term exposure: after several work shifts.</p> <p>BLV: 600 µg/l, toluene [in blood]. Sampling time: at the end of exposure or work shift.</p> |
| Xylene | <p>Government regulation SR c. 355/2006 (Slovakia, 9/2020) [xylene, all isomers]</p> <p>BLV: 781 µmol/mmol creatinine, sum of 2,3,4-methylhippuroic acids [in urine]. Sampling time: at the end of exposure or work shift.</p> <p>BLV: 1334 mg/g creatinine, sum of 2,3,4-methylhippuroic acids [in urine]. Sampling time: at the end of exposure or work shift.</p> <p>BLV: 10355 µmol/l, sum of 2,3,4-methylhippuroic acids [in urine]. Sampling time: at the end of exposure or work shift.</p> <p>BLV: 14.6 µmol/l, xylene [in blood]. Sampling time: at the end of exposure or work shift.</p> <p>BLV: 2000 mg/l, sum of 2,3,4-methylhippuroic acids [in urine]. Sampling time: at the end of exposure or work shift.</p> <p>BLV: 1.5 mg/l, xylene [in blood]. Sampling time: at the end of exposure or work shift.</p> |
| Ethylbenzene | <p>Government regulation SR c. 355/2006 (Slovakia, 9/2020)</p> <p>BLV: 799 µmol/mmol creatinine, mandelic acid and phenylglyoxylic acid [in urine]. Sampling time: at the end of exposure or work shift; long-term exposure: after several work shifts.</p> <p>BLV: 7.44 µmol/mmol creatinine, 2 or 4-ethylfenol [in urine]. Sampling time: at the end of exposure or work shift; long-term exposure: after several work shifts.</p> <p>BLV: 1067 mg/g creatinine, mandelic acid and phenylglyoxylic acid [in urine]. Sampling time: at the end of exposure or work shift; long-term exposure: after several work shifts.</p> <p>BLV: 8.03 mg/g creatinine, 2 or 4-ethylfenol [in urine]. Sampling time: at the end of exposure or work shift; long-term exposure: after several work shifts.</p> <p>BLV: 10590 µmol/l, mandelic acid and phenylglyoxylic acid [in urine]. Sampling time: at the end of exposure or work shift; long-term exposure: after several work shifts.</p> <p>BLV: 98.6 µmol/l, 2 or 4-ethylfenol [in urine]. Sampling time: at the end of exposure or work shift; long-term exposure: after several work shifts.</p> <p>BLV: 1600 mg/l, mandelic acid and phenylglyoxylic acid [in urine]. Sampling time: at the end of exposure or work shift; long-term exposure: after several work shifts.</p> <p>BLV: 12 mg/l, 2 or 4-ethylfenol [in urine]. Sampling time: at the end of exposure or work shift; long-term exposure: after several work shifts.</p> |
| acetone | <p>Regulation on protection of workers from the risks related to exposure to chemical substances at work (Slovenia, 5/2021)</p> <p>BAT: 80 mg/l, acetone [in urine]. Sampling time: at the end of the work shift.</p> |
| Toluene | <p>Regulation on protection of workers from the risks related to exposure to chemical substances at work (Slovenia, 5/2021)</p> |

SECTION 8: Exposure controls/personal protection

| | |
|---------------------------------------|---|
| | <p>BAT: 1.5 mg/l, o-cresol (after hydrolysis) [in urine]. Sampling time: at the end of the work shift, at long-term exposure: at the end of the work shift after several consecutive workdays.</p> <p>BAT: 600 µg/l, toluene [in blood]. Sampling time: immediately after exposure.</p> <p>BAT: 75 µg/l, toluene [in urine]. Sampling time: at the end of the work shift.</p> |
| Xylene | <p>Regulation on protection of workers from the risks related to exposure to chemical substances at work (Slovenia, 5/2021) [xylene (all isomers)]</p> <p>BAT: 2 g/l, methylhippuric acid (all isomers) [in urine]. Sampling time: at the end of the work shift.</p> |
| Propan-2-ol | <p>Regulation on protection of workers from the risks related to exposure to chemical substances at work (Slovenia, 5/2021)</p> <p>BAT: 25 mg/l, acetone [in urine]. Sampling time: at the end of the work shift.</p> <p>BAT: 25 mg/l, acetone [in blood]. Sampling time: at the end of the work shift.</p> |
| Ethylbenzene | <p>Regulation on protection of workers from the risks related to exposure to chemical substances at work (Slovenia, 5/2021)</p> <p>BAT: 250 mg/g creatinine, mandelic acid and phenylglyoxylic acid [in urine]. Sampling time: at the end of the work shift.</p> |
| acetone | <p>National institute of occupational safety and health (Spain, 4/2022)</p> <p>VLB: 50 mg/l, acetone [in urine]. Sampling time: end of shift.</p> |
| Toluene | <p>National institute of occupational safety and health (Spain, 4/2022)</p> <p>VLB: 0.05 mg/l, toluene [in blood]. Sampling time: prior to last shift of workweek.</p> <p>VLB: 0.6 mg/g creatinine, o-cresol [in urine]. Sampling time: end of shift.</p> <p>VLB: 0.08 mg/l, toluene [in urine]. Sampling time: end of shift.</p> |
| Xylene | <p>National institute of occupational safety and health (Spain, 4/2022) [Xylenes]</p> <p>VLB: 1 g/g creatinine, methylhippuric acids [in urine]. Sampling time: end of shift.</p> |
| Propan-2-ol | <p>National institute of occupational safety and health (Spain, 4/2022)</p> <p>VLB: 40 mg/l, acetone [in urine]. Sampling time: end of workweek.</p> |
| Ethylbenzene | <p>National institute of occupational safety and health (Spain, 4/2022)</p> <p>VLB: 700 mg/g creatinine, sum of mandelic acid and acid and phenylglyoxylic acid [in urine]. Sampling time: end of workweek.</p> |
| No exposure indices known. acetone | <p>SUVA (Switzerland, 1/2023)</p> <p>BEI: 50 mg/l, acetone [in urine]. Sampling time: immediately after exposure or after working hours.</p> <p>BEI: 0.86 mmol/l, acetone [in urine]. Sampling time: immediately after exposure or after working hours.</p> |
| Toluene | <p>SUVA (Switzerland, 1/2023)</p> <p>BEI: 2 g/g creatinine, hippuric acid [in urine]. Sampling time: immediately after exposure or after working hours. In case of long-term exposure: after more than one shift.</p> <p>BEI: 1.26 mmol/mmol creatinine, hippuric acid [in urine]. Sampling time: immediately after exposure or after working hours. In case of long-term exposure: after more than one shift.</p> |

SECTION 8: Exposure controls/personal protection

| | |
|--------------|--|
| | <p>BEI: 0.5 mg/l, o-cresol [in urine]. Sampling time: immediately after exposure or after working hours. In case of long-term exposure: after more than one shift.</p> <p>BEI: 4.62 µmol/l, o-cresol [in urine]. Sampling time: immediately after exposure or after working hours. In case of long-term exposure: after more than one shift.</p> <p>BEI: 600 µg/l, toluene [in blood]. Sampling time: immediately after exposure or after working hours.</p> <p>BEI: 6.48 µmol/l, toluene [in blood]. Sampling time: immediately after exposure or after working hours.</p> <p>BEI: 75 µg/l, toluene [in urine]. Sampling time: immediately after exposure or after working hours.</p> |
| Xylene | <p>SUVA (Switzerland, 1/2023) [Xylene, all isomers]</p> <p>BEI: 2 g/l, methyl hippuric acid [in urine]. Sampling time: immediately after exposure or after working hours.</p> |
| Propan-2-ol | <p>SUVA (Switzerland, 1/2023)</p> <p>BEI: 0.4 mmol/l, acetone [in blood]. Sampling time: immediately after exposure or after working hours.</p> <p>BEI: 25 mg/l, acetone [in blood]. Sampling time: immediately after exposure or after working hours.</p> <p>BEI: 0.4 mmol/l, acetone [in urine]. Sampling time: immediately after exposure or after working hours.</p> <p>BEI: 25 mg/l, acetone [in urine]. Sampling time: immediately after exposure or after working hours.</p> |
| Ethylbenzene | <p>SUVA (Switzerland, 1/2023)</p> <p>BEI: 600 mg/g creatinine, mandelic acid + phenylglyoxylic acid [in urine]. Sampling time: immediately after exposure or after working hours.</p> |
| Xylene | <p>EH40/2005 BMGVs (United Kingdom (UK), 8/2018) [Xylene, o-, m-, p- or mixed isomers]</p> <p>BGV: 650 mmol/mol creatinine, methyl hippuric acid [in urine]. Sampling time: post shift.</p> |

Recommended monitoring procedures : Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

| Product/ingredient name | Type | Exposure | Value | Population | Effects |
|-------------------------|------|-----------------------|------------------------|--------------------|----------|
| n-Butyl acetate | DNEL | Short term Oral | 2 mg/kg bw/day | General population | Systemic |
| | DNEL | Long term Oral | 2 mg/kg bw/day | General population | Systemic |
| | DNEL | Short term Dermal | 6 mg/kg bw/day | General population | Systemic |
| | DNEL | Short term Dermal | 11 mg/kg bw/day | Workers | Systemic |
| | DNEL | Long term Inhalation | 35.7 mg/m ³ | General population | Local |
| | DNEL | Short term Inhalation | 300 mg/m ³ | General population | Local |
| | DNEL | Short term Inhalation | 300 mg/m ³ | General population | Systemic |
| | DNEL | Long term Inhalation | 300 mg/m ³ | Workers | Local |

SECTION 8: Exposure controls/personal protection

| | | | | | |
|---------|--------------------------|--------------------------|----------------------------|-----------------------|----------|
| acetone | DNEL | Inhalation Short term | 600 mg/m ³ | Workers | Local |
| | DNEL | Inhalation Short term | 600 mg/m ³ | Workers | Systemic |
| | DNEL | Inhalation Long term | 3.4 mg/kg bw/day | General population | Systemic |
| | DNEL | Dermal Long term | 7 mg/kg bw/day | Workers | Systemic |
| | DNEL | Inhalation Long term | 12 mg/m ³ | General population | Systemic |
| | DNEL | Inhalation Long term | 48 mg/m ³ | Workers | Systemic |
| | DNEL | Oral Long term | 62 mg/kg bw/day | General population | Systemic |
| | DNEL | Dermal Long term | 62 mg/kg bw/day | General population | Systemic |
| | DNEL | Dermal Long term | 186 mg/kg bw/day | Workers | Systemic |
| | DNEL | Inhalation Long term | 200 mg/m ³ | General population | Systemic |
| Toluene | DNEL | Inhalation Long term | 1210 mg/ m ³ | Workers | Systemic |
| | DNEL | Inhalation Short term | 2420 mg/ m ³ | Workers | Local |
| | DNEL | Oral Long term | 8.13 mg/ kg bw/day | General population | Systemic |
| | DNEL | Inhalation Long term | 56.5 mg/m ³ | General population | Local |
| | DNEL | Inhalation Long term | 56.5 mg/m ³ | General population | Systemic |
| | DNEL | Inhalation Long term | 192 mg/m ³ | Workers | Local |
| | DNEL | Inhalation Long term | 192 mg/m ³ | Workers | Systemic |
| | DNEL | Dermal Long term | 226 mg/kg bw/day | General population | Systemic |
| | DNEL | Inhalation Short term | 226 mg/m ³ | General population | Local |
| | DNEL | Inhalation Short term | 226 mg/m ³ | General population | Systemic |
| Xylene | DNEL | Dermal Long term | 384 mg/kg bw/day | Workers | Systemic |
| | DNEL | Inhalation Short term | 384 mg/m ³ | Workers | Local |
| | DNEL | Inhalation Short term | 384 mg/m ³ | Workers | Systemic |
| | DNEL | Inhalation Long term | 65.3 mg/m ³ | General population | Local |
| | DNEL | Inhalation Short term | 260 mg/m ³ | General population | Local |
| | DNEL | Inhalation Short term | 260 mg/m ³ | General population | Systemic |
| | DNEL | Inhalation Long term | 221 mg/m ³ | Workers | Local |
| | DNEL | Oral Long term | 12.5 mg/ kg bw/day | General population | Systemic |
| | DNEL | Inhalation Long term | 65.3 mg/m ³ | General population | Systemic |
| | DNEL | Dermal Long term | 125 mg/kg bw/day | General population | Systemic |
| DNEL | Dermal Long term | 212 mg/kg bw/day | Workers | Systemic | |
| DNEL | Inhalation Long term | 221 mg/m ³ | Workers | Systemic | |
| DNEL | Inhalation Short term | 442 mg/m ³ | Workers | Local | |

SECTION 8: Exposure controls/personal protection

| | | | | | | |
|---------------------|-------------|------------------------------|----------------------------|-----------------------|-----------------------|----------|
| Ethyl acetate | DNEL | Inhalation Short term | 442 mg/m ³ | Workers | Systemic | |
| | DNEL | Inhalation Long term Oral | 4.5 mg/kg bw/day | General population | Systemic | |
| | DNEL | Long term Dermal | 37 mg/kg bw/day | General population | Systemic | |
| | DNEL | Long term Dermal | 63 mg/kg bw/day | Workers | Systemic | |
| | DNEL | Long term Inhalation | 367 mg/m ³ | General population | Local | |
| | DNEL | Long term Inhalation | 367 mg/m ³ | General population | Systemic | |
| | DNEL | Short term Inhalation | 734 mg/m ³ | General population | Local | |
| | DNEL | Short term Inhalation | 734 mg/m ³ | General population | Systemic | |
| | DNEL | Long term Inhalation | 734 mg/m ³ | Workers | Local | |
| | DNEL | Long term Inhalation | 734 mg/m ³ | Workers | Systemic | |
| | DNEL | Short term Inhalation | 1468 mg/ m ³ | Workers | Local | |
| | DNEL | Short term Inhalation | 1468 mg/ m ³ | Workers | Systemic | |
| | iso-butanol | DNEL | Long term Inhalation | 55 mg/m ³ | General population | Local |
| | | DNEL | Long term Inhalation | 310 mg/m ³ | Workers | Local |
| | Propan-2-ol | DNEL | Long term Oral | 26 mg/kg bw/day | General population | Systemic |
| DNEL | | Long term Inhalation | 89 mg/m ³ | General population | Systemic | |
| DNEL | | Long term Dermal | 319 mg/kg bw/day | General population | Systemic | |
| DNEL | | Long term Inhalation | 500 mg/m ³ | Workers | Systemic | |
| DNEL | | Long term Dermal | 888 mg/kg bw/day | Workers | Systemic | |
| Ethylbenzene | DNEL | Long term Oral | 1.6 mg/kg bw/day | General population | Systemic | |
| | DNEL | Long term Inhalation | 15 mg/m ³ | General population | Systemic | |
| | DNEL | Long term Inhalation | 77 mg/m ³ | Workers | Systemic | |
| | DNEL | Long term Dermal | 180 mg/kg bw/day | Workers | Systemic | |
| | DNEL | Short term Inhalation | 293 mg/m ³ | Workers | Local | |
| | DMEL | Long term Inhalation | 442 mg/m ³ | Workers | Local | |
| | DMEL | Short term Inhalation | 884 mg/m ³ | Workers | Systemic | |
| 1-Ethoxy-2-propanol | DNEL | Long term Inhalation | 106 mg/m ³ | Workers | Systemic | |
| | DNEL | Long term Oral | 14 mg/kg bw/day | General population | Systemic | |
| | DNEL | Long term Dermal | 44.3 mg/ kg bw/day | General population | Systemic | |
| | DNEL | Long term Dermal | 74 mg/kg bw/day | Workers | Systemic | |
| | DNEL | Long term Inhalation | 127 mg/m ³ | General population | Systemic | |
| | DNEL | Short term Inhalation | 300 mg/m ³ | General population | Systemic | |
| | DNEL | Short term | 500 mg/m ³ | Workers | Systemic | |

SECTION 8: Exposure controls/personal protection

Inhalation

PNECs

No PNECs available

8.2 Exposure controls

Appropriate engineering controls : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Individual protection measures

Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/or face shield. If inhalation hazards exist, a full-face respirator may be required instead.

Skin protection

Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Recommendations : Wear suitable gloves tested to EN374.

< 1 hour (breakthrough time): Nitrile gloves. thickness > 0.3 mm

1 - 4 hours (breakthrough time): 4H / Silver Shield® gloves.

Body protection : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves. Refer to European Standard EN 1149 for further information on material and design requirements and test methods.

Other skin protection : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Filter type: A

Filter type (spray application): A P

Environmental exposure controls : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

Appearance

| | |
|--|------------------|
| Physical state | : Liquid. |
| Colour | : Colourless. |
| Odour | : Slight |
| Odour threshold | : Not available. |
| Melting point/freezing point | : Not available. |
| Initial boiling point and boiling range | : |

| Ingredient name | °C | °F | Method |
|-----------------|-------|-------|--------|
| acetone | 56.05 | 132.9 | |
| Ethyl acetate | 77.1 | 170.8 | |

| | |
|--|------------------------------|
| Flammability | : Not available. |
| Lower and upper explosion limit | : Lower: 0.8% Upper: 13% |
| Flash point | : Closed cup: -19°C (-2.2°F) |
| Auto-ignition temperature | : |

| Ingredient name | °C | °F | Method |
|---------------------|-----|-----|---------|
| 1-Ethoxy-2-propanol | 255 | 491 | |
| n-Butyl acetate | 415 | 779 | EU A.15 |

| | |
|----------------------------------|-------------------|
| Decomposition temperature | : Not available. |
| pH | : Not applicable. |
| Viscosity | : Not available. |
| Solubility(ies) | : |
| Not available. | |

| | |
|--|-------------------|
| Solubility in water | : Not available. |
| Partition coefficient: n-octanol/ water | : Not applicable. |
| Vapour pressure | : |

| Ingredient name | Vapour Pressure at 20°C | | | Vapour pressure at 50°C | | |
|-----------------|-------------------------|------|--------|-------------------------|-----|--------|
| | mm Hg | kPa | Method | mm Hg | kPa | Method |
| acetone | 180.01463 | 24 | | | | |
| Ethyl acetate | 81.59163 | 10.9 | | | | |

| | |
|---------------------------------|-------------------------|
| Relative density | : Not available. |
| Density | : 0.9 g/cm ³ |
| Vapour density | : Not available. |
| Explosive properties | : Not available. |
| Oxidising properties | : Not available. |
| Particle characteristics | |
| Median particle size | : Not applicable. |

SECTION 10: Stability and reactivity

- 10.1 Reactivity** : No specific test data related to reactivity available for this product or its ingredients.
- 10.2 Chemical stability** : The product is stable.
- 10.3 Possibility of hazardous reactions** : Under normal conditions of storage and use, hazardous reactions will not occur.
- 10.4 Conditions to avoid** : Avoid all possible sources of ignition (spark or flame). Do not pressurise, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.
- 10.5 Incompatible materials** : Reactive or incompatible with the following materials:
oxidising materials
- 10.6 Hazardous decomposition products** : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

| Product/ingredient name | Result | Species | Dose | Exposure |
|-------------------------|---------------------------------|---------|-------------------------|----------|
| n-Butyl acetate | LC50 Inhalation Vapour | Rat | 0.74 mg/l | 4 hours |
| | LD50 Dermal | Rabbit | 14112 mg/kg | - |
| | LD50 Oral | Rat | 10760 mg/kg | - |
| acetone | LD50 Oral | Rat | 5800 mg/kg | - |
| Toluene | LC50 Inhalation Vapour | Rat | 49 g/m ³ | 4 hours |
| | LD50 Oral | Rat | 636 mg/kg | - |
| Xylene | LC50 Inhalation Vapour | Rat | 21.7 mg/l | 4 hours |
| | LD50 Oral | Rat | 4300 mg/kg | - |
| Ethyl acetate | LD50 Oral | Rat | 5620 mg/kg | - |
| iso-butanol | LC50 Inhalation Vapour | Rat | 19200 mg/m ³ | 4 hours |
| | LD50 Dermal | Rabbit | 3400 mg/kg | - |
| | LD50 Oral | Rat | 2460 mg/kg | - |
| Propan-2-ol | LD50 Dermal | Rabbit | 12800 mg/kg | - |
| | LD50 Oral | Rat | 5000 mg/kg | - |
| Ethylbenzene | LC50 Inhalation Dusts and mists | Rat | 29000 mg/l | 4 hours |
| | LD50 Dermal | Rabbit | 15400 mg/kg | - |
| | LD50 Oral | Rat | 3500 mg/kg | - |
| 1-Ethoxy-2-propanol | LD50 Dermal | Rabbit | 8100 mg/kg | - |
| | LD50 Oral | Rat | 4400 mg/kg | - |

Conclusion/Summary : Based on available data, the classification criteria are not met.

Acute toxicity estimates

| Route | ATE value |
|----------------------|----------------|
| Dermal | 15133.07 mg/kg |
| Inhalation (vapours) | 117.01 mg/l |

Irritation/Corrosion

| Product/ingredient name | Result | Species | Score | Exposure | Observation |
|-------------------------|--------------------------|---------|-------|-----------------|-------------|
| n-Butyl acetate | Eyes - Moderate irritant | Rabbit | - | 100 mg | - |
| | Skin - Moderate irritant | Rabbit | - | 24 hours 500 mg | - |
| acetone | Eyes - Mild irritant | Human | - | 186300 ppm | - |
| | Eyes - Mild irritant | Rabbit | - | 10 uL | - |
| | Eyes - Moderate irritant | Rabbit | - | 24 hours 20 mg | - |
| | Eyes - Severe irritant | Rabbit | - | 20 mg | - |
| | Skin - Mild irritant | Rabbit | - | 395 mg | - |

SECTION 11: Toxicological information

| | | | | | |
|---------------------|--------------------------|--------|---|--------------------|---|
| Toluene | Skin - Mild irritant | Rabbit | - | 24 hours 500 mg | - |
| | Eyes - Mild irritant | Rabbit | - | 0.5 minutes 100 mg | - |
| | Eyes - Mild irritant | Rabbit | - | 870 ug | - |
| | Eyes - Severe irritant | Rabbit | - | 24 hours 2 mg | - |
| | Skin - Mild irritant | Pig | - | 24 hours 250 uL | - |
| Xylene | Skin - Mild irritant | Rabbit | - | 435 mg | - |
| | Skin - Moderate irritant | Rabbit | - | 24 hours 20 mg | - |
| | Skin - Moderate irritant | Rabbit | - | 500 mg | - |
| | Eyes - Mild irritant | Rabbit | - | 87 mg | - |
| | Eyes - Severe irritant | Rabbit | - | 24 hours 5 mg | - |
| | Skin - Mild irritant | Rat | - | 8 hours 60 uL | - |
| | Skin - Moderate irritant | Rabbit | - | 100 % | - |
| Propan-2-ol | Skin - Moderate irritant | Rabbit | - | 24 hours 500 mg | - |
| | Eyes - Moderate irritant | Rabbit | - | 10 mg | - |
| | Eyes - Moderate irritant | Rabbit | - | 24 hours 100 mg | - |
| | Eyes - Severe irritant | Rabbit | - | 100 mg | - |
| Ethylbenzene | Skin - Mild irritant | Rabbit | - | 500 mg | - |
| | Eyes - Severe irritant | Rabbit | - | 500 mg | - |
| | Skin - Mild irritant | Rabbit | - | 24 hours 15 mg | - |
| 1-Ethoxy-2-propanol | Eyes - Moderate irritant | Rabbit | - | 24 hours 100 mg | - |

Conclusion/Summary : Causes skin irritation.

Sensitisation

Conclusion/Summary : Based on available data, the classification criteria are not met.

Mutagenicity

Conclusion/Summary : Based on available data, the classification criteria are not met.

Carcinogenicity

Conclusion/Summary : Based on available data, the classification criteria are not met.

Reproductive toxicity

Conclusion/Summary : Based on available data, the classification criteria are not met.

Teratogenicity

Conclusion/Summary : Suspected of damaging the unborn child.

Specific target organ toxicity (single exposure)

| Product/ingredient name | Category | Route of exposure | Target organs |
|-------------------------|------------|-------------------|------------------------------|
| n-Butyl acetate | Category 3 | - | Narcotic effects |
| acetone | Category 3 | - | Narcotic effects |
| Toluene | Category 3 | - | Narcotic effects |
| Xylene | Category 3 | - | Respiratory tract irritation |
| Ethyl acetate | Category 3 | - | Narcotic effects |
| iso-butanol | Category 3 | - | Respiratory tract irritation |
| Propan-2-ol | Category 3 | - | Narcotic effects |
| 1-Ethoxy-2-propanol | Category 3 | - | Narcotic effects |

Specific target organ toxicity (repeated exposure)

SECTION 11: Toxicological information

| Product/ingredient name | Category | Route of exposure | Target organs |
|-------------------------|------------|-------------------|----------------|
| Toluene | Category 2 | - | - |
| Xylene | Category 2 | oral, inhalation | - |
| Ethylbenzene | Category 2 | oral, inhalation | hearing organs |

Aspiration hazard

| Product/ingredient name | Result |
|-------------------------|--------------------------------|
| Toluene | ASPIRATION HAZARD - Category 1 |
| Xylene | ASPIRATION HAZARD - Category 1 |
| Ethylbenzene | ASPIRATION HAZARD - Category 1 |

Information on likely routes of exposure : Not available.

Potential acute health effects

- Eye contact** : Causes serious eye damage.
- Inhalation** : Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness.
- Skin contact** : Causes skin irritation.
- Ingestion** : Can cause central nervous system (CNS) depression.

Symptoms related to the physical, chemical and toxicological characteristics

- Eye contact** : Adverse symptoms may include the following:
pain
watering
redness
- Inhalation** : Adverse symptoms may include the following:
nausea or vomiting
headache
drowsiness/fatigue
dizziness/vertigo
unconsciousness
reduced foetal weight
increase in foetal deaths
skeletal malformations
- Skin contact** : Adverse symptoms may include the following:
pain or irritation
redness
blistering may occur
reduced foetal weight
increase in foetal deaths
skeletal malformations
- Ingestion** : Adverse symptoms may include the following:
stomach pains
reduced foetal weight
increase in foetal deaths
skeletal malformations

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Short term exposure

- Potential immediate effects** : Not available.
- Potential delayed effects** : Not available.

Long term exposure

- Potential immediate effects** : Not available.
- Potential delayed effects** : Not available.

SECTION 11: Toxicological information

Potential chronic health effects

Not available.

| | |
|------------------------------|--|
| Conclusion/Summary | : Not available. |
| General | : May cause damage to organs through prolonged or repeated exposure. |
| Carcinogenicity | : No known significant effects or critical hazards. |
| Mutagenicity | : No known significant effects or critical hazards. |
| Reproductive toxicity | : Suspected of damaging the unborn child. |

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

Not available.

11.2.2 Other information

Not available.

SECTION 12: Ecological information

12.1 Toxicity

| Product/ingredient name | Result | Species | Exposure |
|----------------------------|--------------------------------------|--|----------|
| n-Butyl acetate acetone | Acute LC50 32 mg/l Marine water | Crustaceans - <i>Artemia salina</i> | 48 hours |
| | Acute LC50 18000 µg/l Fresh water | Fish - <i>Pimephales promelas</i> | 96 hours |
| | Acute EC50 20.565 mg/l Marine water | Algae - <i>Ulva pertusa</i> | 96 hours |
| | Acute LC50 6000000 µg/l Fresh water | Crustaceans - <i>Gammarus pulex</i> | 48 hours |
| | Acute LC50 10000 µg/l Fresh water | Daphnia - <i>Daphnia magna</i> | 48 hours |
| | Acute LC50 5600 ppm Fresh water | Fish - <i>Poecilia reticulata</i> | 96 hours |
| | Chronic NOEC 4.95 mg/l Marine water | Algae - <i>Ulva pertusa</i> | 96 hours |
| | Chronic NOEC 0.016 ml/L Fresh water | Crustaceans - <i>Daphniidae</i> | 21 days |
| | Chronic NOEC 0.1 ml/L Fresh water | Daphnia - <i>Daphnia magna</i> - Neonate | 21 days |
| | Chronic NOEC 5 µg/l Marine water | Fish - <i>Gasterosteus aculeatus</i> - Larvae | 42 days |
| Toluene | Acute EC50 12500 µg/l Fresh water | Algae - <i>Pseudokirchneriella subcapitata</i> | 72 hours |
| | Acute EC50 11600 µg/l Fresh water | Crustaceans - <i>Gammarus pseudolimnaeus</i> - Adult | 48 hours |
| | Acute EC50 5.56 mg/l Fresh water | Daphnia - <i>Daphnia magna</i> - Neonate | 48 hours |
| | Acute LC50 5500 µg/l Fresh water | Fish - <i>Oncorhynchus kisutch</i> - Fry | 96 hours |
| Ethyl acetate | Chronic NOEC 1000 µg/l Fresh water | Daphnia - <i>Daphnia magna</i> | 21 days |
| | Acute EC50 2500000 µg/l Fresh water | Algae - <i>Selenastrum sp.</i> | 96 hours |
| | Acute LC50 750000 µg/l Fresh water | Crustaceans - <i>Gammarus pulex</i> | 48 hours |
| | Acute LC50 154000 µg/l Fresh water | Daphnia - <i>Daphnia cucullata</i> | 48 hours |
| | Acute LC50 212500 µg/l Fresh water | Fish - <i>Heteropneustes fossilis</i> | 96 hours |
| | Chronic NOEC 12 mg/l Fresh water | Daphnia - <i>Daphnia magna</i> | 21 days |
| iso-butanol | Chronic NOEC 75.6 mg/l Fresh water | Fish - <i>Pimephales promelas</i> - Embryo | 32 days |
| | Acute LC50 600 mg/l Marine water | Crustaceans - <i>Artemia salina</i> | 48 hours |
| Propan-2-ol | Acute LC50 1030000 µg/l Fresh water | Daphnia - <i>Daphnia magna</i> - Neonate | 48 hours |
| | Acute LC50 1330000 µg/l Fresh water | Fish - <i>Oncorhynchus mykiss</i> | 96 hours |
| | Acute EC50 10100 mg/l Fresh water | Daphnia - <i>Daphnia magna</i> | 48 hours |
| | Acute LC50 1400000 µg/l Marine water | Crustaceans - <i>Crangon crangon</i> | 48 hours |
| | Acute LC50 4200000 µg/l Fresh water | Fish - <i>Rasbora heteromorpha</i> | 96 hours |

Conclusion/Summary : Based on available data, the classification criteria are not met.

12.2 Persistence and degradability

SECTION 12: Ecological information

| Product/ingredient name | Test | Result | Dose | Inoculum |
|-------------------------|------|--------------------------|------|----------|
| iso-butanol | - | 74 % - Readily - 28 days | - | - |

Conclusion/Summary : This product has not been tested for biodegradation.

| Product/ingredient name | Aquatic half-life | Photolysis | Biodegradability |
|-------------------------|-------------------|------------|------------------|
| iso-butanol | - | - | Readily |

12.3 Bioaccumulative potential

| Product/ingredient name | LogP _{ow} | BCF | Potential |
|-------------------------|--------------------|-------------|-----------|
| n-Butyl acetate | 2.3 | - | Low |
| acetone | -0.23 | - | Low |
| Toluene | 2.73 | 90 | Low |
| Xylene | 3.12 | 8.1 to 25.9 | Low |
| Ethyl acetate | 0.68 | 30 | Low |
| iso-butanol | 1 | - | Low |
| Propan-2-ol | 0.05 | - | Low |
| Ethylbenzene | 3.6 | - | Low |
| 1-Ethoxy-2-propanol | <1 | - | Low |

12.4 Mobility in soil

Soil/water partition coefficient (K_{oc}) : Not available.

Mobility : Not available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Endocrine disrupting properties

Not available.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

Hazardous waste : The classification of the product may meet the criteria for a hazardous waste.

European waste catalogue (EWC) : 08.01.11






Packaging

Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

SECTION 13: Disposal considerations

Special precautions : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapour from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

| | ADR/RID | ADN | IMDG | IATA |
|---------------------------------|--|--|---|--|
| 14.1 UN number or ID number | UN1993 | UN1993 | UN1993 | UN1993 |
| 14.2 UN proper shipping name | FLAMMABLE LIQUID, N.O.S. (n-butyl acetate, acetone) | FLAMMABLE LIQUID, N.O.S. (n-butyl acetate, acetone) | FLAMMABLE LIQUID, N.O.S. (xylene, ethyl acetate) | FLAMMABLE LIQUID, N.O.S. (xylene, ethyl acetate) |
| 14.3 Transport hazard class(es) | 3  | 3  | 3   | 3  |
| 14.4 Packing group | II | II | II | II |
| 14.5 Environmental hazards | No. | Yes. | Yes. | Yes. The environmentally hazardous substance mark is not required. |

Additional information

ADR/RID : **Special provisions** 640 (C)
Tunnel code (D/E)

ADN : The product is only regulated as an environmentally hazardous substance when transported in tank vessels.
Special provisions 640 (C)

IMDG : The marine pollutant mark is not required when transported in sizes of ≤5 L or ≤5 kg.

IATA : The environmentally hazardous substance mark may appear if required by other transportation regulations.

14.6 Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Maritime transport in bulk according to IMO instruments : Not relevant/applicable due to nature of the product.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

SECTION 15: Regulatory information

| Product/ingredient name | % | Designation [Usage] |
|-------------------------|-----------|---------------------|
| OW COMBI 2315-05 | ≥90 | 3 |
| Toluene | ≥10 - ≤25 | 48 |

Labelling :

Other EU regulations

Industrial emissions (integrated pollution prevention and control) - Air : Listed

Industrial emissions (integrated pollution prevention and control) - Water : Not listed

Explosive precursors : Not applicable.

Ozone depleting substances (1005/2009/EU)

Not listed.

Prior Informed Consent (PIC) (649/2012/EU)

Not listed.

Persistent Organic Pollutants

Not listed.

Seveso Directive

This product is controlled under the Seveso Directive.

Danger criteria

Category

P5c

National regulations

Austria

VbF class : A I
Very dangerous flammable liquid.

Limitation of the use of organic solvents : Permitted.

Czech Republic

Storage code : I

Denmark

Danish fire class : I-1

Executive Order No. 1795/2015

| Ingredient name | Annex I Section A | Annex I Section B |
|-----------------|-------------------|-------------------|
| Propan-2-ol | Listed | - |
| Ethylbenzene | Listed | - |

MAL-code : 4-3

Protection based on MAL : **According to the regulations on work involving coded products, the following stipulations apply to the use of personal protective equipment:**

General: Gloves must be worn for all work that may result in soiling. Apron/coveralls/protective clothing must be worn when soiling is so great that regular work clothes do not adequately protect skin against contact with the product. A face shield must be worn in work involving spattering if a full mask is not required. In this case, other recommended use of eye protection is not required.

In all spraying operations in which there is return spray, respiratory protection with air supply and arm protectors/apron/coveralls/protective clothing must be worn as appropriate or as instructed.

SECTION 15: Regulatory information

MAL-code: 4-3

Application: When spraying in new* booths if the operator is outside the spray zone. When using scraper or knife, brush, roller, etc. for pre- and post-treatments outside a closed facility, spray booth or spray cabin.

- Air-supplied half mask and eye protection must be worn.

When using scraper or knife, brush, roller, etc. for pre- and post-treatments in cabins or booths of the existing* facility type, if the operator is inside the spray zone.

- Air-supplied half mask, coveralls and eye protection must be worn.

During downtimes, cleaning and repair in closed facilities, spray booths or cabins, if there is a risk of contact with wet paint or organic solvents.

- Air-supplied full mask and coveralls must be worn.

When spraying in existing* spray booths, if the operator is outside the spray zone.

- Air-supplied full mask, arm protectors and apron must be worn.

During non-atomising spraying in existing* facilities of the combined-cabin, spray-cabin and spray-booth type where the operator is working inside the spray zone.

- Air-supplied full mask must be worn.

During all spraying where atomisation occurs in cabins or spray booths where the operator is inside the spray zone and during spraying outside a closed facility, cabin or booth.

- Air-supplied full mask, coveralls and hood must be worn.

Drying: Items for drying/drying ovens that are temporarily placed on such things as rack trolleys, etc. must be equipped with a mechanical exhaust system to prevent fumes from wet items from passing through workers' inhalation zone.

Polishing: When polishing treated surfaces, a mask with dust filter must be worn. When machine grinding, eye protection must be worn. Work gloves must always be worn.

Caution The regulations contain other stipulations in addition to the above.

*See Regulations.

- Low-boiling liquids** : This product contains low-boiling point liquids. Any respiratory protective equipment should be air-fed.
- Restrictions on use** : Not to be used by professional users below 18 years of age. See the National Working Environment Authorities Executive Order regarding Young People At Work.
- List of undesirable substances** : Listed
- Carcinogenic waste** : Waste containers must be labeled: Contains a substance or substances regulated by Danish working environment legislation on cancer risks.

[Finland](#)

[France](#)

SECTION 15: Regulatory information

| | | |
|--|--|--|
| Social Security Code, Articles L 461-1 to L 461-7 | : n-Butyl acetate acetone Toluene Xylene Ethyl acetate iso-butanol Propan-2-ol Ethylbenzene | RG 84 RG 84 RG 4bis, RG 84 RG 4bis, RG 84 RG 84 RG 84 RG 84 RG 84 |
|--|--|--|

Reinforced medical surveillance : Act of July 11, 1977 determining the list of activities which require reinforced medical surveillance: not applicable

Germany

Storage class (TRGS 510) : 3

Hazardous incident ordinance

This product is controlled under the Germany Hazardous Incident Ordinance.

Danger criteria

| Category | Reference number |
|----------|------------------|
| P5c | 1.2.5.3 |

Hazard class for water : 3

Technical instruction on air quality control : TA-Luft Number 5.2.5: 72.9%
TA-Luft Class I - Number 5.2.5: 14.1%

Italy

D.Lgs. 152/06 : Not determined.

Netherlands

Ministry of Social Affairs and Employment (SZW) - Carcinogenic substances and processes, mutagenic or reprotoxic substances

| Ingredient name | Carcinogen | Mutagen | Reproductive toxicity - Fertility | Reproductive toxicity - Development | Harmful via breastfeeding |
|-----------------|------------|---------|-----------------------------------|-------------------------------------|---------------------------|
| tolueen | - | - | - | Development 2 | - |
| xylene | - | - | - | Development 2 | - |

Water Discharge Policy (ABM) : A(1) Highly toxic for aquatic organisms, may have long-term hazardous effects in aquatic environment. Decontamination effort: A

Norway

Sweden

Flammable liquid class (SRVFS 2005:10) : 1

Switzerland

VOC content : VOC (w/w): 74.6%

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

SECTION 15: Regulatory information

15.2 Chemical safety assessment : This product contains substances for which Chemical Safety Assessments are still required.

SECTION 16: Other information

✔ Indicates information that has changed from previously issued version.

Abbreviations and acronyms : ATE = Acute Toxicity Estimate
CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
DMEL = Derived Minimal Effect Level
DNEL = Derived No Effect Level
EUH statement = CLP-specific Hazard statement
N/A = Not available
PBT = Persistent, Bioaccumulative and Toxic
PNEC = Predicted No Effect Concentration
RRN = REACH Registration Number
SGG = Segregation Group
vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

| Classification | Justification |
|---|---|
| Flam. Liq. 2, H225 Skin Irrit. 2, H315 Eye Dam. 1, H318 Repr. 2, H361d STOT SE 3, H336 STOT RE 2, H373 | On basis of test data Calculation method Calculation method Calculation method Calculation method Calculation method |

Full text of abbreviated H statements

| | |
|--------|--|
| H225 | Highly flammable liquid and vapour. |
| H226 | Flammable liquid and vapour. |
| H304 | May be fatal if swallowed and enters airways. |
| H312 | Harmful in contact with skin. |
| H315 | Causes skin irritation. |
| H318 | Causes serious eye damage. |
| H319 | Causes serious eye irritation. |
| H332 | Harmful if inhaled. |
| H335 | May cause respiratory irritation. |
| H336 | May cause drowsiness or dizziness. |
| H361d | Suspected of damaging the unborn child. |
| H373 | May cause damage to organs through prolonged or repeated exposure. |
| EUH066 | Repeated exposure may cause skin dryness or cracking. |

Full text of classifications [CLP/GHS]

| | |
|---------------|---|
| Acute Tox. 4 | ACUTE TOXICITY - Category 4 |
| Asp. Tox. 1 | ASPIRATION HAZARD - Category 1 |
| Eye Dam. 1 | SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1 |
| Eye Irrit. 2 | SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2 |
| Flam. Liq. 2 | FLAMMABLE LIQUIDS - Category 2 |
| Flam. Liq. 3 | FLAMMABLE LIQUIDS - Category 3 |
| Repr. 2 | REPRODUCTIVE TOXICITY - Category 2 |
| Skin Irrit. 2 | SKIN CORROSION/IRRITATION - Category 2 |
| STOT RE 2 | SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 2 |
| STOT SE 3 | SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3 |

Date of issue/ Date of revision : 10/01/2024

Date of previous issue : No previous validation

Version : 1

OW COMBI 2315-05

All variants

Notice to reader

Date of issue/Date of revision : 10/01/2024 **Date of previous issue** : No previous validation **Version** : 1 **51/53**

OW COMBI 2315-05

Label No :56756

SECTION 16: Other information

The information in this SDS is based on the present state of our knowledge and on current laws. The product is not to be used for purposes other than those specified under section 1 without first obtaining written handling instructions. It is always the responsibility of the user to take all necessary steps to fulfil the demands set out in the local rules and legislation. The information in this SDS is meant to be a description of the safety requirements for our product. It is not to be considered a guarantee of the product's properties.

