

# SAFETY DATA SHEET



OWECELL 2110-60 - All variants

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

**Product name** : OWECELL 2110-60 - All variants

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Product use** : Paint.

### 1.3 Details of the supplier of the safety data sheet

Teknos Group Oy, Takkatie 3, FI-00370 HELSINKI, FINLAND. Tel. +358 9 506 091.

**e-mail address of person responsible for this SDS** : Prod-safe@teknos.com

#### National contact

Teknos Group Oy, Takkatie 3, FI-00370 HELSINKI, FINLAND. Tel. +358 9 506 091.

### 1.4 Emergency telephone number

#### National advisory body/Poison Centre

**Telephone number** : In an emergency, call 112

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

**Product definition** : Mixture

#### Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Flam. Liq. 2, H225  
Skin Irrit. 2, H315  
Eye Dam. 1, H318  
Repr. 2, H361d  
STOT SE 3, H336

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

### 2.2 Label elements

**Hazard pictograms** :



**Signal word** : Danger

**Hazard statements** : H225 - Highly flammable liquid and vapour.  
H315 - Causes skin irritation.  
H318 - Causes serious eye damage.  
H336 - May cause drowsiness or dizziness.  
H361d - Suspected of damaging the unborn child.

#### Precautionary statements

**Prevention** : P280 - Wear protective gloves, protective clothing, eye protection, face protection, or hearing protection.  
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

**Date of issue/Date of revision** : 09/01/2024 **Date of previous issue** : 09/01/2024

**Version** : 1.01 1/57

OWECELL 2110-60 - All variants

**Label No** : 52118

## SECTION 2: Hazards identification

<b>Response</b>	: P305 + P351 + P338 + P310 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor.
<b>Storage</b>	: P403 + P233 - Store in a well-ventilated place. Keep container tightly closed.
<b>Disposal</b>	: P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.
<b>Hazardous ingredients</b>	: Contains: n-Butyl acetate; acetone; Toluene and iso-butanol
<b>Supplemental label elements</b>	: Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.
<b>Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles</b>	:

### 2.3 Other hazards

<b>Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII</b>	: This mixture does not contain any substances that are assessed to be a PBT or a vPvB.
<b>Other hazards which do not result in classification</b>	: None known.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures : Mixture

Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Type
titanium dioxide	REACH #: 01-2119489379-17 EC: 236-675-5 CAS: 13463-67-7	≥10 - ≤25	Carc. 2, H351 (inhalation)	-	[1] [*]
n-Butyl acetate	REACH #: 01-2119485493-29 EC: 204-658-1 CAS: 123-86-4 Index: 607-025-00-1	≥10 - ≤25	Flam. Liq. 3, H226 STOT SE 3, H336 EUH066	-	[1] [2]
acetone	REACH #: 01-2119471330-49 EC: 200-662-2 CAS: 67-64-1 Index: 606-001-00-8	≥10 - <25	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336 EUH066	EUH066: C ≥ 25%	[1] [2]
Toluene	REACH #: 01-2119471310-51 EC: 203-625-9 CAS: 108-88-3 Index: 601-021-00-3	<10	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Repr. 2, H361d STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304	-	[1] [2]
Xylene	REACH #: 01-2119488216-32 EC: 215-535-7 CAS: 1330-20-7 Index: 601-022-00-9	<10	Flam. Liq. 3, H226 Acute Tox. 4, H312 Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 STOT RE 2, H373 (oral, inhalation)	ATE [Dermal] = 1100 mg/kg ATE [Inhalation (vapours)] = 11 mg/ l	[1] [2]

## SECTION 3: Composition/information on ingredients

Ethyl acetate	REACH #: 01-2119475103-46 EC: 205-500-4 CAS: 141-78-6 Index: 607-022-00-5	≤10	Asp. Tox. 1, H304 Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336 EUH066	-	[1] [2]
iso-butanol	REACH #: 01-2119484609-23 EC: 201-148-0 CAS: 78-83-1 Index: 603-108-00-1	≤5	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H335 STOT SE 3, H336	-	[1]
2-Methoxy-1-methylethyl acetate	REACH #: 01-2119475791-29 EC: 203-603-9 CAS: 108-65-6 Index: 607-195-00-7	≤5	Flam. Liq. 3, H226	-	[2]
Propan-2-ol	REACH #: 01-2119457558-25 EC: 200-661-7 CAS: 67-63-0 Index: 603-117-00-0	≤3	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336	-	[1]
Ethylbenzene	REACH #: 01-2119489370-35 EC: 202-849-4 CAS: 100-41-4 Index: 601-023-00-4	≤3	Flam. Liq. 2, H225 Acute Tox. 4, H332 STOT RE 2, H373 (hearing organs) (oral, inhalation) Asp. Tox. 1, H304	ATE [Inhalation (vapours)] = 11 mg/l	[1] [2]
1-Ethoxy-2-propanol	REACH #: 01-2119462792-32 EC: 216-374-5 CAS: 1569-02-4 Index: 603-177-00-8	≤3	Flam. Liq. 3, H226 STOT SE 3, H336	-	[1]
<b>See Section 16 for the full text of the H statements declared above.</b>					

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

### Type

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

[\*] The classification as a carcinogen by inhalation applies only to mixtures placed on the market in powder form containing 1% or more of titanium dioxide particles with aerodynamic diameter ≤ 10 µm not bound within a matrix.

Occupational exposure limits, if available, are listed in Section 8.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

#### Eye contact

: Get medical attention immediately. Call a poison center or physician. Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician.

## SECTION 4: First aid measures

- Inhalation** : Get medical attention immediately. Call a poison center or physician. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Skin contact** : Get medical attention immediately. Call a poison center or physician. Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Chemical burns must be treated promptly by a physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

### 4.2 Most important symptoms and effects, both acute and delayed

#### Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:  
pain  
watering  
redness
- Inhalation** : Adverse symptoms may include the following:  
nausea or vomiting  
headache  
drowsiness/fatigue  
dizziness/vertigo  
unconsciousness  
reduced foetal weight  
increase in foetal deaths  
skeletal malformations
- Skin contact** : Adverse symptoms may include the following:  
pain or irritation  
redness  
blistering may occur  
reduced foetal weight  
increase in foetal deaths  
skeletal malformations
- Ingestion** : Adverse symptoms may include the following:  
stomach pains  
reduced foetal weight  
increase in foetal deaths  
skeletal malformations

### 4.3 Indication of any immediate medical attention and special treatment needed

## SECTION 4: First aid measures

- Notes to physician** : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Specific treatments** : No specific treatment.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

- Suitable extinguishing media** : Use dry chemical, CO<sub>2</sub>, water spray (fog) or foam.
- Unsuitable extinguishing media** : Do not use water jet.

### 5.2 Special hazards arising from the substance or mixture

- Hazards from the substance or mixture** : Highly flammable liquid and vapour. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion.
- Hazardous combustion products** : Decomposition products may include the following materials:  
carbon dioxide  
carbon monoxide  
nitrogen oxides  
metal oxide/oxides

### 5.3 Advice for firefighters

- Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Do not breathe vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

### 6.2 Environmental precautions

- : Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

### 6.3 Methods and material for containment and cleaning up

- Small spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

## SECTION 6: Accidental release measures

**Large spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product.

**6.4 Reference to other sections** : See Section 1 for emergency contact information.  
See Section 8 for information on appropriate personal protective equipment.  
See Section 13 for additional waste treatment information.

## SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

### 7.1 Precautions for safe handling

**Protective measures** : Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapour or mist. Do not ingest. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.

**Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

### 7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Eliminate all ignition sources. Separate from oxidising materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

#### Seveso Directive - Reporting thresholds

##### Danger criteria

Category	Notification and MAPP threshold	Safety report threshold
P5c	5000 tonne	50000 tonne

### 7.3 Specific end use(s)

**Recommendations** : Not available.

**Industrial sector specific solutions** : Not available.

## SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

### 8.1 Control parameters

#### Occupational exposure limits

Product/ingredient name	Exposure limit values
n-Butyl acetate	<b>Regulation on Limit Values - MAC (Austria, 4/2021). [Butyl acetate (all isomers except tert-butyl acetate)]</b> CEIL: 480 mg/m <sup>3</sup> 15 minutes. CEIL: 100 ppm 15 minutes. TWA: 241 mg/m <sup>3</sup> 8 hours. TWA: 50 ppm 8 hours.
acetone	<b>Regulation on Limit Values - MAC (Austria, 4/2021).</b> TWA: 500 ppm 8 hours. TWA: 1200 mg/m <sup>3</sup> 8 hours. PEAK: 2000 ppm, 4 times per shift, 15 minutes. PEAK: 4800 mg/m <sup>3</sup> , 4 times per shift, 15 minutes.
Toluene	<b>Regulation on Limit Values - MAC (Austria, 4/2021). Absorbed through skin.</b> TWA: 50 ppm 8 hours. TWA: 190 mg/m <sup>3</sup> 8 hours. PEAK: 100 ppm, 4 times per shift, 15 minutes. PEAK: 380 mg/m <sup>3</sup> , 4 times per shift, 15 minutes.
Xylene	<b>Regulation on Limit Values - MAC (Austria, 4/2021). [Xylenes (all isomers)]</b> PEAK: 442 mg/m <sup>3</sup> , 4 times per shift, 15 minutes. TWA: 50 ppm 8 hours. PEAK: 100 ppm, 4 times per shift, 15 minutes. TWA: 221 mg/m <sup>3</sup> 8 hours.
Ethyl acetate	<b>Regulation on Limit Values - MAC (Austria, 4/2021).</b> TWA: 200 ppm 8 hours. TWA: 734 mg/m <sup>3</sup> 8 hours. PEAK: 1468 mg/m <sup>3</sup> , 4 times per shift, 15 minutes. PEAK: 400 ppm, 4 times per shift, 15 minutes.
iso-butanol	<b>Regulation on Limit Values - MAC (Austria, 4/2021). [Butanol (all isomers except 2-methyl-2-propanol)]</b> PEAK: 200 ppm, 4 times per shift, 15 minutes. TWA: 150 mg/m <sup>3</sup> 8 hours. TWA: 50 ppm 8 hours. PEAK: 600 mg/m <sup>3</sup> , 4 times per shift, 15 minutes.
2-Methoxy-1-methylethyl acetate	<b>Regulation on Limit Values - MAC (Austria, 4/2021). Absorbed through skin.</b> TWA: 50 ppm 8 hours. TWA: 275 mg/m <sup>3</sup> 8 hours. CEIL: 100 ppm, 8 times per shift, 5 minutes. CEIL: 550 mg/m <sup>3</sup> , 8 times per shift, 5 minutes.
Propan-2-ol	<b>Regulation on Limit Values - MAC (Austria, 4/2021).</b> TWA: 200 ppm 8 hours. TWA: 500 mg/m <sup>3</sup> 8 hours. PEAK: 800 ppm, 4 times per shift, 15 minutes. PEAK: 2000 mg/m <sup>3</sup> , 4 times per shift, 15 minutes.
Ethylbenzene	<b>Regulation on Limit Values - MAC (Austria, 4/2021). Absorbed through skin.</b> TWA: 100 ppm 8 hours. TWA: 440 mg/m <sup>3</sup> 8 hours. CEIL: 200 ppm, 8 times per shift, 5 minutes. CEIL: 880 mg/m <sup>3</sup> , 8 times per shift, 5 minutes.
1-Ethoxy-2-propanol	<b>Regulation on Limit Values - MAC (Austria, 4/2021).</b> STEL: 880 mg/m <sup>3</sup> 15 minutes. STEL: 200 ppm 15 minutes. TWA: 220 mg/m <sup>3</sup> 8 hours. TWA: 50 ppm 8 hours.

## SECTION 8: Exposure controls/personal protection

n-Butyl acetate	<p><b>Limit values (Belgium, 5/2021). [butyl acetate, all isomers]</b>            STEL: 712 mg/m<sup>3</sup> 15 minutes.            STEL: 150 ppm 15 minutes.            TWA: 238 mg/m<sup>3</sup> 8 hours.            TWA: 50 ppm 8 hours.</p>
acetone	<p><b>Limit values (Belgium, 5/2021).</b>            TWA: 246 ppm 8 hours.            TWA: 594 mg/m<sup>3</sup> 8 hours.            STEL: 492 ppm 15 minutes.            STEL: 1187 mg/m<sup>3</sup> 15 minutes.</p>
Toluene	<p><b>Limit values (Belgium, 5/2021). Absorbed through skin.</b>            TWA: 20 ppm 8 hours.            TWA: 77 mg/m<sup>3</sup> 8 hours.            STEL: 100 ppm 15 minutes.            STEL: 384 mg/m<sup>3</sup> 15 minutes.</p>
Xylene	<p><b>Limit values (Belgium, 5/2021). [Xylene] Absorbed through skin.</b>            TWA: 50 ppm 8 hours.            TWA: 221 mg/m<sup>3</sup> 8 hours.            STEL: 100 ppm 15 minutes.            STEL: 442 mg/m<sup>3</sup> 15 minutes.</p>
Ethyl acetate	<p><b>Limit values (Belgium, 5/2021).</b>            TWA: 200 ppm 8 hours.            TWA: 734 mg/m<sup>3</sup> 8 hours.            STEL: 1468 mg/m<sup>3</sup> 15 minutes.            STEL: 400 ppm 15 minutes.</p>
iso-butanol	<p><b>Limit values (Belgium, 5/2021).</b>            TWA: 50 ppm 8 hours.            TWA: 154 mg/m<sup>3</sup> 8 hours.</p>
2-Methoxy-1-methylethyl acetate	<p><b>Limit values (Belgium, 5/2021). Absorbed through skin.</b>            TWA: 50 ppm 8 hours.            TWA: 275 mg/m<sup>3</sup> 8 hours.            STEL: 100 ppm 15 minutes.            STEL: 550 mg/m<sup>3</sup> 15 minutes.</p>
Propan-2-ol	<p><b>Limit values (Belgium, 5/2021).</b>            TWA: 200 ppm 8 hours.            TWA: 500 mg/m<sup>3</sup> 8 hours.            STEL: 400 ppm 15 minutes.            STEL: 1000 mg/m<sup>3</sup> 15 minutes.</p>
Ethylbenzene	<p><b>Limit values (Belgium, 5/2021). Absorbed through skin.</b>            TWA: 20 ppm 8 hours.            TWA: 87 mg/m<sup>3</sup> 8 hours.            STEL: 125 ppm 15 minutes.            STEL: 551 mg/m<sup>3</sup> 15 minutes.</p>
n-Butyl acetate	<p><b>Ministry of Labour and Social Policy and the Ministry of Health - Ordinance No 13/2003. (Bulgaria, 6/2021).</b>            Limit value 8 hours: 241 mg/m<sup>3</sup> 8 hours.            Limit value 15 min: 723 mg/m<sup>3</sup> 15 minutes.            Limit value 15 min: 150 ppm 15 minutes.            Limit value 8 hours: 50 ppm 8 hours.</p>
acetone	<p><b>Ministry of Labour and Social Policy and the Ministry of Health - Ordinance No 13/2003. (Bulgaria, 6/2021).</b>            Limit value 8 hours: 600 mg/m<sup>3</sup> 8 hours.            Limit value 15 min: 1400 mg/m<sup>3</sup> 15 minutes.</p>
Toluene	<p><b>Ministry of Labour and Social Policy and the Ministry of Health - Ordinance No 13/2003. (Bulgaria, 6/2021). Absorbed through skin.</b>            Limit value 15 min: 384 mg/m<sup>3</sup> 15 minutes.            Limit value 8 hours: 192 mg/m<sup>3</sup> 8 hours.            Limit value 15 min: 100 ppm 15 minutes.            Limit value 8 hours: 50 ppm 8 hours.</p>
Xylene	<p><b>Ministry of Labour and Social Policy and the Ministry of Health - Ordinance No 13/2003. (Bulgaria, 6/2021). [Xylene (mixture of isomers), pure] Absorbed through skin.</b></p>



## SECTION 8: Exposure controls/personal protection

Ethyl acetate	<p>Limit value 8 hours: 221 mg/m<sup>3</sup> 8 hours.            Limit value 15 min: 442 mg/m<sup>3</sup> 15 minutes.            Limit value 15 min: 100 ppm 15 minutes.            Limit value 8 hours: 50 ppm 8 hours.</p> <p><b>Ministry of Labour and Social Policy and the Ministry of Health - Ordinance No 13/2003. (Bulgaria, 6/2021).</b></p> <p>Limit value 8 hours: 734 mg/m<sup>3</sup> 8 hours.            Limit value 15 min: 400 ppm 15 minutes.            Limit value 15 min: 1468 mg/m<sup>3</sup> 15 minutes.            Limit value 8 hours: 200 ppm 8 hours.</p>
2-Methoxy-1-methylethyl acetate	<p><b>Ministry of Labour and Social Policy and the Ministry of Health - Ordinance No 13/2003. (Bulgaria, 6/2021). Absorbed through skin.</b></p> <p>Limit value 8 hours: 275 mg/m<sup>3</sup> 8 hours.            Limit value 15 min: 550 mg/m<sup>3</sup> 15 minutes.            Limit value 15 min: 100 ppm 15 minutes.            Limit value 8 hours: 50 ppm 8 hours.</p>
Propan-2-ol	<p><b>Ministry of Labour and Social Policy and the Ministry of Health - Ordinance No 13/2003. (Bulgaria, 6/2021).</b></p> <p>Limit value 8 hours: 980 mg/m<sup>3</sup> 8 hours.            Limit value 15 min: 1225 mg/m<sup>3</sup> 15 minutes.</p>
Ethylbenzene	<p><b>Ministry of Labour and Social Policy and the Ministry of Health - Ordinance No 13/2003. (Bulgaria, 6/2021). Absorbed through skin.</b></p> <p>Limit value 8 hours: 435 mg/m<sup>3</sup> 8 hours.            Limit value 15 min: 545 mg/m<sup>3</sup> 15 minutes.</p>
n-Butyl acetate	<p><b>Ministry of Economy, Labour and Entrepreneurship ELV/ STELV (Croatia, 1/2021).</b></p> <p>STELV: 723 mg/m<sup>3</sup> 15 minutes.            STELV: 150 ppm 15 minutes.            ELV: 241 mg/m<sup>3</sup> 8 hours.            ELV: 50 ppm 8 hours.</p>
acetone	<p><b>Ministry of Economy, Labour and Entrepreneurship ELV/ STELV (Croatia, 1/2021).</b></p> <p>ELV: 1210 mg/m<sup>3</sup> 8 hours.            ELV: 500 ppm 8 hours.</p>
Toluene	<p><b>Ministry of Economy, Labour and Entrepreneurship ELV/ STELV (Croatia, 1/2021). Absorbed through skin.</b></p> <p>STELV: 384 mg/m<sup>3</sup> 15 minutes.            STELV: 100 ppm 15 minutes.            ELV: 192 mg/m<sup>3</sup> 8 hours.            ELV: 50 ppm 8 hours.</p>
Xylene	<p><b>Ministry of Economy, Labour and Entrepreneurship ELV/ STELV (Croatia, 1/2021). [xylene (all isomers)] Absorbed through skin.</b></p> <p>STELV: 442 mg/m<sup>3</sup> 15 minutes.            STELV: 100 ppm 15 minutes.            ELV: 221 mg/m<sup>3</sup> 8 hours.            ELV: 50 ppm 8 hours.</p>
Ethyl acetate	<p><b>Ministry of Economy, Labour and Entrepreneurship ELV/ STELV (Croatia, 1/2021).</b></p> <p>STELV: 400 ppm 15 minutes.            ELV: 200 ppm 8 hours.            STELV: 1468 mg/m<sup>3</sup> 15 minutes.            ELV: 734 mg/m<sup>3</sup> 8 hours.</p>
iso-butanol	<p><b>Ministry of Economy, Labour and Entrepreneurship ELV/ STELV (Croatia, 1/2021). Absorbed through skin.</b></p> <p>STELV: 231 mg/m<sup>3</sup> 15 minutes.            STELV: 75 ppm 15 minutes.            ELV: 154 mg/m<sup>3</sup> 8 hours.            ELV: 50 ppm 8 hours.</p>
2-Methoxy-1-methylethyl acetate	<p><b>Ministry of Economy, Labour and Entrepreneurship ELV/ STELV (Croatia, 1/2021). Absorbed through skin.</b></p> <p>STELV: 550 mg/m<sup>3</sup> 15 minutes.</p>

## SECTION 8: Exposure controls/personal protection

Propan-2-ol	<p>STELV: 100 ppm 15 minutes.            ELV: 275 mg/m<sup>3</sup> 8 hours.            ELV: 50 ppm 8 hours.</p> <p><b>Ministry of Economy, Labour and Entrepreneurship ELV/STELV (Croatia, 1/2021).</b></p> <p>STELV: 1250 mg/m<sup>3</sup> 15 minutes.            STELV: 500 ppm 15 minutes.            ELV: 999 mg/m<sup>3</sup> 8 hours.            ELV: 400 ppm 8 hours.</p>
Ethylbenzene	<p><b>Ministry of Economy, Labour and Entrepreneurship ELV/STELV (Croatia, 1/2021). Absorbed through skin.</b></p> <p>STELV: 884 mg/m<sup>3</sup> 15 minutes.            STELV: 200 ppm 15 minutes.            ELV: 442 mg/m<sup>3</sup> 8 hours.            ELV: 100 ppm 8 hours.</p>
n-Butyl acetate	<p><b>Department of labour inspection (Cyprus, 7/2021).</b></p> <p>STEL: 150 ppm 15 minutes.            STEL: 723 mg/m<sup>3</sup> 15 minutes.            TWA: 50 ppm 8 hours.            TWA: 241 mg/m<sup>3</sup> 8 hours.</p>
acetone	<p><b>Department of labour inspection (Cyprus, 7/2021). Absorbed through skin.</b></p> <p>TWA: 500 ppm 8 hours.            TWA: 1210 mg/m<sup>3</sup> 8 hours.</p>
Toluene	<p><b>Department of labour inspection (Cyprus, 7/2021). Absorbed through skin.</b></p> <p>STEL: 100 ppm 15 minutes.            STEL: 384 mg/m<sup>3</sup> 15 minutes.            TWA: 50 ppm 8 hours.            TWA: 192 mg/m<sup>3</sup> 8 hours.</p>
Xylene	<p><b>Department of labour inspection (Cyprus, 7/2021). [Xylene, mixed isomers] Absorbed through skin.</b></p> <p>STEL: 100 ppm 15 minutes.            STEL: 442 mg/m<sup>3</sup> 15 minutes.            TWA: 50 ppm 8 hours.            TWA: 221 mg/m<sup>3</sup> 8 hours.</p>
Ethyl acetate	<p><b>Department of labour inspection (Cyprus, 7/2021).</b></p> <p>STEL: 400 ppm 15 minutes.            STEL: 1468 mg/m<sup>3</sup> 15 minutes.            TWA: 200 ppm 8 hours.            TWA: 734 mg/m<sup>3</sup> 8 hours.</p>
2-Methoxy-1-methylethyl acetate	<p><b>Department of labour inspection (Cyprus, 7/2021). Absorbed through skin.</b></p> <p>STEL: 100 ppm 15 minutes.            STEL: 550 mg/m<sup>3</sup> 15 minutes.            TWA: 50 ppm 8 hours.            TWA: 275 mg/m<sup>3</sup> 8 hours.</p>
Ethylbenzene	<p><b>Department of labour inspection (Cyprus, 7/2021). Absorbed through skin.</b></p> <p>STEL: 884 mg/m<sup>3</sup> 15 minutes.            TWA: 100 ppm 8 hours.            TWA: 442 mg/m<sup>3</sup> 8 hours.            STEL: 200 ppm 15 minutes.</p>
n-Butyl acetate	<p><b>Government regulation of Czech Republic PEL/NPK-P (Czech Republic, 10/2022).</b></p> <p>TWA: 241 mg/m<sup>3</sup> 8 hours.            STEL: 723 mg/m<sup>3</sup> 15 minutes.            STEL: 149.661 ppm 15 minutes.            TWA: 49.887 ppm 8 hours.</p>
acetone	<p><b>Government regulation of Czech Republic PEL/NPK-P (Czech Republic, 10/2022).</b></p> <p>TWA: 800 mg/m<sup>3</sup> 8 hours.            STEL: 1500 mg/m<sup>3</sup> 15 minutes.            STEL: 621 ppm 15 minutes.</p>

## SECTION 8: Exposure controls/personal protection

Toluene	<p>TWA: 331.2 ppm 8 hours.  <b>Government regulation of Czech Republic PEL/NPK-P (Czech Republic, 10/2022). Absorbed through skin.</b>                      TWA: 192 mg/m<sup>3</sup> 8 hours.                      TWA: 50.112 ppm 8 hours.                      STEL: 384 mg/m<sup>3</sup> 15 minutes.                      STEL: 100.224 ppm 15 minutes.</p>
Xylene	<p><b>Government regulation of Czech Republic PEL/NPK-P (Czech Republic, 10/2022). [xylene, technical mixture of isomers and all isomers] Absorbed through skin.</b>                      TWA: 200 mg/m<sup>3</sup> 8 hours.                      TWA: 45.4 ppm 8 hours.                      STEL: 400 mg/m<sup>3</sup> 15 minutes.                      STEL: 90.8 ppm 15 minutes.</p>
Ethyl acetate	<p><b>Government regulation of Czech Republic PEL/NPK-P (Czech Republic, 10/2022).</b>                      TWA: 700 mg/m<sup>3</sup> 8 hours.                      TWA: 191.1 ppm 8 hours.                      STEL: 900 mg/m<sup>3</sup> 15 minutes.                      STEL: 245.7 ppm 15 minutes.</p>
iso-butanol	<p><b>Government regulation of Czech Republic PEL/NPK-P (Czech Republic, 10/2022). [Butanol (all isomers)] Absorbed through skin.</b>                      TWA: 300 mg/m<sup>3</sup> 8 hours.                      TWA: 97.5 ppm 8 hours.                      STEL: 600 mg/m<sup>3</sup> 15 minutes.                      STEL: 195 ppm 15 minutes.</p>
2-Methoxy-1-methylethyl acetate	<p><b>Government regulation of Czech Republic PEL/NPK-P (Czech Republic, 10/2022). Absorbed through skin.</b>                      TWA: 270 mg/m<sup>3</sup> 8 hours.                      TWA: 49.14 ppm 8 hours.                      STEL: 550 mg/m<sup>3</sup> 15 minutes.                      STEL: 100.1 ppm 15 minutes.</p>
Propan-2-ol	<p><b>Government regulation of Czech Republic PEL/NPK-P (Czech Republic, 10/2022). Absorbed through skin.</b>                      TWA: 500 mg/m<sup>3</sup> 8 hours.                      TWA: 200 ppm 8 hours.                      STEL: 1000 mg/m<sup>3</sup> 15 minutes.                      STEL: 400 ppm 15 minutes.</p>
Ethylbenzene	<p><b>Government regulation of Czech Republic PEL/NPK-P (Czech Republic, 10/2022). Absorbed through skin.</b>                      TWA: 200 mg/m<sup>3</sup> 8 hours.                      TWA: 45.4 ppm 8 hours.                      STEL: 500 mg/m<sup>3</sup> 15 minutes.                      STEL: 113.5 ppm 15 minutes.</p>
1-Ethoxy-2-propanol	<p><b>Government regulation of Czech Republic PEL/NPK-P (Czech Republic, 10/2022).</b>                      STEL: 550 mg/m<sup>3</sup> 15 minutes.                      TWA: 270 mg/m<sup>3</sup> 8 hours.                      TWA: 62.37 ppm 8 hours.                      STEL: 127.05 ppm 15 minutes.</p>
n-Butyl acetate	<p><b>Working Environment Authority (Denmark, 6/2022). [Butyl acetate, all isomers]</b>                      TWA: 50 ppm 8 hours.                      TWA: 241 mg/m<sup>3</sup> 8 hours.                      STEL: 723 mg/m<sup>3</sup> 15 minutes.                      STEL: 150 ppm 15 minutes.</p>
acetone	<p><b>Working Environment Authority (Denmark, 6/2022).</b>                      TWA: 250 ppm 8 hours.                      TWA: 600 mg/m<sup>3</sup> 8 hours.                      STEL: 1200 mg/m<sup>3</sup> 15 minutes.                      STEL: 500 ppm 15 minutes.</p>
Toluene	<p><b>Working Environment Authority (Denmark, 6/2022). Absorbed through skin.</b></p>

## SECTION 8: Exposure controls/personal protection

Xylene	<p>TWA: 25 ppm 8 hours.  TWA: 94 mg/m<sup>3</sup> 8 hours.  STEL: 384 mg/m<sup>3</sup> 15 minutes.  STEL: 100 ppm 15 minutes.</p> <p><b>Working Environment Authority (Denmark, 6/2022). [Xylenes, all isomers] Absorbed through skin.</b></p>
Ethyl acetate	<p>TWA: 25 ppm 8 hours.  TWA: 109 mg/m<sup>3</sup> 8 hours.  STEL: 442 mg/m<sup>3</sup> 15 minutes.  STEL: 100 ppm 15 minutes.</p> <p><b>Working Environment Authority (Denmark, 6/2022).</b></p>
iso-butanol	<p>TWA: 150 ppm 8 hours.  TWA: 540 mg/m<sup>3</sup> 8 hours.  STEL: 1468 mg/m<sup>3</sup> 15 minutes.  STEL: 400 ppm 15 minutes.</p> <p><b>Working Environment Authority (Denmark, 6/2022). [Butanol, all isomers] Absorbed through skin.</b></p>
2-Methoxy-1-methylethyl acetate	<p>CEIL: 50 ppm  CEIL: 150 mg/m<sup>3</sup></p> <p><b>Working Environment Authority (Denmark, 6/2022). [2-Methoxy-1-methylethyl acetate] Absorbed through skin.</b></p>
Propan-2-ol	<p>TWA: 50 ppm 8 hours.  TWA: 275 mg/m<sup>3</sup> 8 hours.  STEL: 550 mg/m<sup>3</sup> 15 minutes.  STEL: 100 ppm 15 minutes.</p> <p><b>Working Environment Authority (Denmark, 6/2022). Absorbed through skin.</b></p>
Ethylbenzene	<p>TWA: 200 ppm 8 hours.  TWA: 490 mg/m<sup>3</sup> 8 hours.  STEL: 980 mg/m<sup>3</sup> 15 minutes.  STEL: 400 ppm 15 minutes.</p> <p><b>Working Environment Authority (Denmark, 6/2022). Absorbed through skin. Carcinogen.</b></p>
n-Butyl acetate	<p>TWA: 50 ppm 8 hours.  TWA: 217 mg/m<sup>3</sup> 8 hours.  STEL: 434 mg/m<sup>3</sup> 15 minutes.  STEL: 100 ppm 15 minutes.</p> <p><b>Occupational exposure limits, Regulation No. 293 (Estonia, 12/2022).</b></p>
acetone	<p>STEL: 150 ppm 15 minutes.  STEL: 723 mg/m<sup>3</sup> 15 minutes.  TWA: 50 ppm 8 hours.  TWA: 241 mg/m<sup>3</sup> 8 hours.</p> <p><b>Occupational exposure limits, Regulation No. 293 (Estonia, 12/2022).</b></p>
Toluene	<p>TWA: 1210 mg/m<sup>3</sup> 8 hours.  TWA: 500 ppm 8 hours.</p> <p><b>Occupational exposure limits, Regulation No. 293 (Estonia, 12/2022). Absorbed through skin.</b></p>
Xylene	<p>TWA: 192 mg/m<sup>3</sup> 8 hours.  TWA: 50 ppm 8 hours.  STEL: 384 mg/m<sup>3</sup> 15 minutes.  STEL: 100 ppm 15 minutes.</p> <p><b>Occupational exposure limits, Regulation No. 293 (Estonia, 12/2022). [Xylenes] Absorbed through skin.</b></p>
Ethyl acetate	<p>TWA: 50 ppm 8 hours.  STEL: 100 ppm 15 minutes.  STEL: 450 mg/m<sup>3</sup> 15 minutes.  TWA: 200 mg/m<sup>3</sup> 8 hours.</p> <p><b>Occupational exposure limits, Regulation No. 293 (Estonia, 12/2022).</b></p>
	<p>TWA: 500 mg/m<sup>3</sup> 8 hours.  TWA: 150 ppm 8 hours.  STEL: 1100 mg/m<sup>3</sup> 15 minutes.</p>

## SECTION 8: Exposure controls/personal protection

iso-butanol	<p>STEL: 300 ppm 15 minutes.</p> <p><b>Occupational exposure limits, Regulation No. 293 (Estonia, 12/2022).</b></p> <p>TWA: 150 mg/m<sup>3</sup> 8 hours.</p> <p>TWA: 50 ppm 8 hours.</p>
2-Methoxy-1-methylethyl acetate	<p><b>Occupational exposure limits, Regulation No. 293 (Estonia, 12/2022). Absorbed through skin. Skin sensitiser.</b></p> <p>STEL: 100 ppm 15 minutes.</p> <p>STEL: 550 mg/m<sup>3</sup> 15 minutes.</p> <p>TWA: 275 mg/m<sup>3</sup> 8 hours.</p> <p>TWA: 50 ppm 8 hours.</p>
Propan-2-ol	<p><b>Occupational exposure limits, Regulation No. 293 (Estonia, 12/2022).</b></p> <p>TWA: 350 mg/m<sup>3</sup> 8 hours.</p> <p>TWA: 150 ppm 8 hours.</p> <p>STEL: 600 mg/m<sup>3</sup> 15 minutes.</p> <p>STEL: 250 ppm 15 minutes.</p>
Ethylbenzene	<p><b>Occupational exposure limits, Regulation No. 293 (Estonia, 12/2022). Absorbed through skin. Skin sensitiser.</b></p> <p>TWA: 442 mg/m<sup>3</sup> 8 hours.</p> <p>TWA: 100 ppm 8 hours.</p> <p>STEL: 884 mg/m<sup>3</sup> 15 minutes.</p> <p>STEL: 200 ppm 15 minutes.</p>
n-Butyl acetate	<p><b>EU OEL (Europe, 1/2022). Notes: list of indicative occupational exposure limit values</b></p> <p>STEL: 150 ppm 15 minutes.</p> <p>STEL: 723 mg/m<sup>3</sup> 15 minutes.</p> <p>TWA: 241 mg/m<sup>3</sup> 8 hours.</p> <p>TWA: 50 ppm 8 hours.</p>
acetone	<p><b>EU OEL (Europe, 1/2022). Notes: list of indicative occupational exposure limit values</b></p> <p>TWA: 500 ppm 8 hours.</p> <p>TWA: 1210 mg/m<sup>3</sup> 8 hours.</p>
Toluene	<p><b>EU OEL (Europe, 1/2022). Absorbed through skin. Notes: list of indicative occupational exposure limit values</b></p> <p>TWA: 192 mg/m<sup>3</sup> 8 hours.</p> <p>TWA: 50 ppm 8 hours.</p> <p>STEL: 384 mg/m<sup>3</sup> 15 minutes.</p> <p>STEL: 100 ppm 15 minutes.</p>
Xylene	<p><b>EU OEL (Europe, 1/2022). [xylene, mixed isomers pure] Absorbed through skin. Notes: list of indicative occupational exposure limit values</b></p> <p>TWA: 50 ppm 8 hours.</p> <p>TWA: 221 mg/m<sup>3</sup> 8 hours.</p> <p>STEL: 100 ppm 15 minutes.</p> <p>STEL: 442 mg/m<sup>3</sup> 15 minutes.</p>
Ethyl acetate	<p><b>EU OEL (Europe, 1/2022). Notes: list of indicative occupational exposure limit values</b></p> <p>STEL: 400 ppm 15 minutes.</p> <p>STEL: 1468 mg/m<sup>3</sup> 15 minutes.</p> <p>TWA: 200 ppm 8 hours.</p> <p>TWA: 734 mg/m<sup>3</sup> 8 hours.</p>
2-Methoxy-1-methylethyl acetate	<p><b>EU OEL (Europe, 1/2022). Absorbed through skin. Notes: list of indicative occupational exposure limit values</b></p> <p>TWA: 50 ppm 8 hours.</p> <p>TWA: 275 mg/m<sup>3</sup> 8 hours.</p> <p>STEL: 100 ppm 15 minutes.</p> <p>STEL: 550 mg/m<sup>3</sup> 15 minutes.</p>
Ethylbenzene	<p><b>EU OEL (Europe, 1/2022). Absorbed through skin. Notes: list of indicative occupational exposure limit values</b></p> <p>TWA: 100 ppm 8 hours.</p> <p>TWA: 442 mg/m<sup>3</sup> 8 hours.</p> <p>STEL: 200 ppm 15 minutes.</p> <p>STEL: 884 mg/m<sup>3</sup> 15 minutes.</p>

## SECTION 8: Exposure controls/personal protection

n-Butyl acetate	<b>Institute of Occupational Health, Ministry of Social Affairs (Finland, 10/2021).</b> TWA: 150 ppm 8 hours. TWA: 720 mg/m <sup>3</sup> 8 hours. STEL: 200 ppm 15 minutes. STEL: 960 mg/m <sup>3</sup> 15 minutes.
acetone	<b>Institute of Occupational Health, Ministry of Social Affairs (Finland, 10/2021).</b> TWA: 500 ppm 8 hours. TWA: 1200 mg/m <sup>3</sup> 8 hours. STEL: 630 ppm 15 minutes. STEL: 1500 mg/m <sup>3</sup> 15 minutes.
Toluene	<b>Institute of Occupational Health, Ministry of Social Affairs (Finland, 10/2021). Absorbed through skin. Ototoxicant.</b> TWA: 25 ppm 8 hours. TWA: 81 mg/m <sup>3</sup> 8 hours. STEL: 100 ppm 15 minutes. STEL: 380 mg/m <sup>3</sup> 15 minutes.
Xylene	<b>Institute of Occupational Health, Ministry of Social Affairs (Finland, 10/2021). [Xylenes] Absorbed through skin.</b> STEL: 440 mg/m <sup>3</sup> 15 minutes. TWA: 220 mg/m <sup>3</sup> 8 hours. TWA: 50 ppm 8 hours. STEL: 100 ppm 15 minutes.
Ethyl acetate	<b>Institute of Occupational Health, Ministry of Social Affairs (Finland, 10/2021).</b> TWA: 200 ppm 8 hours. TWA: 730 mg/m <sup>3</sup> 8 hours. STEL: 400 ppm 15 minutes. STEL: 1470 mg/m <sup>3</sup> 15 minutes.
iso-butanol	<b>Institute of Occupational Health, Ministry of Social Affairs (Finland, 10/2021). [Butanols] Absorbed through skin.</b> TWA: 50 ppm 8 hours. TWA: 150 mg/m <sup>3</sup> 8 hours. STEL: 75 ppm 15 minutes. STEL: 230 mg/m <sup>3</sup> 15 minutes.
2-Methoxy-1-methylethyl acetate	<b>Institute of Occupational Health, Ministry of Social Affairs (Finland, 10/2021). Absorbed through skin.</b> TWA: 50 ppm 8 hours. TWA: 270 mg/m <sup>3</sup> 8 hours. STEL: 100 ppm 15 minutes. STEL: 550 mg/m <sup>3</sup> 15 minutes.
Propan-2-ol	<b>Institute of Occupational Health, Ministry of Social Affairs (Finland, 10/2021).</b> TWA: 200 ppm 8 hours. TWA: 500 mg/m <sup>3</sup> 8 hours. STEL: 250 ppm 15 minutes. STEL: 620 mg/m <sup>3</sup> 15 minutes.
Ethylbenzene	<b>Institute of Occupational Health, Ministry of Social Affairs (Finland, 10/2021). Absorbed through skin.</b> TWA: 50 ppm 8 hours. TWA: 220 mg/m <sup>3</sup> 8 hours. STEL: 200 ppm 15 minutes. STEL: 880 mg/m <sup>3</sup> 15 minutes.
n-Butyl acetate	<b>Ministry of Labor (France, 10/2022). Notes: Binding regulatory limit values (article R. 4412-149 of the Labor Code)</b> TWA: 50 ppm 8 hours. TWA: 241 mg/m <sup>3</sup> 8 hours. STEL: 150 ppm 15 minutes. STEL: 723 mg/m <sup>3</sup> 15 minutes.
acetone	<b>Ministry of Labor (France, 10/2022). Notes: Binding regulatory limit values (article R. 4412-149 of the Labor Code)</b> TWA: 500 ppm 8 hours. TWA: 1210 mg/m <sup>3</sup> 8 hours.

## SECTION 8: Exposure controls/personal protection

Toluene	<p>STEL: 2420 mg/m<sup>3</sup> 15 minutes.          STEL: 1000 ppm 15 minutes.  <b>Ministry of Labor (France, 10/2022). Absorbed through skin.</b>  <b>Notes: Binding regulatory limit values (article R. 4412-149 of the Labor Code)</b>          TWA: 20 ppm 8 hours.          TWA: 76.8 mg/m<sup>3</sup> 8 hours.          STEL: 100 ppm 15 minutes.          STEL: 384 mg/m<sup>3</sup> 15 minutes.</p>
Xylene	<p><b>Ministry of Labor (France, 10/2022). [xylenes, mixed isomers, pure] Absorbed through skin. Notes: Binding regulatory limit values (article R. 4412-149 of the Labor Code)</b>          STEL: 442 mg/m<sup>3</sup> 15 minutes.          STEL: 100 ppm 15 minutes.          TWA: 221 mg/m<sup>3</sup> 8 hours.          TWA: 50 ppm 8 hours.</p>
Ethyl acetate	<p><b>Ministry of Labor (France, 10/2022). Notes: Binding regulatory limit values (article R. 4412-149 of the Labor Code)</b>          TWA: 200 ppm 8 hours.          TWA: 734 mg/m<sup>3</sup> 8 hours.          STEL: 1468 mg/m<sup>3</sup> 15 minutes.          STEL: 400 ppm 15 minutes.</p>
iso-butanol	<p><b>Ministry of Labor (France, 10/2022). Notes: Permissible limit values (circulars)</b>          TWA: 50 ppm 8 hours.          TWA: 150 mg/m<sup>3</sup> 8 hours.</p>
2-Methoxy-1-methylethyl acetate	<p><b>Ministry of Labor (France, 10/2022). Absorbed through skin. Notes: Binding regulatory limit values (article R. 4412-149 of the Labor Code)</b>          STEL: 550 mg/m<sup>3</sup> 15 minutes.          STEL: 100 ppm 15 minutes.          TWA: 275 mg/m<sup>3</sup> 8 hours.          TWA: 50 ppm 8 hours.</p>
Propan-2-ol	<p><b>Ministry of Labor (France, 10/2022). Notes: Permissible limit values (circulars)</b>          STEL: 400 ppm 15 minutes.          STEL: 980 mg/m<sup>3</sup> 15 minutes.</p>
Ethylbenzene	<p><b>Ministry of Labor (France, 10/2022). Absorbed through skin. Notes: Binding regulatory limit values (article R. 4412-149 of the Labor Code)</b>          TWA: 20 ppm 8 hours.          TWA: 88.4 mg/m<sup>3</sup> 8 hours.          STEL: 442 mg/m<sup>3</sup> 15 minutes.          STEL: 100 ppm 15 minutes.</p>
n-Butyl acetate	<p><b>DFG MAC-values list (Germany, 7/2022).</b>          TWA: 100 ppm 8 hours.          PEAK: 200 ppm, 4 times per shift, 15 minutes.          TWA: 480 mg/m<sup>3</sup> 8 hours.          PEAK: 960 mg/m<sup>3</sup>, 4 times per shift, 15 minutes.  <b>TRGS 900 OEL (Germany, 6/2022).</b>          TWA: 300 mg/m<sup>3</sup> 8 hours.          TWA: 62 ppm 8 hours.          PEAK: 600 mg/m<sup>3</sup> 15 minutes.          PEAK: 124 ppm 15 minutes.</p>
acetone	<p><b>TRGS 900 OEL (Germany, 6/2022).</b>          TWA: 1200 mg/m<sup>3</sup> 8 hours.          PEAK: 2400 mg/m<sup>3</sup> 15 minutes.          TWA: 500 ppm 8 hours.          PEAK: 1000 ppm 15 minutes.  <b>DFG MAC-values list (Germany, 7/2022).</b>          TWA: 500 ppm 8 hours.          PEAK: 1000 ppm, 4 times per shift, 15 minutes.          TWA: 1200 mg/m<sup>3</sup> 8 hours.          PEAK: 2400 mg/m<sup>3</sup>, 4 times per shift, 15 minutes.</p>

## SECTION 8: Exposure controls/personal protection

Toluene	<p><b>TRGS 900 OEL (Germany, 6/2022). Absorbed through skin.</b>  TWA: 190 mg/m<sup>3</sup> 8 hours.  PEAK: 380 mg/m<sup>3</sup> 15 minutes.  TWA: 50 ppm 8 hours.  PEAK: 100 ppm 15 minutes.</p> <p><b>DFG MAC-values list (Germany, 7/2022). Absorbed through skin.</b>  TWA: 50 ppm 8 hours.  PEAK: 100 ppm, 4 times per shift, 15 minutes.  TWA: 190 mg/m<sup>3</sup> 8 hours.  PEAK: 380 mg/m<sup>3</sup>, 4 times per shift, 15 minutes.</p>
Xylene	<p><b>TRGS 900 OEL (Germany, 6/2022). [xylene] Absorbed through skin.</b>  TWA: 220 mg/m<sup>3</sup> 8 hours.  PEAK: 440 mg/m<sup>3</sup> 15 minutes.  TWA: 50 ppm 8 hours.  PEAK: 100 ppm 15 minutes.</p> <p><b>DFG MAC-values list (Germany, 7/2022). [Xylene (all isomers)] Absorbed through skin.</b>  TWA: 50 ppm 8 hours.  PEAK: 100 ppm, 4 times per shift, 15 minutes.  TWA: 220 mg/m<sup>3</sup> 8 hours.  PEAK: 440 mg/m<sup>3</sup>, 4 times per shift, 15 minutes.</p>
Ethyl acetate	<p><b>TRGS 900 OEL (Germany, 6/2022).</b>  TWA: 730 mg/m<sup>3</sup> 8 hours.  PEAK: 1460 mg/m<sup>3</sup> 15 minutes.  TWA: 200 ppm 8 hours.  PEAK: 400 ppm 15 minutes.</p> <p><b>DFG MAC-values list (Germany, 7/2022).</b>  TWA: 200 ppm 8 hours.  PEAK: 400 ppm, 4 times per shift, 15 minutes.  TWA: 750 mg/m<sup>3</sup> 8 hours.  PEAK: 1500 mg/m<sup>3</sup>, 4 times per shift, 15 minutes.</p>
iso-butanol	<p><b>TRGS 900 OEL (Germany, 6/2022).</b>  TWA: 310 mg/m<sup>3</sup> 8 hours.  PEAK: 310 mg/m<sup>3</sup> 15 minutes.  TWA: 100 ppm 8 hours.  PEAK: 100 ppm 15 minutes.</p> <p><b>DFG MAC-values list (Germany, 7/2022).</b>  TWA: 100 ppm 8 hours.  PEAK: 100 ppm, 4 times per shift, 15 minutes.  TWA: 310 mg/m<sup>3</sup> 8 hours.  PEAK: 310 mg/m<sup>3</sup>, 4 times per shift, 15 minutes.</p>
2-Methoxy-1-methylethyl acetate	<p><b>TRGS 900 OEL (Germany, 6/2022).</b>  TWA: 270 mg/m<sup>3</sup> 8 hours.  PEAK: 270 mg/m<sup>3</sup> 15 minutes.  TWA: 50 ppm 8 hours.  PEAK: 50 ppm 15 minutes.</p> <p><b>DFG MAC-values list (Germany, 7/2022).</b>  TWA: 50 ppm 8 hours.  PEAK: 50 ppm, 4 times per shift, 15 minutes.  TWA: 270 mg/m<sup>3</sup> 8 hours.  PEAK: 270 mg/m<sup>3</sup>, 4 times per shift, 15 minutes.</p>
Propan-2-ol	<p><b>TRGS 900 OEL (Germany, 6/2022).</b>  TWA: 500 mg/m<sup>3</sup> 8 hours.  PEAK: 1000 mg/m<sup>3</sup> 15 minutes.  TWA: 200 ppm 8 hours.  PEAK: 400 ppm 15 minutes.</p> <p><b>DFG MAC-values list (Germany, 7/2022).</b>  TWA: 200 ppm 8 hours.  PEAK: 400 ppm, 4 times per shift, 15 minutes.  TWA: 500 mg/m<sup>3</sup> 8 hours.  PEAK: 1000 mg/m<sup>3</sup>, 4 times per shift, 15 minutes.</p>
Ethylbenzene	<p><b>TRGS 900 OEL (Germany, 6/2022). Absorbed through skin.</b></p>



## SECTION 8: Exposure controls/personal protection

	<p>TWA: 88 mg/m<sup>3</sup> 8 hours. PEAK: 176 mg/m<sup>3</sup> 15 minutes. TWA: 20 ppm 8 hours. PEAK: 40 ppm 15 minutes.</p> <p><b>DFG MAC-values list (Germany, 7/2022). Absorbed through skin.</b> PEAK: 40 ppm, 4 times per shift, 15 minutes. PEAK: 176 mg/m<sup>3</sup>, 4 times per shift, 15 minutes. TWA: 88 mg/m<sup>3</sup> 8 hours. TWA: 20 ppm 8 hours.</p>
1-Ethoxy-2-propanol	<p><b>DFG MAC-values list (Germany, 7/2022). Absorbed through skin.</b> TWA: 86 mg/m<sup>3</sup> 8 hours. PEAK: 172 mg/m<sup>3</sup>, 4 times per shift, 15 minutes. TWA: 20 ppm 8 hours. PEAK: 40 ppm, 4 times per shift, 15 minutes.</p> <p><b>TRGS 900 OEL (Germany, 6/2022). Absorbed through skin.</b> TWA: 86 mg/m<sup>3</sup> 8 hours. PEAK: 172 mg/m<sup>3</sup> 15 minutes. TWA: 20 ppm 8 hours.</p>
n-Butyl acetate	<p><b>Presidential Decree 307/1986: Occupational exposure limit values (Greece, 9/2021).</b> TWA: 50 ppm 8 hours. TWA: 241 mg/m<sup>3</sup> 8 hours. STEL: 150 ppm 15 minutes. STEL: 723 mg/m<sup>3</sup> 15 minutes.</p>
acetone	<p><b>Presidential Decree 307/1986: Occupational exposure limit values (Greece, 9/2021).</b> TWA: 1780 mg/m<sup>3</sup> 8 hours. STEL: 3560 mg/m<sup>3</sup> 15 minutes.</p>
Toluene	<p><b>Presidential Decree 307/1986: Occupational exposure limit values (Greece, 9/2021). Absorbed through skin.</b> TWA: 50 ppm 8 hours. TWA: 192 mg/m<sup>3</sup> 8 hours. STEL: 100 ppm 15 minutes. STEL: 384 mg/m<sup>3</sup> 15 minutes.</p>
Xylene	<p><b>Presidential Decree 307/1986: Occupational exposure limit values (Greece, 9/2021). [Xylenes (all isomers)] Absorbed through skin.</b> TWA: 100 ppm 8 hours. TWA: 435 mg/m<sup>3</sup> 8 hours. STEL: 150 ppm 15 minutes. STEL: 650 mg/m<sup>3</sup> 15 minutes.</p>
Ethyl acetate	<p><b>Presidential Decree 307/1986: Occupational exposure limit values (Greece, 9/2021).</b> TWA: 200 ppm 8 hours. TWA: 734 mg/m<sup>3</sup> 8 hours. STEL: 1468 mg/m<sup>3</sup> 15 minutes. STEL: 400 ppm 15 minutes.</p>
iso-butanol	<p><b>Presidential Decree 307/1986: Occupational exposure limit values (Greece, 9/2021).</b> TWA: 100 ppm 8 hours. TWA: 300 mg/m<sup>3</sup> 8 hours. STEL: 100 ppm 15 minutes. STEL: 300 mg/m<sup>3</sup> 15 minutes.</p>
2-Methoxy-1-methylethyl acetate	<p><b>Presidential Decree 307/1986: Occupational exposure limit values (Greece, 9/2021). Absorbed through skin.</b> TWA: 50 ppm 8 hours. TWA: 275 mg/m<sup>3</sup> 8 hours. STEL: 100 ppm 15 minutes. STEL: 550 mg/m<sup>3</sup> 15 minutes.</p>
Propan-2-ol	<p><b>Presidential Decree 307/1986: Occupational exposure limit values (Greece, 9/2021).</b> TWA: 400 ppm 8 hours.</p>

## SECTION 8: Exposure controls/personal protection

Ethylbenzene	<p>TWA: 980 mg/m<sup>3</sup> 8 hours.          STEL: 500 ppm 15 minutes.          STEL: 1225 mg/m<sup>3</sup> 15 minutes.</p> <p><b>Presidential Decree 307/1986: Occupational exposure limit values (Greece, 9/2021).</b></p> <p>TWA: 100 ppm 8 hours.          TWA: 435 mg/m<sup>3</sup> 8 hours.          STEL: 125 ppm 15 minutes.          STEL: 545 mg/m<sup>3</sup> 15 minutes.</p>
n-Butyl acetate	<p><b>5/2020. (II. 6.) ITM Decree (Hungary, 12/2022). Skin sensitiser. Inhalation sensitiser.</b></p> <p>TWA: 241 mg/m<sup>3</sup> 8 hours.          PEAK: 723 mg/m<sup>3</sup> 15 minutes.          PEAK: 150 ppm 15 minutes.          TWA: 50 ppm 8 hours.</p>
acetone	<p><b>5/2020. (II. 6.) ITM Decree (Hungary, 12/2022). Skin sensitiser. Inhalation sensitiser.</b></p> <p>TWA: 1210 mg/m<sup>3</sup> 8 hours.          TWA: 500 ppm 8 hours.</p>
Toluene	<p><b>5/2020. (II. 6.) ITM Decree (Hungary, 12/2022). Absorbed through skin. Skin sensitiser. Inhalation sensitiser.</b></p> <p>TWA: 192 mg/m<sup>3</sup> 8 hours.          PEAK: 384 mg/m<sup>3</sup> 15 minutes.          PEAK: 100 ppm 15 minutes.          TWA: 50 ppm 8 hours.</p>
Xylene	<p><b>5/2020. (II. 6.) ITM Decree (Hungary, 12/2022). [xylene, mixture of isomers] Absorbed through skin.</b></p> <p>TWA: 221 mg/m<sup>3</sup> 8 hours.          PEAK: 442 mg/m<sup>3</sup> 15 minutes.          PEAK: 100 ppm 15 minutes.          TWA: 50 ppm 8 hours.</p>
Ethyl acetate	<p><b>5/2020. (II. 6.) ITM Decree (Hungary, 12/2022). Skin sensitiser. Inhalation sensitiser.</b></p> <p>TWA: 734 mg/m<sup>3</sup> 8 hours.          PEAK: 1468 mg/m<sup>3</sup> 15 minutes.          PEAK: 400 ppm 15 minutes.          TWA: 200 ppm 8 hours.</p>
2-Methoxy-1-methylethyl acetate	<p><b>5/2020. (II. 6.) ITM Decree (Hungary, 12/2022).</b></p> <p>TWA: 275 mg/m<sup>3</sup> 8 hours.          PEAK: 550 mg/m<sup>3</sup> 15 minutes.          PEAK: 100 ppm 15 minutes.          TWA: 50 ppm 8 hours.</p>
Propan-2-ol	<p><b>5/2020. (II. 6.) ITM Decree (Hungary, 12/2022). Absorbed through skin. Skin sensitiser. Inhalation sensitiser.</b></p> <p>TWA: 500 mg/m<sup>3</sup> 8 hours.          PEAK: 1000 mg/m<sup>3</sup> 15 minutes.          PEAK: 400 ppm 15 minutes.          TWA: 200 ppm 8 hours.</p>
Ethylbenzene	<p><b>5/2020. (II. 6.) ITM Decree (Hungary, 12/2022). Absorbed through skin. Skin sensitiser. Inhalation sensitiser.</b></p> <p>TWA: 442 mg/m<sup>3</sup> 8 hours.          PEAK: 884 mg/m<sup>3</sup> 15 minutes.          PEAK: 200 ppm 15 minutes.          TWA: 100 ppm 8 hours.</p>
n-Butyl acetate	<p><b>Ministry of Welfare, List of Exposure Limits (Iceland, 5/2021). [butyl acetate, all isomers]</b></p> <p>TWA: 241 mg/m<sup>3</sup> 8 hours.          TWA: 50 ppm 8 hours.          STEL: 723 mg/m<sup>3</sup> 15 minutes.          STEL: 150 ppm 15 minutes.</p>
acetone	<p><b>Ministry of Welfare, List of Exposure Limits (Iceland, 5/2021).</b></p> <p>TWA: 600 mg/m<sup>3</sup> 8 hours.          TWA: 250 ppm 8 hours.</p>
Toluene	<p><b>Ministry of Welfare, List of Exposure Limits (Iceland, 5/2021).</b></p>

## SECTION 8: Exposure controls/personal protection

Xylene	<p><b>Absorbed through skin.</b>          STEL: 188 mg/m<sup>3</sup> 15 minutes.          STEL: 50 ppm 15 minutes.          TWA: 94 mg/m<sup>3</sup> 8 hours.          TWA: 25 ppm 8 hours.</p> <p><b>Ministry of Welfare, List of Exposure Limits (Iceland, 5/2021).</b>  <b>[xylene, all isomers] Absorbed through skin.</b>          STEL: 442 mg/m<sup>3</sup> 15 minutes.          STEL: 100 ppm 15 minutes.          TWA: 109 mg/m<sup>3</sup> 8 hours.          TWA: 25 ppm 8 hours.</p>
Ethyl acetate	<p><b>Ministry of Welfare, List of Exposure Limits (Iceland, 5/2021).</b>          TWA: 540 mg/m<sup>3</sup> 8 hours.          TWA: 150 ppm 8 hours.</p>
iso-butanol	<p><b>Ministry of Welfare, List of Exposure Limits (Iceland, 5/2021).</b>  <b>[butanol, all isomers, except n-butanol] Absorbed through skin.</b>          STEL: 150 mg/m<sup>3</sup> 15 minutes.          STEL: 50 ppm 15 minutes.</p>
2-Methoxy-1-methylethyl acetate	<p><b>Ministry of Welfare, List of Exposure Limits (Iceland, 5/2021).</b>  <b>Absorbed through skin.</b>          STEL: 550 mg/m<sup>3</sup> 15 minutes.          STEL: 100 ppm 15 minutes.          TWA: 275 mg/m<sup>3</sup> 8 hours.          TWA: 50 ppm 8 hours.</p>
Ethylbenzene	<p><b>Ministry of Welfare, List of Exposure Limits (Iceland, 5/2021).</b>  <b>Absorbed through skin.</b>          STEL: 884 mg/m<sup>3</sup> 15 minutes.          STEL: 200 ppm 15 minutes.          TWA: 200 mg/m<sup>3</sup> 8 hours.          TWA: 50 ppm 8 hours.</p>
n-Butyl acetate	<p><b>NAOSH (Ireland, 5/2021). Notes: EU derived Occupational Exposure Limit Values</b>          OELV-8hr: 50 ppm 8 hours.          OELV-8hr: 241 mg/m<sup>3</sup> 8 hours.          OELV-15min: 150 ppm 15 minutes.          OELV-15min: 723 mg/m<sup>3</sup> 15 minutes.</p>
acetone	<p><b>NAOSH (Ireland, 5/2021). Notes: EU derived Occupational Exposure Limit Values</b>          OELV-8hr: 500 ppm 8 hours.          OELV-8hr: 1210 mg/m<sup>3</sup> 8 hours.</p>
Toluene	<p><b>NAOSH (Ireland, 5/2021). Absorbed through skin. Notes: EU derived Occupational Exposure Limit Values</b>          OELV-8hr: 50 ppm 8 hours.          OELV-8hr: 192 mg/m<sup>3</sup> 8 hours.          OELV-15min: 100 ppm 15 minutes.          OELV-15min: 384 mg/m<sup>3</sup> 15 minutes.</p>
Xylene	<p><b>NAOSH (Ireland, 5/2021). [xylene mixed isomers] Absorbed through skin. Notes: EU derived Occupational Exposure Limit Values</b>          OELV-8hr: 50 ppm 8 hours.          OELV-8hr: 221 mg/m<sup>3</sup> 8 hours.          OELV-15min: 100 ppm 15 minutes.          OELV-15min: 442 mg/m<sup>3</sup> 15 minutes.</p>
Ethyl acetate	<p><b>NAOSH (Ireland, 5/2021). Notes: EU derived Occupational Exposure Limit Values</b>          OELV-8hr: 200 ppm 8 hours.          OELV-15min: 400 ppm 15 minutes.          OELV-15min: 1468 mg/m<sup>3</sup> 15 minutes.          OELV-8hr: 734 mg/m<sup>3</sup> 8 hours.</p>
iso-butanol	<p><b>NAOSH (Ireland, 5/2021). Notes: Advisory Occupational Exposure Limit Values (OELVs)</b>          OELV-8hr: 50 ppm 8 hours.          OELV-8hr: 150 mg/m<sup>3</sup> 8 hours.</p>

## SECTION 8: Exposure controls/personal protection

2-Methoxy-1-methylethyl acetate	<p>OELV-15min: 75 ppm 15 minutes.  OELV-15min: 225 mg/m<sup>3</sup> 15 minutes.  <b>NAOSH (Ireland, 5/2021). Absorbed through skin. Notes: EU derived Occupational Exposure Limit Values</b>  OELV-8hr: 50 ppm 8 hours.  OELV-8hr: 275 mg/m<sup>3</sup> 8 hours.  OELV-15min: 100 ppm 15 minutes.  OELV-15min: 550 mg/m<sup>3</sup> 15 minutes.</p>
Propan-2-ol	<p><b>NAOSH (Ireland, 5/2021). Absorbed through skin. Notes: Advisory Occupational Exposure Limit Values (OELVs)</b>  OELV-8hr: 200 ppm 8 hours.  OELV-15min: 400 ppm 15 minutes.</p>
Ethylbenzene	<p><b>NAOSH (Ireland, 5/2021). Absorbed through skin. Notes: EU derived Occupational Exposure Limit Values</b>  OELV-8hr: 100 ppm 8 hours.  OELV-8hr: 442 mg/m<sup>3</sup> 8 hours.  OELV-15min: 200 ppm 15 minutes.  OELV-15min: 884 mg/m<sup>3</sup> 15 minutes.</p>
n-Butyl acetate	<p><b>EU OEL (Europe, 1/2022). Notes: list of indicative occupational exposure limit values</b>  STEL: 150 ppm 15 minutes.  STEL: 723 mg/m<sup>3</sup> 15 minutes.  TWA: 241 mg/m<sup>3</sup> 8 hours.  TWA: 50 ppm 8 hours.</p>
acetone	<p><b>Legislative Decree No. 819/2008. Title IX. Protection from chemical agents, carcinogens and mutagens (Italy, 6/2020).</b>  8 hours: 500 ppm 8 hours.  8 hours: 1210 mg/m<sup>3</sup> 8 hours.</p>
Toluene	<p><b>Legislative Decree No. 819/2008. Title IX. Protection from chemical agents, carcinogens and mutagens (Italy, 6/2020). Absorbed through skin.</b>  8 hours: 50 ppm 8 hours.  8 hours: 192 mg/m<sup>3</sup> 8 hours.</p>
Xylene	<p><b>Legislative Decree No. 819/2008. Title IX. Protection from chemical agents, carcinogens and mutagens (Italy, 6/2020). [Xylenes, mixed isomers, pure] Absorbed through skin.</b>  8 hours: 50 ppm 8 hours.  8 hours: 221 mg/m<sup>3</sup> 8 hours.  Short Term: 100 ppm 15 minutes.  Short Term: 442 mg/m<sup>3</sup> 15 minutes.</p>
Ethyl acetate	<p><b>Legislative Decree No. 819/2008. Title IX. Protection from chemical agents, carcinogens and mutagens (Italy, 6/2020).</b>  Short Term: 400 ppm 15 minutes.  Short Term: 1468 mg/m<sup>3</sup> 15 minutes.  8 hours: 200 ppm 8 hours.  8 hours: 734 mg/m<sup>3</sup> 8 hours.</p>
2-Methoxy-1-methylethyl acetate	<p><b>Legislative Decree No. 819/2008. Title IX. Protection from chemical agents, carcinogens and mutagens (Italy, 6/2020). Absorbed through skin.</b>  8 hours: 50 ppm 8 hours.  8 hours: 275 mg/m<sup>3</sup> 8 hours.  Short Term: 100 ppm 15 minutes.  Short Term: 550 mg/m<sup>3</sup> 15 minutes.</p>
Ethylbenzene	<p><b>Legislative Decree No. 819/2008. Title IX. Protection from chemical agents, carcinogens and mutagens (Italy, 6/2020). Absorbed through skin.</b>  8 hours: 100 ppm 8 hours.  8 hours: 442 mg/m<sup>3</sup> 8 hours.  Short Term: 200 ppm 15 minutes.  Short Term: 884 mg/m<sup>3</sup> 15 minutes.</p>

## SECTION 8: Exposure controls/personal protection

n-Butyl acetate	<b>Ministers Cabinet Regulations Nr.325 - AER (Latvia, 2/2021).</b> TWA: 241 mg/m <sup>3</sup> 8 hours. STEL: 150 ppm 15 minutes. STEL: 723 mg/m <sup>3</sup> 15 minutes. TWA: 50 ppm 8 hours.
acetone	<b>Ministers Cabinet Regulations Nr.325 - AER (Latvia, 2/2021).</b> TWA: 1210 mg/m <sup>3</sup> 8 hours. TWA: 500 ppm 8 hours.
Toluene	<b>Ministers Cabinet Regulations Nr.325 - AER (Latvia, 2/2021).</b> <b>Absorbed through skin.</b> TWA: 50 mg/m <sup>3</sup> 8 hours. STEL: 150 mg/m <sup>3</sup> 15 minutes. TWA: 14 ppm 8 hours. STEL: 40 ppm 15 minutes.
Xylene	<b>Ministers Cabinet Regulations Nr.325 - AER (Latvia, 2/2021).</b> <b>[Xylenes] Absorbed through skin.</b> TWA: 221 mg/m <sup>3</sup> 8 hours. TWA: 50 ppm 8 hours. STEL: 100 ppm 15 minutes. STEL: 442 mg/m <sup>3</sup> 15 minutes.
Ethyl acetate	<b>Ministers Cabinet Regulations Nr.325 - AER (Latvia, 2/2021).</b> TWA: 200 mg/m <sup>3</sup> 8 hours. STEL: 400 ppm 15 minutes. STEL: 1468 mg/m <sup>3</sup> 15 minutes. TWA: 54 ppm 8 hours.
iso-butanol	<b>Ministers Cabinet Regulations Nr.325 - AER (Latvia, 2/2021).</b> <b>[Butylalcohol]</b> TWA: 10 mg/m <sup>3</sup> 8 hours.
2-Methoxy-1-methylethyl acetate	<b>Ministers Cabinet Regulations Nr.325 - AER (Latvia, 2/2021).</b> <b>Absorbed through skin.</b> TWA: 50 ppm 8 hours. TWA: 275 mg/m <sup>3</sup> 8 hours. STEL: 100 ppm 15 minutes. STEL: 550 mg/m <sup>3</sup> 15 minutes.
Propan-2-ol	<b>Ministers Cabinet Regulations Nr.325 - AER (Latvia, 2/2021).</b> TWA: 350 mg/m <sup>3</sup> 8 hours. STEL: 600 mg/m <sup>3</sup> 15 minutes.
Ethylbenzene	<b>Ministers Cabinet Regulations Nr.325 - AER (Latvia, 2/2021).</b> <b>Absorbed through skin.</b> TWA: 442 mg/m <sup>3</sup> 8 hours. TWA: 100 ppm 8 hours. STEL: 200 ppm 15 minutes. STEL: 884 mg/m <sup>3</sup> 15 minutes.
n-Butyl acetate	<b>Lithuanian Hygiene Standard HN 23 (Lithuania, 7/2022).</b> TWA: 241 mg/m <sup>3</sup> 8 hours. TWA: 50 ppm 8 hours. STEL: 723 mg/m <sup>3</sup> 15 minutes. STEL: 150 ppm 15 minutes.
acetone	<b>Lithuanian Hygiene Standard HN 23 (Lithuania, 7/2022).</b> TWA: 1210 mg/m <sup>3</sup> 8 hours. TWA: 500 ppm 8 hours. STEL: 2420 mg/m <sup>3</sup> 15 minutes. STEL: 1000 ppm 15 minutes.
Toluene	<b>Lithuanian Hygiene Standard HN 23 (Lithuania, 7/2022).</b> <b>Absorbed through skin.</b> TWA: 192 mg/m <sup>3</sup> 8 hours. TWA: 50 ppm 8 hours. STEL: 384 mg/m <sup>3</sup> 15 minutes. STEL: 100 ppm 15 minutes.
Xylene	<b>Lithuanian Hygiene Standard HN 23 (Lithuania, 7/2022).</b> <b>[xylene, mixed isomers, pure] Absorbed through skin.</b> STEL: 442 mg/m <sup>3</sup> 15 minutes. TWA: 50 ppm 8 hours. STEL: 100 ppm 15 minutes.

## SECTION 8: Exposure controls/personal protection

Ethyl acetate	TWA: 221 mg/m <sup>3</sup> 8 hours. <b>Lithuanian Hygiene Standard HN 23 (Lithuania, 7/2022).</b> TWA: 500 mg/m <sup>3</sup> 8 hours. TWA: 150 ppm 8 hours. CEIL: 1100 mg/m <sup>3</sup> CEIL: 300 ppm
iso-butanol	<b>Lithuanian Hygiene Standard HN 23 (Lithuania, 7/2022).</b> <b>Absorbed through skin.</b> TWA: 10 mg/m <sup>3</sup> 8 hours.
2-Methoxy-1-methylethyl acetate	<b>Lithuanian Hygiene Standard HN 23 (Lithuania, 7/2022).</b> <b>Absorbed through skin.</b> TWA: 250 mg/m <sup>3</sup> 8 hours. TWA: 50 ppm 8 hours. STEL: 400 mg/m <sup>3</sup> 15 minutes. STEL: 75 ppm 15 minutes.
Propan-2-ol	<b>Lithuanian Hygiene Standard HN 23 (Lithuania, 7/2022).</b> TWA: 350 mg/m <sup>3</sup> 8 hours. TWA: 150 ppm 8 hours. STEL: 600 mg/m <sup>3</sup> 15 minutes. STEL: 250 ppm 15 minutes.
Ethylbenzene	<b>Lithuanian Hygiene Standard HN 23 (Lithuania, 7/2022).</b> <b>Absorbed through skin.</b> TWA: 442 mg/m <sup>3</sup> 8 hours. TWA: 100 ppm 8 hours. STEL: 884 mg/m <sup>3</sup> 15 minutes. STEL: 200 ppm 15 minutes.
n-Butyl acetate	<b>Grand-Duchy Regulation 2016. Chemical agents. Annex I (Luxembourg, 3/2021).</b> STEL: 150 ppm 15 minutes. STEL: 723 mg/m <sup>3</sup> 15 minutes. TWA: 50 ppm 8 hours. TWA: 241 mg/m <sup>3</sup> 8 hours.
acetone	<b>Grand-Duchy Regulation 2016. Chemical agents. Annex I (Luxembourg, 3/2021).</b> TWA: 500 ppm 8 hours. TWA: 1210 mg/m <sup>3</sup> 8 hours.
Toluene	<b>Grand-Duchy Regulation 2016. Chemical agents. Annex I (Luxembourg, 3/2021). Absorbed through skin.</b> STEL: 100 ppm 15 minutes. STEL: 384 mg/m <sup>3</sup> 15 minutes. TWA: 50 ppm 8 hours. TWA: 192 mg/m <sup>3</sup> 8 hours.
Xylene	<b>Grand-Duchy Regulation 2016. Chemical agents. Annex I (Luxembourg, 3/2021). [xylenes, mixed isomers, pure]</b> <b>Absorbed through skin.</b> TWA: 50 ppm 8 hours. TWA: 221 mg/m <sup>3</sup> 8 hours. STEL: 100 ppm 15 minutes. STEL: 442 mg/m <sup>3</sup> 15 minutes.
Ethyl acetate	<b>Grand-Duchy Regulation 2016. Chemical agents. Annex I (Luxembourg, 3/2021).</b> STEL: 400 ppm 15 minutes. STEL: 1468 mg/m <sup>3</sup> 15 minutes. TWA: 200 ppm 8 hours. TWA: 734 mg/m <sup>3</sup> 8 hours.
2-Methoxy-1-methylethyl acetate	<b>Grand-Duchy Regulation 2016. Chemical agents. Annex I (Luxembourg, 3/2021). Absorbed through skin.</b> TWA: 50 ppm 8 hours. TWA: 275 mg/m <sup>3</sup> 8 hours. STEL: 100 ppm 15 minutes. STEL: 550 mg/m <sup>3</sup> 15 minutes.
Ethylbenzene	<b>Grand-Duchy Regulation 2016. Chemical agents. Annex I (Luxembourg, 3/2021). Absorbed through skin.</b> TWA: 100 ppm 8 hours.

## SECTION 8: Exposure controls/personal protection

n-Butyl acetate	<p>TWA: 442 mg/m<sup>3</sup> 8 hours.          STEL: 200 ppm 15 minutes.          STEL: 884 mg/m<sup>3</sup> 15 minutes.</p> <p><b>EU OEL (Europe, 1/2022). Notes: list of indicative occupational exposure limit values</b></p> <p>STEL: 150 ppm 15 minutes.          STEL: 723 mg/m<sup>3</sup> 15 minutes.          TWA: 241 mg/m<sup>3</sup> 8 hours.          TWA: 50 ppm 8 hours.</p>
acetone	<p><b>EU OEL (Europe, 1/2022). Notes: list of indicative occupational exposure limit values</b></p> <p>TWA: 500 ppm 8 hours.          TWA: 1210 mg/m<sup>3</sup> 8 hours.</p>
Toluene	<p><b>EU OEL (Europe, 1/2022). Absorbed through skin. Notes: list of indicative occupational exposure limit values</b></p> <p>TWA: 192 mg/m<sup>3</sup> 8 hours.          TWA: 50 ppm 8 hours.          STEL: 384 mg/m<sup>3</sup> 15 minutes.          STEL: 100 ppm 15 minutes.</p>
Xylene	<p><b>EU OEL (Europe, 1/2022). [xylene, mixed isomers pure] Absorbed through skin. Notes: list of indicative occupational exposure limit values</b></p> <p>TWA: 50 ppm 8 hours.          TWA: 221 mg/m<sup>3</sup> 8 hours.          STEL: 100 ppm 15 minutes.          STEL: 442 mg/m<sup>3</sup> 15 minutes.</p>
Ethyl acetate	<p><b>EU OEL (Europe, 1/2022). Notes: list of indicative occupational exposure limit values</b></p> <p>STEL: 400 ppm 15 minutes.          STEL: 1468 mg/m<sup>3</sup> 15 minutes.          TWA: 200 ppm 8 hours.          TWA: 734 mg/m<sup>3</sup> 8 hours.</p>
2-Methoxy-1-methylethyl acetate	<p><b>EU OEL (Europe, 1/2022). Absorbed through skin. Notes: list of indicative occupational exposure limit values</b></p> <p>TWA: 50 ppm 8 hours.          TWA: 275 mg/m<sup>3</sup> 8 hours.          STEL: 100 ppm 15 minutes.          STEL: 550 mg/m<sup>3</sup> 15 minutes.</p>
Ethylbenzene	<p><b>EU OEL (Europe, 1/2022). Absorbed through skin. Notes: list of indicative occupational exposure limit values</b></p> <p>TWA: 100 ppm 8 hours.          TWA: 442 mg/m<sup>3</sup> 8 hours.          STEL: 200 ppm 15 minutes.          STEL: 884 mg/m<sup>3</sup> 15 minutes.</p>
n-Butyl acetate	<p><b>Ministry of Social Affairs and Employment, Legal limit values (Netherlands, 12/2022).</b></p> <p>OEL, 8-h TWA: 241 mg/m<sup>3</sup> 8 hours.          STEL,15-min: 723 mg/m<sup>3</sup> 15 minutes.          STEL,15-min: 150 ppm 15 minutes.          OEL, 8-h TWA: 50 ppm 8 hours.</p>
acetone	<p><b>Ministry of Social Affairs and Employment, Legal limit values (Netherlands, 12/2022).</b></p> <p>STEL,15-min: 2420 mg/m<sup>3</sup> 15 minutes.          OEL, 8-h TWA: 1210 mg/m<sup>3</sup> 8 hours.          OEL, 8-h TWA: 500 ppm 8 hours.          STEL,15-min: 1000 ppm 15 minutes.</p>
Toluene	<p><b>Ministry of Social Affairs and Employment, Legal limit values (Netherlands, 12/2022).</b></p> <p>OEL, 8-h TWA: 150 mg/m<sup>3</sup> 8 hours.          STEL,15-min: 384 mg/m<sup>3</sup> 15 minutes.          STEL,15-min: 100 ppm 15 minutes.          OEL, 8-h TWA: 39 ppm 8 hours.</p>
Xylene	<p><b>Ministry of Social Affairs and Employment, Legal limit values (Netherlands, 12/2022). [xylenes (all isomers)] Absorbed</b></p>

## SECTION 8: Exposure controls/personal protection

	<p>through skin.          OEL, 8-h TWA: 210 mg/m<sup>3</sup> 8 hours.          STEL, 15-min: 442 mg/m<sup>3</sup> 15 minutes.          STEL, 15-min: 100 ppm 15 minutes.          OEL, 8-h TWA: 47.5 ppm 8 hours.</p>
Ethyl acetate	<p><b>Ministry of Social Affairs and Employment, Legal limit values (Netherlands, 12/2022).</b>          STEL, 15-min: 1468 mg/m<sup>3</sup> 15 minutes.          OEL, 8-h TWA: 734 mg/m<sup>3</sup> 8 hours.          STEL, 15-min: 400 ppm 15 minutes.          OEL, 8-h TWA: 200 ppm 8 hours.</p>
2-Methoxy-1-methylethyl acetate	<p><b>Ministry of Social Affairs and Employment, Legal limit values (Netherlands, 12/2022).</b>          OEL, 8-h TWA: 550 mg/m<sup>3</sup> 8 hours.          OEL, 8-h TWA: 100 ppm 8 hours.</p>
Ethylbenzene	<p><b>Ministry of Social Affairs and Employment, Legal limit values (Netherlands, 12/2022). Absorbed through skin.</b>          OEL, 8-h TWA: 215 mg/m<sup>3</sup> 8 hours.          STEL, 15-min: 430 mg/m<sup>3</sup> 15 minutes.          STEL, 15-min: 97.3 ppm 15 minutes.          OEL, 8-h TWA: 48.6 ppm 8 hours.</p>
n-Butyl acetate	<p><b>FOR-2011-12-06-1358 (Norway, 12/2022).</b>          STEL: 723 mg/m<sup>3</sup> 15 minutes.          STEL: 150 ppm 15 minutes.  <b>FOR-2011-12-06-1358 (Norway, 12/2022). Notes: indicative limit value</b>          TWA: 241 mg/m<sup>3</sup> 8 hours.          TWA: 50 ppm 8 hours.</p>
acetone	<p><b>FOR-2011-12-06-1358 (Norway, 12/2022). Notes: indicative limit value</b>          TWA: 125 ppm 8 hours.          TWA: 295 mg/m<sup>3</sup> 8 hours.</p>
Toluene	<p><b>FOR-2011-12-06-1358 (Norway, 12/2022). Absorbed through skin. Notes: indicative limit value</b>          TWA: 25 ppm 8 hours.          TWA: 94 mg/m<sup>3</sup> 8 hours.</p>
Xylene	<p><b>FOR-2011-12-06-1358 (Norway, 12/2022). [Xylene, all isomers] Absorbed through skin. Notes: indicative limit value</b>          TWA: 25 ppm 8 hours.          TWA: 108 mg/m<sup>3</sup> 8 hours.</p>
Ethyl acetate	<p><b>FOR-2011-12-06-1358 (Norway, 12/2022). Notes: indicative limit value</b>          TWA: 200 ppm 8 hours.          TWA: 734 mg/m<sup>3</sup> 8 hours.  <b>FOR-2011-12-06-1358 (Norway, 12/2022).</b>          STEL: 1468 mg/m<sup>3</sup> 15 minutes.          STEL: 400 ppm 15 minutes.</p>
iso-butanol	<p><b>FOR-2011-12-06-1358 (Norway, 12/2022). Absorbed through skin.</b>          CEIL: 75 mg/m<sup>3</sup>          CEIL: 25 ppm</p>
2-Methoxy-1-methylethyl acetate	<p><b>FOR-2011-12-06-1358 (Norway, 12/2022). Absorbed through skin. Notes: indicative limit value</b>          TWA: 50 ppm 8 hours.          TWA: 270 mg/m<sup>3</sup> 8 hours.</p>
Propan-2-ol	<p><b>FOR-2011-12-06-1358 (Norway, 12/2022).</b>          TWA: 100 ppm 8 hours.          TWA: 245 mg/m<sup>3</sup> 8 hours.</p>
Ethylbenzene	<p><b>FOR-2011-12-06-1358 (Norway, 12/2022). Absorbed through skin. Carcinogen. Notes: indicative limit value</b>          TWA: 5 ppm 8 hours.          TWA: 20 mg/m<sup>3</sup> 8 hours.</p>



## SECTION 8: Exposure controls/personal protection

n-Butyl acetate	<p><b>Regulation of the Minister of Family, Labor and Social Policy of 18 February 2021, regarding the highest permissible concentrations and values of agents harmful to health in the work environment (Journal of Laws 2021, item 325) (Poland, 2/2021).</b></p> <p>TWA: 240 mg/m<sup>3</sup> 8 hours. STEL: 720 mg/m<sup>3</sup> 15 minutes.</p>
acetone	<p><b>Regulation of the Minister of Family, Labor and Social Policy of 18 February 2021, regarding the highest permissible concentrations and values of agents harmful to health in the work environment (Journal of Laws 2021, item 325) (Poland, 2/2021).</b></p> <p>TWA: 600 mg/m<sup>3</sup> 8 hours. STEL: 1800 mg/m<sup>3</sup> 15 minutes.</p>
Toluene	<p><b>Regulation of the Minister of Family, Labor and Social Policy of 18 February 2021, regarding the highest permissible concentrations and values of agents harmful to health in the work environment (Journal of Laws 2021, item 325) (Poland, 2/2021). Absorbed through skin.</b></p> <p>TWA: 100 mg/m<sup>3</sup> 8 hours. STEL: 200 mg/m<sup>3</sup> 15 minutes.</p>
Xylene	<p><b>Regulation of the Minister of Family, Labor and Social Policy of 18 February 2021, regarding the highest permissible concentrations and values of agents harmful to health in the work environment (Journal of Laws 2021, item 325) (Poland, 2/2021). [xylene – mixed isomers (1,2-, 1,3-, 1,4-)] Absorbed through skin.</b></p> <p>TWA: 100 mg/m<sup>3</sup> 8 hours. STEL: 200 mg/m<sup>3</sup> 15 minutes.</p>
Ethyl acetate	<p><b>Regulation of the Minister of Family, Labor and Social Policy of 18 February 2021, regarding the highest permissible concentrations and values of agents harmful to health in the work environment (Journal of Laws 2021, item 325) (Poland, 2/2021).</b></p> <p>TWA: 734 mg/m<sup>3</sup> 8 hours. STEL: 1468 mg/m<sup>3</sup> 15 minutes.</p>
iso-butanol	<p><b>Regulation of the Minister of Family, Labor and Social Policy of 18 February 2021, regarding the highest permissible concentrations and values of agents harmful to health in the work environment (Journal of Laws 2021, item 325) (Poland, 2/2021). Absorbed through skin.</b></p> <p>TWA: 100 mg/m<sup>3</sup> 8 hours. STEL: 200 mg/m<sup>3</sup> 15 minutes.</p>
2-Methoxy-1-methylethyl acetate	<p><b>Regulation of the Minister of Family, Labor and Social Policy of 18 February 2021, regarding the highest permissible concentrations and values of agents harmful to health in the work environment (Journal of Laws 2021, item 325) (Poland, 2/2021). Absorbed through skin.</b></p> <p>TWA: 260 mg/m<sup>3</sup> 8 hours. STEL: 520 mg/m<sup>3</sup> 15 minutes.</p>
Propan-2-ol	<p><b>Regulation of the Minister of Family, Labor and Social Policy of 18 February 2021, regarding the highest permissible concentrations and values of agents harmful to health in the work environment (Journal of Laws 2021, item 325) (Poland, 2/2021). Absorbed through skin.</b></p> <p>TWA: 900 mg/m<sup>3</sup> 8 hours. STEL: 1200 mg/m<sup>3</sup> 15 minutes.</p>
Ethylbenzene	<p><b>Regulation of the Minister of Family, Labor and Social Policy of 18 February 2021, regarding the highest permissible concentrations and values of agents harmful to health in the work environment (Journal of Laws 2021, item 325) (Poland, 2/2021). Absorbed through skin.</b></p> <p>TWA: 200 mg/m<sup>3</sup> 8 hours.</p>

## SECTION 8: Exposure controls/personal protection

n-Butyl acetate	STEL: 400 mg/m <sup>3</sup> 15 minutes. <b>Portuguese Institute of Quality (Portugal, 11/2014).</b> TWA: 150 ppm 8 hours. STEL: 200 ppm 15 minutes.
acetone	<b>Portuguese Institute of Quality (Portugal, 11/2014).</b> TWA: 500 ppm 8 hours. STEL: 750 ppm 15 minutes.
Toluene	<b>Portuguese Institute of Quality (Portugal, 11/2014). Absorbed through skin.</b> TWA: 20 ppm 8 hours.
Xylene	<b>Portuguese Institute of Quality (Portugal, 11/2014). [Xylene]</b> TWA: 100 ppm 8 hours. STEL: 150 ppm 15 minutes.
Ethyl acetate	<b>Portuguese Institute of Quality (Portugal, 11/2014).</b> TWA: 400 ppm 8 hours.
iso-butanol	<b>Portuguese Institute of Quality (Portugal, 11/2014).</b> TWA: 50 ppm 8 hours.
2-Methoxy-1-methylethyl acetate	<b>EU OEL (Europe, 1/2022). Absorbed through skin. Notes: list of indicative occupational exposure limit values</b> TWA: 50 ppm 8 hours. TWA: 275 mg/m <sup>3</sup> 8 hours. STEL: 100 ppm 15 minutes. STEL: 550 mg/m <sup>3</sup> 15 minutes.
Propan-2-ol	<b>Portuguese Institute of Quality (Portugal, 11/2014).</b> TWA: 200 ppm 8 hours. STEL: 400 ppm 15 minutes.
Ethylbenzene	<b>Portuguese Institute of Quality (Portugal, 11/2014).</b> TWA: 20 ppm 8 hours.
n-Butyl acetate	<b>HG 1218/2006, Annex 1, with subsequent modifications and additions (Romania, 3/2021).</b> VLA: 241 mg/m <sup>3</sup> 8 hours. VLA: 50 ppm 8 hours. Short term: 723 mg/m <sup>3</sup> 15 minutes. Short term: 150 ppm 15 minutes.
acetone	<b>HG 1218/2006, Annex 1, with subsequent modifications and additions (Romania, 3/2021).</b> VLA: 1210 mg/m <sup>3</sup> 8 hours. VLA: 500 ppm 8 hours.
Toluene	<b>HG 1218/2006, Annex 1, with subsequent modifications and additions (Romania, 3/2021). Absorbed through skin.</b> VLA: 192 mg/m <sup>3</sup> 8 hours. VLA: 50 ppm 8 hours. Short term: 384 mg/m <sup>3</sup> 15 minutes. Short term: 100 ppm 15 minutes.
Xylene	<b>HG 1218/2006, Annex 1, with subsequent modifications and additions (Romania, 3/2021). [Xylene] Absorbed through skin.</b> VLA: 221 mg/m <sup>3</sup> 8 hours. VLA: 50 ppm 8 hours. Short term: 442 mg/m <sup>3</sup> 15 minutes. Short term: 100 ppm 15 minutes.
Ethyl acetate	<b>HG 1218/2006, Annex 1, with subsequent modifications and additions (Romania, 3/2021).</b> VLA: 734 mg/m <sup>3</sup> 8 hours. VLA: 200 ppm 8 hours. Short term: 1468 mg/m <sup>3</sup> 15 minutes. Short term: 400 ppm 15 minutes.
iso-butanol	<b>HG 1218/2006, Annex 1, with subsequent modifications and additions (Romania, 3/2021).</b> VLA: 100 mg/m <sup>3</sup> 8 hours. VLA: 33 ppm 8 hours. Short term: 200 mg/m <sup>3</sup> 15 minutes. Short term: 66 ppm 15 minutes.
2-Methoxy-1-methylethyl acetate	<b>HG 1218/2006, Annex 1, with subsequent modifications and</b>

## SECTION 8: Exposure controls/personal protection

Propan-2-ol	<p><b>additions (Romania, 3/2021). Absorbed through skin.</b>  VLA: 275 mg/m<sup>3</sup> 8 hours.  VLA: 50 ppm 8 hours.  Short term: 550 mg/m<sup>3</sup> 15 minutes.  Short term: 100 ppm 15 minutes.</p> <p><b>HG 1218/2006, Annex 1, with subsequent modifications and additions (Romania, 3/2021).</b>  VLA: 200 mg/m<sup>3</sup> 8 hours.  VLA: 81 ppm 8 hours.  Short term: 500 mg/m<sup>3</sup> 15 minutes.  Short term: 203 ppm 15 minutes.</p>
Ethylbenzene	<p><b>HG 1218/2006, Annex 1, with subsequent modifications and additions (Romania, 3/2021). Absorbed through skin.</b>  VLA: 442 mg/m<sup>3</sup> 8 hours.  VLA: 100 ppm 8 hours.  Short term: 884 mg/m<sup>3</sup> 15 minutes.</p>
n-Butyl acetate	<p><b>Government regulation SR c. 355/2006 (Slovakia, 9/2020).</b>  <b>[Butyl acetates]</b>  TWA: 241 mg/m<sup>3</sup>, (Butyl acetates) 8 hours.  TWA: 50 ppm, (Butyl acetates) 8 hours.  STEL: 723 mg/m<sup>3</sup>, (Butyl acetates) 15 minutes.  STEL: 150 ppm, (Butyl acetates) 15 minutes.</p>
acetone	<p><b>Government regulation SR c. 355/2006 (Slovakia, 9/2020).</b>  TWA: 1210 mg/m<sup>3</sup> 8 hours.  TWA: 500 ppm 8 hours.</p>
Toluene	<p><b>Government regulation SR c. 355/2006 (Slovakia, 9/2020).</b>  <b>Absorbed through skin.</b>  TWA: 192 mg/m<sup>3</sup> 8 hours.  TWA: 50 ppm 8 hours.  STEL: 384 mg/m<sup>3</sup> 15 minutes.  STEL: 100 ppm 15 minutes.</p>
Xylene	<p><b>Government regulation SR c. 355/2006 (Slovakia, 9/2020).</b>  <b>[xylene, mixed isomers] Absorbed through skin.</b>  TWA: 221 mg/m<sup>3</sup>, (xylene, mixed isomers) 8 hours.  TWA: 50 ppm, (xylene, mixed isomers) 8 hours.  STEL: 442 mg/m<sup>3</sup>, (xylene, mixed isomers) 15 minutes.  STEL: 100 ppm, (xylene, mixed isomers) 15 minutes.</p>
Ethyl acetate	<p><b>Government regulation SR c. 355/2006 (Slovakia, 9/2020).</b>  TWA: 734 mg/m<sup>3</sup> 8 hours.  TWA: 200 ppm 8 hours.  STEL: 1468 mg/m<sup>3</sup> 15 minutes.  STEL: 400 ppm 15 minutes.</p>
iso-butanol	<p><b>Government regulation SR c. 355/2006 (Slovakia, 9/2020).</b>  <b>[Butyl alcohols]</b>  TWA: 310 mg/m<sup>3</sup>, (Butyl alcohols) 8 hours.  TWA: 100 ppm, (Butyl alcohols) 8 hours.</p>
2-Methoxy-1-methylethyl acetate	<p><b>Government regulation SR c. 355/2006 (Slovakia, 9/2020).</b>  <b>Absorbed through skin.</b>  TWA: 275 mg/m<sup>3</sup> 8 hours.  TWA: 50 ppm 8 hours.  STEL: 550 mg/m<sup>3</sup> 15 minutes.  STEL: 100 ppm 15 minutes.</p>
Propan-2-ol	<p><b>Government regulation SR c. 355/2006 (Slovakia, 9/2020).</b>  TWA: 500 mg/m<sup>3</sup> 8 hours.  TWA: 200 ppm 8 hours.  STEL: 1000 mg/m<sup>3</sup> 15 minutes.  STEL: 400 ppm 15 minutes.</p>
Ethylbenzene	<p><b>Government regulation SR c. 355/2006 (Slovakia, 9/2020).</b>  <b>Absorbed through skin.</b>  TWA: 442 mg/m<sup>3</sup> 8 hours.  TWA: 100 ppm 8 hours.  STEL: 884 mg/m<sup>3</sup> 15 minutes.  STEL: 200 ppm 15 minutes.</p>

## SECTION 8: Exposure controls/personal protection

n-Butyl acetate	<p><b>Regulation on protection of workers from the risks related to exposure to chemical substances at work (Slovenia, 5/2021).</b>  TWA: 241 mg/m<sup>3</sup> 8 hours.  TWA: 50 ppm 8 hours.  KTV: 723 mg/m<sup>3</sup>, 4 times per shift, 15 minutes.  KTV: 150 ppm, 4 times per shift, 15 minutes.</p>
acetone	<p><b>Regulation on protection of workers from the risks related to exposure to chemical substances at work (Slovenia, 5/2021).</b>  TWA: 1210 mg/m<sup>3</sup> 8 hours.  TWA: 500 ppm 8 hours.  KTV: 1000 ppm, 4 times per shift, 15 minutes.  KTV: 2420 mg/m<sup>3</sup>, 4 times per shift, 15 minutes.</p>
Toluene	<p><b>Regulation on protection of workers from the risks related to exposure to chemical substances at work (Slovenia, 5/2021).</b>  <b>Absorbed through skin.</b>  TWA: 192 mg/m<sup>3</sup> 8 hours.  TWA: 50 ppm 8 hours.  KTV: 384 mg/m<sup>3</sup>, 4 times per shift, 15 minutes.  KTV: 100 ppm, 4 times per shift, 15 minutes.</p>
Xylene	<p><b>Regulation on protection of workers from the risks related to exposure to chemical substances at work (Slovenia, 5/2021).</b>  <b>[xylene (mixture of isomers)] Absorbed through skin.</b>  TWA: 221 mg/m<sup>3</sup> 8 hours.  TWA: 50 ppm 8 hours.  KTV: 442 mg/m<sup>3</sup>, 4 times per shift, 15 minutes.  KTV: 100 ppm, 4 times per shift, 15 minutes.</p>
Ethyl acetate	<p><b>Regulation on protection of workers from the risks related to exposure to chemical substances at work (Slovenia, 5/2021).</b>  TWA: 734 mg/m<sup>3</sup> 8 hours.  TWA: 200 ppm 8 hours.  KTV: 1468 mg/m<sup>3</sup>, 4 times per shift, 15 minutes.  KTV: 400 ppm, 4 times per shift, 15 minutes.</p>
iso-butanol	<p><b>Regulation on protection of workers from the risks related to exposure to chemical substances at work (Slovenia, 5/2021).</b>  TWA: 310 mg/m<sup>3</sup> 8 hours.  TWA: 100 ppm 8 hours.  KTV: 310 mg/m<sup>3</sup>, 4 times per shift, 15 minutes.  KTV: 100 ppm, 4 times per shift, 15 minutes.</p>
2-Methoxy-1-methylethyl acetate	<p><b>Regulation on protection of workers from the risks related to exposure to chemical substances at work (Slovenia, 5/2021).</b>  <b>Absorbed through skin.</b>  TWA: 275 mg/m<sup>3</sup> 8 hours.  TWA: 50 ppm 8 hours.  KTV: 550 mg/m<sup>3</sup>, 4 times per shift, 15 minutes.  KTV: 100 ppm, 4 times per shift, 15 minutes.</p>
Propan-2-ol	<p><b>Regulation on protection of workers from the risks related to exposure to chemical substances at work (Slovenia, 5/2021).</b>  TWA: 500 mg/m<sup>3</sup> 8 hours.  TWA: 200 ppm 8 hours.  KTV: 1000 mg/m<sup>3</sup>, 4 times per shift, 15 minutes.  KTV: 400 ppm, 4 times per shift, 15 minutes.</p>
Ethylbenzene	<p><b>Regulation on protection of workers from the risks related to exposure to chemical substances at work (Slovenia, 5/2021).</b>  <b>Absorbed through skin.</b>  TWA: 442 mg/m<sup>3</sup> 8 hours.  TWA: 100 ppm 8 hours.  KTV: 884 mg/m<sup>3</sup>, 4 times per shift, 15 minutes.  KTV: 200 ppm, 4 times per shift, 15 minutes.</p>
1-Ethoxy-2-propanol	<p><b>Regulation on protection of workers from the risks related to exposure to chemical substances at work (Slovenia, 5/2021).</b>  <b>Absorbed through skin.</b>  KTV: 100 ppm, 4 times per shift, 15 minutes.  TWA: 50 ppm 8 hours.  KTV: 440 mg/m<sup>3</sup>, 4 times per shift, 15 minutes.</p>

## SECTION 8: Exposure controls/personal protection

n-Butyl acetate	TWA: 220 mg/m <sup>3</sup> 8 hours. <b>National institute of occupational safety and health (Spain, 4/2022).</b> TWA: 50 ppm 8 hours. TWA: 241 mg/m <sup>3</sup> 8 hours. STEL: 150 ppm 15 minutes. STEL: 723 mg/m <sup>3</sup> 15 minutes.
acetone	<b>National institute of occupational safety and health (Spain, 4/2022).</b> TWA: 500 ppm 8 hours. TWA: 1210 mg/m <sup>3</sup> 8 hours.
Toluene	<b>National institute of occupational safety and health (Spain, 4/2022). Absorbed through skin.</b> TWA: 50 ppm 8 hours. TWA: 192 mg/m <sup>3</sup> 8 hours. STEL: 100 ppm 15 minutes. STEL: 384 mg/m <sup>3</sup> 15 minutes.
Xylene	<b>National institute of occupational safety and health (Spain, 4/2022). [Xylene, mixture of isomers] Absorbed through skin.</b> TWA: 50 ppm 8 hours. TWA: 221 mg/m <sup>3</sup> 8 hours. STEL: 100 ppm 15 minutes. STEL: 442 mg/m <sup>3</sup> 15 minutes.
Ethyl acetate	<b>National institute of occupational safety and health (Spain, 4/2022).</b> TWA: 200 ppm 8 hours. TWA: 734 mg/m <sup>3</sup> 8 hours. STEL: 1468 mg/m <sup>3</sup> 15 minutes. STEL: 400 ppm 15 minutes.
iso-butanol	<b>National institute of occupational safety and health (Spain, 4/2022).</b> TWA: 50 ppm 8 hours. TWA: 154 mg/m <sup>3</sup> 8 hours.
2-Methoxy-1-methylethyl acetate	<b>National institute of occupational safety and health (Spain, 4/2022). Absorbed through skin.</b> TWA: 50 ppm 8 hours. TWA: 275 mg/m <sup>3</sup> 8 hours. STEL: 100 ppm 15 minutes. STEL: 550 mg/m <sup>3</sup> 15 minutes.
Propan-2-ol	<b>National institute of occupational safety and health (Spain, 4/2022).</b> TWA: 200 ppm 8 hours. TWA: 500 mg/m <sup>3</sup> 8 hours. STEL: 400 ppm 15 minutes. STEL: 1000 mg/m <sup>3</sup> 15 minutes.
Ethylbenzene	<b>National institute of occupational safety and health (Spain, 4/2022). Absorbed through skin.</b> TWA: 100 ppm 8 hours. TWA: 441 mg/m <sup>3</sup> 8 hours. STEL: 200 ppm 15 minutes. STEL: 884 mg/m <sup>3</sup> 15 minutes.
n-Butyl acetate	<b>Work environment authority Regulation 2018:1 (Sweden, 9/2021). [butyl acetate]</b> TWA: 50 ppm 8 hours. TWA: 241 mg/m <sup>3</sup> 8 hours. STEL: 150 ppm 15 minutes. STEL: 723 mg/m <sup>3</sup> 15 minutes.
acetone	<b>Work environment authority Regulation 2018:1 (Sweden, 9/2021).</b> TWA: 250 ppm 8 hours. TWA: 600 mg/m <sup>3</sup> 8 hours. STEL: 500 ppm 15 minutes. STEL: 1200 mg/m <sup>3</sup> 15 minutes.
Toluene	<b>Work environment authority Regulation 2018:1 (Sweden,</b>

## SECTION 8: Exposure controls/personal protection

Xylene	<p><b>9/2021). Absorbed through skin. Ototoxicant.</b>  TWA: 50 ppm 8 hours.  TWA: 192 mg/m<sup>3</sup> 8 hours.  STEL: 100 ppm 15 minutes.  STEL: 384 mg/m<sup>3</sup> 15 minutes.</p> <p><b>Work environment authority Regulation 2018:1 (Sweden, 9/2021). [xylene] Absorbed through skin.</b>  TWA: 50 ppm 8 hours.  TWA: 221 mg/m<sup>3</sup> 8 hours.  STEL: 100 ppm 15 minutes.  STEL: 442 mg/m<sup>3</sup> 15 minutes.</p>
Ethyl acetate	<p><b>Work environment authority Regulation 2018:1 (Sweden, 9/2021).</b>  TWA: 150 ppm 8 hours.  TWA: 550 mg/m<sup>3</sup> 8 hours.  STEL: 300 ppm 15 minutes.  STEL: 1100 mg/m<sup>3</sup> 15 minutes.</p>
iso-butanol	<p><b>Work environment authority Regulation 2018:1 (Sweden, 9/2021). Absorbed through skin.</b>  TWA: 50 ppm 8 hours.  TWA: 150 mg/m<sup>3</sup> 8 hours.  STEL: 75 ppm 15 minutes.  STEL: 250 mg/m<sup>3</sup> 15 minutes.</p>
2-Methoxy-1-methylethyl acetate	<p><b>Work environment authority Regulation 2018:1 (Sweden, 9/2021). Absorbed through skin.</b>  TWA: 50 ppm 8 hours.  TWA: 275 mg/m<sup>3</sup> 8 hours.  STEL: 100 ppm 15 minutes.  STEL: 550 mg/m<sup>3</sup> 15 minutes.</p>
Propan-2-ol	<p><b>Work environment authority Regulation 2018:1 (Sweden, 9/2021).</b>  TWA: 150 ppm 8 hours.  TWA: 350 mg/m<sup>3</sup> 8 hours.  STEL: 250 ppm 15 minutes.  STEL: 600 mg/m<sup>3</sup> 15 minutes.</p>
Ethylbenzene	<p><b>Work environment authority Regulation 2018:1 (Sweden, 9/2021). Absorbed through skin.</b>  TWA: 50 ppm 8 hours.  TWA: 220 mg/m<sup>3</sup> 8 hours.  STEL: 200 ppm 15 minutes.  STEL: 884 mg/m<sup>3</sup> 15 minutes.</p>
n-Butyl acetate	<p><b>SUVA (Switzerland, 1/2023).</b>  TWA: 50 ppm 8 hours.  TWA: 240 mg/m<sup>3</sup> 8 hours.  STEL: 150 ppm 15 minutes.  STEL: 720 mg/m<sup>3</sup> 15 minutes.</p>
acetone	<p><b>SUVA (Switzerland, 1/2023).</b>  TWA: 500 ppm 8 hours.  TWA: 1200 mg/m<sup>3</sup> 8 hours.  STEL: 1000 ppm 15 minutes.  STEL: 2400 mg/m<sup>3</sup> 15 minutes.</p>
Toluene	<p><b>SUVA (Switzerland, 1/2023). Absorbed through skin.</b>  TWA: 50 ppm 8 hours.  TWA: 190 mg/m<sup>3</sup> 8 hours.  STEL: 200 ppm 15 minutes.  STEL: 760 mg/m<sup>3</sup> 15 minutes.</p>
Xylene	<p><b>SUVA (Switzerland, 1/2023). [Xylenes (all isomers)] Absorbed through skin.</b>  TWA: 50 ppm 8 hours.  TWA: 220 mg/m<sup>3</sup> 8 hours.  STEL: 100 ppm 15 minutes.  STEL: 440 mg/m<sup>3</sup> 15 minutes.</p>
Ethyl acetate	<p><b>SUVA (Switzerland, 1/2023).</b>  STEL: 400 ppm 15 minutes.</p>

## SECTION 8: Exposure controls/personal protection

iso-butanol	<p>STEL: 1460 mg/m<sup>3</sup> 15 minutes. TWA: 200 ppm 8 hours. TWA: 730 mg/m<sup>3</sup> 8 hours. <b>SUVA (Switzerland, 1/2023).</b> TWA: 50 ppm 8 hours. TWA: 150 mg/m<sup>3</sup> 8 hours. STEL: 50 ppm 15 minutes. STEL: 150 mg/m<sup>3</sup> 15 minutes.</p>
2-Methoxy-1-methylethyl acetate	<p><b>SUVA (Switzerland, 1/2023).</b> TWA: 50 ppm 8 hours. TWA: 275 mg/m<sup>3</sup> 8 hours. STEL: 50 ppm 15 minutes. STEL: 275 mg/m<sup>3</sup> 15 minutes.</p>
Propan-2-ol	<p><b>SUVA (Switzerland, 1/2023).</b> TWA: 200 ppm 8 hours. TWA: 500 mg/m<sup>3</sup> 8 hours. STEL: 400 ppm 15 minutes. STEL: 1000 mg/m<sup>3</sup> 15 minutes.</p>
Ethylbenzene	<p><b>SUVA (Switzerland, 1/2023). Absorbed through skin.</b> TWA: 50 ppm 8 hours. TWA: 220 mg/m<sup>3</sup> 8 hours. STEL: 50 ppm 15 minutes. STEL: 220 mg/m<sup>3</sup> 15 minutes.</p>
1-Ethoxy-2-propanol	<p><b>SUVA (Switzerland, 1/2023). Absorbed through skin.</b> STEL: 100 ppm 15 minutes. STEL: 440 mg/m<sup>3</sup> 15 minutes. TWA: 50 ppm 8 hours. TWA: 220 mg/m<sup>3</sup> 8 hours.</p>
n-Butyl acetate	<p><b>EH40/2005 WELs (United Kingdom (UK), 1/2020).</b> STEL: 966 mg/m<sup>3</sup> 15 minutes. STEL: 200 ppm 15 minutes. TWA: 724 mg/m<sup>3</sup> 8 hours. TWA: 150 ppm 8 hours.</p>
acetone	<p><b>EH40/2005 WELs (United Kingdom (UK), 1/2020).</b> STEL: 3620 mg/m<sup>3</sup> 15 minutes. STEL: 1500 ppm 15 minutes. TWA: 500 ppm 8 hours. TWA: 1210 mg/m<sup>3</sup> 8 hours.</p>
Toluene	<p><b>EH40/2005 WELs (United Kingdom (UK), 1/2020). Absorbed through skin.</b> STEL: 384 mg/m<sup>3</sup> 15 minutes. TWA: 191 mg/m<sup>3</sup> 8 hours. TWA: 50 ppm 8 hours. STEL: 100 ppm 15 minutes.</p>
Xylene	<p><b>EH40/2005 WELs (United Kingdom (UK), 1/2020). [xylene, o-,m-, p- or mixed isomers] Absorbed through skin.</b> STEL: 441 mg/m<sup>3</sup> 15 minutes. TWA: 50 ppm 8 hours. TWA: 220 mg/m<sup>3</sup> 8 hours. STEL: 100 ppm 15 minutes.</p>
Ethyl acetate	<p><b>EH40/2005 WELs (United Kingdom (UK), 1/2020).</b> STEL: 400 ppm 15 minutes. TWA: 200 ppm 8 hours. STEL: 1468 mg/m<sup>3</sup> 15 minutes. TWA: 734 mg/m<sup>3</sup> 8 hours.</p>
iso-butanol	<p><b>EH40/2005 WELs (United Kingdom (UK), 1/2020).</b> STEL: 231 mg/m<sup>3</sup> 15 minutes. STEL: 75 ppm 15 minutes. TWA: 154 mg/m<sup>3</sup> 8 hours. TWA: 50 ppm 8 hours.</p>
2-Methoxy-1-methylethyl acetate	<p><b>EH40/2005 WELs (United Kingdom (UK), 1/2020). Absorbed through skin.</b> STEL: 548 mg/m<sup>3</sup> 15 minutes. TWA: 50 ppm 8 hours.</p>

## SECTION 8: Exposure controls/personal protection

Propan-2-ol	TWA: 274 mg/m <sup>3</sup> 8 hours. STEL: 100 ppm 15 minutes. <b>EH40/2005 WELs (United Kingdom (UK), 1/2020).</b> STEL: 1250 mg/m <sup>3</sup> 15 minutes. STEL: 500 ppm 15 minutes. TWA: 999 mg/m <sup>3</sup> 8 hours.
Ethylbenzene	TWA: 400 ppm 8 hours. <b>EH40/2005 WELs (United Kingdom (UK), 1/2020). Absorbed through skin.</b> STEL: 552 mg/m <sup>3</sup> 15 minutes. STEL: 125 ppm 15 minutes. TWA: 100 ppm 8 hours.
2-Methoxy-1-methylethyl acetate	TWA: 441 mg/m <sup>3</sup> 8 hours. <b>EH40/2005 WELs (United Kingdom (UK), 1/2020). Absorbed through skin.</b> STEL: 548 mg/m <sup>3</sup> 15 minutes. TWA: 50 ppm 8 hours.
1-Methoxy 2-propanol	TWA: 274 mg/m <sup>3</sup> 8 hours. STEL: 100 ppm 15 minutes. <b>EH40/2005 WELs (United Kingdom (UK), 1/2020). Absorbed through skin.</b> STEL: 560 mg/m <sup>3</sup> 15 minutes. STEL: 150 ppm 15 minutes. TWA: 375 mg/m <sup>3</sup> 8 hours.
Formaldehyde	TWA: 100 ppm 8 hours. <b>EH40/2005 WELs (United Kingdom (UK), 1/2020).</b> STEL: 2.5 mg/m <sup>3</sup> 15 minutes. STEL: 2 ppm 15 minutes. TWA: 2 ppm 8 hours. TWA: 2.5 mg/m <sup>3</sup> 8 hours.

### Biological exposure indices

Product/ingredient name	Exposure indices
Toluene	<b>VGU BEI (Austria, 9/2020)</b> BEI Fitness: 250 µg/l, toluene [in blood]. Sampling time: one year. BEI Fitness: 0.8 mg/l, o-cresol [in urine]. Sampling time: one year. BEI Fitness: 130000 /µl, platelets (non-pathological differential blood count) [in blood]. Sampling time: one year. BEI Fitness: 150000 /µl, platelets [in blood]. Sampling time: one year. BEI Fitness: 3700 to 13000 /µl, leukocytes (non-pathological differential blood count) [in blood]. Sampling time: one year. BEI Fitness: 4000 to 13000 /µl, leukocytes [in blood]. Sampling time: one year. BEI Fitness - men: 3.8 million/µl, erythrocytes [in blood]. Sampling time: one year. BEI Fitness - women: 3.2 million/µl, erythrocytes [in blood]. Sampling time: one year. BEI Fitness - men: 12 g/dl, hemoglobin [in blood]. Sampling time: one year. BEI Fitness - women: 10 g/dl, hemoglobin [in blood]. Sampling time: one year.
Xylene	<b>VGU BEI (Austria, 9/2020) [xylenes]</b> BEI Fitness: 1000 µg/l, xylene [in blood]. Sampling time: one year. BEI Fitness: 1.5 g/l, methylhippuricacid [in urine]. Sampling time: one year.
No exposure indices known.	



## SECTION 8: Exposure controls/personal protection

acetone	<p><b>Ministry of Labour and Social Policy and the Ministry of Health - Ordinance No 13/2003. (Bulgaria, 6/2021)</b>            BLV: 80 mg/l, acetone [in urine]. Sampling time: after the end of the exposure or the end of the work shift.</p>
Toluene	<p><b>Ministry of Labour and Social Policy and the Ministry of Health - Ordinance No 13/2003. (Bulgaria, 6/2021)</b>            BLV: 1.6 mmol/mmol creatinine, hippuric acid [in urine]. Sampling time: after the end of the exposure or the end of the work shift.</p>
Ethylbenzene	<p><b>Ministry of Labour and Social Policy and the Ministry of Health - Ordinance No 13/2003. (Bulgaria, 6/2021) Notes: significant skin resorption possible</b>            BLV: 2000 mg/g creatinine, mandelic acid and phenylglyoxylic acid – in total [in urine]. Sampling time: after the end of the exposure or the end of the work shift.</p>
acetone	<p><b>Ministry of Economy, Labour and Entrepreneurship ILV/STEL (Croatia, 10/2018)</b>            BEI: 20 mg/g creatinine, acetone [in urine]. Sampling time: at the end of the work shift.            BEI: 39 mmol/mol creatinine, acetone [in urine]. Sampling time: at the end of the work shift.            BEI: 20 mg/l, acetone [in blood]. Sampling time: at the end of the work shift.            BEI: 0.34 mmol/l, acetone [in blood]. Sampling time: at the end of the work shift.</p>
Toluene	<p><b>Ministry of Economy, Labour and Entrepreneurship ILV/STEL (Croatia, 10/2018)</b>            BEI: 20 ppm, toluene [in end exhaled air]. Sampling time: during exposure.            BEI: 0.83 µmol/l, toluene [in end exhaled air]. Sampling time: during exposure.            BEI: 1 mg/l, toluene [in blood]. Sampling time: at the end of the work shift.            BEI: 10.85 µmol/l, toluene [in blood]. Sampling time: at the end of the work shift.            BEI: 1.05 mmol/mol creatinine, o-cresol [in urine]. Sampling time: at the end of the work shift.            BEI: 1 mg/g creatinine, o-cresol [in urine]. Sampling time: at the end of the work shift.            BEI: 1.58 mol/mol creatinine, hippuric acid [in urine]. Sampling time: at the end of the work shift.            BEI: 2.5 g/g creatinine, hippuric acid [in urine]. Sampling time: at the end of the work shift.</p>
Xylene	<p><b>Ministry of Economy, Labour and Entrepreneurship ILV/STEL (Croatia, 10/2018) [xylene]</b>            BEI: 1.5 mg/l, xylene [in blood]. Sampling time: at the end of the work shift.            BEI: 14.13 µmol/l, xylene [in blood]. Sampling time: at the end of the work shift.            BEI: 0.88 mol/mol creatinine, methylhippuric acid [in urine]. Sampling time: at the end of the work shift.            BEI: 1.5 g/g creatinine, methylhippuric acid [in urine]. Sampling time: at the end of the work shift.</p>
Propan-2-ol	<p><b>Ministry of Economy, Labour and Entrepreneurship ILV/STEL (Croatia, 10/2018)</b>            BEI: 50 mg/l, acetone [in urine]. Sampling time: at the end of the work shift.            BEI: 50 mg/l, acetone [in blood]. Sampling time: at the end of the work shift.            BEI: 0.86 µmol/l, acetone [in urine]. Sampling time: at the end of</p>

## SECTION 8: Exposure controls/personal protection

<p>Ethylbenzene</p>	<p>the work shift. BEI: 0.86 µmol/l, acetone [in blood]. Sampling time: at the end of the work shift.</p> <p><b>Ministry of Economy, Labour and Entrepreneurship ILV/STEL (Croatia, 10/2018)</b> BEI: 1.5 mg/l, ethylbenzene [in blood]. Sampling time: during exposure. BEI: 14.1 µmol/l, ethylbenzene [in blood]. Sampling time: during exposure. BEI: 1.12 mol/mol creatinine, almond acid [in urine]. Sampling time: at the end of the work shift and at the end of the working week. BEI: 1.5 g/g creatinine, almond acid [in urine]. Sampling time: at the end of the work shift and at the end of the working week.</p>
<p>No exposure indices known.</p>	
<p>Toluene</p>	<p><b>Government regulation of Czech Republic Limit Values of Biological Exposure Tests (Czech Republic, 9/2015)</b> Biological limit values: 1000 µmol/mmol creatinine, hippuric acid [in urine]. Sampling time: end of the shift. Biological limit values: 1600 mg/g, hippuric acid [in urine]. Sampling time: end of the shift. Biological limit values: 1.6 µmol/mmol creatinine, o-kresol (after hydrolysis) [in urine]. Sampling time: end of the shift. Biological limit values: 1.5 mg/g creatinine, o-kresol (after hydrolysis) [in urine]. Sampling time: end of the shift.</p>
<p>Xylene</p>	<p><b>Government regulation of Czech Republic Limit Values of Biological Exposure Tests (Czech Republic, 9/2015) [Xylene]</b> Biological limit values: 820 µmol/mmol creatinine, methylhippuric acid [in urine]. Sampling time: end of the shift. Biological limit values: 1400 mg/g creatinine, methylhippuric acid [in urine]. Sampling time: end of the shift.</p>
<p>Ethylbenzene</p>	<p><b>Government regulation of Czech Republic Limit Values of Biological Exposure Tests (Czech Republic, 9/2015)</b> Biological limit values: 1100 µmol/mmol creatinine, almond acid [in urine]. Sampling time: end of the shift. Biological limit values: 1500 mg/g creatinine, almond acid [in urine]. Sampling time: end of the shift.</p>
<p>No exposure indices known.</p>	
<p>No exposure indices known.</p>	
<p>No exposure indices known.</p>	
<p>Toluene</p>	<p><b>Institute of Occupational Health, Ministry of Social Affairs (Finland, 9/2020)</b> BEI: 500 nmol/l, toluene [in blood]. Sampling time: the morning after the working day.</p>
<p>Xylene</p>	<p><b>Institute of Occupational Health, Ministry of Social Affairs (Finland, 9/2020) [Xylene]</b> BEI: 5 mmol/l, methylhippuric acid [in urine]. Sampling time: at the end of the work shift.</p>
<p>Ethylbenzene</p>	<p><b>Institute of Occupational Health, Ministry of Social Affairs (Finland, 9/2020)</b> BEI: 5.2 mmol/l, mandelic acid [in urine]. Sampling time: after work shift at the end of the working week or exposure period.</p>
<p>No exposure indices known.</p>	

## SECTION 8: Exposure controls/personal protection

acetone	<p><b>DFG BEI-values list (Germany, 7/2022)</b> BEI: 50 mg/l, acetone [in urine]. Sampling time: end of exposure or end of shift.</p> <p><b>TRGS 903 - BEI Values (Germany, 2/2022)</b> BEI: 80 mg/l, acetone [in urine]. Sampling time: end of exposure or end of shift.</p>
Toluene	<p><b>DFG BEI-values list (Germany, 7/2022) Notes: danger from percutaneous absorption (see p. 211 and p. 228).</b> BEI: 600 µg/l, toluene [in blood]. Sampling time: immediately after exposure. BEI: 1.5 mg/l, o-cresol (after hydrolysis) [in urine]. Sampling time: end of exposure or end of shift / for long-term exposures: at the end of the shift after several shifts. BEI: 75 µg/l, toluene [in urine]. Sampling time: end of exposure or end of shift.</p> <p><b>TRGS 903 - BEI Values (Germany, 2/2022)</b> BEI: 600 µg/l, toluene [in whole blood]. Sampling time: immediately after exposure. BEI: 1.5 mg/l, o-cresol (after hydrolysis) [in urine]. Sampling time: end of exposure or end of shift; for long-term exposures: at the end of shift after several shifts. BEI: 75 µg/l, toluene [in urine]. Sampling time: end of exposure or end of shift.</p>
Xylene	<p><b>DFG BEI-values list (Germany, 7/2022) [Xylene (all isomers)] Notes: danger from percutaneous absorption (see p. 211 and p. 228).</b> BEI: 2000 mg/l, methylhippuric acid (toluric acid) (all isomers) [in urine]. Sampling time: end of exposure or end of shift.</p> <p><b>TRGS 903 - BEI Values (Germany, 2/2022) [Xylene (all isomers)]</b> BEI: 2000 mg/l, methylhippuric acid [in urine]. Sampling time: end of exposure or end of shift.</p>
Propan-2-ol	<p><b>DFG BEI-values list (Germany, 7/2022)</b> BEI: 25 mg/l, acetone [in blood]. Sampling time: end of exposure or end of shift. BEI: 25 mg/l, acetone [in urine]. Sampling time: end of exposure or end of shift.</p> <p><b>TRGS 903 - BEI Values (Germany, 2/2022)</b> BEI: 25 mg/l, acetone [in whole blood]. Sampling time: end of exposure or end of shift. BEI: 25 mg/l, acetone [in urine]. Sampling time: end of exposure or end of shift.</p>
Ethylbenzene	<p><b>DFG BEI-values list (Germany, 7/2022) Notes: danger from percutaneous absorption (see p. 211 and p. 228).</b> BEI: 250 mg/g creatinine, mandelic acid plus phenyl glyoxylic acid [in urine]. Sampling time: end of exposure or end of shift.</p> <p><b>TRGS 903 - BEI Values (Germany, 2/2022)</b> BEI: 250 mg/g creatinine, mandelic acid plus phenylglyoxylic acid [in urine]. Sampling time: end of exposure or end of shift.</p>
1-Ethoxy-2-propanol	<p><b>DFG BEI-values list (Germany, 7/2022) Notes: danger from percutaneous absorption (see p. 211 and p. 228).</b> BEI: See Section XII.2: Substances for which no BAT values are currently be derived, but documentaries in the "work Medico-toxicological justifications for BAT values, EKA and BLW", 1-ethoxy-2-propanol [in urine]. Sampling time: end of exposure or end of shift.</p>
No exposure indices known.	

## SECTION 8: Exposure controls/personal protection

acetone	<p><b>5/2020. (II. 6.) ITM Decree (Hungary, 12/2022)</b>            BEI: 1380 µmol/l, acetone [in urine]. Sampling time: at the end of the shift.            BEI: 80 mg/l, acetone [in urine]. Sampling time: at the end of the shift.</p>
Toluene	<p><b>5/2020. (II. 6.) ITM Decree (Hungary, 12/2022)</b>            BEI: 1 mg/g creatinine, o-cresol [in urine]. Sampling time: at the end of the shift.            BEI: 1 µmol/mmol creatinine, o-cresol [in urine]. Sampling time: at the end of the shift.</p>
Xylene	<p><b>5/2020. (II. 6.) ITM Decree (Hungary, 12/2022) [xylene]</b>            BEI: 1500 mg/g creatinine, methylhippuric acid [in urine].            Sampling time: at the end of the shift.            BEI: 860 µmol/mmol creatinine, methylhippuric acid [in urine].            Sampling time: at the end of the shift.</p>
Propan-2-ol	<p><b>5/2020. (II. 6.) ITM Decree (Hungary, 12/2022)</b>            BEI: 430 µmol/l, acetone [in urine]. Sampling time: at the end of the shift.            BEI: 25 mg/l, acetone [in urine]. Sampling time: at the end of the shift.</p>
Ethylbenzene	<p><b>5/2020. (II. 6.) ITM Decree (Hungary, 12/2022)</b>            BEI: 1500 mg/g creatinine, mandelic acid [in urine]. Sampling time: at the end of the working week; at the end of the shift.            BEI: 1110 µmol/mmol creatinine, mandelic acid [in urine].            Sampling time: at the end of the working week; at the end of the shift.</p>
No exposure indices known.	
acetone	<p><b>NAOSH (Ireland, 1/2011)</b>            BMGV: 50 mg/l, acetone [in urine]. Sampling time: end of shift - As soon as possible after exposure ceases.</p>
Toluene	<p><b>NAOSH (Ireland, 1/2011)</b>            BMGV: 0.3 mg/g creatinine, o-cresol [in urine]. Sampling time: end of shift - As soon as possible after exposure ceases.            BMGV: 0.03 mg/l, toluene [in urine]. Sampling time: end of shift - As soon as possible after exposure ceases.            BMGV: 0.02 mg/l, toluene [in blood]. Sampling time: prior to last shift of workweek.</p>
Xylene	<p><b>NAOSH (Ireland, 1/2011) [Xylene]</b>            BMGV: 1.5 g/g creatinine, methylhippuric acids [in urine].            Sampling time: end of shift - As soon as possible after exposure ceases.</p>
Propan-2-ol	<p><b>NAOSH (Ireland, 1/2011)</b>            BMGV: 40 mg/l, acetone [in urine]. Sampling time: end of shift at end of workweek.</p>
Ethylbenzene	<p><b>NAOSH (Ireland, 1/2011)</b>            BMGV: Semi-quantitative, the biological analyte is an indicator of exposure to the substance but the quantitative interpretation of the measurement is ambiguous. These analytes should be used as a screening test if a quantitative test is not practical; or as a confirmatory test if the quantitative test is not specific and the origin of the determinant is in question., ethylbenzene [in endexhaled air].            Sampling time: not critical.            BMGV: 0.7 g/g creatinine [Semi-quantitative, the biological analyte is an indicator of exposure to the substance but the quantitative interpretation of the measurement is ambiguous.            These analytes should be used as a screening test if a quantitative</p>

## SECTION 8: Exposure controls/personal protection

<p>No exposure indices known.</p>	<p>test is not practical; or as a confirmatory test if the quantitative test is not specific and the origin of the determinant is in question.], mandelic acid and phenylglyoxylic acid [in urine]. Sampling time: end of shift at end of workweek.</p>
<p>Toluene</p>	<p><b>Minister Cabinet Regulations No.325 - BEI (Latvia, 7/2018)</b>          BEI: 0.05 mg/l, toluene [in blood].          BEI: 1.6 g/g creatinine, hippuric acid [in urine]. Sampling time: end of the shift.</p>
<p>No exposure indices known.</p>	
<p>No exposure indices known.</p>	
<p>No exposure indices known.</p>	
<p>No exposure indices known.</p>	
<p>No exposure indices known.</p>	
<p>No exposure indices known.</p>	
<p>acetone</p>	<p><b>Portuguese Institute of Quality (Portugal, 11/2014)</b>          BEI: 50 mg/l, acetone [in urine]. Sampling time: end of shift.</p>
<p>Toluene</p>	<p><b>Portuguese Institute of Quality (Portugal, 11/2014)</b>          BEI: 0.3 mg/g creatinine, o-cresol [in urine]. Sampling time: end of shift.          BEI: 0.03 mg/l, toluene [in urine]. Sampling time: end of shift.          BEI: 0.02 mg/l, toluene [in blood]. Sampling time: end of shift at the end of the workweek.</p>
<p>Xylene</p>	<p><b>Portuguese Institute of Quality (Portugal, 11/2014) [Xylenes]</b>          BEI: 1.5 g/g creatinine, (o, m, p) -methyl-boronic acids [in urine]. Sampling time: end of shift.</p>
<p>Propan-2-ol</p>	<p><b>Portuguese Institute of Quality (Portugal, 11/2014)</b>          BEI: 40 mg/l, acetone [in urine]. Sampling time: end of shift at the end of the workweek.</p>
<p>Ethylbenzene</p>	<p><b>Portuguese Institute of Quality (Portugal, 11/2014)</b>          BEI: 0.7 g/g creatinine, sum of mandelic acid and phenylglyoxylic acid [in urine]. Sampling time: end of shift.</p>
<p>acetone</p>	<p><b>HG 1218/2006, Annex 2, with subsequent modifications and additions (Romania, 3/2020)</b>          OBLV: 50 mg/l, acetone [in urine]. Sampling time: end of shift.</p>
<p>Toluene</p>	<p><b>HG 1218/2006, Annex 2, with subsequent modifications and additions (Romania, 3/2020)</b>          OBLV: 3 mg/l, o-cresol [in urine]. Sampling time: end of shift.          OBLV: 2 g/l, hippuric acid [in urine]. Sampling time: end of shift.</p>
<p>Xylene</p>	<p><b>HG 1218/2006, Annex 2, with subsequent modifications and additions (Romania, 3/2020) [Xylene]</b>          OBLV: 3 g/l, methylhippuric acid [in urine]. Sampling time: end of shift.</p>
<p>Propan-2-ol</p>	<p><b>HG 1218/2006, Annex 2, with subsequent modifications and additions (Romania, 3/2020)</b>          OBLV: 50 mg/l, acetone [in urine]. Sampling time: end of shift.</p>
<p>Ethylbenzene</p>	<p><b>HG 1218/2006, Annex 2, with subsequent modifications and additions (Romania, 3/2020)</b>          OBLV: 1.5 g/g creatinine, mandelic acid [in urine]. Sampling time: end of the week.</p>

## SECTION 8: Exposure controls/personal protection

acetone

### Government regulation SR c. 355/2006 (Slovakia, 9/2020)

BLV: 103.9 µmol/mmol creatinine, acetone [in urine]. Sampling time: at the end of exposure or work shift.

BLV: 53.36 mg/g creatinine, acetone [in urine]. Sampling time: at the end of exposure or work shift.

BLV: 1378 µmol/l, acetone [in urine]. Sampling time: at the end of exposure or work shift.

BLV: 80 mg/l, acetone [in urine]. Sampling time: at the end of exposure or work shift.

Toluene

### Government regulation SR c. 355/2006 (Slovakia, 9/2020)

BLV: 1010 µmol/mmol creatinine, hippuric acid [in urine]. Sampling time: at the end of exposure or work shift.

BLV: 1.08 µmol/mmol creatinine, o-cresol [in urine]. Sampling time: at the end of exposure or work shift; long-term exposure: after several work shifts.

BLV: 1600 mg/g creatinine, hippuric acid [in urine]. Sampling time: at the end of exposure or work shift.

BLV: 1.03 mg/g creatinine, o-cresol [in urine]. Sampling time: at the end of exposure or work shift; long-term exposure: after several work shifts.

BLV: 13399 µmol/l, hippuric acid [in urine]. Sampling time: at the end of exposure or work shift.

BLV: 14.3 µmol/l, o-cresol [in urine]. Sampling time: at the end of exposure or work shift; long-term exposure: after several work shifts.

BLV: 6517 nmol/l, toluene [in blood]. Sampling time: at the end of exposure or work shift.

BLV: 2401 mg/l, hippuric acid [in urine]. Sampling time: at the end of exposure or work shift.

BLV: 1.5 mg/l, o-cresol [in urine]. Sampling time: at the end of exposure or work shift; long-term exposure: after several work shifts.

BLV: 600 µg/l, toluene [in blood]. Sampling time: at the end of exposure or work shift.

Xylene

### Government regulation SR c. 355/2006 (Slovakia, 9/2020) [xylene, all isomers]

BLV: 781 µmol/mmol creatinine, sum of 2,3,4-methylhippuroic acids [in urine]. Sampling time: at the end of exposure or work shift.

BLV: 1334 mg/g creatinine, sum of 2,3,4-methylhippuroic acids [in urine]. Sampling time: at the end of exposure or work shift.

BLV: 10355 µmol/l, sum of 2,3,4-methylhippuroic acids [in urine]. Sampling time: at the end of exposure or work shift.

BLV: 14.6 µmol/l, xylene [in blood]. Sampling time: at the end of exposure or work shift.

BLV: 2000 mg/l, sum of 2,3,4-methylhippuroic acids [in urine]. Sampling time: at the end of exposure or work shift.

BLV: 1.5 mg/l, xylene [in blood]. Sampling time: at the end of exposure or work shift.

Ethylbenzene

### Government regulation SR c. 355/2006 (Slovakia, 9/2020)

BLV: 799 µmol/mmol creatinine, mandelic acid and phenylglyoxylic acid [in urine]. Sampling time: at the end of exposure or work shift; long-term exposure: after several work shifts.

BLV: 7.44 µmol/mmol creatinine, 2 or 4-ethylfenol [in urine]. Sampling time: at the end of exposure or work shift; long-term exposure: after several work shifts.

BLV: 1067 mg/g creatinine, mandelic acid and phenylglyoxylic acid [in urine]. Sampling time: at the end of exposure or work shift; long-term exposure: after several work shifts.

BLV: 8.03 mg/g creatinine, 2 or 4-ethylfenol [in urine]. Sampling time: at the end of exposure or work shift; long-term exposure:

## SECTION 8: Exposure controls/personal protection

	<p>after several work shifts.            BLV: 10590 µmol/l, mandelic acid and phenylglyoxylic acid [in urine]. Sampling time: at the end of exposure or work shift; long-term exposure: after several work shifts.            BLV: 98.6 µmol/l, 2 or 4-ethylfenol [in urine]. Sampling time: at the end of exposure or work shift; long-term exposure: after several work shifts.            BLV: 1600 mg/l, mandelic acid and phenylglyoxylic acid [in urine]. Sampling time: at the end of exposure or work shift; long-term exposure: after several work shifts.            BLV: 12 mg/l, 2 or 4-ethylfenol [in urine]. Sampling time: at the end of exposure or work shift; long-term exposure: after several work shifts.</p>
acetone	<p><b>Regulation on protection of workers from the risks related to exposure to chemical substances at work (Slovenia, 5/2021)</b>            BAT: 80 mg/l, acetone [in urine]. Sampling time: at the end of the work shift.</p>
Toluene	<p><b>Regulation on protection of workers from the risks related to exposure to chemical substances at work (Slovenia, 5/2021)</b>            BAT: 1.5 mg/l, o-cresol (after hydrolysis) [in urine]. Sampling time: at the end of the work shift, at long-term exposure: at the end of the work shift after several consecutive workdays.            BAT: 600 µg/l, toluene [in blood]. Sampling time: immediately after exposure.            BAT: 75 µg/l, toluene [in urine]. Sampling time: at the end of the work shift.</p>
Xylene	<p><b>Regulation on protection of workers from the risks related to exposure to chemical substances at work (Slovenia, 5/2021) [xylene (all isomers)]</b>            BAT: 2 g/l, methylhippuric acid (all isomers) [in urine]. Sampling time: at the end of the work shift.</p>
Propan-2-ol	<p><b>Regulation on protection of workers from the risks related to exposure to chemical substances at work (Slovenia, 5/2021)</b>            BAT: 25 mg/l, acetone [in urine]. Sampling time: at the end of the work shift.            BAT: 25 mg/l, acetone [in blood]. Sampling time: at the end of the work shift.</p>
Ethylbenzene	<p><b>Regulation on protection of workers from the risks related to exposure to chemical substances at work (Slovenia, 5/2021)</b>            BAT: 250 mg/g creatinine, mandelic acid and phenylglyoxylic acid [in urine]. Sampling time: at the end of the work shift.</p>
acetone	<p><b>National institute of occupational safety and health (Spain, 4/2022)</b>            VLB: 50 mg/l, acetone [in urine]. Sampling time: end of shift.</p>
Toluene	<p><b>National institute of occupational safety and health (Spain, 4/2022)</b>            VLB: 0.05 mg/l, toluene [in blood]. Sampling time: prior to last shift of workweek.            VLB: 0.6 mg/g creatinine, o-cresol [in urine]. Sampling time: end of shift.            VLB: 0.08 mg/l, toluene [in urine]. Sampling time: end of shift.</p>
Xylene	<p><b>National institute of occupational safety and health (Spain, 4/2022) [Xylenes]</b>            VLB: 1 g/g creatinine, methylhippuric acids [in urine]. Sampling time: end of shift.</p>
Propan-2-ol	

## SECTION 8: Exposure controls/personal protection

<p>Ethylbenzene</p> <p>No exposure indices known.</p>	<p><b>National institute of occupational safety and health (Spain, 4/2022)</b> VLB: 40 mg/l, acetone [in urine]. Sampling time: end of workweek.</p> <p><b>National institute of occupational safety and health (Spain, 4/2022)</b> VLB: 700 mg/g creatinine, sum of mandelic acid and acid and phenylglyoxylic acid [in urine]. Sampling time: end of workweek.</p>
<p>acetone</p>	<p><b>SUVA (Switzerland, 1/2023)</b> BEI: 50 mg/l, acetone [in urine]. Sampling time: immediately after exposure or after working hours. BEI: 0.86 mmol/l, acetone [in urine]. Sampling time: immediately after exposure or after working hours.</p>
<p>Toluene</p>	<p><b>SUVA (Switzerland, 1/2023)</b> BEI: 2 g/g creatinine, hippuric acid [in urine]. Sampling time: immediately after exposure or after working hours. In case of long-term exposure: after more than one shift. BEI: 1.26 mmol/mmol creatinine, hippuric acid [in urine]. Sampling time: immediately after exposure or after working hours. In case of long-term exposure: after more than one shift. BEI: 0.5 mg/l, o-cresol [in urine]. Sampling time: immediately after exposure or after working hours. In case of long-term exposure: after more than one shift. BEI: 4.62 µmol/l, o-cresol [in urine]. Sampling time: immediately after exposure or after working hours. In case of long-term exposure: after more than one shift. BEI: 600 µg/l, toluene [in blood]. Sampling time: immediately after exposure or after working hours. BEI: 6.48 µmol/l, toluene [in blood]. Sampling time: immediately after exposure or after working hours. BEI: 75 µg/l, toluene [in urine]. Sampling time: immediately after exposure or after working hours.</p>
<p>Xylene</p>	<p><b>SUVA (Switzerland, 1/2023) [Xylene, all isomers]</b> BEI: 2 g/l, methyl hippuric acid [in urine]. Sampling time: immediately after exposure or after working hours.</p>
<p>Propan-2-ol</p>	<p><b>SUVA (Switzerland, 1/2023)</b> BEI: 0.4 mmol/l, acetone [in blood]. Sampling time: immediately after exposure or after working hours. BEI: 25 mg/l, acetone [in blood]. Sampling time: immediately after exposure or after working hours. BEI: 0.4 mmol/l, acetone [in urine]. Sampling time: immediately after exposure or after working hours. BEI: 25 mg/l, acetone [in urine]. Sampling time: immediately after exposure or after working hours.</p>
<p>Ethylbenzene</p>	<p><b>SUVA (Switzerland, 1/2023)</b> BEI: 600 mg/g creatinine, mandelic acid + phenylglyoxylic acid [in urine]. Sampling time: immediately after exposure or after working hours.</p>
<p>Xylene</p>	<p><b>EH40/2005 BMGVs (United Kingdom (UK), 8/2018) [Xylene, o-, m-, p- or mixed isomers]</b> BGV: 650 mmol/mol creatinine, methyl hippuric acid [in urine]. Sampling time: post shift.</p>



## SECTION 8: Exposure controls/personal protection

**Recommended monitoring procedures** : Reference should be made to monitoring standards, such as the following:  
 European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

### DNELs/DMELs

Product/ingredient name	Type	Exposure	Value	Population	Effects
n-Butyl acetate	DNEL	Short term Oral	2 mg/kg bw/day	General population	Systemic
	DNEL	Long term Oral	2 mg/kg bw/day	General population	Systemic
	DNEL	Short term Dermal	6 mg/kg bw/day	General population	Systemic
	DNEL	Short term Dermal	11 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	35.7 mg/m <sup>3</sup>	General population	Local
	DNEL	Short term Inhalation	300 mg/m <sup>3</sup>	General population	Local
	DNEL	Short term Inhalation	300 mg/m <sup>3</sup>	General population	Systemic
	DNEL	Long term Inhalation	300 mg/m <sup>3</sup>	Workers	Local
	DNEL	Short term Inhalation	600 mg/m <sup>3</sup>	Workers	Local
	DNEL	Short term Inhalation	600 mg/m <sup>3</sup>	Workers	Systemic
	DNEL	Long term Dermal	3.4 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	7 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	12 mg/m <sup>3</sup>	General population	Systemic
	DNEL	Long term Inhalation	48 mg/m <sup>3</sup>	Workers	Systemic
acetone	DNEL	Long term Oral	62 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	62 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	186 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	200 mg/m <sup>3</sup>	General population	Systemic
	DNEL	Long term Inhalation	1210 mg/m <sup>3</sup>	Workers	Systemic
	DNEL	Short term Inhalation	2420 mg/m <sup>3</sup>	Workers	Local
Toluene	DNEL	Long term Oral	8.13 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	56.5 mg/m <sup>3</sup>	General population	Local
	DNEL	Long term Inhalation	56.5 mg/m <sup>3</sup>	General population	Systemic
	DNEL	Long term Inhalation	192 mg/m <sup>3</sup>	Workers	Local
	DNEL	Long term Inhalation	192 mg/m <sup>3</sup>	Workers	Systemic
	DNEL	Long term Dermal	226 mg/kg bw/day	General population	Systemic

## SECTION 8: Exposure controls/personal protection

Xylene	DNEL	Short term Inhalation	226 mg/m <sup>3</sup>	General population	Local	
	DNEL	Short term Inhalation	226 mg/m <sup>3</sup>	General population	Systemic	
	DNEL	Long term Dermal	384 mg/kg bw/day	Workers	Systemic	
	DNEL	Short term Inhalation	384 mg/m <sup>3</sup>	Workers	Local	
	DNEL	Short term Inhalation	384 mg/m <sup>3</sup>	Workers	Systemic	
	DNEL	Long term Inhalation	65.3 mg/m <sup>3</sup>	General population	Local	
	DNEL	Short term Inhalation	260 mg/m <sup>3</sup>	General population	Local	
	DNEL	Short term Inhalation	260 mg/m <sup>3</sup>	General population	Systemic	
	DNEL	Long term Inhalation	221 mg/m <sup>3</sup>	Workers	Local	
	DNEL	Long term Oral	12.5 mg/kg bw/day	General population	Systemic	
	DNEL	Long term Inhalation	65.3 mg/m <sup>3</sup>	General population	Systemic	
	DNEL	Long term Dermal	125 mg/kg bw/day	General population	Systemic	
	DNEL	Long term Dermal	212 mg/kg bw/day	Workers	Systemic	
	DNEL	Long term Inhalation	221 mg/m <sup>3</sup>	Workers	Systemic	
	Ethyl acetate	DNEL	Short term Inhalation	442 mg/m <sup>3</sup>	Workers	Local
DNEL		Short term Inhalation	442 mg/m <sup>3</sup>	Workers	Systemic	
DNEL		Long term Oral	4.5 mg/kg bw/day	General population	Systemic	
DNEL		Long term Dermal	37 mg/kg bw/day	General population	Systemic	
DNEL		Long term Dermal	63 mg/kg bw/day	Workers	Systemic	
DNEL		Long term Inhalation	367 mg/m <sup>3</sup>	General population	Local	
DNEL		Long term Inhalation	367 mg/m <sup>3</sup>	General population	Systemic	
DNEL		Short term Inhalation	734 mg/m <sup>3</sup>	General population	Local	
DNEL		Short term Inhalation	734 mg/m <sup>3</sup>	General population	Systemic	
DNEL		Long term Inhalation	734 mg/m <sup>3</sup>	Workers	Local	
DNEL		Long term Inhalation	734 mg/m <sup>3</sup>	Workers	Systemic	
DNEL		Short term Inhalation	1468 mg/m <sup>3</sup>	Workers	Local	
DNEL		Short term Inhalation	1468 mg/m <sup>3</sup>	Workers	Systemic	
iso-butanol		DNEL	Long term Inhalation	55 mg/m <sup>3</sup>	General population	Local
		DNEL	Long term Inhalation	310 mg/m <sup>3</sup>	Workers	Local
2-Methoxy-1-methylethyl acetate	DNEL	Long term Inhalation	33 mg/m <sup>3</sup>	General population	Local	
	DNEL	Long term Inhalation	33 mg/m <sup>3</sup>	General population	Systemic	
	DNEL	Long term Oral	36 mg/kg bw/day	General population	Systemic	
	DNEL	Long term Inhalation	275 mg/m <sup>3</sup>	Workers	Systemic	

## SECTION 8: Exposure controls/personal protection

Propan-2-ol	DNEL	Long term Dermal	320 mg/kg bw/day	General population	Systemic
	DNEL	Short term Inhalation	550 mg/m <sup>3</sup>	Workers	Local
	DNEL	Long term Dermal	796 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Oral	26 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	89 mg/m <sup>3</sup>	General population	Systemic
	DNEL	Long term Dermal	319 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	500 mg/m <sup>3</sup>	Workers	Systemic
	DNEL	Long term Dermal	888 mg/kg bw/day	Workers	Systemic
Ethylbenzene	DNEL	Long term Oral	1.6 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	15 mg/m <sup>3</sup>	General population	Systemic
	DNEL	Long term Inhalation	77 mg/m <sup>3</sup>	Workers	Systemic
	DNEL	Long term Dermal	180 mg/kg bw/day	Workers	Systemic
1-Ethoxy-2-propanol	DNEL	Short term Inhalation	293 mg/m <sup>3</sup>	Workers	Local
	DMEL	Long term Inhalation	442 mg/m <sup>3</sup>	Workers	Local
	DMEL	Short term Inhalation	884 mg/m <sup>3</sup>	Workers	Systemic
	DNEL	Long term Inhalation	106 mg/m <sup>3</sup>	Workers	Systemic
	DNEL	Long term Oral	14 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	44.3 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	74 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	127 mg/m <sup>3</sup>	General population	Systemic
DNEL	Short term Inhalation	300 mg/m <sup>3</sup>	General population	Systemic	
DNEL	Short term Inhalation	500 mg/m <sup>3</sup>	Workers	Systemic	

### PNECs

No PNECs available

## 8.2 Exposure controls

### **Appropriate engineering controls**

: Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

### **Individual protection measures**

#### **Hygiene measures**

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

## SECTION 8: Exposure controls/personal protection

- Eye/face protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/or face shield. If inhalation hazards exist, a full-face respirator may be required instead.
- Skin protection**
- Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
- Recommendations : Wear suitable gloves tested to EN374.
- < 1 hour (breakthrough time): Nitrile gloves. thickness > 0.3 mm
- 1 - 4 hours (breakthrough time): 4H / Silver Shield® gloves.
- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves. Refer to European Standard EN 1149 for further information on material and design requirements and test methods.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.
- Filter type: A
- Filter type (spray application): A P
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

## SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

### 9.1 Information on basic physical and chemical properties

#### Appearance

- Physical state** : Liquid.
- Colour** : Various
- Odour** : Slight
- Odour threshold** : Not available.
- Melting point/freezing point** : Not available.
- Initial boiling point and boiling range** :

Ingredient name	°C	°F	Method
acetone	56.05	132.9	
Ethyl acetate	77.1	170.8	

- Flammability** : Not available.
- Lower and upper explosion limit** : Lower: 0.8%  
Upper: 13%

## SECTION 9: Physical and chemical properties

**Flash point** : Closed cup: -19°C (-2.2°F)

**Auto-ignition temperature** :

Ingredient name	°C	°F	Method
1-Ethoxy-2-propanol	255	491	
2-Methoxy-1-methylethyl acetate	333	631.4	DIN 51794

**Decomposition temperature** : Not available.

**pH** : Not applicable.

**Viscosity** : Not available.

**Solubility(ies)** :

Not available.

**Solubility in water** : Not available.

**Partition coefficient: n-octanol/ water** : Not applicable.

**Vapour pressure** :

Ingredient name	Vapour Pressure at 20°C			Vapour pressure at 50°C		
	mm Hg	kPa	Method	mm Hg	kPa	Method
acetone	180.01463	24				
Ethyl acetate	81.59163	10.9				

**Relative density** : Not available.

**Density** : 1.1 g/cm<sup>3</sup>

**Vapour density** : Not available.

**Explosive properties** : Not available.

**Oxidising properties** : Not available.

### Particle characteristics

**Median particle size** : Not applicable.

## SECTION 10: Stability and reactivity

**10.1 Reactivity** : No specific test data related to reactivity available for this product or its ingredients.

**10.2 Chemical stability** : The product is stable.

**10.3 Possibility of hazardous reactions** : Under normal conditions of storage and use, hazardous reactions will not occur.

**10.4 Conditions to avoid** : Avoid all possible sources of ignition (spark or flame). Do not pressurise, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.

**10.5 Incompatible materials** : Reactive or incompatible with the following materials:  
oxidising materials

**10.6 Hazardous decomposition products** : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
n-Butyl acetate	LC50 Inhalation Vapour	Rat	0.74 mg/l	4 hours
	LD50 Dermal	Rabbit	14112 mg/kg	-
acetone	LD50 Oral	Rat	10760 mg/kg	-
	LD50 Oral	Rat	5800 mg/kg	-
Toluene	LC50 Inhalation Vapour	Rat	49 g/m <sup>3</sup>	4 hours
	LD50 Oral	Rat	636 mg/kg	-
Xylene	LC50 Inhalation Vapour	Rat	21.7 mg/l	4 hours
	LD50 Oral	Rat	4300 mg/kg	-
Ethyl acetate	LD50 Oral	Rat	5620 mg/kg	-
	LD50 Oral	Rat	5620 mg/kg	-
iso-butanol	LC50 Inhalation Vapour	Rat	19200 mg/m <sup>3</sup>	4 hours
	LD50 Dermal	Rabbit	3400 mg/kg	-
2-Methoxy-1-methylethyl acetate	LD50 Oral	Rat	2460 mg/kg	-
	LD50 Dermal	Rabbit	>5 g/kg	-
Propan-2-ol	LD50 Oral	Rat	8532 mg/kg	-
	LD50 Dermal	Rabbit	12800 mg/kg	-
Ethylbenzene	LD50 Oral	Rat	5000 mg/kg	-
	LC50 Inhalation Dusts and mists	Rat	29000 mg/l	4 hours
1-Ethoxy-2-propanol	LD50 Dermal	Rabbit	15400 mg/kg	-
	LD50 Oral	Rat	3500 mg/kg	-
1-Ethoxy-2-propanol	LD50 Dermal	Rabbit	8100 mg/kg	-
	LD50 Oral	Rat	4400 mg/kg	-

**Conclusion/Summary** : Based on available data, the classification criteria are not met.

#### Acute toxicity estimates

Route	ATE value
Dermal	17521.95 mg/kg
Inhalation (vapours)	140.6 mg/l

#### Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
titanium dioxide	Skin - Mild irritant	Human	-	72 hours 300 ug l	-
n-Butyl acetate	Eyes - Moderate irritant	Rabbit	-	100 mg	-
	Skin - Moderate irritant	Rabbit	-	24 hours 500 mg	-
acetone	Eyes - Mild irritant	Human	-	186300 ppm	-
	Eyes - Mild irritant	Rabbit	-	10 uL	-
	Eyes - Moderate irritant	Rabbit	-	24 hours 20 mg	-
Toluene	Eyes - Severe irritant	Rabbit	-	20 mg	-
	Skin - Mild irritant	Rabbit	-	395 mg	-
	Skin - Mild irritant	Rabbit	-	24 hours 500 mg	-
Xylene	Eyes - Mild irritant	Rabbit	-	0.5 minutes 100 mg	-
	Eyes - Mild irritant	Rabbit	-	870 ug	-
	Eyes - Severe irritant	Rabbit	-	24 hours 2 mg	-
Xylene	Skin - Mild irritant	Pig	-	24 hours 250 uL	-
	Skin - Mild irritant	Rabbit	-	435 mg	-
	Skin - Moderate irritant	Rabbit	-	24 hours 20 mg	-
Xylene	Skin - Moderate irritant	Rabbit	-	500 mg	-
	Eyes - Mild irritant	Rabbit	-	87 mg	-
	Eyes - Severe irritant	Rabbit	-	24 hours 5 mg	-

## SECTION 11: Toxicological information

Propan-2-ol	Skin - Mild irritant	Rat	-	8 hours 60 uL	-
	Skin - Moderate irritant	Rabbit	-	100 %	-
	Skin - Moderate irritant	Rabbit	-	24 hours 500 mg	-
Ethylbenzene	Eyes - Moderate irritant	Rabbit	-	10 mg	-
	Eyes - Moderate irritant	Rabbit	-	24 hours 100 mg	-
	Eyes - Severe irritant	Rabbit	-	100 mg	-
1-Ethoxy-2-propanol	Skin - Mild irritant	Rabbit	-	500 mg	-
	Eyes - Severe irritant	Rabbit	-	500 mg	-
	Skin - Mild irritant	Rabbit	-	24 hours 15 mg	-
	Eyes - Moderate irritant	Rabbit	-	24 hours 100 mg	-

**Conclusion/Summary** : Causes skin irritation.

### Sensitisation

**Conclusion/Summary** : Based on available data, the classification criteria are not met.

### Mutagenicity

**Conclusion/Summary** : Based on available data, the classification criteria are not met.

### Carcinogenicity

It has been observed that the carcinogenic hazard of this product arises when respirable dust is inhaled in quantities leading to significant impairment of particle clearance mechanisms in the lung.

**Conclusion/Summary** : Based on available data, the classification criteria are not met.

### Reproductive toxicity

**Conclusion/Summary** : Based on available data, the classification criteria are not met.

### Teratogenicity

**Conclusion/Summary** : Suspected of damaging the unborn child.

### Specific target organ toxicity (single exposure)

Product/ingredient name	Category	Route of exposure	Target organs
n-Butyl acetate	Category 3	-	Narcotic effects
acetone	Category 3	-	Narcotic effects
Toluene	Category 3	-	Narcotic effects
Xylene	Category 3	-	Respiratory tract irritation
Ethyl acetate	Category 3	-	Narcotic effects
iso-butanol	Category 3	-	Respiratory tract irritation
Propan-2-ol	Category 3	-	Narcotic effects
1-Ethoxy-2-propanol	Category 3	-	Narcotic effects

### Specific target organ toxicity (repeated exposure)

Product/ingredient name	Category	Route of exposure	Target organs
Toluene	Category 2	-	-
Xylene	Category 2	oral, inhalation	-
Ethylbenzene	Category 2	oral, inhalation	hearing organs

### Aspiration hazard

Product/ingredient name	Result
Toluene	ASPIRATION HAZARD - Category 1
Xylene	ASPIRATION HAZARD - Category 1
Ethylbenzene	ASPIRATION HAZARD - Category 1

**Information on likely routes of exposure** : Not available.

### Potential acute health effects

## SECTION 11: Toxicological information

<b>Eye contact</b>	: Causes serious eye damage.
<b>Inhalation</b>	: Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness.
<b>Skin contact</b>	: Causes skin irritation.
<b>Ingestion</b>	: Can cause central nervous system (CNS) depression.

### Symptoms related to the physical, chemical and toxicological characteristics

<b>Eye contact</b>	: Adverse symptoms may include the following: pain watering redness
<b>Inhalation</b>	: Adverse symptoms may include the following: nausea or vomiting headache drowsiness/fatigue dizziness/vertigo unconsciousness reduced foetal weight increase in foetal deaths skeletal malformations
<b>Skin contact</b>	: Adverse symptoms may include the following: pain or irritation redness blistering may occur reduced foetal weight increase in foetal deaths skeletal malformations
<b>Ingestion</b>	: Adverse symptoms may include the following: stomach pains reduced foetal weight increase in foetal deaths skeletal malformations

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

#### Short term exposure

<b>Potential immediate effects</b>	: Not available.
<b>Potential delayed effects</b>	: Not available.

#### Long term exposure

<b>Potential immediate effects</b>	: Not available.
<b>Potential delayed effects</b>	: Not available.

#### Potential chronic health effects

Not available.

<b>Conclusion/Summary</b>	: Not available.
<b>General</b>	: No known significant effects or critical hazards.
<b>Carcinogenicity</b>	: No known significant effects or critical hazards.
<b>Mutagenicity</b>	: No known significant effects or critical hazards.
<b>Reproductive toxicity</b>	: Suspected of damaging the unborn child.

### 11.2 Information on other hazards

#### 11.2.1 Endocrine disrupting properties

Not available.

#### 11.2.2 Other information

Not available.



## SECTION 12: Ecological information

### 12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
Titanium dioxide	Acute LC50 3 mg/l Fresh water	Crustaceans - <i>Ceriodaphnia dubia</i> - Neonate	48 hours
	Acute LC50 6.5 mg/l Fresh water	Daphnia - <i>Daphnia pulex</i> - Neonate	48 hours
	Acute LC50 >1000000 µg/l Marine water	Fish - <i>Fundulus heteroclitus</i>	96 hours
n-Butyl acetate	Acute LC50 32 mg/l Marine water	Crustaceans - <i>Artemia salina</i>	48 hours
	Acute LC50 18000 µg/l Fresh water	Fish - <i>Pimephales promelas</i>	96 hours
	Acute EC50 20.565 mg/l Marine water	Algae - <i>Ulva pertusa</i>	96 hours
	Acute LC50 6000000 µg/l Fresh water	Crustaceans - <i>Gammarus pulex</i>	48 hours
	Acute LC50 10000 µg/l Fresh water	Daphnia - <i>Daphnia magna</i>	48 hours
	Acute LC50 5600 ppm Fresh water	Fish - <i>Poecilia reticulata</i>	96 hours
	Chronic NOEC 4.95 mg/l Marine water	Algae - <i>Ulva pertusa</i>	96 hours
	Chronic NOEC 0.016 ml/L Fresh water	Crustaceans - <i>Daphniidae</i>	21 days
Toluene	Chronic NOEC 0.1 ml/L Fresh water	Daphnia - <i>Daphnia magna</i> - Neonate	21 days
	Chronic NOEC 5 µg/l Marine water	Fish - <i>Gasterosteus aculeatus</i> - Larvae	42 days
	Acute EC50 12500 µg/l Fresh water	Algae - <i>Pseudokirchneriella subcapitata</i>	72 hours
	Acute EC50 11600 µg/l Fresh water	Crustaceans - <i>Gammarus pseudolimnaeus</i> - Adult	48 hours
Ethyl acetate	Acute EC50 5.56 mg/l Fresh water	Daphnia - <i>Daphnia magna</i> - Neonate	48 hours
	Acute LC50 5500 µg/l Fresh water	Fish - <i>Oncorhynchus kisutch</i> - Fry	96 hours
	Chronic NOEC 1000 µg/l Fresh water	Daphnia - <i>Daphnia magna</i>	21 days
	Acute EC50 2500000 µg/l Fresh water	Algae - <i>Selenastrum sp.</i>	96 hours
	Acute LC50 750000 µg/l Fresh water	Crustaceans - <i>Gammarus pulex</i>	48 hours
	Acute LC50 154000 µg/l Fresh water	Daphnia - <i>Daphnia cucullata</i>	48 hours
	Acute LC50 212500 µg/l Fresh water	Fish - <i>Heteropneustes fossilis</i>	96 hours
iso-butanol	Chronic NOEC 12 mg/l Fresh water	Daphnia - <i>Daphnia magna</i>	21 days
	Chronic NOEC 75.6 mg/l Fresh water	Fish - <i>Pimephales promelas</i> - Embryo	32 days
Propan-2-ol	Acute LC50 600 mg/l Marine water	Crustaceans - <i>Artemia salina</i>	48 hours
	Acute LC50 1030000 µg/l Fresh water	Daphnia - <i>Daphnia magna</i> - Neonate	48 hours
Propan-2-ol	Acute LC50 1330000 µg/l Fresh water	Fish - <i>Oncorhynchus mykiss</i>	96 hours
	Acute EC50 10100 mg/l Fresh water	Daphnia - <i>Daphnia magna</i>	48 hours
	Acute LC50 1400000 µg/l Marine water	Crustaceans - <i>Crangon crangon</i>	48 hours
Propan-2-ol	Acute LC50 4200000 µg/l Fresh water	Fish - <i>Rasbora heteromorpha</i>	96 hours

**Conclusion/Summary** : Based on available data, the classification criteria are not met.

### 12.2 Persistence and degradability

Product/ingredient name	Test	Result	Dose	Inoculum
iso-butanol	-	74 % - Readily - 28 days	-	-

**Conclusion/Summary** : This product has not been tested for biodegradation.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
iso-butanol	-	-	Readily

### 12.3 Bioaccumulative potential

## SECTION 12: Ecological information

Product/ingredient name	LogP <sub>ow</sub>	BCF	Potential
n-Butyl acetate	2.3	-	Low
acetone	-0.23	-	Low
Toluene	2.73	90	Low
Xylene	3.12	8.1 to 25.9	Low
Ethyl acetate	0.68	30	Low
iso-butanol	1	-	Low
2-Methoxy-1-methylethyl acetate	1.2	-	Low
Propan-2-ol	0.05	-	Low
Ethylbenzene	3.6	-	Low
1-Ethoxy-2-propanol	<1	-	Low

### 12.4 Mobility in soil

**Soil/water partition coefficient (K<sub>oc</sub>)** : Not available.

**Mobility** : Not available.

### 12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

### 12.6 Endocrine disrupting properties

Not available.

### 12.7 Other adverse effects

No known significant effects or critical hazards.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

#### Product

**Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

**Hazardous waste** : The classification of the product may meet the criteria for a hazardous waste.






**European waste catalogue (EWC)** : 08.01.11

#### Packaging

**Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

**Special precautions** : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapour from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

## SECTION 14: Transport information

	ADR/RID	ADN	IMDG	IATA
14.1 UN number or ID number	UN1993	UN1993	UN1993	UN1993
14.2 UN proper shipping name	FLAMMABLE LIQUID, N.O.S. (n-butyl acetate, acetone)	FLAMMABLE LIQUID, N.O.S. (n-butyl acetate, acetone)	FLAMMABLE LIQUID, N.O.S. (xylene, ethyl acetate)	FLAMMABLE LIQUID, N.O.S. (xylene, ethyl acetate)
14.3 Transport hazard class(es)	3 	3 	3  	3 
14.4 Packing group	II	II	II	II
14.5 Environmental hazards	No.	Yes.	Yes.	Yes. The environmentally hazardous substance mark is not required.

### Additional information

- ADR/RID** : **Special provisions** 640 (C)  
**Tunnel code** (D/E)
- ADN** : The product is only regulated as an environmentally hazardous substance when transported in tank vessels.  
**Special provisions** 640 (C)
- IMDG** : The marine pollutant mark is not required when transported in sizes of ≤5 L or ≤5 kg.
- IATA** : The environmentally hazardous substance mark may appear if required by other transportation regulations.

**14.6 Special precautions for user** : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

**14.7 Maritime transport in bulk according to IMO instruments** : Not relevant/applicable due to nature of the product.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### EU Regulation (EC) No. 1907/2006 (REACH)

##### Annex XIV - List of substances subject to authorisation

###### Annex XIV

None of the components are listed.

###### Substances of very high concern

None of the components are listed.

##### Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Product/ingredient name	%	Designation [Usage]
OWECCELL 2110-60	≥90	3
Toluene	<10	48

**Labelling** :

#### Other EU regulations

## SECTION 15: Regulatory information

**Industrial emissions (integrated pollution prevention and control) - Air** : Listed

**Industrial emissions (integrated pollution prevention and control) - Water** : Not listed

**Explosive precursors** : Not applicable.

### Ozone depleting substances (1005/2009/EU)

Not listed.

### Prior Informed Consent (PIC) (649/2012/EU)

Not listed.

### Persistent Organic Pollutants

Not listed.

### Seveso Directive

This product is controlled under the Seveso Directive.

#### Danger criteria

Category
P5c

### National regulations

#### Austria

**VbF class** : A I  
Very dangerous flammable liquid.

**Limitation of the use of organic solvents** : Permitted.

#### Czech Republic

**Storage code** : I

#### Denmark

**Danish fire class** : I-1

### Executive Order No. 1795/2015

Ingredient name	Annex I Section A	Annex I Section B
titanium dioxide	Listed	-
Propan-2-ol	Listed	-
Ethylbenzene	Listed	-

**MAL-code** : 4-3

**Protection based on MAL** : According to the regulations on work involving coded products, the following stipulations apply to the use of personal protective equipment:

**General:** Gloves must be worn for all work that may result in soiling. Apron/coveralls/protective clothing must be worn when soiling is so great that regular work clothes do not adequately protect skin against contact with the product. A face shield must be worn in work involving spattering if a full mask is not required. In this case, other recommended use of eye protection is not required.

In all spraying operations in which there is return spray, respiratory protection with air supply and arm protectors/apron/coveralls/protective clothing must be worn as appropriate or as instructed.

## SECTION 15: Regulatory information

MAL-code: 4-3

**Application:** When spraying in new\* booths if the operator is outside the spray zone. When using scraper or knife, brush, roller, etc. for pre- and post-treatments outside a closed facility, spray booth or spray cabin.

- Air-supplied half mask and eye protection must be worn.

When using scraper or knife, brush, roller, etc. for pre- and post-treatments in cabins or booths of the existing\* facility type, if the operator is inside the spray zone.

- Air-supplied half mask, coveralls and eye protection must be worn.

During downtimes, cleaning and repair in closed facilities, spray booths or cabins, if there is a risk of contact with wet paint or organic solvents.

- Air-supplied full mask and coveralls must be worn.

When spraying in existing\* spray booths, if the operator is outside the spray zone.

- Air-supplied full mask, arm protectors and apron must be worn.

During non-atomising spraying in existing\* facilities of the combined-cabin, spray-cabin and spray-booth type where the operator is working inside the spray zone.

- Air-supplied full mask must be worn.

During all spraying where atomisation occurs in cabins or spray booths where the operator is inside the spray zone and during spraying outside a closed facility, cabin or booth.

- Air-supplied full mask, coveralls and hood must be worn.

**Drying:** Items for drying/drying ovens that are temporarily placed on such things as rack trolleys, etc. must be equipped with a mechanical exhaust system to prevent fumes from wet items from passing through workers' inhalation zone.

**Polishing:** When polishing treated surfaces, a mask with dust filter must be worn. When machine grinding, eye protection must be worn. Work gloves must always be worn.

**Caution** The regulations contain other stipulations in addition to the above.

\*See Regulations.

- Low-boiling liquids** : This product contains low-boiling point liquids. Any respiratory protective equipment should be air-fed.
- Restrictions on use** : Not to be used by professional users below 18 years of age. See the National Working Environment Authorities Executive Order regarding Young People At Work.
- List of undesirable substances** : Listed
- Carcinogenic waste** : Waste containers must be labeled: Contains a substance or substances regulated by Danish working environment legislation on cancer risks.

### Finland

### France

<b>Social Security Code, Articles L 461-1 to L 461-7</b>	:	n-Butyl acetate	RG 84
		acetone	RG 84
		Toluene	RG 4bis, RG 84
		Xylene	RG 4bis, RG 84
		Ethyl acetate	RG 84
		iso-butanol	RG 84
		2-Methoxy-1-methylethyl acetate	RG 84

## SECTION 15: Regulatory information

Propan-2-ol  
Ethylbenzene

RG 84  
RG 84

**Reinforced medical surveillance** : Act of July 11, 1977 determining the list of activities which require reinforced medical surveillance: not applicable

### Germany

**Storage class (TRGS 510)** : 3

### Hazardous incident ordinance

This product is controlled under the Germany Hazardous Incident Ordinance.

### Danger criteria

Category	Reference number
P5c	1.2.5.3

**Hazard class for water** : 3

**Technical instruction on air quality control** : TA-Luft Number 5.2.5: 51.2%  
TA-Luft Class I - Number 5.2.5: 8.3%

### Italy

**D.Lgs. 152/06** : Not determined.

### Netherlands

**Ministry of Social Affairs and Employment (SZW) - Carcinogenic substances and processes, mutagenic or reprotoxic substances**

Ingredient name	Carcinogen	Mutagen	Reproductive toxicity - Fertility	Reproductive toxicity - Development	Harmful via breastfeeding
tolueen	-	-	-	Development 2	-
xylene	-	-	-	Development 2	-

**Water Discharge Policy (ABM)** : A(1) Highly toxic for aquatic organisms, may have long-term hazardous effects in aquatic environment. Decontamination effort: A

### Norway

### Sweden

**Flammable liquid class (SRVFS 2005:10)** : 1

### Switzerland

**VOC content** : VOC (w/w): 58.7%

### International regulations

#### Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

#### Montreal Protocol

Not listed.

#### Stockholm Convention on Persistent Organic Pollutants

Not listed.

#### Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

#### UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

**15.2 Chemical safety assessment** : This product contains substances for which Chemical Safety Assessments are still required.

## SECTION 16: Other information

✔ Indicates information that has changed from previously issued version.

### Abbreviations and acronyms

: ATE = Acute Toxicity Estimate  
CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]  
DMEL = Derived Minimal Effect Level  
DNEL = Derived No Effect Level  
EUH statement = CLP-specific Hazard statement  
N/A = Not available  
PBT = Persistent, Bioaccumulative and Toxic  
PNEC = Predicted No Effect Concentration  
RRN = REACH Registration Number  
SGG = Segregation Group  
vPvB = Very Persistent and Very Bioaccumulative

### Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Flam. Liq. 2, H225 Skin Irrit. 2, H315 Eye Dam. 1, H318 Repr. 2, H361d STOT SE 3, H336	On basis of test data Calculation method Calculation method Calculation method Calculation method

### Full text of abbreviated H statements

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer.
H361d	Suspected of damaging the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.
EUH066	Repeated exposure may cause skin dryness or cracking.

### Full text of classifications [CLP/GHS]

Acute Tox. 4	ACUTE TOXICITY - Category 4
Asp. Tox. 1	ASPIRATION HAZARD - Category 1
Carc. 2	CARCINOGENICITY - Category 2
Eye Dam. 1	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1
Eye Irrit. 2	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2
Flam. Liq. 2	FLAMMABLE LIQUIDS - Category 2
Flam. Liq. 3	FLAMMABLE LIQUIDS - Category 3
Repr. 2	REPRODUCTIVE TOXICITY - Category 2
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2
STOT RE 2	SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 2
STOT SE 3	SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3

**Date of issue/ Date of revision** : 09/01/2024

**Date of previous issue** : 09/01/2024

**Version** : 1.01

OWECELL 2110-60

All variants

### Notice to reader

**Date of issue/Date of revision** : 09/01/2024 **Date of previous issue** : 09/01/2024 **Version** : 1.01 55/57

OWECELL 2110-60 - All variants

**Label No** :52118

## SECTION 16: Other information

The information in this SDS is based on the present state of our knowledge and on current laws. The product is not to be used for purposes other than those specified under section 1 without first obtaining written handling instructions. It is always the responsibility of the user to take all necessary steps to fulfil the demands set out in the local rules and legislation. The information in this SDS is meant to be a description of the safety requirements for our product. It is not to be considered a guarantee of the product's properties.



