Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2020/878 - Malta

SAFETY DATA SHEET



PLATIN ANTIGLISS 4546-15 - All variants

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

Product name

: PLATIN ANTIGLISS 4546-15 - All variants

1.2 Relevant identified uses of the substance or mixture and uses advised againstProduct use: Paint.

1.3 Details of the supplier of the safety data sheet

Teknos Group Oy, Takkatie 3, FI-00370 HELSINKI, FINLAND. Tel. +358 9 506 091. e-mail address of person : Prod-safe@teknos.com

responsible for this SDS

National contact

Teknos Group Oy, Takkatie 3, FI-00370 HELSINKI, FINLAND. Tel. +358 9 506 091.

1.4 Emergency telephone number

National advisory body/Poison Centre

 Telephone number
 : Malta Competition and Consumer Affairs Authority (MCCAA): +356 2395 2000

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture <u>Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]</u> Not classified.

The product is not classified as hazardous according to Regulation (EC) 1272/2008 as amended. See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements Signal word : No signal word. **Hazard statements** : No known significant effects or critical hazards. **Precautionary statements Prevention** : Not applicable. Response : Not applicable. **Storage** : Not applicable. **Disposal** : Not applicable. **Supplemental label** : Contains 1,2-benzisothiazol-3(2H)-one and reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. elements 220-239-6] (3:1). May produce an allergic reaction. Safety data sheet available on request. **Annex XVII - Restrictions** ŝ on the manufacture, placing on the market and use of certain dangerous

2.3 Other hazards

articles

substances, mixtures and

 Date of issue/Date of revision
 : 14/01/2025
 Date of previous issue
 : No previous validation
 Version
 : 1
 1/17

 PLATIN ANTIGLISS 4546-15 - All variants
 Label No :38817

SECTION 2: Hazards identification

Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII : This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

Other hazards which do : None known. not result in classification

SECTION 3: Composition/information on ingredients

3.2 Mixtures	: Mixture				
Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Туре
2-(2-butoxyethoxy)ethanol	REACH #: 01-2119475104-44 EC: 203-961-6 CAS: 112-34-5 Index: 603-096-00-8	≤3	Eye Irrit. 2, H319	-	[1] [2]
2-Butoxyethanol	REACH #: 01-2119475108-36 EC: 203-905-0 CAS: 111-76-2 Index: 603-014-00-0	≤3	Acute Tox. 4, H302 Acute Tox. 3, H331 Skin Irrit. 2, H315 Eye Irrit. 2, H319	ATE [Oral] = 1200 mg/kg ATE [Inhalation (vapours)] = 3 mg/l	[1] [2]
1,2-benzisothiazol-3(2H)- one	EC: 220-120-9 CAS: 2634-33-5 Index: 613-088-00-6	<0.05	Acute Tox. 4, H302 Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Acute 1, H400	ATE [Oral] = 1020 mg/kg Skin Sens. 1, H317: C ≥ 0.05% M [Acute] = 1	[1]
reaction mass of: 5-chloro- 2-methyl-4-isothiazolin- 3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol- 3-one [EC no. 220-239-6] (3:1)	CAS: 55965-84-9 Index: 613-167-00-5	<0.0015	Acute Tox. 3, H301 Acute Tox. 2, H310 Acute Tox. 2, H330 Skin Corr. 1C, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 EUH071	ATE [Oral] = 53 mg/ kg ATE [Dermal] = 50 mg/kg ATE [Inhalation (vapours)] = 0.5 mg/l Skin Corr. 1C, H314: $C \ge 0.6\%$ Eye Dam. 1, H318: $C \ge 0.6\%$ Eye Irrit. 2, H319: $0.06\% \le C < 0.6\%$ Skin Sens. 1, H317: $C \ge 0.0015\%$ M [Acute] = 100 M [Chronic] = 100	[1]
			See Section 16 for the full text of the H statements declared above.		

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Туре

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures			
Eye contact	: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Get medical attention if irritation occurs.		
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical attention if symptoms occur. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.		
Skin contact	 Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur. 		
Ingestion	: Wash out mouth with water. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Do not induce vomiting unless directed to do so by medical personnel. Get medical attention if symptoms occur.		
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training.		

Over-exposure signs/symptoms			
Eye contact	: No specific data.		
Inhalation	: No specific data.		
Skin contact	: No specific data.		
Ingestion	: No specific data.		

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician	: In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Specific treatments	: No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media			
Suitable extinguishing media	1	Use an extinguishing agent suitable for the surrounding fire.	
Unsuitable extinguishing media	:	None known.	
5.2 Special hazards arising f	rom	the substance or mixture	
Hazards from the substance or mixture	-	In a fire or if heated, a pressure increase will occur and the container may burst.	
Hazardous combustion products	:	Decomposition products may include the following materials: carbon dioxide carbon monoxide nitrogen oxides metal oxide/oxides	
5.3 Advice for firefighters			
Special protective actions for fire-fighters	-	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.	
Special protective equipment for fire-fighters	:	Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.	

SECTION 6: Accidental release measures

6.1 Personal precautions, pro	tective equipment and emergency procedures
For non-emergency personnel	: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Put on appropriate personal protective equipment.
For emergency responders	: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
6.2 Environmental precautions	: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
6.3 Methods and material for	containment and cleaning up
Small spill	: Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	: Stop leak if without risk. Move containers from spill area. Prevent entry into sewers water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Dispose of via a licensed waste disposal contractor. Contain and collect spillage with non-combustible, absorbent material e. g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.
6.4 Reference to other sections	: See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8).
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)

available.
a

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

8.1 Control parameters

Occupational exposure limits

Product/ingredient name	Exposure limit values
2-(2-butoxyethoxy)ethanol	EU OEL (Europe, 1/2022) TWA 8 hours: 67.5 mg/m ³ . TWA 8 hours: 10 ppm. STEL 15 minutes: 101.2 mg/m ³ . STEL 15 minutes: 15 ppm.
2-Butoxyethanol	EU OEL (Europe, 1/2022) Absorbed through skin. TWA 8 hours: 20 ppm. TWA 8 hours: 98 mg/m ³ . STEL 15 minutes: 50 ppm. STEL 15 minutes: 246 mg/m ³ .

		STEL 15 minutes. 240 mg/m .
Biological exposure indices		
Product/ingredient name		Exposure indices
No exposure indices known.		
Recommended monitoring procedures	: Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.	
DNELs/DMELs		
Product/ingredient name		Result
2-(2-butoxyethoxy)ethanol		DNEL - General population - Long term - Oral 6.25 mg/kg bw/day <u>Effects</u> : Systemic
		DNEL - Workers - Long term - Inhalation 67.5 mg/m³ <u>Effects</u> : Local
		DNEL - Workers - Short term - Inhalation 101.2 mg/m³ <u>Effects</u> : Local
2-Butoxyethanol		DNEL - General population - Long term - Oral 6.3 mg/kg bw/day <u>Effects</u> : Systemic
		DNEL - General population - Short term - Oral 26.7 mg/kg bw/day <u>Effects</u> : Systemic
		DNEL - General population - Long term - Inhalation 59 mg/m ³

Effects: Systemic

DNEL - Workers - Long term - Inhalation 98 mg/m³ <u>Effects</u>: Systemic

DNEL - General population - Short term - Inhalation

SECTION 8: Exposure controls/personal protection

SECTION 8: Exposure controls/pe	-
	147 mg/m³ <u>Effects</u> : Local
	DNEL - Workers - Short term - Inhalation 246 mg/m³ <u>Effects</u> : Local
	DNEL - General population - Short term - Inhalation 426 mg/m ³ <u>Effects</u> : Systemic
	DNEL - Workers - Short term - Inhalation 1091 mg/m ³ <u>Effects</u> : Systemic
1,2-benzisothiazol-3(2H)-one	DNEL - General population - Long term - Dermal 0.345 mg/kg bw/day <u>Effects</u> : Systemic
	DNEL - Workers - Long term - Dermal 0.966 mg/kg bw/day <u>Effects</u> : Systemic
	DNEL - General population - Long term - Inhalation 1.2 mg/m ³ <u>Effects</u> : Systemic
	DNEL - Workers - Long term - Inhalation 6.81 mg/m ³ <u>Effects</u> : Systemic
reaction mass of: 5-chloro-2-methyl- 4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	DNEL - General population - Long term - Inhalation 0.02 mg/m ³ <u>Effects</u> : Local
	DNEL - Workers - Long term - Inhalation 0.02 mg/m³ <u>Effects</u> : Local
	DNEL - General population - Short term - Inhalation 0.04 mg/m ³ Effects: Local
	DNEL - Workers - Short term - Inhalation 0.04 mg/m³ <u>Effects</u> : Local
	DNEL - General population - Long term - Oral 0.09 mg/kg bw/day <u>Effects</u> : Systemic
	DNEL - General population - Short term - Oral

DNEL - General population - Short term - Oral 0.11 mg/kg bw/day <u>Effects</u>: Systemic

PNECs

Not available.

8.2 Exposure controls

Appropriate engineering controls

: Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

6/17

 Date of issue/Date of revision
 : 14/01/2025
 Date of previous issue
 : No previous validation
 Version
 : 1

 PLATIN ANTIGLISS 4546-15 - All variants
 Label No :38817

SECTION 8: Exposure controls/personal protection

•	· · ·
Individual protection measu	<u>res</u>
Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.
Skin protection	
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
	Recommendations : Wear suitable gloves tested to EN374.
	> 8 hours (breakthrough time): Nitrile gloves. thickness > 0.3 mm
	Not recommended polyvinyl alcohol (PVA) gloves
Body protection	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	 Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.
	Filter type (spray application): A P
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

Appearance	
Physical state	: Liquid.
Colour	: Various
Odour	: Slight
Odour threshold	: Not available.
Melting point/freezing point	: Not available.
Initial boiling point and boiling range	:

Ingredient name		°C	°F	Method	
water		100	212		
2-Butoxyethanol		171 to 171.5	339.8 to 340.7	IP 123-93	
Flammability	: Not ava	ilable.			
Lower and upper explosion limit	Lower: 0.8% (2-(2-butoxyethoxy)ethanol) Upper: 12.6% (propane-1,2-diol)				
Flash point	: Closed cup: >100°C (>212°F)				
Auto-ignition temperature	:				

: 14/01/2025 Date of previous issue

Ingredient name	°C	°F	Method	
2-(2-butoxyethoxy)ethanol	210	410	DIN 51794	
2-Butoxyethanol	230	446	DIN 51794	
Decomposition temperature	: Not available.			
н	: 7 to 9			
/iscosity	: Not available.			
olubility(ies)	1			
Not available.				
Solubility in water	: Not available.			
Partition coefficient: n-octanol	I: Not applicable.			

Vapour pressure

water

	Vapour Pressure at 20°C		V	apour pres	sure at 50°C	
Ingredient name	mm Hg	kPa	Method	mm Hg	kPa	Method
water	17.5	2.3				
2-Butoxyethanol	0.75006	0.1				
Relative density	: Not	available.	ŀ		-	
)ensity	: 1.1	g/cm³				
apour density	: Not	available.				
Particle characteristics						
Median particle size	: Not	applicable.				
2 Other information						
.2.1 Information with reg	ard to physic	al hazard o	classes			
Explosive properties	: Not	available.				
Oxidising properties	: Not	available.				

9.2.2 Other safety characteristics

Not applicable.

SECTION 10: Stability and reactivity

11

10.1 Reactivity	No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	The product is stable.
10.3 Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur.
10.4 Conditions to avoid	No specific data.
10.5 Incompatible materials	No specific data.
10.6 Hazardous decomposition products	 Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Product/ingredient name

2-(2-butoxyethoxy)ethanol

Result

Rabbit - Dermal - LD50 2700 mg/kg

Rat - Oral - LD50

4500 mg/kg Toxic effects: Behavioral - Tetany Lung, Thorax, or Respiration - Dyspnea Liver - Other changes

1,2-benzisothiazol-3(2H)-one

Rat - Oral - LD50 1020 mg/kg

reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)

Rat - Oral - LD50

53 mg/kg Toxic effects: Behavioral - Somnolence (general depressed activity) Behavioral - Ataxia Lung, Thorax, or Respiration -Respiratory depression

Conclusion/Summary [Product] : Not available.

Acute toxicity estimates

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
PLATIN ANTIGLISS 4546-15 2-(2-butoxyethoxy)ethanol 2-Butoxyethanol 1,2-benzisothiazol-3(2H)-one reaction mass of: 5-chloro-2-methyl-4-isothiazolin- 3-one [EC no. 247-500-7] and 2-methyl-2H- isothiazol-3-one [EC no. 220-239-6] (3:1)	60483.9 4500 1200 1020 53	N/A 2700 N/A N/A 50	166448.7 N/A N/A N/A N/A	151.2 N/A 3 N/A 0.5	N/A N/A N/A N/A N/A

Skin corrosion/irritation

Product/ingredient name

2-Butoxyethanol

1,2-benzisothiazol-3(2H)-one

Result

Rabbit - Skin - Mild irritant Amount/concentration applied: 500 mg

Human - Skin - Mild irritant Duration of treatment/exposure: 48 hours Amount/concentration applied: 5 %

Human - Skin - Severe irritant

Amount/concentration applied: 0.01 %

reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)

Conclusion/Summary [Product] : Not available.

Serious eye damage/eye irritation **Product/ingredient name**

Result

SECTION 11: Toxicological information	on
2-(2-butoxyethoxy)ethanol	Rabbit - Eyes - Moderate irritantDuration of treatment/exposure: 24 hoursAmount/concentration applied: 20 mg
	Rabbit - Eyes - Severe irritant Amount/concentration applied: 20 mg
2-Butoxyethanol	Rabbit - Eyes - Moderate irritant <u>Duration of treatment/exposure</u> : 24 hours <u>Amount/concentration applied</u> : 100 mg
	Rabbit - Eyes - Severe irritant Amount/concentration applied: 100 mg
Conclusion/Summary [Product] : Not available.	
Respiratory corrosion/irritation Not available.	
Conclusion/Summary [Product] : Not available	
Respiratory or skin sensitization Not available.	
Skin Conclusion/Summary [Product] : Not available	
Respiratory Conclusion/Summary [Product] : Not available.	
<u>Germ cell mutagenicity</u> Not available.	
Conclusion/Summary [Product] : Not available	
Carcinogenicity Not available.	
Conclusion/Summary [Product] : Not available	
Reproductive toxicity Not available.	
Conclusion/Summary [Product] : Not available	
<u>Specific target organ toxicity (single exposure)</u> Not available.	
Specific target organ toxicity (repeated exposure) Not available.	
<u>Aspiration hazard</u> Not available.	
Information on likely routes of exposure	

SECTION 11: Toxicological information

Not available.	
Potential acute health effect	t <u>s</u>
Eye contact	: No known significant effects or critical hazards.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: No known significant effects or critical hazards.
Ingestion	: No known significant effects or critical hazards.
Symptoms related to the ph	ysical, chemical and toxicological characteristics
Eye contact	: No specific data.
Inhalation	: No specific data.
Skin contact	: No specific data.
Ingestion	: No specific data.
Delayed and immediate effe	cts as well as chronic effects from short and long-term exposure
Short term exposure	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Long term exposure	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Potential chronic health effe	ets
Not available.	
Conclusion/Summary [Pro	oduct] : Not available.
General	: No known significant effects or critical hazards.
Carcinogenicity	: No known significant effects or critical hazards.
Mutagenicity	: No known significant effects or critical hazards.
Reproductive toxicity	: No known significant effects or critical hazards.
11.2 Information on other haz	zards

11.2.1 Endocrine disrupting properties

Not available.

Conclusion/Summary [Product]

: The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

11.2.2 Other information

Not available.

SECTION 12: Ecological information

12.1 Toxicity

Product/ingredient name

2-(2-butoxyethoxy)ethanol

2-Butoxyethanol

Result

Date of previous issue

Acute - LC50 - Fresh water

Fish - Bluegill - *Lepomis macrochirus* <u>Size</u>: 33 to 75 mm 1300000 µg/l [96 hours] <u>Effect</u>: Mortality

Acute - LC50 - Marine water

Fish - Inland silverside - *Menidia beryllina* <u>Size</u>: 40 to 100 mm 1250000 µg/l [96 hours] <u>Effect</u>: Mortality

Acute - LC50 - Marine water

Crustaceans - Common shrimp, sand shrimp - *Crangon* crangon

SECTION 12: Ecological information	
------------------------------------	--

800000 µg/l [48 hours] <u>Effect</u>: Mortality

1,2-benzisothiazol-3(2H)-one

Acute - LC50 - Fresh water

OECD [Fish, Acute Toxicity Test] Fish - Trout - *Onorhynchus Mykiss* 1.9 mg/l [96 hours]

Acute - EC50 OECD 202 [Daphnia sp. Acute Immobilization Test and Reproduction Test] Daphnia - Daphnia - Daphnia Magna 3.7 mg/l [48 hours]

Acute - EC50 - Marine water

OECD 201 [Alga, Growth Inhibition Test] Algae - Algae - *Skeletonema Costatum* 0.36 mg/l [72 hours]

Acute - NOEC - Marine water

OECD 201 [Alga, Growth Inhibition Test] Algae - Algae - *Skeletonema Costatum* 0.15 mg/l [72 hours]

Conclusion/Summary [Product] : Not available.

12.2 Persistence and degradability

Product/ingredient name

1,2-benzisothiazol-3(2H)-one

Result EU

24% [28 days]

Conclusion/Summary [Product] : Not available.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
1,2-benzisothiazol-3(2H)-one	-	-	Inherent

12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
2-(2-butoxyethoxy)ethanol 2-Butoxyethanol	1 0.81		Low Low
1,2-benzisothiazol-3(2H)-one			Low

12.4 Mobility in soil

Soil/water partition coefficient

Product/ingredient name	logKoc	Кос
2-(2-butoxyethoxy)ethanol	1.56	36.5981
2-Butoxyethanol	1.83	67.3685
1,2-benzisothiazol-3(2H)-one	1.86	73.142

Results of PMT and vPvM assessment

Product/ingredient name	PMT	Р	Μ	Т	vPvM	vP	vM
2-(2-butoxyethoxy)ethanol 2-Butoxyethanol 1,2-benzisothiazol-3(2H)-one reaction mass of: 5-chloro- 2-methyl-4-isothiazolin- 3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol- 3-one [EC no. 220-239-6] (3: 1)	No No No						

Date of issue/Date of revision

PLATIN ANTIGLISS 4546-15 - All variants

: 14/01/2025 Date of previous issue

: No previous validation

Label No :38817

Version :1

12/17

SECTION 12: Ecological information

Mobility

: Not available.

Conclusion/Summary

: The product does not meet the criteria to be considered as a PMT or vPvM.

12.5 Results of PBT and vPvB assessment Regulation (EC) No. 1907/2006 [REACH]

Product/ingredient name	PBT	Р	В	т	vPvB	vP	vB
2-(2-butoxyethoxy)ethanol 2-Butoxyethanol 1,2-benzisothiazol-3(2H)-one reaction mass of: 5-chloro- 2-methyl-4-isothiazolin- 3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol- 3-one [EC no. 220-239-6] (3: 1)	No	No No No	No No No	No No No	No No No	No No No	No No No

Regulation (EC) No. 1272/2008 [CLP]

Product/ingredient name	PBT	Р	В	т	vPvB	vP	vB
2-(2-butoxyethoxy)ethanol	No	No	No	No	No	No	No
2-Butoxyethanol	No	No	No	No	No	No	No
1,2-benzisothiazol-3(2H)-one	No	No	No	No	No	No	No
reaction mass of: 5-chloro-	No	No	No	No	No	No	No
2-methyl-4-isothiazolin-							
3-one [EC no. 247-500-7]							
and 2-methyl-2H-isothiazol-							
3-one [EC no. 220-239-6] (3:							
1)							

Conclusion/Summary Regulation (EC) No. 1272/2008 [CLP] : The product does not meet the criteria to be considered as a PBT or vPvB.

12.6 Endocrine disrupting properties

Not available.

Conclusion/Summary [Product]

: The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

13.1 Waste treatment methods **Product** Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. : 08.01.19 **European waste** catalogue (EWC) Packaging Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Date of issue/Date of revision	: 14/01/2025	Date of previous issue	: No previous validation	Version : 1	13/17
PLATIN ANTIGLISS 4546-15 - A	All variants			Label No :388	17

SECTION 13: Disposal considerations

Special precautions

: This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

	ADR/RID	ADN	IMDG	IATA
14.1 UN number or ID number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-	-
14.3 Transport hazard class(es)	-	-	-	-
14.4 Packing group	-	-	-	-
14.5 Environmental hazards	No.	No.	No.	No.

14.6 Special precautions for : Transport within user's premises: always transport in closed containers that are user upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Maritime transport in bulk according to IMO

: Not relevant/applicable due to nature of the product.

instruments

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

ż

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Product/ingredient name	%	Designation [Usage]
2-(2-butoxyethoxy)ethanol	≤3	55 [Consumer paint]

Labelling	L	.at	bel	lin	g		
-----------	---	-----	-----	-----	---	--	--

Other EU regulations		
Industrial emissions (integrated pollution prevention and control) - Air	:	Not listed
Air Industrial emissions (integrated pollution prevention and control) - Water	:	Not listed
Explosive precursors	:	Not applicable.
Ozone depleting substance	es	<u>(EU 2024/590)</u>

Date of issue/Date of revision : 14/01/2025 Date of previous issue

SECTION 15: Regulatory information

Not listed.

Prior Informed Consent (PIC) (649/2012/EU)

Not listed.

Persistent Organic Pollutants

Not listed.

Seveso Directive

This product is not controlled under the Seveso Directive.

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

15.2 Chemical safety assessment

: This product contains substances for which Chemical Safety Assessments are still required.

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and acronyms	 ATE = Acute Toxicity Estimate CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008] DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level EUH statement = CLP-specific Hazard statement N/A = Not available PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration RRN = REACH Registration Number SGG = Segregation Group
	vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Not classified.

Full text of abbreviated H statements

H301	Toxic if swallowed.
H302	Harmful if swallowed.
H310	Fatal in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H331	Toxic if inhaled.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
EUH071	Corrosive to the respiratory tract.

: No previous validation

SECTION 16: Other information

Full text of classifications [CLP/GHS]

I un text of classificati	
Acute Tox. 2	ACUTE TOXICITY - Category 2
Acute Tox. 3	ACUTE TOXICITY - Category 3
Acute Tox. 4	ACUTE TOXICITY - Category 4
Aquatic Acute 1	SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1
Aquatic Chronic 1	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1
Eye Dam. 1	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1
Eye Irrit. 2	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2
Skin Corr. 1C	SKIN CORROSION/IRRITATION - Category 1C
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2
Skin Sens. 1	SKIN SENSITISATION - Category 1
Skin Sens. 1A	SKIN SENSITISATION - Category 1A
Date of issue/ Date of	: 14/01/2025
revision	
Date of previous issue	No previous validation
Version	: 1

PLATIN ANTIGUSS 4546-15

Notice to reader

The information in this SDS is based on the present state of our knowledge and on current laws. The product is not to be used for purposes other than those specified under section 1 without first obtaining written handling instructions. It is always the responsibility of the user to take all necessary steps to fulfil the demands set out in the local rules and legislation. The information in this SDS is meant to be a description of the safety requirements for our product. It is not to be considered a guarantee of the product's properties.

Date of issue/Date of revision: 14/01/2025Date of previous issuePLATIN ANTIGLISS 4546-15 - All variants