SAFETY DATA SHEET



SAFIR 20

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : SAFIR 20

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Lacquers.

1.3 Details of the supplier of the safety data sheet

Teknos Group Oy, Takkatie 3, FI-00370 HELSINKI, FINLAND. Tel. +358 9 506 091.

e-mail address of person responsible for this SDS

: Prod-safe@teknos.com

National contact

Teknos Group Oy, Takkatie 3, FI-00370 HELSINKI, FINLAND. Tel. +358 9 506 091.

1.4 Emergency telephone number

National advisory body/Poison Centre

Telephone number : In an emergency, call 112

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition: Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Not classified.

The product is not classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Signal word : No signal word.

Hazard statements : No known significant effects or critical hazards.

Precautionary statements

Prevention : Not applicable.

Response : Not applicable.

Storage : Not applicable.

Disposal : Not applicable.

Supplemental label

elements

: Contains triisobutyl phosphate, adipohydrazide, 1,2-benzisothiazol-3(2H)-one and reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1). May produce an allergic

foto leterale est con la la la companya

Safety data sheet available on request. Contains biocidal products for in-can

preservation: BIT and Bronopol and C(M)IT/MIT (3:1).

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Date of issue/Date of revision : 24/02/2025 Date of previous issue : 05/09/2022 Version : 5 1/24

SECTION 2: Hazards identification

2.3 Other hazards

Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII : This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

Other hazards which do not result in classification

: None known.

SECTION 3: Composition/information on ingredients

3.2 Mixtures : Mixture

| Product/ingredient name | Identifiers | % | Classification | Specific Conc. Limits, M-factors and ATEs | Type |
|---|---|---------|---|---|---------|
| I ∕-Methoxy 2-propanol | REACH #: 01-2119457435-35 EC: 203-539-1 CAS: 107-98-2 Index: 603-064-00-3 | ≤3 | Flam. Liq. 3, H226 STOT SE 3, H336 | - | [1] [2] |
| Polyether modified trisiloxane | CAS: 27306-78-1 | ≤1 | Acute Tox. 4, H302 Acute Tox. 4, H332 Eye Irrit. 2, H319 Aquatic Chronic 2, H411 | ATE [Oral] = 500 mg/kg ATE [Inhalation (vapours)] = 11 mg/ | [1] |
| triisobutyl phosphate | REACH #: 01-2119957118-32 EC: 204-798-3 CAS: 126-71-6 | <1 | Skin Sens. 1B, H317 | - | [1] |
| adipohydrazide | REACH #: 01-2119962900-36 EC: 213-999-5 CAS: 1071-93-8 | ≤0.3 | Skin Sens. 1, H317 Aquatic Chronic 2, H411 | - | [1] |
| 1,2-benzisothiazol-3(2H)- one | EC: 220-120-9 CAS: 2634-33-5 Index: 613-088-00-6 | <0.036 | Acute Tox. 4, H302 Acute Tox. 2, H330 Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 | ATE [Oral] = 450 mg/kg ATE [Inhalation (dusts and mists)] = 0.21 mg/l Skin Sens. 1, H317: C ≥ 0.036% M [Acute] = 1 M [Chronic] = 1 | [1] |
| reaction mass of: 5-chloro- 2-methyl-4-isothiazolin- 3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol- 3-one [EC no. 220-239-6] (3:1) | EC: 911-418-6 CAS: 55965-84-9 Index: 613-167-00-5 | ≤0.0014 | Acute Tox. 3, H301 Acute Tox. 2, H310 Acute Tox. 2, H330 Skin Corr. 1C, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 EUH071 | ATE [Oral] = 53 mg/kg ATE [Dermal] = 50 mg/kg ATE [Inhalation (vapours)] = 0.5 mg/l Skin Corr. 1C, H314: $C \ge 0.6\%$ Eye Dam. 1, H318: $C \ge 0.6\%$ Eye Irrit. 2, H319: $0.06\% \le C < 0.6\%$ Skin Sens. 1, H317: $C \ge 0.0015\%$ M [Acute] = 100 M [Chronic] = 100 | |

 Date of issue/Date of revision
 : 24/02/2025
 Date of previous issue
 : 05/09/2022
 Version
 : 5
 2/24

 SAFIR 20
 Label No :39081

| SECTION 3: Compo | SECTION 3: Composition/information on ingredients | | | | |
|-------------------------|---|--|---|--|--|
| | | | See Section 16 for the full text of the H statements declared above. | | |

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

- [1] Substance classified with a health or environmental hazard
- [2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

Eye contact: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower

eyelids. Check for and remove any contact lenses. Get medical attention if irritation

occurs.

Inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing.

Get medical attention if symptoms occur. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be

kept under medical surveillance for 48 hours.

Skin contact : Flush contaminated skin with plenty of water. Remove contaminated clothing and

shoes. Get medical attention if symptoms occur.

Ingestion: Wash out mouth with water. If material has been swallowed and the exposed

person is conscious, give small quantities of water to drink. Do not induce vomiting unless directed to do so by medical personnel. Get medical attention if symptoms

occur.

Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training.

4.2 Most important symptoms and effects, both acute and delayed

Over-exposure signs/symptoms

Eye contact : No specific data.

Inhalation : No specific data.

Skin contact : No specific data.

Ingestion : No specific data.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician : In case of inhalation of decomposition products in a fire, symptoms may be delayed.

The exposed person may need to be kept under medical surveillance for 48 hours.

Specific treatments : No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing

media

: Use an extinguishing agent suitable for the surrounding fire.

Unsuitable extinguishing

media

: None known.

5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture

: In a fire or if heated, a pressure increase will occur and the container may burst.

Hazardous combustion

products

: Decomposition products may include the following materials:

carbon dioxide carbon monoxide nitrogen oxides metal oxide/oxides

Date of issue/Date of revision : 24/02/2025 Date of previous issue : 05/09/2022 Version : 5 3/24

SECTION 5: Firefighting measures

5.3 Advice for firefighters

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Put on appropriate personal protective equipment.

For emergency responders: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions

: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

6.3 Methods and material for containment and cleaning up

Small spill

: Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Dispose of via a licensed waste disposal contractor. Contain and collect spillage with non-combustible, absorbent material e. g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

6.4 Reference to other sections

See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

Protective measures Advice on general occupational hygiene

- : Put on appropriate personal protective equipment (see Section 8).
- : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Date of issue/Date of revision • 24/02/2025 .05/09/2022 Version :5 Date of previous issue 4/24

SECTION 7: Handling and storage

7.3 Specific end use(s)

Recommendations : Not available.

Industrial sector specific : Not available.

solutions

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

8.1 Control parameters

Occupational exposure limits

| Product/ingredient name | Exposure limit values |
|---|---|
| Ethyldiglycol | Regulation on Limit Values - MAC (Austria, 4/2021) PEAK 15 minutes: 140 mg/m³ 4 times per shift. PEAK 15 minutes: 24 ppm 4 times per shift. TWA 8 hours: 35 mg/m³. TWA 8 hours: 6 ppm. |
| 1-Methoxy 2-propanol | Regulation on Limit Values - MAC (Austria, 4/2021) Absorbed through skin. TWA 8 hours: 50 ppm. TWA 8 hours: 187 mg/m³. CEIL: 50 ppm. CEIL: 187 mg/m³. |
| triisobutyl phosphate | Regulation on Limit Values - MAC (Austria, 4/2021) CEIL 60 minutes: 100 mg/m³ 3 times per shift. TWA 8 hours: 50 mg/m³. |
| reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) | Regulation on Limit Values - MAC (Austria, 4/2021) [5-Chlor-2-methyl-2,3-dihydroisothiazol-3-on und 2-Methyl-2,3-dihydroisothiazol-3-on (Gemisch im Verhältnis 3:1)] Skin sensitiser. TWA 8 hours: 0.05 mg/m³. |
| | Limit values (Belgium, 12/2023) Absorbed through skin. TWA 8 hours: 50 ppm. TWA 8 hours: 184 mg/m³. STEL 15 minutes: 100 ppm. STEL 15 minutes: 369 mg/m³. |
| I ∕-Methoxy 2-propanol | Ministry of Labour and Social Policy and the Ministry of Health - Ordinance No 13/2003. (Bulgaria, 4/2024) Absorbed through skin. Limit value 8 hours: 375 mg/m³. Limit value 15 minutes: 568 mg/m³. Limit value 15 minutes: 150 ppm. Limit value 8 hours: 100 ppm. |
| Methoxy 2-propanol | Ordinance on the protection of workers from exposure to hazardous chemicals at work, exposure limit values (Annex I) (Croatia, 12/2023) STELV 15 minutes: 568 mg/m³. STELV 15 minutes: 150 ppm. ELV 8 hours: 375 mg/m³. ELV 8 hours: 100 ppm. |
| triisobutyl phosphate | Ordinance on the protection of workers from exposure to hazardous chemicals at work, exposure limit values (Annex I) (Croatia, 12/2023) [tributil-fosfat] STELV 15 minutes: 5 mg/m³. ELV 8 hours: 5 mg/m³. |

 Date of issue/Date of revision
 : 24/02/2025
 Date of previous issue
 : 05/09/2022
 Version
 : 5
 5/24

 SAFIR 20
 Label No :39081

7-Methoxy 2-propanol Department of labour inspection (Cyprus, 7/2021) Absorbed through skin. STEL 15 minutes: 150 ppm. STEL 15 minutes: 568 mg/m³. TWA 8 hours: 100 ppm. TWA 8 hours: 375 mg/m³. 1-Methoxy 2-propanol Government regulation of Czech Republic PEL/NPK-P (Czech Republic, 12/2023) Absorbed through skin. TWA 8 hours: 270 mg/m³. TWA 8 hours: 72.09 ppm. STEL 15 minutes: 550 mg/m³. STEL 15 minutes: 146.84 ppm. 1-Methoxy 2-propanol Working Environment Authority (Denmark, 3/2024) [1-methoxy-2-propanol] Absorbed through skin. TWA 8 hours: 50 ppm. TWA 8 hours: 185 mg/m³. STEL 15 minutes: 568 mg/m³. STEL 15 minutes: 150 ppm. 1-Methoxy 2-propanol Occupational exposure limits, Regulation No. 293 (Estonia, 4/2024) Absorbed through skin, Sensitiser. TWA 8 hours: 375 mg/m³. TWA 8 hours: 100 ppm. STEL 15 minutes: 568 mg/m³. STEL 15 minutes: 150 ppm. EU OEL (Europe, 1/2022) Absorbed through skin. 1-Methoxy 2-propanol TWA 8 hours: 100 ppm. TWA 8 hours: 375 mg/m³. STEL 15 minutes: 150 ppm. STEL 15 minutes: 568 mg/m³. Institute of Occupational Health, Ministry of Social Affairs 1-Methoxy 2-propanol (Finland, 10/2021) Absorbed through skin. TWA 8 hours: 100 ppm. TWA 8 hours: 370 mg/m³. STEL 15 minutes: 150 ppm. STEL 15 minutes: 560 mg/m³. 1-Methoxy 2-propanol Ministry of Labor (France, 6/2024) Absorbed through skin. TWA 8 hours: 50 ppm. Notes: Binding regulatory limit values (article R. 4412-149 of the Labor Code) TWA 8 hours: 188 mg/m³. Notes: Binding regulatory limit values (article R. 4412-149 of the Labor Code) STEL 15 minutes: 375 mg/m³. Notes: Binding regulatory limit

Ethyldiglycol

1-Methoxy 2-propanol

values (article R. 4412-149 of the Labor Code)

STEL 15 minutes: 100 ppm. Notes: Binding regulatory limit values

(article R. 4412-149 of the Labor Code)

TRGS 900 OEL (Germany, 6/2024)

TWA 8 hours: 35 mg/m³. PEAK 15 minutes: 70 mg/m³.

TWA 8 hours: 6 ppm. PEAK 15 minutes: 12 ppm.

DFG MAC-values list (Germany, 7/2023) Develop C.

PEAK 15 minutes: 100 mg/m³ 4 times per shift [Interval: 1 hour].

Form: inhalable fraction.

TWA 8 hours: 50 mg/m³. Form: inhalable fraction.

TRGS 900 OEL (Germany, 6/2024)

TWA 8 hours: 370 mg/m³. PEAK 15 minutes: 740 mg/m³. TWA 8 hours: 100 ppm. PEAK 15 minutes: 200 ppm.

DFG MAC-values list (Germany, 7/2023) Develop C.

TWA 8 hours: 100 ppm.

PEAK 15 minutes: 200 ppm 4 times per shift [Interval: 1 hour].

Date of issue/Date of revision Date of previous issue .05/09/2022 · 24/02/2025 Version: 5 6/24 SAFIR 20 Label No: 39081

triisobutyl phosphate

Methoxy 2-propanol

1-Methoxy 2-propanol

1,2-benzisothiazol-3(2H)-one

TWA 8 hours: 370 mg/m³.

PEAK 15 minutes: 740 mg/m³ 4 times per shift [Interval: 1 hour].

TRGS 900 OEL (Germany, 6/2024) Skin sensitiser.

TWA 8 hours: 50 mg/m³. PEAK 15 minutes: 100 mg/m³.

DFG MAC-values list (Germany, 7/2023) Skin sensitiser.
DFG MAC-values list (Germany, 7/2023) Skin sensitiser.

Presidential Decree 307/1986: Occupational exposure limit values (Greece, 9/2021) Absorbed through skin.

TWA 8 hours: 100 ppm. TWA 8 hours: 360 mg/m³. STEL 15 minutes: 300 ppm. STEL 15 minutes: 1080 mg/m³.

5/2020. (II. 6.) ITM Decree (Hungary, 12/2023) Absorbed through

skin.

TWA 8 hours: 375 mg/m³. PEAK 15 minutes: 568 mg/m³. PEAK 15 minutes: 150 ppm. TWA 8 hours: 100 ppm.

Ministry of Welfare, List of Exposure Limits (Iceland, 11/2023)

Absorbed through skin.

STEL 15 minutes: 568 mg/m³. STEL 15 minutes: 150 ppm. TWA 8 hours: 185 mg/m³. TWA 8 hours: 50 ppm.

✓ Methoxy 2-propanol NAOSH (Ireland, 4/2024) Notes: EU derived Occupational

Exposure Limit Values
OELV 8 hours: 100 ppm.
OELV 8 hours: 375 mg/m³.
OELV 15 minutes: 150 ppm.
OELV 15 minutes: 568 mg/m³.

triisobutyl phosphate NAOSH (Ireland, 4/2024) [tributyl phosphate] Notes: Advisory

Occupational Exposure Limit Values (OELVs)

OELV 8 hours: 5 mg/m³.

Methoxy 2-propanol

Legislative Decree No. 81/2008. Title IX. Protection from chemical agents, carcinogens and mutagens (Italy, 6/2020)

Absorbed through skin.

Limit value 8 hours: 100 ppm. Limit value 8 hours: 375 mg/m³. Short Term 15 minutes: 150 ppm. Short Term 15 minutes: 568 mg/m³.

Ministers Cabinet Regulations Nr.325 - AER (Latvia, 3/2024)

Absorbed through skin. TWA 8 hours: 100 ppm. STEL 15 minutes: 568 mg/m³. TWA 8 hours: 375 mg/m³. STEL 15 minutes: 150 ppm.

I/-Methoxy 2-propanol Lithuanian Hygiene Standard HN 23 (Lithuania, 1/2024)

Absorbed through skin.
TWA 8 hours: 190 mg/m³.
TWA 8 hours: 50 ppm.
STEL 15 minutes: 300 mg/m³.
STEL 15 minutes: 75 ppm.

(Luxembourg, 3/2021) Absorbed through skin.

TWA 8 hours: 100 ppm. TWA 8 hours: 375 mg/m³. STEL 15 minutes: 150 ppm. STEL 15 minutes: 568 mg/m³.

Date of issue/Date of revision : 24/02/2025 Date of previous issue : 05/09/2022 Version : 5 7/24

1-Methoxy 2-propanol

EU OEL (Europe, 1/2022) Absorbed through skin.

TWA 8 hours: 100 ppm. TWA 8 hours: 375 mg/m³. STEL 15 minutes: 150 ppm. STEL 15 minutes: 568 mg/m³.

1-Methoxy 2-propanol

Ministry of Social Affairs and Employment, Legal limit values (Netherlands, 5/2024) Absorbed through skin.

TWA 8 hours: 375 mg/m³. STEL 15 minutes: 563 mg/m³. TWA 8 hours: 100 ppm.

STEL 15 minutes: 150 ppm.

1-Methoxy 2-propanol

FOR-2011-12-06-1358 (Norway, 12/2022) Absorbed through skin.

TWA 8 hours: 50 ppm. TWA 8 hours: 180 mg/m³.

Methoxy 2-propanol

Regulation of the Minister of Family, Labor and Social Policy of June 12, 2018 on the maximum permissible concentrations and intensities of factors harmful to health in the work environment (Journal of Laws of 2018, item 1286) (Poland,

8/2023) Absorbed through skin. TWA 8 hours: 180 mg/m³. STEL 15 minutes: 360 mg/m³.

1-Methoxy 2-propanol

Portuguese Institute of Quality (Portugal, 11/2014) A4.

TWA 8 hours: 50 ppm. STEL 15 minutes: 100 ppm.

1-Methoxy 2-propanol

HG 1218/2006, Annex 1, with subsequent modifications and additions (Romania, 3/2024) Absorbed through skin.

VLA 8 hours: 375 mg/m³. VLA 8 hours: 100 ppm.

Short term 15 minutes: 568 mg/m³. Short term 15 minutes: 150 ppm.

triisobutyl phosphate

HG 1218/2006, Annex 1, with subsequent modifications and

additions (Romania, 3/2024) [Butilfosfaţi (di şi tri)]

VLA 8 hours: 2 mg/m³.

Short term 15 minutes: 5 mg/m³.

Government regulation SR c. 355/2006 (Slovakia, 7/2024)

Absorbed through skin, Inhalation sensitiser.

TWA 8 hours: 375 mg/m³. TWA 8 hours: 100 ppm. STEL 15 minutes: 568 mg/m³. STEL 15 minutes: 150 ppm.

Ethyldiglycol

Regulation on protection of workers from the risks related to exposure to chemical substances at work (Slovenia, 4/2024)

KTV 15 minutes: 12 ppm 4 times per shift [time between two exposure events at this concentration must be at least 60 minutes].

TWA 8 hours: 6 ppm.

KTV 15 minutes: 70 mg/m³ 4 times per shift [time between two exposure events at this concentration must be at least 60 minutes].

TWA 8 hours: 35 mg/m³.

1-Methoxy 2-propanol

Regulation on protection of workers from the risks related to exposure to chemical substances at work (Slovenia, 4/2024)

Absorbed through skin.
TWA 8 hours: 375 mg/m³.
TWA 8 hours: 100 ppm.

KTV 15 minutes: 568 mg/m³ 4 times per shift [time between two exposure events at this concentration must be at least 60 minutes]. KTV 15 minutes: 150 ppm 4 times per shift [time between two exposure events at this concentration must be at least 60 minutes].

triisobutyl phosphate

Regulation on protection of workers from the risks related to exposure to chemical substances at work (Slovenia, 4/2024)

KTV 15 minutes: 100 mg/m³ 4 times per shift [time between two exposure events at this concentration must be at least 60 minutes].

Date of issue/Date of revision: 24/02/2025Date of previous issue: 05/09/2022Version: 58/3SAFIR 20Label No : 39081

TWA 8 hours: 50 mg/m³. 1-Methoxy 2-propanol National institute of occupational safety and health (Spain, 1/2024) Absorbed through skin. TWA 8 hours: 100 ppm. TWA 8 hours: 375 mg/m³. STEL 15 minutes: 150 ppm. STEL 15 minutes: 568 mg/m³. **Ethyldiglycol** Work environment authority Regulation 2018:1 (Sweden, 11/2022) Absorbed through skin. TWA 8 hours: 15 ppm. TWA 8 hours: 80 mg/m³. STEL 15 minutes: 30 ppm. STEL 15 minutes: 170 mg/m³. 1-Methoxy 2-propanol Work environment authority Regulation 2018:1 (Sweden, 11/2022) Absorbed through skin. STEL 15 minutes: 150 ppm. STEL 15 minutes: 568 mg/m³. TWA 8 hours: 190 mg/m³. TWA 8 hours: 50 ppm. **Ethyldiglycol** SUVA (Switzerland, 1/2024) STEL 15 minutes: 100 mg/m³. Form: Inhalable fraction of Vapor and aerosols. TWA 8 hours: 50 mg/m³. Form: Inhalable fraction of Vapor and aerosols. 1-Methoxy 2-propanol SUVA (Switzerland, 1/2024) TWA 8 hours: 100 ppm. TWA 8 hours: 360 mg/m³. STEL 15 minutes: 200 ppm. STEL 15 minutes: 720 mg/m³. reaction mass of: 5-chloro-2-methyl-SUVA (Switzerland, 1/2024) Sensitiser. 4-isothiazolin-3-one [EC no. 247-500-7] and STEL 15 minutes: 0.4 mg/m³. Form: Inhalable fraction. 2-methyl-2H-isothiazol-3-one [EC no. TWA 8 hours: 0.2 mg/m³. Form: Inhalable fraction. 220-239-6] (3:1) 1-Methoxy 2-propanol EH40/2005 WELs (United Kingdom (UK), 1/2020) Absorbed through skin. STEL 15 minutes: 560 mg/m³. STEL 15 minutes: 150 ppm. TWA 8 hours: 375 mg/m³. TWA 8 hours: 100 ppm.

Biological exposure indices

triisobutyl phosphate

| Product/ingredient name | Exposure indices |
|----------------------------|------------------|
| No exposure indices known. | |
| | |

phosphate, all isomers]
STEL 15 minutes: 5 mg/m³.
TWA 8 hours: 5 mg/m³.

EH40/2005 WELs (United Kingdom (UK), 1/2020) [tributyl

 Date of issue/Date of revision
 : 24/02/2025
 Date of previous issue
 : 05/09/2022
 Version
 : 5
 9/24

 SAFIR 20
 Label No :39081

1-Methoxy 2-propanol

DFG BEI-values list (Germany, 7/2023)

BEI: 15 mg/l, propylene glycol 1-methyl ether [in urine]. Sampling time: end of exposure or end of shift.

TRGS 903 - BEI Values (Germany, 2/2024)

BEI: 15 mg/l, 1-methoxypropan-2-ol [in urine]. Sampling time: end of exposure or end of shift.

No exposure indices known.

1-Methoxy 2-propanol

No exposure indices known.

No exposure indices known.

✓ Methoxy 2-propanol

No exposure indices known.

Regulation on protection of workers from the risks related to exposure to chemical substances at work (Slovenia, 4/2024)

BAT: 15 mg/l, 1-methoxypropan-2-ol [in urine]. Sampling time: at the end of the work shift.

SUVA (Switzerland, 1/2024)

BEI: 20 mg/l, 1-methoxypropanol-2 [in urine]. Sampling time: immediately after exposure or after working hours.

BEI: 221.9 μmol/l, 1-methoxypropanol-2 [in urine]. Sampling time: immediately after exposure or after working hours.

Recommended monitoring procedures

Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

Product/ingredient name

1-Methoxy 2-propanol

Result

DNEL - General population - Long term - Oral

33 mg/kg bw/day Effects: Systemic

DNEL - General population - Long term - Inhalation

43.9 mg/m³ Effects: Systemic

DNEL - General population - Long term - Dermal

 Date of issue/Date of revision
 : 24/02/2025
 Date of previous issue
 : 05/09/2022
 Version
 : 5
 10/24

 SAFIR 20
 Label No :39081

triisobutyl phosphate

4-isothiazolin-3-one [EC no. 247-500-7] and

2-methyl-2H-isothiazol-3-one [EC no.

220-239-6] (3:1)

78 mg/kg bw/day Effects: Systemic

DNEL - Workers - Long term - Dermal

183 mg/kg bw/day Effects: Systemic

DNEL - Workers - Long term - Inhalation

369 mg/m³

Effects: Systemic

DNEL - Workers - Short term - Inhalation

553.5 mg/m³ Effects: Local

DNEL - Workers - Short term - Inhalation

553.5 mg/m³ Effects: Systemic

DNEL - General population - Long term - Oral

2.13 mg/kg bw/day Effects: Systemic

DNEL - General population - Long term - Dermal

2.13 mg/kg bw/day Effects: Systemic

DNEL - Workers - Long term - Dermal

4.25 mg/kg bw/day Effects: Systemic

DNEL - General population - Long term - Inhalation

8.89 mg/m³ Effects: Systemic

DNEL - Workers - Long term - Inhalation

50 mg/m³

Effects: Systemic

adipohydrazide DNEL - Workers - Long term - Inhalation

17.5 mg/m³
<u>Effects</u>: Systemic

1,2-benzisothiazol-3(2H)-one DNEL - General population - Long term - Dermal

0.345 mg/kg bw/day Effects: Systemic

DNEL - Workers - Long term - Dermal

0.966 mg/kg bw/day <u>Effects</u>: Systemic

DNEL - General population - Long term - Inhalation

1.2 mg/m³ Effects: Systemic

DNEL - Workers - Long term - Inhalation

6.81 mg/m³ Effects: Systemic

reaction mass of: 5-chloro-2-methyl- DNEL - General population - Long term - Inhalation

0.02 mg/m³ Effects: Local

DNEL - Workers - Long term - Inhalation 0.02 mg/m³

 Date of issue/Date of revision
 : 24/02/2025
 Date of previous issue
 : 05/09/2022
 Version
 : 5
 11/24

 SAFIR 20
 Label No : 39081

Effects: Local

DNEL - General population - Short term - Inhalation

0.04 mg/m³ Effects: Local

DNEL - Workers - Short term - Inhalation

0.04 mg/m³ Effects: Local

DNEL - General population - Long term - Oral

0.09 mg/kg bw/day Effects: Systemic

DNEL - General population - Short term - Oral

0.11 mg/kg bw/day Effects: Systemic

PNECs

Not available.

8.2 Exposure controls

Appropriate engineering controls

 Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

Individual protection measures

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.

Skin protection

Hand protection

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

Recommendations: Wear suitable gloves tested to EN374.

> 8 hours (breakthrough time): Nitrile gloves. thickness > 0.3 mm Not recommended polyvinyl alcohol (PVA) gloves

Body protection

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection

: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Filter type (spray application): A F

Environmental exposure controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

 Date of issue/Date of revision
 : 24/02/2025
 Date of previous issue
 : 05/09/2022
 Version
 : 5
 12/24

 SAFIR 20
 Label No :39081

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

Appearance

Physical state : Liquid. Colour : Various : Slight **Odour**

Not available. **Odour threshold** Melting point/freezing point : Not available.

Initial boiling point and

boiling range

| Ingredient name | °C | °F | Method |
|----------------------|--------|-------|----------|
| water | 100 | 212 | |
| 1-Methoxy 2-propanol | 120.17 | 248.3 | OECD 103 |

Flammability : Not available.

Lower and upper explosion

limit

: Lower: 1.2% (2-(2-ethoxyethoxy)ethanol) Upper: 23.5% (2-(2-ethoxyethoxy)ethanol)

Flash point : Closed cup: >100°C (>212°F)

Auto-ignition temperature

| Ingredient name | °C | °F | Method |
|-----------------------|-----|-------|--------|
| E thyldiglycol | 204 | 399.2 | |
| 1-Methoxy 2-propanol | 270 | 518 | |

Decomposition temperature : Not available.

7 to 8 [Conc. (% w/w): 100%] pН

Not available. **Viscosity**

Solubility(ies)

Not available.

Solubility in water : Not available. Partition coefficient: n-octanol/ : Not applicable.

water

Vapour pressure

| | Vapour Pressure at 20°C | | | Vaj | oour pressu | re at 50°C |
|----------------------|-------------------------|-----|--------|-------|-------------|------------|
| Ingredient name | mm Hg | kPa | Method | mm Hg | kPa | Method |
| water | 17.5 | 2.3 | | | | |
| 1-Methoxy 2-propanol | 8.5 | 1.1 | | | | |

Relative density : Not available. **Density** 1 g/cm³ Vapour density : Not available.

Particle characteristics

Median particle size : Not applicable.

9.2 Other information

9.2.1 Information with regard to physical hazard classes

Explosive properties : Not available. **Oxidising properties** : Not available.

9.2.2 Other safety characteristics

Not applicable.

Date of issue/Date of revision : 24/02/2025 : 05/09/2022 Version:5 13/24 Date of previous issue SAFIR 20

Label No: 39081

SECTION 10: Stability and reactivity

: No specific test data related to reactivity available for this product or its ingredients. 10.1 Reactivity

10.2 Chemical stability : The product is stable.

10.3 Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will not occur.

10.4 Conditions to avoid : No specific data.

10.5 Incompatible materials : No specific data.

10.6 Hazardous decomposition products : Under normal conditions of storage and use, hazardous decomposition products

should not be produced.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Product/ingredient name Result

1-Methoxy 2-propanol Rabbit - Dermal - LD50

13 g/kg

Rat - Oral - LD50 6600 ma/ka

Toxic effects: Brain and Coverings - Other degenerative changes Behavioral - General anesthetic Lung, Thorax, or

Respiration - Dyspnea

Polyether modified trisiloxane Rat - Inhalation - LC50 Vapour

2 g/m³ [4 hours]

triisobutyl phosphate Rat - Oral - LD50

>5 g/kg

1,2-benzisothiazol-3(2H)-one Rat - Oral - LD50

1020 mg/kg

reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no.

220-239-6] (3:1)

Rat - Oral - LD50

53 mg/kg

Toxic effects: Behavioral - Somnolence (general depressed activity) Behavioral - Ataxia Lung, Thorax, or Respiration -

Respiratory depression

Conclusion/Summary [Product]: Not available.

Acute toxicity estimates

| Product/ingredient name | Oral (mg/ kg) | Dermal (mg/kg) | Inhalation (gases) (ppm) | Inhalation (vapours) (mg/l) | Inhalation (dusts and mists) (mg/l) |
|--|------------------|-------------------|--------------------------------|-----------------------------------|--|
| SAFIR 20 | 17642.1 | 83230.2 | N/A | 695.1 | N/A |
| 1-Methoxy 2-propanol | 6600 | 13000 | N/A | N/A | N/A |
| Polyether modified trisiloxane | 500 | N/A | N/A | 11 | N/A |
| 1,2-benzisothiazol-3(2H)-one | 450 | N/A | N/A | N/A | 0.21 |
| reaction mass of: 5-chloro-2-methyl-4-isothiazolin- | 53 | 50 | N/A | 0.5 | N/A |
| 3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) | | | | | |

Skin corrosion/irritation

Date of issue/Date of revision .05/09/2022 : 24/02/2025 Date of previous issue Version: 5 14/24 SAFIR 20 Label No: 39081

SECTION 11: Toxicological information

Product/ingredient name

Result

1-Methoxy 2-propanol

Rabbit - Skin - Mild irritant

Amount/concentration applied: 500 mg

triisobutyl phosphate

Rabbit - Skin - Moderate irritant

Amount/concentration applied: 500 uL

1,2-benzisothiazol-3(2H)-one

Human - Skin - Mild irritant

<u>Duration of treatment/exposure</u>: 48 hours <u>Amount/concentration applied</u>: 5 %

reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no.

Human - Skin - Severe irritant

Amount/concentration applied: 0.01 %

220-239-6] (3:1)

Conclusion/Summary [Product] : Not available.

Serious eye damage/eye irritation

Product/ingredient name Result

> <u>Duration of treatment/exposure</u>: 24 hours <u>Amount/concentration applied</u>: 500 mg

triisobutyl phosphate Rabbit - Eyes - Moderate irritant

Amount/concentration applied: 100 uL

Conclusion/Summary [Product] : Not available.

Respiratory corrosion/irritation

Not available.

Conclusion/Summary [Product] : Not available.

Respiratory or skin sensitization

Not available.

Skin

Conclusion/Summary [Product] : Not available.

Respiratory

Conclusion/Summary [Product]: Not available.

Germ cell mutagenicity

Not available.

Conclusion/Summary [Product] : Not available.

Carcinogenicity

Not available.

Conclusion/Summary [Product] : Not available.

Reproductive toxicity

Not available.

 Date of issue/Date of revision
 : 24/02/2025
 Date of previous issue
 : 05/09/2022
 Version
 : 5
 15/24

 SAFIR 20
 Label No :39081

SECTION 11: Toxicological information

Conclusion/Summary [Product] : Not available.

Specific target organ toxicity (single exposure)

Product/ingredient name Result

√Methoxy 2-propanol STOT SE 3, H336 (Narcotic effects)

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.

Information on likely routes of exposure

Not available.

Potential acute health effects

Eye contact
 Inhalation
 No known significant effects or critical hazards.
 Skin contact
 No known significant effects or critical hazards.
 Ingestion
 No known significant effects or critical hazards.
 Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : No specific data.

Inhalation : No specific data.

Skin contact : No specific data.

Ingestion : No specific data.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Short term exposure

Potential immediate : Not available.

effects

Potential delayed effects : Not available.

Long term exposure

Potential immediate : Not available.

effects

Potential delayed effects : Not available.

Potential chronic health effects

Not available.

Conclusion/Summary [Product]: Not available.

General : No known significant effects or critical hazards.
 Carcinogenicity : No known significant effects or critical hazards.
 Mutagenicity : No known significant effects or critical hazards.
 Reproductive toxicity : No known significant effects or critical hazards.

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

Not available.

Conclusion/Summary [Product]: The product does not meet the criteria to be considered as having endocrine

disrupting properties according to the criteria set out in either Regulation (EC)

No. 1907/2006 or Regulation (EC) No 1272/2008.

11.2.2 Other information

Not available.

 Date of issue/Date of revision
 : 24/02/2025
 Date of previous issue
 : 05/09/2022
 Version
 : 5
 16/24

 SAFID 20
 1 abol No : 30081

SECTION 12: Ecological information

12.1 Toxicity

Product/ingredient name

2-benzisothiazol-3(2H)-one

Result

Acute - LC50 - Fresh water

OECD [Fish, Acute Toxicity Test] Fish - Trout - Onorhynchus Mykiss

1.9 mg/l [96 hours]

Acute - EC50

OECD 202 [Daphnia sp. Acute Immobilization Test and

Reproduction Test]

Daphnia - Daphnia - Daphnia Magna

3.7 mg/l [48 hours]

Acute - EC50 - Marine water

OECD 201 [Alga, Growth Inhibition Test] Algae - Algae - Skeletonema Costatum

0.36 mg/l [72 hours]

Acute - NOEC - Marine water

OECD 201 [Alga, Growth Inhibition Test] Algae - Algae - Skeletonema Costatum

0.15 mg/l [72 hours]

Conclusion/Summary [Product] : Not available.

12.2 Persistence and degradability

Product/ingredient name 1,2-benzisothiazol-3(2H)-one Result

EU

24% [28 days]

Conclusion/Summary [Product] : Not available.

| Product/ingredient name | Aquatic half-life | Photolysis | Biodegradability | |
|------------------------------|-------------------|------------|------------------|--|
| 1,2-benzisothiazol-3(2H)-one | - | - | Inherent | |

12.3 Bioaccumulative potential

| Product/ingredient name | LogPow | BCF | Potential |
|------------------------------|--------|-----|-----------|
| Methoxy 2-propanol | <1 | | Low |
| 1,2-benzisothiazol-3(2H)-one | - | 3.2 | Low |

12.4 Mobility in soil

Soil/water partition coefficient

| Product/ingredient name | logKoc | Koc |
|------------------------------|--------|---------|
| Methoxy 2-propanol | 1.02 | 10.447 |
| triisobutyl phosphate | 2.68 | 482.732 |
| adipohydrazide | 1.74 | 55.2165 |
| 1,2-benzisothiazol-3(2H)-one | 1.86 | 73.142 |

Results of PMT and vPvM assessment

| Dura da a de la Companya de la compa | DMT | | | | - D - M | | |
|--|-----|----|----|----|---------|----|----|
| Product/ingredient name | PMT | Р | M | | vPvM | νP | vM |
| √Methoxy 2-propanol | No | No | No | No | No | No | No |
| Polyether modified trisiloxane | No | No | No | No | No | No | No |
| triisobutyl phosphate | No | No | No | No | No | No | No |
| adipohydrazide | No | No | No | No | No | No | No |
| 1,2-benzisothiazol-3(2H)-one | No | No | No | No | No | No | No |
| reaction mass of: 5-chloro- 2-methyl-4-isothiazolin- 3-one [EC no. 247-500-7] | No | No | No | No | No | No | No |

17/24

Date of issue/Date of revision : 24/02/2025 Date of previous issue : 05/09/2022 Version:5 SAFIR 20 Label No: 39081

SECTION 12: Ecological information

and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3: 1)

Mobility

: Not available.

Conclusion/Summary

: The product does not meet the criteria to be considered as a PMT or vPvM.

12.5 Results of PBT and vPvB assessment Regulation (EC) No. 1907/2006 [REACH]

| Product/ingredient name | PBT | P | В | Т | vPvB | vP | vB | |
|------------------------------|-----|----|----|----|------|----|----|--|
| Methoxy 2-propanol | No | No | No | No | No | No | No | |
| Polyether modified | No | No | No | No | No | No | No | |
| trisiloxane | | | | | | | | |
| triisobutyl phosphate | No | No | No | No | No | No | No | |
| adipohydrazide | No | No | No | No | No | No | No | |
| 1,2-benzisothiazol-3(2H)-one | No | No | No | No | No | No | No | |
| reaction mass of: 5-chloro- | No | No | No | No | No | No | No | |
| 2-methyl-4-isothiazolin- | | | | | | | | |
| 3-one [EC no. 247-500-7] | | | | | | | | |
| and 2-methyl-2H-isothiazol- | | | | | | | | |
| 3-one [EC no. 220-239-6] (3: | | | | | | | | |
| 1) | | | | | | | | |

Regulation (EC) No. 1272/2008 [CLP]

| Product/ingredient name | PBT | P | В | Т | vPvB | vP | vB | |
|--|-----|----|----|----|------|----|----|--|
| | No | No | No | No | No | No | No | |
| Polyether modified trisiloxane | No | No | No | No | No | No | No | |
| triisobutyl phosphate | No | No | No | No | No | No | No | |
| adipohydrazide | No | No | No | No | No | No | No | |
| 1,2-benzisothiazol-3(2H)-one | No | No | No | No | No | No | No | |
| reaction mass of: 5-chloro- 2-methyl-4-isothiazolin- 3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol- 3-one [EC no. 220-239-6] (3: 1) | No | No | No | No | No | No | No | |

Conclusion/Summary Regulation (EC) No. 1272/2008 [CLP]

: The product does not meet the criteria to be considered as a PBT or vPvB.

12.6 Endocrine disrupting properties

Not available.

Conclusion/Summary [Product]

: The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Date of issue/Date of revision : 24/02/2025 : 05/09/2022 Version:5 18/24 Date of previous issue

SECTION 13: Disposal considerations

Methods of disposal

: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

European waste catalogue (EWC)

: 080112, 200128

Packaging

Methods of disposal

: The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Special precautions

: This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

| | ADR/RID | ADN | IMDG | IATA |
|------------------------------------|----------------|----------------|----------------|----------------|
| 14.1 UN number or ID number | Not regulated. | Not regulated. | Not regulated. | Not regulated. |
| 14.2 UN proper shipping name | - | - | - | - |
| 14.3 Transport hazard class(es) | - | - | - | - |
| 14.4 Packing group | - | - | - | - |
| 14.5 Environmental hazards | No. | No. | No. | No. |

14.6 Special precautions for user

: **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Maritime transport in bulk according to IMO instruments

: Not relevant/applicable due to nature of the product.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Labelling :

Other EU regulations

 Date of issue/Date of revision
 : 24/02/2025
 Date of previous issue
 : 05/09/2022
 Version
 : 5
 19/24

 SAFIR 20
 Label No :39081

SECTION 15: Regulatory information

: Not listed

: Not listed

Industrial emissions (integrated pollution

prevention and control) -

Air

Industrial emissions (integrated pollution

prevention and control) -

Water

Explosive precursors : Not applicable.

Ozone depleting substances (EU 2024/590)

Not listed.

Prior Informed Consent (PIC) (649/2012/EU)

Not listed.

Persistent Organic Pollutants

Not listed.

Seveso Directive

This product is not controlled under the Seveso Directive.

National regulations

<u>Austria</u>

Limitation of the use of

organic solvents

: Permitted.

Belgium

Czech Republic

Storage code : W

Denmark

Fire class : \overline{W} -1 MAL-code : \overline{I} -3

Protection based on MAL

: According to the regulations on work involving coded products, the following stipulations apply to the use of personal protective equipment:

General: Gloves must be worn for all work that may result in soiling. Apron/coveralls/protective clothing must be worn when soiling is so great that regular work clothes do not adequately protect skin against contact with the product. A face shield must be worn in work involving spattering if a full mask is not required. In this case, other recommended use of eye protection is not required.

In all spraying operations in which there is return spray, the following must be worn: respiratory protection and arm protectors/apron/coveralls/protective clothing as appropriate or as instructed.

MAL-code: 1-3

Application: When using scraper or knife, brush, roller, etc, for pre- and post-treatments in cabins or booths of the existing* facility type, if the operator is inside the spray zone.

- Coveralls must be worn.

During downtimes, cleaning and repair in closed facilities, spray booths or cabins, if there is a risk of contact with wet paint or organic solvents.

- Gas filter mask and coveralls must be worn.

When spraying in existing* spray booths, if the operator is outside the spray zone.

- Full mask with combined filter, arm protectors and apron must be worn.

 Date of issue/Date of revision
 : 24/02/2025
 Date of previous issue
 : 05/09/2022
 Version
 : 5
 20/24

 SAFIR 20
 Label No :39081

SECTION 15: Regulatory information

During non-atomising spraying in existing* facilities of the combined-cabin, spraycabin and spray-booth type where the operator is working inside the spray zone.

- Air-supplied half mask and eye protection must be worn.

During all spraying where atomisation occurs in cabins or spray booths where the operator is inside the spray zone and during spraying outside a closed facility, cabin or booth.

Air-supplied full mask, coveralls and hood must be worn.

Drying: Items for drying/drying ovens that are temporarily placed on such things as rack trolleys, etc, must be equipped with a mechanical exhaust system to prevent fumes from wet items from passing through workers' inhalation zone.

Polishing: When polishing treated surfaces, a mask with dust filter must be worn. When machine grinding, eye protection must be worn. Work gloves must always be worn.

Caution The regulations contain other stipulations in addition to the above.

*See Regulations.

Restrictions on use

: Not to be used by professional users below 18 years of age. See the National Working Environment Authorities Executive Order regarding Young People At Work.

List of undesirable substances

: Not listed

Finland France

Social Security Code,

Articles L 461-1 to L 461-7

Reinforced medical surveillance

: 1-Methoxy 2-propanol **RG 84** triisobutyl phosphate **RG 34**

: Act of July 11, 1977 determining the list of activities which require reinforced medical surveillance: not applicable

Germany

Storage class (TRGS 510) : 10 **Hazardous incident ordinance**

This product is not controlled under the Germany Hazardous Incident Ordinance.

Hazard class for water

Technical instruction on air quality control (TA Luft)

| Number [Class] | Description | % |
|----------------|----------------------------|------|
| 5 .2.1 | Total dust | 14.7 |
| 5.2.2 [III] | Dusty inorganic substances | 0.03 |
| 5.2.5 | Organic substances | 28.8 |
| 5.2.5 [I] | Organic substances | 8.3 |

AOX

: The product contains organically bound halogens and can contribute to the AOX value in waste water.

Italy

D.Lgs. 152/06 : Not determined.

Netherlands

Water Discharge Policy

(ABM)

: A(4) Low hazard for aquatic organisms, may have long-term hazardous effects in aquatic environment. Decontamination effort: A

Norway Sweden Switzerland

VOC content : Exempt.

Date of issue/Date of revision : 24/02/2025 · 05/09/2022 21/24 Date of previous issue Version : 5 SAFIR 20 Label No: 39081

SECTION 15: Regulatory information

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

15.2 Chemical safety assessment

: This product contains substances for which Chemical Safety Assessments are still

required.

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and acronyms

: ATE = Acute Toxicity Estimate

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No.

1272/2008]

DMEL = Derived Minimal Effect Level
DNEL = Derived No Effect Level

EUH statement = CLP-specific Hazard statement

N/A = Not available

PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration RRN = REACH Registration Number

SGG = Segregation Group

vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Not classified.

Full text of abbreviated H statements

| H226 | Flammable liquid and vapour. |
|--------|---|
| H301 | Toxic if swallowed. |
| H302 | Harmful if swallowed. |
| H310 | Fatal in contact with skin. |
| H314 | Causes severe skin burns and eye damage. |
| H315 | Causes skin irritation. |
| H317 | May cause an allergic skin reaction. |
| H318 | Causes serious eye damage. |
| H319 | Causes serious eye irritation. |
| H330 | Fatal if inhaled. |
| H332 | Harmful if inhaled. |
| H336 | May cause drowsiness or dizziness. |
| H400 | Very toxic to aquatic life. |
| H410 | Very toxic to aquatic life with long lasting effects. |
| H411 | Toxic to aquatic life with long lasting effects. |
| EUH071 | Corrosive to the respiratory tract. |

Full text of classifications [CLP/GHS]

Date of issue/Date of revision : 24/02/2025 Date of previous issue : 05/09/2022 Version : 5 22/24

SECTION 16: Other information

Acute Tox. 2 **ACUTE TOXICITY - Category 2** Acute Tox. 3 **ACUTE TOXICITY - Category 3** Acute Tox. 4 **ACUTE TOXICITY - Category 4** Aquatic Acute 1 SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1 Aquatic Chronic 1 Aquatic Chronic 2 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2 Eye Dam. 1 SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1 Eye Irrit. 2 SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2 Flam. Liq. 3 FLAMMABLE LIQUIDS - Category 3 Skin Corr. 1C SKIN CORROSION/IRRITATION - Category 1C Skin Irrit. 2 SKIN CORROSION/IRRITATION - Category 2 Skin Sens. 1 SKIN SENSITISATION - Category 1 Skin Sens. 1A SKIN SENSITISATION - Category 1A Skin Sens. 1B SKIN SENSITISATION - Category 1B STOT SE 3 SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3

Date of issue/ Date of

Date of previous issue

revision

: 24/02/2025

: 05/09/2022

Version : 5

Notice to reader

The information in this SDS is based on the present state of our knowledge and on current laws. The product is not to be used for purposes other than those specified under section 1 without first obtaining written handling instructions. It is always the responsibility of the user to take all necessary steps to fulfil the demands set out in the local rules and legislation. The information in this SDS is meant to be a description of the safety requirements for our product. It is not to be considered a guarantee of the product's properties.

Date of issue/Date of revision · 05/09/2022 Version: 5 23/24 : 24/02/2025 Date of previous issue SAFIR 20 Label No: 39081

 Date of issue/Date of revision
 : 24/02/2025
 Date of previous issue
 : 05/09/2022
 Version
 : 5
 24/24

 SAFIR 20
 Label No :39081