

SAFETY DATA SHEET



SUPREMO KLARLACK 3990-25 - FARBLOS-INCOLORE-COLOURLESS

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : SUPREMO KLARLACK 3990-25 - FARBLOS-INCOLORE-COLOURLESS

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Paint.

1.3 Details of the supplier of the safety data sheet

Teknos Group Oy, Takkatie 3, FI-00370 HELSINKI, FINLAND. Tel. +358 9 506 091.

e-mail address of person responsible for this SDS : Prod-safe@teknos.com

National contact

Teknos Ireland Limited, 52 Ballymoughan Road, Magherafelt, BT45 6HN, UK. Tel. +44 (0) 2879 301 472.

1.4 Emergency telephone number

National advisory body/Poison Centre

Telephone number : NHS: 111

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Flam. Liq. 2, H225

Eye Irrit. 2, H319

Skin Sens. 1, H317

STOT SE 3, H336

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Hazard pictograms :



Signal word : Danger

Hazard statements : H225 - Highly flammable liquid and vapour.
H317 - May cause an allergic skin reaction.
H319 - Causes serious eye irritation.
H336 - May cause drowsiness or dizziness.

Precautionary statements

Prevention : P280 - Wear protective gloves. Wear eye or face protection.
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261 - Avoid breathing vapour.

Response : P304 + P312 - IF INHALED: Call a POISON CENTER or doctor if you feel unwell.

Storage : P403 + P233 - Store in a well-ventilated place. Keep container tightly closed.

Date of issue/Date of revision : 31/07/2024 **Date of previous issue** : No previous validation **Version** : 1 1/20

SUPREMO KLARLACK 3990-25 - FARBLOS-INCOLORE-COLOURLESS

Label No : 56246

SECTION 2: Hazards identification

| | |
|---|---|
| Disposal | : P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations. |
| Hazardous ingredients | : Contains: n-Butyl acetate; Ethyl acetate; EO bis(benztriazolyl)phenylpropionat and Fatty acids, C14-18 and C16-18-unsatd., maleated |
| Supplemental label elements | : |
| Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles | : |

2.3 Other hazards

| | |
|--|---|
| Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII | : This mixture does not contain any substances that are assessed to be a PBT or a vPvB. |
| Other hazards which do not result in classification | : None known. |

SECTION 3: Composition/information on ingredients

3.2 Mixtures : Mixture

| Product/ingredient name | Identifiers | % | Classification | Specific Conc. Limits, M-factors and ATEs | Type |
|---------------------------------|--|-----------|--|---|---------|
| n-Butyl acetate | REACH #: 01-2119485493-29 EC: 204-658-1 CAS: 123-86-4 Index: 607-025-00-1 | ≥25 - ≤50 | Flam. Liq. 3, H226 STOT SE 3, H336 EUH066 | - | [1] [2] |
| Ethyl acetate | REACH #: 01-2119475103-46 EC: 205-500-4 CAS: 141-78-6 Index: 607-022-00-5 | ≥10 - ≤25 | Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336 EUH066 | - | [1] [2] |
| Xylene | REACH #: 01-2119488216-32 EC: 215-535-7 CAS: 1330-20-7 Index: 601-022-00-9 | <10 | Flam. Liq. 3, H226 Acute Tox. 4, H312 Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 STOT RE 2, H373 (oral, inhalation) Asp. Tox. 1, H304 | ATE [Dermal] = 1100 mg/kg ATE [Inhalation (vapours)] = 11 mg/ l | [1] [2] |
| 2-Methoxy-1-methylethyl acetate | REACH #: 01-2119475791-29 EC: 203-603-9 CAS: 108-65-6 Index: 607-195-00-7 | ≤5 | Flam. Liq. 3, H226 | - | [2] |
| Ethylbenzene | REACH #: 01-2119489370-35 EC: 202-849-4 CAS: 100-41-4 Index: 601-023-00-4 | ≤3 | Flam. Liq. 2, H225 Acute Tox. 4, H332 STOT RE 2, H373 (hearing organs) (oral, inhalation) Asp. Tox. 1, H304 | ATE [Inhalation (vapours)] = 11 mg/ l | [1] [2] |
| EO bis(benztriazolyl) | REACH #: | ≤0.3 | Skin Sens. 1A, H317 | - | [1] |

Date of issue/Date of revision : 31/07/2024 Date of previous issue : No previous validation Version : 1 2/20

SUPREMO KLARLACK 3990-25 - FARBLOS-INCOLORE-COLOURLESS

Label No : 56246

SECTION 3: Composition/information on ingredients

| | | | | | |
|--|---|------|---|--|---------|
| phenylpropionat | 01-0000015075-76 EC: 400-830-7 CAS: 104810-48-2 Index: 607-176-00-3 | | Aquatic Chronic 2, H411 | | |
| Fatty acids, C14-18 and C16-18-unsatd., maleated | REACH #: 01-2119976378-19 EC: 288-306-2 CAS: 85711-46-2 | ≤0.3 | Skin Irrit. 2, H315 Skin Sens. 1, H317 | - | [1] |
| Methyl methacrylate | REACH #: 01-2119452498-28 EC: 201-297-1 CAS: 80-62-6 Index: 607-035-00-6 | ≤0.3 | Flam. Liq. 2, H225 Skin Irrit. 2, H315 Skin Sens. 1, H317 STOT SE 3, H335 | - | [1] [2] |
| methanol | REACH #: 01-2119433307-44 EC: 200-659-6 CAS: 67-56-1 Index: 603-001-00-X | <0.1 | Flam. Liq. 2, H225 Acute Tox. 3, H301 Acute Tox. 3, H311 Acute Tox. 3, H331 STOT SE 1, H370 | ATE [Oral] = 100 mg/kg ATE [Dermal] = 300 mg/kg ATE [Inhalation (vapours)] = 3 mg/l STOT SE 1, H370: C ≥ 10% STOT SE 2, H371: 3% ≤ C < 10% | [1] [2] |
| Toluene | REACH #: 01-2119471310-51 EC: 203-625-9 CAS: 108-88-3 Index: 601-021-00-3 | ≤0.1 | Flam. Liq. 2, H225 Skin Irrit. 2, H315 Repr. 2, H361d STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304 | - | [1] [2] |
| Maleic anhydride | REACH #: 01-2119472428-31 EC: 203-571-6 CAS: 108-31-6 Index: 607-096-00-9 | ≤0.1 | Acute Tox. 4, H302 Skin Corr. 1B, H314 Eye Dam. 1, H318 Resp. Sens. 1, H334 Skin Sens. 1A, H317 STOT RE 1, H372 (respiratory system) (inhalation) EUH071 | ATE [Oral] = 400 mg/kg Skin Sens. 1, H317: C ≥ 0.001% | [1] [2] |
| cumene | EC: 202-704-5 CAS: 98-82-8 Index: 601-024-00-X | <0.1 | Flam. Liq. 3, H226 Carc. 1B, H350 STOT SE 3, H335 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 | - | [1] [2] |
| benzene | EC: 200-753-7 CAS: 71-43-2 Index: 601-020-00-8 | <0.1 | Flam. Liq. 2, H225 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Muta. 1B, H340 Carc. 1A, H350 STOT RE 1, H372 Asp. Tox. 1, H304 Aquatic Chronic 3, H412 See Section 16 for the full text of the H statements declared above. | - | [1] [2] |

SECTION 3: Composition/information on ingredients

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Skin contact** : Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. If necessary, call a poison center or physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:
pain or irritation
watering
redness
- Inhalation** : Adverse symptoms may include the following:
nausea or vomiting
headache
drowsiness/fatigue
dizziness/vertigo
unconsciousness
- Skin contact** : Adverse symptoms may include the following:
irritation
redness
- Ingestion** : No specific data.

4.3 Indication of any immediate medical attention and special treatment needed

Date of issue/*Date of revision* : 31/07/2024 *Date of previous issue* : No previous validation *Version* : 1 4/20

SUPREMO KLARLACK 3990-25 - FARBLOS-INCOLORE-COLOURLESS

Label No : 56246

SECTION 4: First aid measures

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media** : Use dry chemical, CO₂, water spray (fog) or foam.
- Unsuitable extinguishing media** : Do not use water jet.

5.2 Special hazards arising from the substance or mixture

- Hazards from the substance or mixture** : Highly flammable liquid and vapour. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion.
- Hazardous combustion products** : Decomposition products may include the following materials:
carbon dioxide
carbon monoxide

5.3 Advice for firefighters

- Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions

- : Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

6.3 Methods and material for containment and cleaning up

- Small spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

SECTION 6: Accidental release measures

Large spill : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product.

6.4 Reference to other sections : See Section 1 for emergency contact information.
See Section 8 for information on appropriate personal protective equipment.
See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

Protective measures : Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapour or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Eliminate all ignition sources. Separate from oxidising materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

Seveso Directive - Reporting thresholds

Danger criteria

| Category | Notification and MAPP threshold | Safety report threshold |
|----------|---------------------------------|-------------------------|
| P5c | 5000 tonne | 50000 tonne |

7.3 Specific end use(s)

Recommendations : Not available.

Industrial sector specific solutions : Not available.

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

8.1 Control parameters

Occupational exposure limits

| Product/ingredient name | Exposure limit values |
|---------------------------------|---|
| n-Butyl acetate | EH40/2005 WELs (United Kingdom (UK), 1/2020). STEL: 966 mg/m ³ 15 minutes. STEL: 200 ppm 15 minutes. TWA: 724 mg/m ³ 8 hours. TWA: 150 ppm 8 hours. |
| Ethyl acetate | EH40/2005 WELs (United Kingdom (UK), 1/2020). STEL: 400 ppm 15 minutes. TWA: 200 ppm 8 hours. STEL: 1468 mg/m ³ 15 minutes. TWA: 734 mg/m ³ 8 hours. |
| Xylene | EH40/2005 WELs (United Kingdom (UK), 1/2020). [xylene, o-,m-, p- or mixed isomers] Absorbed through skin. STEL: 441 mg/m ³ 15 minutes. TWA: 50 ppm 8 hours. TWA: 220 mg/m ³ 8 hours. STEL: 100 ppm 15 minutes. |
| 2-Methoxy-1-methylethyl acetate | EH40/2005 WELs (United Kingdom (UK), 1/2020). Absorbed through skin. STEL: 548 mg/m ³ 15 minutes. TWA: 50 ppm 8 hours. TWA: 274 mg/m ³ 8 hours. STEL: 100 ppm 15 minutes. |
| Ethylbenzene | EH40/2005 WELs (United Kingdom (UK), 1/2020). Absorbed through skin. STEL: 552 mg/m ³ 15 minutes. STEL: 125 ppm 15 minutes. TWA: 100 ppm 8 hours. TWA: 441 mg/m ³ 8 hours. |
| Methyl methacrylate | EH40/2005 WELs (United Kingdom (UK), 1/2020). STEL: 416 mg/m ³ 15 minutes. STEL: 100 ppm 15 minutes. TWA: 208 mg/m ³ 8 hours. TWA: 50 ppm 8 hours. |
| methanol | EH40/2005 WELs (United Kingdom (UK), 1/2020). Absorbed through skin. STEL: 333 mg/m ³ 15 minutes. STEL: 250 ppm 15 minutes. TWA: 266 mg/m ³ 8 hours. TWA: 200 ppm 8 hours. |
| Toluene | EH40/2005 WELs (United Kingdom (UK), 1/2020). Absorbed through skin. STEL: 384 mg/m ³ 15 minutes. TWA: 191 mg/m ³ 8 hours. TWA: 50 ppm 8 hours. STEL: 100 ppm 15 minutes. |
| Maleic anhydride | EH40/2005 WELs (United Kingdom (UK), 1/2020). Inhalation sensitiser. STEL: 3 mg/m ³ 15 minutes. TWA: 1 mg/m ³ 8 hours. |
| cumene | EH40/2005 WELs (United Kingdom (UK), 1/2020). Absorbed through skin. STEL: 250 mg/m ³ 15 minutes. STEL: 50 ppm 15 minutes. TWA: 25 ppm 8 hours. TWA: 125 mg/m ³ 8 hours. |
| benzene | EH40/2005 WELs (United Kingdom (UK), 1/2020). Absorbed |

SECTION 8: Exposure controls/personal protection

through skin.

TWA: 1 ppm 8 hours.

TWA: 3.25 mg/m³ 8 hours.

Biological exposure indices

| Product/ingredient name | Exposure indices |
|-------------------------|--|
| Xylene | EH40/2005 BMGVs (United Kingdom (UK), 8/2018) [Xylene, o-, m-, p- or mixed isomers] BGV: 650 mmol/mol creatinine, methyl hippuric acid [in urine]. Sampling time: post shift. |

Recommended monitoring procedures : Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

| Product/ingredient name | Type | Exposure | Value | Population | Effects |
|-------------------------|------|-----------------------|------------------------|--------------------|----------|
| n-Butyl acetate | DNEL | Short term Oral | 2 mg/kg bw/day | General population | Systemic |
| | DNEL | Long term Oral | 2 mg/kg bw/day | General population | Systemic |
| | DNEL | Short term Dermal | 6 mg/kg bw/day | General population | Systemic |
| | DNEL | Short term Dermal | 11 mg/kg bw/day | Workers | Systemic |
| | DNEL | Long term Inhalation | 35.7 mg/m ³ | General population | Local |
| | DNEL | Short term Inhalation | 300 mg/m ³ | General population | Local |
| | DNEL | Short term Inhalation | 300 mg/m ³ | General population | Systemic |
| | DNEL | Long term Inhalation | 300 mg/m ³ | Workers | Local |
| | DNEL | Short term Inhalation | 600 mg/m ³ | Workers | Local |
| | DNEL | Short term Inhalation | 600 mg/m ³ | Workers | Systemic |
| | DNEL | Long term Dermal | 3.4 mg/kg bw/day | General population | Systemic |
| | DNEL | Long term Dermal | 7 mg/kg bw/day | Workers | Systemic |
| | DNEL | Long term Inhalation | 12 mg/m ³ | General population | Systemic |
| | DNEL | Long term Inhalation | 48 mg/m ³ | Workers | Systemic |
| Ethyl acetate | DNEL | Long term Oral | 4.5 mg/kg bw/day | General population | Systemic |
| | DNEL | Long term Dermal | 37 mg/kg bw/day | General population | Systemic |
| | DNEL | Long term Dermal | 63 mg/kg bw/day | Workers | Systemic |
| | DNEL | Long term Inhalation | 367 mg/m ³ | General population | Local |
| | DNEL | Long term Inhalation | 367 mg/m ³ | General population | Systemic |
| | DNEL | Short term Inhalation | 734 mg/m ³ | General population | Local |
| | DNEL | Short term Inhalation | 734 mg/m ³ | General population | Local |
| | DNEL | Short term Inhalation | 734 mg/m ³ | General | Systemic |

SECTION 8: Exposure controls/personal protection

| | | | | | | |
|---------------------|---|--------------------------|----------------------------|-----------------------|-----------------------|----------|
| Xylene | DNEL | Inhalation Long term | 734 mg/m ³ | population Workers | Local | |
| | DNEL | Inhalation Long term | 734 mg/m ³ | Workers | Systemic | |
| | DNEL | Inhalation Short term | 1468 mg/ m ³ | Workers | Local | |
| | DNEL | Inhalation Short term | 1468 mg/ m ³ | Workers | Systemic | |
| | DNEL | Inhalation Long term | 65.3 mg/m ³ | General population | Local | |
| | DNEL | Inhalation Short term | 260 mg/m ³ | General population | Local | |
| | DNEL | Inhalation Short term | 260 mg/m ³ | General population | Systemic | |
| | DNEL | Inhalation Long term | 221 mg/m ³ | Workers | Local | |
| | DNEL | Inhalation Long term | 12.5 mg/ kg bw/day | General population | Systemic | |
| | DNEL | Oral Long term | 65.3 mg/m ³ | General population | Systemic | |
| | DNEL | Dermal Long term | 125 mg/kg bw/day | General population | Systemic | |
| | DNEL | Dermal Long term | 212 mg/kg bw/day | Workers | Systemic | |
| | DNEL | Inhalation Long term | 221 mg/m ³ | Workers | Systemic | |
| | DNEL | Inhalation Short term | 442 mg/m ³ | Workers | Local | |
| | DNEL | Inhalation Short term | 442 mg/m ³ | Workers | Systemic | |
| | 2-Methoxy-1-methylethyl acetate | DNEL | Inhalation Long term | 33 mg/m ³ | General population | Local |
| | | DNEL | Inhalation Long term | 33 mg/m ³ | General population | Systemic |
| | | DNEL | Oral Long term | 36 mg/kg bw/day | General population | Systemic |
| DNEL | | Inhalation Long term | 275 mg/m ³ | Workers | Systemic | |
| DNEL | | Dermal Long term | 320 mg/kg bw/day | General population | Systemic | |
| DNEL | | Inhalation Short term | 550 mg/m ³ | Workers | Local | |
| DNEL | | Dermal Long term | 796 mg/kg bw/day | Workers | Systemic | |
| Ethylbenzene | | DNEL | Oral Long term | 1.6 mg/kg bw/day | General population | Systemic |
| | | DNEL | Inhalation Long term | 15 mg/m ³ | General population | Systemic |
| | | DNEL | Inhalation Long term | 77 mg/m ³ | Workers | Systemic |
| | DNEL | Dermal Long term | 180 mg/kg bw/day | Workers | Systemic | |
| | DNEL | Inhalation Short term | 293 mg/m ³ | Workers | Local | |
| | DMEL | Inhalation Long term | 442 mg/m ³ | Workers | Local | |
| | DMEL | Inhalation Short term | 884 mg/m ³ | Workers | Systemic | |
| | Fatty acids, C14-18 and C16-18-unsatd., maleated | DNEL | Oral Long term | 1.5 mg/kg bw/day | General population | Systemic |
| DNEL | | Dermal Long term | 1.5 mg/kg bw/day | General population | Systemic | |
| DNEL | | Dermal Long term | 3 mg/kg bw/day | Workers | Systemic | |
| Methyl methacrylate | DNEL | Oral Long term | 8.2 mg/kg | General | Systemic | |

SECTION 8: Exposure controls/personal protection

| | | | | | |
|------------------|------------------|-----------------------|---------------------------------|----------------------------------|----------|
| Maleic anhydride | DNEL | Short term Inhalation | bw/day 208 mg/m ³ | population General population | Local |
| | DNEL | Short term Inhalation | 416 mg/m ³ | Workers | Local |
| | DNEL | Short term Dermal | 1.5 mg/cm ² | General population | Local |
| | DNEL | Long term Dermal | 1.5 mg/cm ² | General population | Local |
| | DNEL | Short term Dermal | 1.5 mg/cm ² | Workers | Local |
| | DNEL | Long term Dermal | 1.5 mg/cm ² | Workers | Local |
| | DNEL | Long term Dermal | 8.2 mg/kg bw/day | General population | Systemic |
| | DNEL | Long term Dermal | 13.67 mg/kg bw/day | Workers | Systemic |
| | DNEL | Long term Inhalation | 74.3 mg/m ³ | General population | Systemic |
| | DNEL | Long term Inhalation | 104 mg/m ³ | General population | Local |
| | DNEL | Long term Inhalation | 208 mg/m ³ | Workers | Local |
| | DNEL | Long term Inhalation | 348.4 mg/m ³ | Workers | Systemic |
| | DNEL | Long term Inhalation | 0.081 mg/m ³ | Workers | Local |
| | DNEL | Long term Inhalation | 0.081 mg/m ³ | Workers | Systemic |
| | DNEL | Short term Inhalation | 0.2 mg/m ³ | Workers | Local |
| | DNEL | Short term Inhalation | 0.2 mg/m ³ | Workers | Systemic |
| | DNEL | Long term Inhalation | 0.05 mg/m ³ | General population | Systemic |
| | DNEL | Long term Oral | 0.06 mg/kg bw/day | General population | Systemic |
| | DNEL | Long term Inhalation | 0.08 mg/m ³ | General population | Local |
| | DNEL | Short term Oral | 0.1 mg/kg bw/day | General population | Systemic |
| | DNEL | Short term Dermal | 0.1 mg/kg bw/day | General population | Systemic |
| | DNEL | Long term Dermal | 0.1 mg/kg bw/day | General population | Systemic |
| | DNEL | Short term Dermal | 0.2 mg/kg bw/day | Workers | Systemic |
| DNEL | Long term Dermal | 0.2 mg/kg bw/day | Workers | Systemic | |

PNECs

No PNECs available

8.2 Exposure controls

Appropriate engineering controls

: Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Individual protection measures

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

SECTION 8: Exposure controls/personal protection

- Eye/face protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.
- Skin protection**
- Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
- Recommendations : Wear suitable gloves tested to EN374.
< 1 hour (breakthrough time): Nitrile gloves. thickness > 0.3 mm
1 - 4 hours (breakthrough time): 4H / Silver Shield® gloves.
- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves. Refer to European Standard EN 1149 for further information on material and design requirements and test methods.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.
- Filter type: A
Filter type (spray application): A P
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

Appearance

- Physical state** : Liquid.
- Colour** : Various
- Odour** : Slight
- Odour threshold** : Not available.
- Melting point/freezing point** : Not available.
- Initial boiling point and boiling range** :

| Ingredient name | °C | °F | Method |
|-----------------|------|-------|----------|
| Ethyl acetate | 77.1 | 170.8 | |
| n-Butyl acetate | 126 | 258.8 | OECD 103 |

- Flammability** : Not available.
- Lower and upper explosion limit** : Lower: 0.8% (xylene)
Upper: 11.5% (ethyl acetate)
- Flash point** : Closed cup: -1°C (30.2°F)

Date of issue/Date of revision : 31/07/2024 **Date of previous issue** : No previous validation **Version** : 1 **11/20**

SUPREMO KLARLACK 3990-25 - FARBLOS-INCOLORE-COLOURLESS

Label No :56246

SECTION 9: Physical and chemical properties

Auto-ignition temperature :

| Ingredient name | °C | °F | Method |
|---------------------------------|-----|-------|-----------|
| 2-Methoxy-1-methylethyl acetate | 333 | 631.4 | DIN 51794 |
| n-Butyl acetate | 415 | 779 | EU A.15 |

Decomposition temperature : Not available.

pH : Not available.

Viscosity : Not available.

Solubility(ies) :

Not available.

Solubility in water : Not available.

Partition coefficient: n-octanol/ water : Not applicable.

Vapour pressure :

| Ingredient name | Vapour Pressure at 20°C | | | Vapour pressure at 50°C | | |
|-----------------|-------------------------|------|----------------|-------------------------|-----|--------|
| | mm Hg | kPa | Method | mm Hg | kPa | Method |
| Ethyl acetate | 81.59163 | 10.9 | | | | |
| n-Butyl acetate | 11.25096 | 1.5 | DIN EN 13016-2 | | | |

Relative density : Not available.

Density : 0.9 g/cm³

Vapour density : Not available.

Explosive properties : Not available.

Oxidising properties : Not available.

Particle characteristics

Median particle size : Not applicable.

SECTION 10: Stability and reactivity

10.1 Reactivity : No specific test data related to reactivity available for this product or its ingredients.

10.2 Chemical stability : The product is stable.

10.3 Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will not occur.

10.4 Conditions to avoid : Avoid all possible sources of ignition (spark or flame). Do not pressurise, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.

10.5 Incompatible materials : Reactive or incompatible with the following materials:
oxidising materials

10.6 Hazardous decomposition products : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

SECTION 11: Toxicological information

| Product/ingredient name | Result | Species | Dose | Exposure |
|---------------------------------|---------------------------------|---------|-------------------------|----------|
| n-Butyl acetate | LC50 Inhalation Vapour | Rat | 0.74 mg/l | 4 hours |
| | LD50 Dermal | Rabbit | 14112 mg/kg | - |
| | LD50 Oral | Rat | 10760 mg/kg | - |
| Ethyl acetate | LD50 Oral | Rat | 5620 mg/kg | - |
| Xylene | LC50 Inhalation Vapour | Rat | 21.7 mg/l | 4 hours |
| | LD50 Oral | Rat | 4300 mg/kg | - |
| 2-Methoxy-1-methylethyl acetate | LD50 Dermal | Rabbit | >5 g/kg | - |
| Ethylbenzene | LD50 Oral | Rat | 8532 mg/kg | - |
| | LC50 Inhalation Dusts and mists | Rat | 29000 mg/l | 4 hours |
| | LD50 Dermal | Rabbit | 15400 mg/kg | - |
| Methyl methacrylate | LD50 Oral | Rat | 3500 mg/kg | - |
| | LC50 Inhalation Vapour | Rat | 78000 mg/m ³ | 4 hours |
| | LD50 Dermal | Rabbit | >5 g/kg | - |
| Maleic anhydride | LD50 Oral | Rat | 7872 mg/kg | - |
| | LD50 Dermal | Rabbit | 2620 mg/kg | - |
| | LD50 Oral | Rat | 400 mg/kg | - |

Conclusion/Summary : Based on available data, the classification criteria are not met.

Acute toxicity estimates

| Route | ATE value |
|----------------------|----------------|
| Dermal | 13244.31 mg/kg |
| Inhalation (vapours) | 105.71 mg/l |

Irritation/Corrosion

| Product/ingredient name | Result | Species | Score | Exposure | Observation |
|-------------------------|--------------------------|------------------------|--------|-----------------|-------------|
| n-Butyl acetate | Eyes - Moderate irritant | Rabbit | - | 100 mg | - |
| | Skin - Moderate irritant | Rabbit | - | 24 hours 500 mg | - |
| Xylene | Eyes - Mild irritant | Rabbit | - | 87 mg | - |
| | Eyes - Severe irritant | Rabbit | - | 24 hours 5 mg | - |
| | Skin - Mild irritant | Rat | - | 8 hours 60 uL | - |
| | Skin - Moderate irritant | Rabbit | - | 100 % | - |
| | Skin - Moderate irritant | Rabbit | - | 24 hours 500 mg | - |
| | Ethylbenzene | Eyes - Severe irritant | Rabbit | - | 500 mg |
| Ethylbenzene | Skin - Mild irritant | Rabbit | - | 24 hours 15 mg | - |
| | | | | | |
| Maleic anhydride | Eyes - Severe irritant | Rabbit | - | 1 % | - |

Conclusion/Summary : Based on available data, the classification criteria are not met.

Sensitisation

Conclusion/Summary : May cause an allergic skin reaction.

Mutagenicity

Conclusion/Summary : Based on available data, the classification criteria are not met.

Carcinogenicity

Conclusion/Summary : Based on available data, the classification criteria are not met.

Reproductive toxicity

Conclusion/Summary : Based on available data, the classification criteria are not met.

Teratogenicity

Conclusion/Summary : Based on available data, the classification criteria are not met.

Specific target organ toxicity (single exposure)

SECTION 11: Toxicological information

| Product/ingredient name | Category | Route of exposure | Target organs |
|-------------------------|------------|-------------------|------------------------------|
| n-Butyl acetate | Category 3 | - | Narcotic effects |
| Ethyl acetate | Category 3 | - | Narcotic effects |
| Xylene | Category 3 | - | Respiratory tract irritation |
| Methyl methacrylate | Category 3 | - | Respiratory tract irritation |

Specific target organ toxicity (repeated exposure)

| Product/ingredient name | Category | Route of exposure | Target organs |
|-------------------------|------------|-------------------|--------------------|
| Xylene | Category 2 | oral, inhalation | - |
| Ethylbenzene | Category 2 | oral, inhalation | hearing organs |
| Maleic anhydride | Category 1 | inhalation | respiratory system |

Aspiration hazard

| Product/ingredient name | Result |
|-------------------------|--------------------------------|
| Xylene | ASPIRATION HAZARD - Category 1 |
| Ethylbenzene | ASPIRATION HAZARD - Category 1 |

Information on likely routes of exposure : Not available.

Potential acute health effects

- Eye contact** : Causes serious eye irritation.
- Inhalation** : Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness.
- Skin contact** : May cause an allergic skin reaction.
- Ingestion** : Can cause central nervous system (CNS) depression.

Symptoms related to the physical, chemical and toxicological characteristics

- Eye contact** : Adverse symptoms may include the following:
pain or irritation
watering
redness
- Inhalation** : Adverse symptoms may include the following:
nausea or vomiting
headache
drowsiness/fatigue
dizziness/vertigo
unconsciousness
- Skin contact** : Adverse symptoms may include the following:
irritation
redness
- Ingestion** : No specific data.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Short term exposure

- Potential immediate effects** : Not available.
- Potential delayed effects** : Not available.

Long term exposure

- Potential immediate effects** : Not available.
- Potential delayed effects** : Not available.

Potential chronic health effects

SECTION 11: Toxicological information

Not available.

- Conclusion/Summary** : Not available.
- General** : Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
- Carcinogenicity** : No known significant effects or critical hazards.
- Mutagenicity** : No known significant effects or critical hazards.
- Reproductive toxicity** : No known significant effects or critical hazards.

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

Not available.

11.2.2 Other information

Not available.

SECTION 12: Ecological information

12.1 Toxicity

| Product/ingredient name | Result | Species | Exposure |
|-------------------------|-------------------------------------|--|----------|
| n-Butyl acetate | Acute LC50 32 mg/l Marine water | Crustaceans - <i>Artemia salina</i> | 48 hours |
| Ethyl acetate | Acute LC50 18000 µg/l Fresh water | Fish - <i>Pimephales promelas</i> | 96 hours |
| | Acute EC50 2500000 µg/l Fresh water | Algae - <i>Selenastrum sp.</i> | 96 hours |
| | Acute LC50 750000 µg/l Fresh water | Crustaceans - <i>Gammarus pulex</i> | 48 hours |
| | Acute LC50 154000 µg/l Fresh water | Daphnia - <i>Daphnia cucullata</i> | 48 hours |
| | Acute LC50 212500 µg/l Fresh water | Fish - <i>Heteropneustes fossilis</i> | 96 hours |
| | Chronic NOEC 12 mg/l Fresh water | Daphnia - <i>Daphnia magna</i> | 21 days |
| Methyl methacrylate | Chronic NOEC 75.6 mg/l Fresh water | Fish - <i>Pimephales promelas</i> - Embryo | 32 days |
| | Acute LC50 130000 µg/l Fresh water | Fish - <i>Pimephales promelas</i> - Adult | 96 hours |
| Maleic anhydride | Acute LC50 230000 µg/l Fresh water | Fish - <i>Gambusia affinis</i> - Adult | 96 hours |

Conclusion/Summary : Based on available data, the classification criteria are not met.

12.2 Persistence and degradability

Conclusion/Summary : This product has not been tested for biodegradation.

12.3 Bioaccumulative potential

| Product/ingredient name | LogP _{ow} | BCF | Potential |
|---------------------------------|--------------------|-------------|-----------|
| n-Butyl acetate | 2.3 | - | Low |
| Ethyl acetate | 0.68 | 30 | Low |
| Xylene | 3.12 | 8.1 to 25.9 | Low |
| 2-Methoxy-1-methylethyl acetate | 1.2 | - | Low |
| Ethylbenzene | 3.6 | - | Low |
| Methyl methacrylate | 1.38 | - | Low |
| Maleic anhydride | -2.78 | - | Low |

12.4 Mobility in soil

Soil/water partition coefficient (K_{oc}) : Not available.

Mobility : Not available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

SECTION 12: Ecological information

12.6 Endocrine disrupting properties

Not available.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.





European waste catalogue (EWC) : 08.01.11

Packaging

Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Special precautions : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapour from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

| | ADR/RID | ADN | IMDG | IATA |
|---------------------------------|--|--|---|--|
| 14.1 UN number or ID number | UN1993 | UN1993 | UN1993 | UN1993 |
| 14.2 UN proper shipping name | FLAMMABLE LIQUID, N.O.S. (n-butyl acetate, ethyl acetate) | FLAMMABLE LIQUID, N.O.S. (n-butyl acetate, ethyl acetate) | FLAMMABLE LIQUID, N.O.S. (ethyl acetate, xylene) | FLAMMABLE LIQUID, N.O.S. (ethyl acetate, xylene) |
| 14.3 Transport hazard class(es) | 3  | 3  | 3  | 3  |
| 14.4 Packing group | II | II | II | II |
| 14.5 Environmental hazards | No. | Yes. | No. | No. |

Additional information

ADR/RID : **Special provisions** 640 (C)
Tunnel code (D/E)

ADN : The product is only regulated as an environmentally hazardous substance when transported in tank vessels.
Special provisions 640 (C)

SECTION 14: Transport information

14.6 Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Maritime transport in bulk according to IMO instruments : Not relevant/applicable due to nature of the product.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

| Product/ingredient name | % | Designation [Usage] |
|--------------------------|-----|---------------------|
| SUPREMO KLARLACK 3990-25 | ≥90 | 3 |

Labelling :

Other EU regulations

Industrial emissions (integrated pollution prevention and control) - Air : Not listed

Industrial emissions (integrated pollution prevention and control) - Water : Not listed

Explosive precursors : Not applicable.

Ozone depleting substances (1005/2009/EU)

Not listed.

Prior Informed Consent (PIC) (649/2012/EU)

Not listed.

Persistent Organic Pollutants

Not listed.

Seveso Directive

This product is controlled under the Seveso Directive.

Danger criteria

| Category |
|----------|
| P5c |

National regulations

| Product/ingredient name | List name | Name on list | Classification | Notes |
|-------------------------|--|-----------------|----------------|-------|
| benzene | UK Occupational Exposure Limits EH40 - WEL | benzene; benzol | Carc. | - |

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

SECTION 15: Regulatory information

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

15.2 Chemical safety assessment

: This product contains substances for which Chemical Safety Assessments are still required.

SECTION 16: Other information

✔ Indicates information that has changed from previously issued version.

Abbreviations and acronyms

: ATE = Acute Toxicity Estimate
CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
DMEL = Derived Minimal Effect Level
DNEL = Derived No Effect Level
EUH statement = CLP-specific Hazard statement
N/A = Not available
PBT = Persistent, Bioaccumulative and Toxic
PNEC = Predicted No Effect Concentration
RRN = REACH Registration Number
SGG = Segregation Group
vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

| Classification | Justification |
|---|---|
| Flam. Liq. 2, H225 Eye Irrit. 2, H319 Skin Sens. 1, H317 STOT SE 3, H336 | On basis of test data Calculation method Calculation method Calculation method |

Full text of abbreviated H statements

| | |
|-------|--|
| H225 | Highly flammable liquid and vapour. |
| H226 | Flammable liquid and vapour. |
| H301 | Toxic if swallowed. |
| H302 | Harmful if swallowed. |
| H304 | May be fatal if swallowed and enters airways. |
| H311 | Toxic in contact with skin. |
| H312 | Harmful in contact with skin. |
| H314 | Causes severe skin burns and eye damage. |
| H315 | Causes skin irritation. |
| H317 | May cause an allergic skin reaction. |
| H318 | Causes serious eye damage. |
| H319 | Causes serious eye irritation. |
| H331 | Toxic if inhaled. |
| H332 | Harmful if inhaled. |
| H334 | May cause allergy or asthma symptoms or breathing difficulties if inhaled. |
| H335 | May cause respiratory irritation. |
| H336 | May cause drowsiness or dizziness. |
| H340 | May cause genetic defects. |
| H350 | May cause cancer. |
| H361d | Suspected of damaging the unborn child. |
| H370 | Causes damage to organs. |
| H372 | Causes damage to organs through prolonged or repeated exposure. |
| H373 | May cause damage to organs through prolonged or repeated exposure. |
| H411 | Toxic to aquatic life with long lasting effects. |

Date of issue/Date of revision : 31/07/2024 Date of previous issue : No previous validation Version : 1 18/20

SUPREMO KLARLACK 3990-25 - FARBLOS-INCOLORE-COLOURLESS

Label No :56246

SECTION 16: Other information

| | |
|--------|---|
| H412 | Harmful to aquatic life with long lasting effects. |
| EUH066 | Repeated exposure may cause skin dryness or cracking. |
| EUH071 | Corrosive to the respiratory tract. |

[Full text of classifications \[CLP/GHS\]](#)

| | |
|-------------------|---|
| Acute Tox. 3 | ACUTE TOXICITY - Category 3 |
| Acute Tox. 4 | ACUTE TOXICITY - Category 4 |
| Aquatic Chronic 2 | LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2 |
| Aquatic Chronic 3 | LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3 |
| Asp. Tox. 1 | ASPIRATION HAZARD - Category 1 |
| Carc. 1A | CARCINOGENICITY - Category 1A |
| Carc. 1B | CARCINOGENICITY - Category 1B |
| Eye Dam. 1 | SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1 |
| Eye Irrit. 2 | SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2 |
| Flam. Liq. 2 | FLAMMABLE LIQUIDS - Category 2 |
| Flam. Liq. 3 | FLAMMABLE LIQUIDS - Category 3 |
| Muta. 1B | GERM CELL MUTAGENICITY - Category 1B |
| Repr. 2 | REPRODUCTIVE TOXICITY - Category 2 |
| Resp. Sens. 1 | RESPIRATORY SENSITISATION - Category 1 |
| Skin Corr. 1B | SKIN CORROSION/IRRITATION - Category 1B |
| Skin Irrit. 2 | SKIN CORROSION/IRRITATION - Category 2 |
| Skin Sens. 1 | SKIN SENSITISATION - Category 1 |
| Skin Sens. 1A | SKIN SENSITISATION - Category 1A |
| STOT RE 1 | SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 1 |
| STOT RE 2 | SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 2 |
| STOT SE 1 | SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 1 |
| STOT SE 3 | SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3 |

Date of issue/ Date of revision : 31/07/2024

Date of previous issue : No previous validation

Version : 1

SUPREMO KLARLACK 3990-25_FARBLOS-
INCOLORE-COLOURLESS

FARBLOS-INCOLORE-COLOURLESS

[Notice to reader](#)

The information in this SDS is based on the present state of our knowledge and on current laws. The product is not to be used for purposes other than those specified under section 1 without first obtaining written handling instructions. It is always the responsibility of the user to take all necessary steps to fulfil the demands set out in the local rules and legislation. The information in this SDS is meant to be a description of the safety requirements for our product. It is not to be considered a guarantee of the product's properties.

Date of issue/Date of revision : 31/07/2024 **Date of previous issue** : No previous validation **Version** : 1 **19/20**

SUPREMO KLARLACK 3990-25 - FARBLOS-INCOLORE-COLOURLESS

Label No :56246

