

# SAFETY DATA SHEET



TEKNOCRYL AQUA 2935-20 - All variants

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

**Product name** : TEKNOCRYL AQUA 2935-20 - All variants

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Product use** : Paint.

### 1.3 Details of the supplier of the safety data sheet

Teknos Group Oy, Takkatie 3, FI-00370 HELSINKI, FINLAND. Tel. +358 9 506 091.

**e-mail address of person responsible for this SDS** : Prod-safe@teknos.com

#### National contact

Teknos Group Oy, Takkatie 3, FI-00370 HELSINKI, FINLAND. Tel. +358 9 506 091.

### 1.4 Emergency telephone number

#### National advisory body/Poison Centre

**Telephone number** : In an emergency, call 112

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

**Product definition** : Mixture

#### Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Aquatic Chronic 3, H412

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

### 2.2 Label elements

**Signal word** : No signal word.

**Hazard statements** : H412 - Harmful to aquatic life with long lasting effects.

#### Precautionary statements

**Prevention** : P273 - Avoid release to the environment.

**Response** : Not applicable.

**Storage** : Not applicable.

**Disposal** : P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.

**Supplemental label elements** : Contains 2,4,7,9-tetramethyl-5-decyne-4,7-diol, adipohydrazide and 2-methyl-2H-isothiazol-3-one. May produce an allergic reaction.

**Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles** :

### 2.3 Other hazards

**Date of issue/Date of revision** : 09/10/2024 **Date of previous issue** : 09/10/2024

**Version** : 1.01 1/22

TEKNOCRYL AQUA 2935-20 - All variants

**Label No** : 40924

## SECTION 2: Hazards identification

**Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII** : This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

**Other hazards which do not result in classification** : None known.

## SECTION 3: Composition/information on ingredients

**3.2 Mixtures** : Mixture

Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Type
2-Butoxyethanol	REACH #: 01-2119475108-36 EC: 203-905-0 CAS: 111-76-2 Index: 603-014-00-0	≤5	Acute Tox. 4, H302 Acute Tox. 3, H331 Skin Irrit. 2, H315 Eye Irrit. 2, H319	ATE [Oral] = 1200 mg/kg ATE [Inhalation (vapours)] = 3 mg/l	[1] [2]
Trizinc bis(orthophosphate)	REACH #: 01-2119485044-40 EC: 231-944-3 CAS: 7779-90-0 Index: 030-011-00-6	<2.5	Aquatic Acute 1, H400 Aquatic Chronic 1, H410	M [Acute] = 1 M [Chronic] = 1	[1]
Silanamine, 1,1,1-trimethyl-N-(trimethylsilyl)-, hydrolysis products with silica	EC: 272-697-1 CAS: 68909-20-6 Index: 014-052-00-7	≤3	STOT RE 2, H373 (lungs) (inhalation) EUH066	-	[1]
titanium dioxide	REACH #: 01-2119489379-17 EC: 236-675-5 CAS: 13463-67-7	≤1	Carc. 2, H351 (inhalation)	-	[1] [*]
2,4,7,9-tetramethyl-5-decyne-4,7-diol	REACH #: 01-2119954390-39 EC: 204-809-1 CAS: 126-86-3	<1	Eye Dam. 1, H318 Skin Sens. 1B, H317 Aquatic Chronic 3, H412	-	[1]
adipohydrazide	REACH #: 01-2119962900-36 EC: 213-999-5 CAS: 1071-93-8	≤0.3	Skin Sens. 1, H317 Aquatic Chronic 2, H411	-	[1]
2-Dimethylaminoethanol	REACH #: 01-2119492298-24 EC: 203-542-8 CAS: 108-01-0 Index: 603-047-00-0	≤0.3	Flam. Liq. 3, H226 Acute Tox. 4, H302 Acute Tox. 4, H312 Acute Tox. 3, H331 Skin Corr. 1B, H314 Eye Dam. 1, H318 STOT SE 3, H335	ATE [Oral] = 2000 mg/kg ATE [Dermal] = 1100 mg/kg ATE [Inhalation (gases)] = 1641 ppm STOT SE 3, H335: C ≥ 5%	[1]
2-methyl-2H-isothiazol-3-one	EC: 220-239-6 CAS: 2682-20-4	<0.0015	Acute Tox. 3, H301 Acute Tox. 3, H311 Acute Tox. 2, H330 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 EUH071	ATE [Oral] = 100 mg/kg ATE [Dermal] = 300 mg/kg ATE [Inhalation (dusts and mists)] = 0.11 mg/l Skin Sens. 1, H317: C ≥ 0.0015% M [Acute] = 10	[1]

Date of issue/Date of revision

: 09/10/2024

Date of previous issue

: 09/10/2024

Version : 1.01 2/22

TEKNOCRYL AQUA 2935-20 - All variants

Label No : 40924

## SECTION 3: Composition/information on ingredients

			<b>See Section 16 for the full text of the H statements declared above.</b>	M [Chronic] = 1	
--	--	--	---	-----------------	--

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

### Type

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

[\*] The classification as a carcinogen by inhalation applies only to mixtures placed on the market in powder form containing 1% or more of titanium dioxide particles with aerodynamic diameter  $\leq 10 \mu\text{m}$  not bound within a matrix.

Occupational exposure limits, if available, are listed in Section 8.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Get medical attention if irritation occurs.
- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Skin contact** : Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur.
- Ingestion** : Wash out mouth with water. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Do not induce vomiting unless directed to do so by medical personnel.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training.

### 4.2 Most important symptoms and effects, both acute and delayed

#### Over-exposure signs/symptoms

- Eye contact** : No specific data.
- Inhalation** : No specific data.
- Skin contact** : No specific data.
- Ingestion** : No specific data.

### 4.3 Indication of any immediate medical attention and special treatment needed

- Notes to physician** : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Specific treatments** : No specific treatment.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

- Suitable extinguishing media** : Use an extinguishing agent suitable for the surrounding fire.
- Unsuitable extinguishing media** : None known.

### 5.2 Special hazards arising from the substance or mixture

- Hazards from the substance or mixture** : In a fire or if heated, a pressure increase will occur and the container may burst. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

## SECTION 5: Firefighting measures

**Hazardous combustion products** : Decomposition products may include the following materials:  
carbon dioxide  
carbon monoxide  
nitrogen oxides  
sulfur oxides  
phosphorus oxides  
metal oxide/oxides

### 5.3 Advice for firefighters

**Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

**Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

**For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Put on appropriate personal protective equipment.

**For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

**6.2 Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

### 6.3 Methods and material for containment and cleaning up

**Small spill** : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

**Large spill** : Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spill product.

**6.4 Reference to other sections** : See Section 1 for emergency contact information.  
See Section 8 for information on appropriate personal protective equipment.  
See Section 13 for additional waste treatment information.

## SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

### 7.1 Precautions for safe handling

**Protective measures** : Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapour or mist. Avoid release to the environment. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

**Date of issue/Date of revision** : 09/10/2024 **Date of previous issue** : 09/10/2024 **Version** : 1.01 4/22

TEKNOCRYL AQUA 2935-20 - All variants

**Label No** : 40924

## SECTION 7: Handling and storage

### Advice on general occupational hygiene

: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

### 7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

### 7.3 Specific end use(s)

**Recommendations** : Not available.

**Industrial sector specific solutions** : Not available.

## SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

### 8.1 Control parameters

#### Occupational exposure limits

Product/ingredient name	Exposure limit values
2-Butoxyethanol	<b>Regulation on Limit Values - MAC (Austria, 4/2021). Absorbed through skin.</b> TWA: 20 ppm 8 hours. TWA: 98 mg/m <sup>3</sup> 8 hours. PEAK: 40 ppm, 4 times per shift, 30 minutes. PEAK: 200 mg/m <sup>3</sup> , 4 times per shift, 30 minutes.
2-methyl-2H-isothiazol-3-one	<b>Regulation on Limit Values - MAC (Austria, 4/2021). [5-chloro-2-methyl-2,3-dihydroisothiazol-3-one and 2-methyl-2,3-dihydroisothiazol-3-one (mixture in the ratio 3:1)] Skin sensitiser.</b> TWA: 0.05 mg/m <sup>3</sup> 8 hours.
2-Butoxyethanol	<b>Limit values (Belgium, 5/2021). Absorbed through skin.</b> TWA: 20 ppm 8 hours. TWA: 98 mg/m <sup>3</sup> 8 hours. STEL: 50 ppm 15 minutes. STEL: 246 mg/m <sup>3</sup> 15 minutes.
2-Butoxyethanol	<b>Ministry of Labour and Social Policy and the Ministry of Health - Ordinance No 13/2003. (Bulgaria, 6/2021). Absorbed through skin.</b> Limit value 8 hours: 98 mg/m <sup>3</sup> 8 hours. Limit value 15 min: 246 mg/m <sup>3</sup> 15 minutes. Limit value 15 min: 50 ppm 15 minutes. Limit value 8 hours: 20 ppm 8 hours.
2-Butoxyethanol	<b>Ministry of Economy, Labour and Entrepreneurship ELV/ STELV (Croatia, 1/2021). Absorbed through skin.</b> STELV: 246 mg/m <sup>3</sup> 15 minutes. STELV: 50 ppm 15 minutes. ELV: 98 mg/m <sup>3</sup> 8 hours. ELV: 20 ppm 8 hours.
2-Dimethylaminoethanol	<b>Ministry of Economy, Labour and Entrepreneurship ELV/ STELV (Croatia, 1/2021).</b> STELV: 22 mg/m <sup>3</sup> 15 minutes. STELV: 6 ppm 15 minutes. ELV: 7.4 mg/m <sup>3</sup> 8 hours. ELV: 2 ppm 8 hours.

## SECTION 8: Exposure controls/personal protection

2-Butoxyethanol	<b>Department of labour inspection (Cyprus, 7/2021). Absorbed through skin.</b> STEL: 50 ppm 15 minutes. STEL: 246 mg/m <sup>3</sup> 15 minutes. TWA: 20 ppm 8 hours. TWA: 98 mg/m <sup>3</sup> 8 hours.
2-Butoxyethanol	<b>Government regulation of Czech Republic PEL/NPK-P (Czech Republic, 10/2022). Absorbed through skin.</b> TWA: 100 mg/m <sup>3</sup> 8 hours. TWA: 20.4 ppm 8 hours. STEL: 200 mg/m <sup>3</sup> 15 minutes. STEL: 40.8 ppm 15 minutes.
2-Butoxyethanol	<b>Working Environment Authority (Denmark, 6/2022). Absorbed through skin.</b> TWA: 20 ppm 8 hours. TWA: 98 mg/m <sup>3</sup> 8 hours. STEL: 246 mg/m <sup>3</sup> 15 minutes. STEL: 50 ppm 15 minutes.
2-Butoxyethanol	<b>Occupational exposure limits, Regulation No. 293 (Estonia, 12/2022). Absorbed through skin. Skin sensitiser.</b> TWA: 98 mg/m <sup>3</sup> 8 hours. TWA: 20 ppm 8 hours. STEL: 246 mg/m <sup>3</sup> 15 minutes. STEL: 50 ppm 15 minutes.
2-Butoxyethanol	<b>EU OEL (Europe, 1/2022). Absorbed through skin. Notes: list of indicative occupational exposure limit values</b> TWA: 20 ppm 8 hours. TWA: 98 mg/m <sup>3</sup> 8 hours. STEL: 50 ppm 15 minutes. STEL: 246 mg/m <sup>3</sup> 15 minutes.
2-Butoxyethanol	<b>Institute of Occupational Health, Ministry of Social Affairs (Finland, 10/2021). Absorbed through skin.</b> TWA: 20 ppm 8 hours. TWA: 98 mg/m <sup>3</sup> 8 hours. STEL: 50 ppm 15 minutes. STEL: 250 mg/m <sup>3</sup> 15 minutes.
2-Butoxyethanol	<b>Ministry of Labor (France, 10/2022). Absorbed through skin. Notes: Binding regulatory limit values (article R. 4412-149 of the Labor Code)</b> TWA: 10 ppm 8 hours. TWA: 49 mg/m <sup>3</sup> 8 hours. STEL: 246 mg/m <sup>3</sup> 15 minutes. STEL: 50 ppm 15 minutes.
2-Butoxyethanol	<b>TRGS 900 OEL (Germany, 6/2022). Absorbed through skin.</b> TWA: 49 mg/m <sup>3</sup> 8 hours. PEAK: 98 mg/m <sup>3</sup> 15 minutes. TWA: 10 ppm 8 hours. PEAK: 20 ppm 15 minutes. <b>DFG MAC-values list (Germany, 7/2022). Absorbed through skin.</b> TWA: 10 ppm 8 hours. PEAK: 20 ppm, 4 times per shift, 15 minutes. TWA: 49 mg/m <sup>3</sup> 8 hours. PEAK: 98 mg/m <sup>3</sup> , 4 times per shift, 15 minutes.
2-methyl-2H-isothiazol-3-one	<b>DFG MAC-values list (Germany, 7/2022). Skin sensitiser.</b>
2-Butoxyethanol	<b>Presidential Decree 307/1986: Occupational exposure limit values (Greece, 9/2021). Absorbed through skin.</b> TWA: 25 ppm 8 hours. TWA: 120 mg/m <sup>3</sup> 8 hours.



## SECTION 8: Exposure controls/personal protection

2-Butoxyethanol	<p><b>5/2020. (II. 6.) ITM Decree (Hungary, 12/2022). Absorbed through skin. Skin sensitiser. Inhalation sensitiser.</b>  TWA: 98 mg/m<sup>3</sup> 8 hours.  PEAK: 246 mg/m<sup>3</sup> 15 minutes.  PEAK: 50 ppm 15 minutes.  TWA: 20 ppm 8 hours.</p>
2-Butoxyethanol	<p><b>Ministry of Welfare, List of Exposure Limits (Iceland, 5/2021). Absorbed through skin.</b>  STEL: 246 mg/m<sup>3</sup> 15 minutes.  STEL: 50 ppm 15 minutes.  TWA: 100 mg/m<sup>3</sup> 8 hours.  TWA: 20 ppm 8 hours.</p>
2-Butoxyethanol	<p><b>NAOSH (Ireland, 5/2021). Absorbed through skin. Notes: EU derived Occupational Exposure Limit Values</b>  OELV-8hr: 20 ppm 8 hours.  OELV-8hr: 98 mg/m<sup>3</sup> 8 hours.  OELV-15min: 50 ppm 15 minutes.  OELV-15min: 246 mg/m<sup>3</sup> 15 minutes.</p>
2-Butoxyethanol	<p><b>Legislative Decree No. 819/2008. Title IX. Protection from chemical agents, carcinogens and mutagens (Italy, 6/2020). Absorbed through skin.</b>  8 hours: 20 ppm 8 hours.  8 hours: 98 mg/m<sup>3</sup> 8 hours.  Short Term: 50 ppm 15 minutes.  Short Term: 246 mg/m<sup>3</sup> 15 minutes.</p>
2-Butoxyethanol	<p><b>Ministers Cabinet Regulations Nr.325 - AER (Latvia, 2/2021). Absorbed through skin.</b>  TWA: 98 mg/m<sup>3</sup> 8 hours.  TWA: 20 ppm 8 hours.  STEL: 50 ppm 15 minutes.  STEL: 246 mg/m<sup>3</sup> 15 minutes.</p>
2-Dimethylaminoethanol	<p><b>Ministers Cabinet Regulations Nr.325 - AER (Latvia, 2/2021).</b>  TWA: 5 mg/m<sup>3</sup> 8 hours.</p>
2-Butoxyethanol	<p><b>Lithuanian Hygiene Standard HN 23 (Lithuania, 7/2022). Absorbed through skin.</b>  TWA: 50 mg/m<sup>3</sup> 8 hours.  TWA: 10 ppm 8 hours.  STEL: 100 mg/m<sup>3</sup> 15 minutes.  STEL: 20 ppm 15 minutes.</p>
2-Butoxyethanol	<p><b>Grand-Duchy Regulation 2016. Chemical agents. Annex I (Luxembourg, 3/2021). Absorbed through skin.</b>  TWA: 20 ppm 8 hours.  TWA: 98 mg/m<sup>3</sup> 8 hours.  STEL: 50 ppm 15 minutes.  STEL: 246 mg/m<sup>3</sup> 15 minutes.</p>
2-Butoxyethanol	<p><b>EU OEL (Europe, 1/2022). Absorbed through skin. Notes: list of indicative occupational exposure limit values</b>  TWA: 20 ppm 8 hours.  TWA: 98 mg/m<sup>3</sup> 8 hours.  STEL: 50 ppm 15 minutes.  STEL: 246 mg/m<sup>3</sup> 15 minutes.</p>
2-Butoxyethanol	<p><b>Ministry of Social Affairs and Employment, Legal limit values (Netherlands, 12/2022). Absorbed through skin.</b>  OEL, 8-h TWA: 100 mg/m<sup>3</sup> 8 hours.  STEL, 15-min: 246 mg/m<sup>3</sup> 15 minutes.  OEL, 8-h TWA: 20.4 ppm 8 hours.  STEL, 15-min: 50 ppm 15 minutes.</p>
2-Butoxyethanol	<p><b>FOR-2011-12-06-1358 (Norway, 12/2022). Absorbed through skin. Notes: indicative limit value</b>  TWA: 10 ppm 8 hours.  TWA: 50 mg/m<sup>3</sup> 8 hours.</p>

## SECTION 8: Exposure controls/personal protection

2-Butoxyethanol	<p><b>Regulation of the Minister of Family, Labor and Social Policy of 18 February 2021, regarding the highest permissible concentrations and values of agents harmful to health in the work environment (Journal of Laws 2021, item 325) (Poland, 2/2021). Absorbed through skin.</b>  TWA: 98 mg/m<sup>3</sup> 8 hours.  STEL: 200 mg/m<sup>3</sup> 15 minutes.</p>
2-Butoxyethanol	<p><b>Portuguese Institute of Quality (Portugal, 11/2014).</b>  TWA: 20 ppm 8 hours.</p>
2-Butoxyethanol	<p><b>HG 1218/2006, Annex 1, with subsequent modifications and additions (Romania, 3/2021). Absorbed through skin.</b>  VLA: 98 mg/m<sup>3</sup> 8 hours.  VLA: 20 ppm 8 hours.  Short term: 246 mg/m<sup>3</sup> 15 minutes.  Short term: 50 ppm 15 minutes.</p>
2-Butoxyethanol	<p><b>Government regulation SR c. 355/2006 (Slovakia, 9/2020). Absorbed through skin.</b>  TWA: 98 mg/m<sup>3</sup> 8 hours.  TWA: 20 ppm 8 hours.  STEL: 246 mg/m<sup>3</sup> 15 minutes.  STEL: 50 ppm 15 minutes.</p>
2-Butoxyethanol	<p><b>Regulation on protection of workers from the risks related to exposure to chemical substances at work (Slovenia, 5/2021). Absorbed through skin.</b>  TWA: 98 mg/m<sup>3</sup> 8 hours.  TWA: 20 ppm 8 hours.  KTV: 246 mg/m<sup>3</sup>, 4 times per shift, 15 minutes.  KTV: 50 ppm, 4 times per shift, 15 minutes.</p>
2-Butoxyethanol	<p><b>National institute of occupational safety and health (Spain, 4/2022). Absorbed through skin.</b>  TWA: 20 ppm 8 hours.  TWA: 98 mg/m<sup>3</sup> 8 hours.  STEL: 245 mg/m<sup>3</sup> 15 minutes.  STEL: 50 ppm 15 minutes.</p>
2-Butoxyethanol	<p><b>Work environment authority Regulation 2018:1 (Sweden, 9/2021). Absorbed through skin.</b>  TWA: 10 ppm 8 hours.  TWA: 50 mg/m<sup>3</sup> 8 hours.  STEL: 50 ppm 15 minutes.  STEL: 246 mg/m<sup>3</sup> 15 minutes.</p>
2-Butoxyethanol	<p><b>SUVA (Switzerland, 1/2023). Absorbed through skin.</b>  TWA: 10 ppm 8 hours.  TWA: 49 mg/m<sup>3</sup> 8 hours.  STEL: 20 ppm 15 minutes.  STEL: 98 mg/m<sup>3</sup> 15 minutes.</p>
2-Butoxyethanol	<p><b>EH40/2005 WELs (United Kingdom (UK), 1/2020). Absorbed through skin.</b>  STEL: 50 ppm 15 minutes.  TWA: 25 ppm 8 hours.  STEL: 246 mg/m<sup>3</sup> 15 minutes.  TWA: 123 mg/m<sup>3</sup> 8 hours.</p>
Ethanediol	<p><b>EH40/2005 WELs (United Kingdom (UK), 1/2020). Absorbed through skin.</b>  TWA: 10 mg/m<sup>3</sup> 8 hours. Form: Particulate  TWA: 20 ppm 8 hours. Form: Vapour  STEL: 40 ppm 15 minutes. Form: Vapour  TWA: 52 mg/m<sup>3</sup> 8 hours. Form: Vapour  STEL: 104 mg/m<sup>3</sup> 15 minutes. Form: Vapour</p>
1-Methoxy 2-propanol	<p><b>EH40/2005 WELs (United Kingdom (UK), 1/2020). Absorbed through skin.</b>  STEL: 560 mg/m<sup>3</sup> 15 minutes.  STEL: 150 ppm 15 minutes.</p>



## SECTION 8: Exposure controls/personal protection

2-Dimethylaminoethanol	TWA: 375 mg/m <sup>3</sup> 8 hours. TWA: 100 ppm 8 hours. <b>EH40/2005 WELs (United Kingdom (UK), 1/2020).</b> STEL: 22 mg/m <sup>3</sup> 15 minutes. STEL: 6 ppm 15 minutes. TWA: 2 ppm 8 hours. TWA: 7.4 mg/m <sup>3</sup> 8 hours.
Ammonia	<b>EH40/2005 WELs (United Kingdom (UK), 1/2020). [ammonia anhydrous]</b> STEL: 25 mg/m <sup>3</sup> 15 minutes. Form: anhydrous STEL: 35 ppm 15 minutes. Form: anhydrous TWA: 25 ppm 8 hours. Form: anhydrous TWA: 18 mg/m <sup>3</sup> 8 hours. Form: anhydrous
2-aminoethanol	<b>EH40/2005 WELs (United Kingdom (UK), 1/2020). Absorbed through skin.</b> STEL: 7.6 mg/m <sup>3</sup> 15 minutes. STEL: 3 ppm 15 minutes. TWA: 1 ppm 8 hours. TWA: 2.5 mg/m <sup>3</sup> 8 hours.

### Biological exposure indices

Product/ingredient name	Exposure indices
No exposure indices known.	
No exposure indices known.	
No exposure indices known.	
No exposure indices known.	
No exposure indices known.	
2-Butoxyethanol	<b>Government regulation of Czech Republic Limit Values of Biological Exposure Tests (Czech Republic, 9/2015)</b> Biological limit values: 0.17 mmol/mmol creatinine, butoxyacetic acid (after hydrolysis) [in urine]. Sampling time: the end of the shift at the end of the week. Biological limit values: 200 mg/g creatinine, butoxyacetic acid (after hydrolysis) [in urine]. Sampling time: the end of the shift at the end of the week.
No exposure indices known.	
No exposure indices known.	
No exposure indices known.	
No exposure indices known.	
No exposure indices known.	
2-Butoxyethanol	<b>DFG BEI-values list (Germany, 7/2022) Notes: danger from percutaneous absorption (see p. 211 and p. 228).</b> BEI: 150 mg/g creatinine, butoxyacetic acid (after hydrolysis) [in urine]. Sampling time: end of exposure or end of shift / for long-term exposures: at the end of the shift after several shifts. <b>TRGS 903 - BEI Values (Germany, 2/2022)</b> BEI: 150 mg/g creatinine, butoxy acetic acid (after hydrolysis) [in urine]. Sampling time: end of exposure or end of shift; for long-term exposures: at the end of shift after several shifts.
No exposure indices known.	
No exposure indices known.	
No exposure indices known.	
2-Butoxyethanol	<b>NAOSH (Ireland, 1/2011)</b> BMGV: 200 mg/g creatinine, BAA [in urine]. Sampling time: end of shift - As soon as possible after exposure ceases.
No exposure indices known.	

## SECTION 8: Exposure controls/personal protection

No exposure indices known.	
No exposure indices known.	
No exposure indices known.	
No exposure indices known.	
No exposure indices known.	
No exposure indices known.	
No exposure indices known.	
2-Butoxyethanol	<b>Portuguese Institute of Quality (Portugal, 11/2014)</b> BEI: 200 mg/g creatinine, butoxyacetic acid (BAA) [in urine]. Sampling time: end of shift.
No exposure indices known.	
No exposure indices known.	
2-Butoxyethanol	<b>Regulation on protection of workers from the risks related to exposure to chemical substances at work (Slovenia, 5/2021)</b> BAT: 150 mg/g creatinine, butoxyacetic acid (after hydrolysis) [in urine]. Sampling time: at the end of the work shift, at long-term exposure: at the end of the work shift after several consecutive workdays.
2-Butoxyethanol	<b>National institute of occupational safety and health (Spain, 4/2022)</b> VLB: 200 mg/g creatinine, butoxyacetic acid [in urine]. Sampling time: end of shift.
No exposure indices known.	
2-Butoxyethanol	<b>SUVA (Switzerland, 1/2023)</b> BEI: 150 mg/g creatinine, 2-butoxy acetic acid (after hydrolysis) [in urine]. Sampling time: immediately after exposure or after working hours. In case of long-term exposure: after more than one shift.
2-Butoxyethanol	<b>EH40/2005 BMGVs (United Kingdom (UK), 8/2018)</b> BGV: 240 mmol/mol creatinine, butoxyacetic acid [in urine]. Sampling time: post shift.

**Recommended monitoring procedures** : Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

### DNELs/DMELs

Product/ingredient name	Type	Exposure	Value	Population	Effects
2-Butoxyethanol	DNEL	Long term Oral	6.3 mg/kg bw/day	General population	Systemic
	DNEL	Short term Oral	26.7 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	59 mg/m <sup>3</sup>	General population	Systemic
	DNEL	Long term Inhalation	98 mg/m <sup>3</sup>	Workers	Systemic
	DNEL	Short term Inhalation	147 mg/m <sup>3</sup>	General population	Local
	DNEL	Short term Inhalation	246 mg/m <sup>3</sup>	Workers	Local
	DNEL	Short term Inhalation	426 mg/m <sup>3</sup>	General population	Systemic
	DNEL	Short term Inhalation	1091 mg/	Workers	Systemic

Date of issue/Date of revision : 09/10/2024 Date of previous issue : 09/10/2024 Version : 1.01 10/22

TEKNOCRYL AQUA 2935-20 - All variants

Label No : 40924

## SECTION 8: Exposure controls/personal protection

Trizinc bis(orthophosphate)	DNEL	Inhalation Long term Oral	m <sup>3</sup> 0.83 mg/ kg bw/day	General population	Systemic	
	DNEL	Long term Inhalation	2.5 mg/m <sup>3</sup>	General population	Systemic	
	DNEL	Long term Inhalation	5 mg/m <sup>3</sup>	Workers	Systemic	
	DNEL	Long term Dermal	83 mg/kg bw/day	General population	Systemic	
	DNEL	Long term Dermal	83 mg/kg bw/day	Workers	Systemic	
2,4,7,9-tetramethyl-5-decyne-4,7-diol	DNEL	Long term Oral	0.25 mg/ kg bw/day	General population	Systemic	
	DNEL	Long term Dermal	0.25 mg/ kg bw/day	General population	Systemic	
	DNEL	Long term Inhalation	0.43 mg/m <sup>3</sup>	General population	Systemic	
	DNEL	Long term Dermal	0.5 mg/kg bw/day	Workers	Systemic	
	DNEL	Short term Oral	0.75 mg/ kg bw/day	General population	Systemic	
	DNEL	Short term Dermal	0.75 mg/ kg bw/day	General population	Systemic	
	DNEL	Short term Inhalation	1.29 mg/m <sup>3</sup>	General population	Systemic	
	DNEL	Short term Dermal	1.5 mg/kg bw/day	Workers	Systemic	
	DNEL	Long term Inhalation	1.76 mg/m <sup>3</sup>	Workers	Systemic	
	DNEL	Short term Inhalation	5.28 mg/m <sup>3</sup>	Workers	Systemic	
	adipohydrazide	DNEL	Long term Inhalation	17.5 mg/m <sup>3</sup>	Workers	Systemic
	2-Dimethylaminoethanol	DNEL	Long term Oral	0.126 mg/ kg bw/day	General population	Systemic
		DNEL	Long term Dermal	0.25 mg/ kg bw/day	Workers	Systemic
		DNEL	Long term Inhalation	0.43755 mg/m <sup>3</sup>	General population	Systemic
		DNEL	Short term Dermal	1.2 mg/kg bw/day	Workers	Systemic
DNEL		Long term Inhalation	1.76 mg/m <sup>3</sup>	Workers	Local	
DNEL		Long term Inhalation	1.76 mg/m <sup>3</sup>	Workers	Systemic	
DNEL		Short term Inhalation	5.28 mg/m <sup>3</sup>	Workers	Systemic	
DNEL		Short term Inhalation	13.53 mg/ m <sup>3</sup>	Workers	Local	
2-methyl-2H-isothiazol-3-one		DNEL	Short term Dermal	100 µg/cm <sup>2</sup>	Workers	Local
		DNEL	Long term Inhalation	0.021 mg/ m <sup>3</sup>	General population	Local
	DNEL	Long term Inhalation	0.021 mg/ m <sup>3</sup>	Workers	Local	
	DNEL	Long term Oral	0.027 mg/ kg bw/day	General population	Systemic	
	DNEL	Short term Inhalation	0.043 mg/ m <sup>3</sup>	General population	Local	
	DNEL	Short term Inhalation	0.043 mg/ m <sup>3</sup>	Workers	Local	
	DNEL	Short term Oral	0.053 mg/ kg bw/day	General population	Systemic	

### PNECs

No PNECs available

## SECTION 8: Exposure controls/personal protection

### 8.2 Exposure controls

**Appropriate engineering controls** : Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

#### Individual protection measures

**Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

**Eye/face protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.

#### Skin protection

**Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Recommendations : Wear suitable gloves tested to EN374.

> 8 hours (breakthrough time): Nitrile gloves. thickness > 0.3 mm

Not recommended polyvinyl alcohol (PVA) gloves

**Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

**Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

**Respiratory protection** : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Filter type (spray application): A P

**Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

## SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

### 9.1 Information on basic physical and chemical properties

#### Appearance

**Physical state** : Liquid.

**Colour** : Various

**Odour** : Slight

**Odour threshold** : Not available.

**Melting point/freezing point** : Not available.

**Initial boiling point and boiling range** :

## SECTION 9: Physical and chemical properties

Ingredient name	°C	°F	Method
water	100	212	
water	100	212	

- Flammability** : Not available.
- Lower and upper explosion limit** : Lower: Not applicable.  
Upper: Not applicable.
- Flash point** : Closed cup: >100°C (>212°F)
- Auto-ignition temperature** :

Ingredient name	°C	°F	Method
2-Butoxyethanol	230	446	DIN 51794

- Decomposition temperature** : Not available.
- pH** : 8.6 to 9.2
- Viscosity** : Not available.
- Solubility(ies)** :  
Not available.
- Solubility in water** : Not available.
- Partition coefficient: n-octanol/ water** : Not applicable.
- Vapour pressure** :

Ingredient name	Vapour Pressure at 20°C			Vapour pressure at 50°C		
	mm Hg	kPa	Method	mm Hg	kPa	Method
water	17.5	2.3				
water	17.5	2.3				

- Relative density** : Not available.
- Density** : 1.2 g/cm<sup>3</sup>
- Vapour density** : Not available.
- Explosive properties** : Not available.
- Oxidising properties** : Not available.
- Particle characteristics**
- Median particle size** : Not applicable.

### 9.2 Other information

No additional information.

## SECTION 10: Stability and reactivity

- 10.1 Reactivity** : No specific test data related to reactivity available for this product or its ingredients.
- 10.2 Chemical stability** : The product is stable.
- 10.3 Possibility of hazardous reactions** : Under normal conditions of storage and use, hazardous reactions will not occur.
- 10.4 Conditions to avoid** : No specific data.
- 10.5 Incompatible materials** : No specific data.
- 10.6 Hazardous decomposition products** : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

**Date of issue/Date of revision** : 09/10/2024 **Date of previous issue** : 09/10/2024

**Version** : 1.01 13/22

TEKNOCRYL AQUA 2935-20 - All variants

**Label No** : 40924

## SECTION 11: Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
2-Dimethylaminoethanol	LC50 Inhalation Gas. LD50 Oral	Rat Rat	1641 ppm 2 g/kg	4 hours -
2-methyl-2H-isothiazol-3-one	LC50 Inhalation Dusts and mists	Rat	0.11 mg/l	4 hours

**Conclusion/Summary** : Based on available data, the classification criteria are not met.

#### Acute toxicity estimates

Route	ATE value
Oral Inhalation (gases) Inhalation (vapours)	30000 mg/kg 1641000 ppm 75 mg/l

#### Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
2-Butoxyethanol	Eyes - Moderate irritant	Rabbit	-	24 hours 100 mg	-
titanium dioxide	Eyes - Severe irritant	Rabbit	-	100 mg	-
	Skin - Mild irritant	Rabbit	-	500 mg	-
	Skin - Mild irritant	Human	-	72 hours 300 ug l	-
	2,4,7,9-tetramethyl-5-decyne-4,7-diol	Eyes - Severe irritant	Rabbit	-	0.1 MI
2-Dimethylaminoethanol	Skin - Mild irritant	Rabbit	-	0.5 g	-
	Eyes - Severe irritant	Rabbit	-	5 uL	-
	Skin - Mild irritant	Rabbit	-	445 mg	-

**Conclusion/Summary** : Based on available data, the classification criteria are not met.

#### Sensitisation

**Conclusion/Summary** : Based on available data, the classification criteria are not met.

#### Mutagenicity

**Conclusion/Summary** : Based on available data, the classification criteria are not met.

#### Carcinogenicity

**Conclusion/Summary** : Based on available data, the classification criteria are not met.

#### Reproductive toxicity

**Conclusion/Summary** : Based on available data, the classification criteria are not met.

#### Teratogenicity

**Conclusion/Summary** : Based on available data, the classification criteria are not met.

#### Specific target organ toxicity (single exposure)

Product/ingredient name	Category	Route of exposure	Target organs
2-Dimethylaminoethanol	Category 3	-	Respiratory tract irritation

#### Specific target organ toxicity (repeated exposure)

Product/ingredient name	Category	Route of exposure	Target organs
Silanamine, 1,1,1-trimethyl-N-(trimethylsilyl)-, hydrolysis products with silica	Category 2	inhalation	lungs

#### Aspiration hazard

Not available.

**Information on likely routes of exposure** : Not available.

Date of issue/Date of revision

: 09/10/2024

Date of previous issue

: 09/10/2024

Version : 1.01 14/22

TEKNOCRYL AQUA 2935-20 - All variants

Label No : 40924



## SECTION 11: Toxicological information

### Potential acute health effects

<b>Eye contact</b>	: No known significant effects or critical hazards.
<b>Inhalation</b>	: No known significant effects or critical hazards.
<b>Skin contact</b>	: No known significant effects or critical hazards.
<b>Ingestion</b>	: No known significant effects or critical hazards.

### Symptoms related to the physical, chemical and toxicological characteristics

<b>Eye contact</b>	: No specific data.
<b>Inhalation</b>	: No specific data.
<b>Skin contact</b>	: No specific data.
<b>Ingestion</b>	: No specific data.

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

#### Short term exposure

<b>Potential immediate effects</b>	: Not available.
<b>Potential delayed effects</b>	: Not available.

#### Long term exposure

<b>Potential immediate effects</b>	: Not available.
<b>Potential delayed effects</b>	: Not available.

#### Potential chronic health effects

Not available.

<b>Conclusion/Summary</b>	: Not available.
<b>General</b>	: No known significant effects or critical hazards.
<b>Carcinogenicity</b>	: No known significant effects or critical hazards.
<b>Mutagenicity</b>	: No known significant effects or critical hazards.
<b>Reproductive toxicity</b>	: No known significant effects or critical hazards.

## 11.2 Information on other hazards

### 11.2.1 Endocrine disrupting properties

Not available.

### 11.2.2 Other information

Not available.

## SECTION 12: Ecological information

### 12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
2-Butoxyethanol	Acute EC50 >1000 mg/l Fresh water	Daphnia - <i>Daphnia magna</i>	48 hours
	Acute LC50 800000 µg/l Marine water	Crustaceans - <i>Crangon crangon</i>	48 hours
	Acute LC50 1250000 µg/l Marine water	Fish - <i>Menidia beryllina</i>	96 hours
Trizinc bis(orthophosphate)	Acute EC50 0.32 mg/l	Algae - <i>Selenastrum capricornutum</i>	72 hours
	Acute EC50 0.96 mg/l	Crustaceans - <i>Ceriodaphnia dubia</i>	48 hours
titanium dioxide	Acute LC50 3 mg/l Fresh water	Crustaceans - <i>Ceriodaphnia dubia</i> - Neonate	48 hours
	Acute LC50 6.5 mg/l Fresh water	Daphnia - <i>Daphnia pulex</i> - Neonate	48 hours
	Acute LC50 >1000000 µg/l Marine water	Fish - <i>Fundulus heteroclitus</i>	96 hours
2,4,7,9-tetramethyl-5-decyne-4,7-diol	EC50 91 mg/l	Daphnia - <i>Daphnia magna</i>	48 hours
	LC50 42 mg/l	Fish - <i>Cyprinus carpio</i>	96 hours

**Date of issue/Date of revision** : 09/10/2024 **Date of previous issue** : 09/10/2024 **Version** : 1.01 15/22

TEKNOCRYL AQUA 2935-20 - All variants

**Label No** : 40924

## SECTION 12: Ecological information

2-methyl-2H-isothiazol-3-one	Acute EC50 0.18 ppm Fresh water Acute LC50 0.07 ppm Fresh water	Daphnia - <i>Daphnia magna</i> Fish - <i>Oncorhynchus mykiss</i>	48 hours 96 hours
------------------------------	--	---	----------------------

**Conclusion/Summary** : Harmful to aquatic life with long lasting effects.

### 12.2 Persistence and degradability

**Conclusion/Summary** : This product has not been tested for biodegradation.

### 12.3 Bioaccumulative potential

Product/ingredient name	LogP <sub>ow</sub>	BCF	Potential
2-Butoxyethanol	0.81	-	Low
Trizinc bis(orthophosphate)	-	60960	High
2-Dimethylaminoethanol	-0.55	-	Low

### 12.4 Mobility in soil

**Soil/water partition coefficient (K<sub>oc</sub>)** : Not available.

**Mobility** : Not available.

### 12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

### 12.6 Endocrine disrupting properties

Not available.

### 12.7 Other adverse effects

No known significant effects or critical hazards.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

#### Product

**Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

**European waste catalogue (EWC)** : 08 01 12

#### Packaging

**Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

**Special precautions** : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

## SECTION 14: Transport information

	ADR/RID	ADN	IMDG	IATA
14.1 UN number or ID number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-	-
14.3 Transport hazard class(es)	-	-	-	-
14.4 Packing group	-	-	-	-
14.5 Environmental hazards	No.	No.	No.	No.

**14.6 Special precautions for user** : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

**14.7 Maritime transport in bulk according to IMO instruments** : Not relevant/applicable due to nature of the product.

## SECTION 15: Regulatory information

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**  
**EU Regulation (EC) No. 1907/2006 (REACH)**

**Annex XIV - List of substances subject to authorisation**

**Annex XIV**

None of the components are listed.

**Substances of very high concern**

None of the components are listed.

**Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles**

Product/ingredient name	%	Designation [Usage]
TEKNOCRYL AQUA 2935-20	≥90	3

**Labelling** :

**Other EU regulations**

**Industrial emissions (integrated pollution prevention and control) - Air** : Not listed

**Industrial emissions (integrated pollution prevention and control) - Water** : Not listed

**Explosive precursors** : Not applicable.

**Ozone depleting substances (1005/2009/EU)**

Not listed.

**Prior Informed Consent (PIC) (649/2012/EU)**

Not listed.

## SECTION 15: Regulatory information

### Persistent Organic Pollutants

Not listed.

### Seveso Directive

This product is not controlled under the Seveso Directive.

### National regulations

#### Austria

**VbF class** : Not regulated.

**Limitation of the use of organic solvents** : Permitted.

#### Czech Republic

**Storage code** : IV

#### Denmark

**Danish fire class** : IV-1

### Executive Order No. 1795/2015

Ingredient name	Annex I Section A	Annex I Section B
carbon black respirable	Listed	-
titanium dioxide	Listed	-

**MAL-code** : 1-6

**Protection based on MAL** : **According to the regulations on work involving coded products, the following stipulations apply to the use of personal protective equipment:**

**General:** Gloves must be worn for all work that may result in soiling. Apron/coveralls/protective clothing must be worn when soiling is so great that regular work clothes do not adequately protect skin against contact with the product. A face shield must be worn in work involving spattering if a full mask is not required. In this case, other recommended use of eye protection is not required.

In all spraying operations in which there is return spray, the following must be worn: respiratory protection and arm protectors/apron/coveralls/protective clothing as appropriate or as instructed.

MAL-code: 1-6

**Application:** When using scraper or knife, brush, roller etc. for pre- and post-treatments in a spray booth where the operator is outside the spray zone and when working in similar new\* facilities of the combined-cabin, spray-cabin and spray-booth type where the operator is working inside the spray zone. When spraying in new\* booths and cabins with non-atomizing guns. When using scraper or knife, brush, roller, etc. for pre- and post-treatments in cabins or booths of the existing\* facility type, if the operator is inside the spray zone. When using scraper or knife, brush, roller, etc. for pre- and post-treatments outside a closed facility, spray booth or spray cabin.

- Protective clothing must be worn.

During downtimes, cleaning and repair in closed facilities, spray booths or cabins, if there is a risk of contact with wet paint or organic solvents.

- Gas filter mask and protective clothing must be worn.

When spraying in existing\* spray booths, if the operator is outside the spray zone.

- Air-supplied full mask and protective clothing must be worn.

During non-atomising spraying in existing\* facilities of the combined-cabin, spray-cabin and spray-booth type where the operator is working inside the spray zone.

- Air-supplied half mask, protective clothing and eye protection must be worn.

## SECTION 15: Regulatory information

During all spraying where atomisation occurs in cabins or spray booths where the operator is inside the spray zone and during spraying outside a closed facility, cabin or booth.

- Air-supplied full mask, protective clothing and hood must be worn.

**Drying:** Items for drying/drying ovens that are temporarily placed on such things as rack trolleys, etc, must be equipped with a mechanical exhaust system to prevent fumes from wet items from passing through workers' inhalation zone.

**Polishing:** When polishing treated surfaces, a mask with dust filter must be worn. When machine grinding, eye protection must be worn. Work gloves must always be worn.

**Caution** The regulations contain other stipulations in addition to the above.

\*See Regulations.

- Restrictions on use** : Not to be used by professional users below 18 years of age. See the National Working Environment Authorities Executive Order regarding Young People At Work.
- List of undesirable substances** : Not listed
- Carcinogenic waste** : Waste containers must be labeled: Contains a substance or substances regulated by Danish working environment legislation on cancer risks.

### Finland

### France

**Social Security Code, Articles L 461-1 to L 461-7** : 2-Butoxyethanol RG 84

**Reinforced medical surveillance** : Act of July 11, 1977 determining the list of activities which require reinforced medical surveillance: not applicable

### Germany

**Storage class (TRGS 510)** : 10

### Hazardous incident ordinance

This product is not controlled under the Germany Hazardous Incident Ordinance.

**Hazard class for water** : 1

**Technical instruction on air quality control** : TA-Luft Number 5.2.5: 16.7%

**AOX** : The product contains organically bound halogens and can contribute to the AOX value in waste water.

### Italy

**D.Lgs. 152/06** : Not determined.

### Netherlands

**Ministry of Social Affairs and Employment (SZW) - Carcinogenic substances and processes, mutagenic or reprotoxic substances**

Ingredient name	Carcinogen	Mutagen	Reproductive toxicity - Fertility	Reproductive toxicity - Development	Harmful via breastfeeding
silica, crystalline (NL-carcinogen specific)	Listed	-	-	-	-

**Water Discharge Policy (ABM)** : Z(1) Non biodegradable substances with hazardous properties for humans and the environment (carcinogenicity/ mutagenicity/ reprotoxicity/ bioaccumulative potential/ toxicity or persistence). Decontamination effort: Z

### Norway

### Sweden

### Switzerland

## SECTION 15: Regulatory information

**VOC content** : VOC (w/w): 4.2%

### International regulations

#### Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

#### Montreal Protocol

Not listed.

#### Stockholm Convention on Persistent Organic Pollutants

Not listed.

#### Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

#### UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

**15.2 Chemical safety assessment** : This product contains substances for which Chemical Safety Assessments are still required.

## SECTION 16: Other information

✔ Indicates information that has changed from previously issued version.

### **Abbreviations and acronyms**

: ATE = Acute Toxicity Estimate  
CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]  
DMEL = Derived Minimal Effect Level  
DNEL = Derived No Effect Level  
EUH statement = CLP-specific Hazard statement  
N/A = Not available  
PBT = Persistent, Bioaccumulative and Toxic  
PNEC = Predicted No Effect Concentration  
RRN = REACH Registration Number  
SGG = Segregation Group  
vPvB = Very Persistent and Very Bioaccumulative

### Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Aquatic Chronic 3, H412	Calculation method

### Full text of abbreviated H statements

H226	Flammable liquid and vapour.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H311	Toxic in contact with skin.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H331	Toxic if inhaled.
H335	May cause respiratory irritation.
H351	Suspected of causing cancer.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.
EUH071	Corrosive to the respiratory tract.

**Date of issue/Date of revision** : 09/10/2024 **Date of previous issue** : 09/10/2024

**Version** : 1.01 20/22

TEKNOCRYL AQUA 2935-20 - All variants

**Label No** : 40924



## SECTION 16: Other information

### [Full text of classifications \[CLP/GHS\]](#)

Acute Tox. 2	ACUTE TOXICITY - Category 2
Acute Tox. 3	ACUTE TOXICITY - Category 3
Acute Tox. 4	ACUTE TOXICITY - Category 4
Aquatic Acute 1	SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1
Aquatic Chronic 1	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1
Aquatic Chronic 2	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2
Aquatic Chronic 3	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3
Carc. 2	CARCINOGENICITY - Category 2
Eye Dam. 1	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1
Eye Irrit. 2	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2
Flam. Liq. 3	FLAMMABLE LIQUIDS - Category 3
Skin Corr. 1B	SKIN CORROSION/IRRITATION - Category 1B
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2
Skin Sens. 1	SKIN SENSITISATION - Category 1
Skin Sens. 1A	SKIN SENSITISATION - Category 1A
Skin Sens. 1B	SKIN SENSITISATION - Category 1B
STOT RE 2	SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 2
STOT SE 3	SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3

**Date of issue/ Date of revision** : 09/10/2024

**Date of previous issue** : 09/10/2024

**Version** : 1.01

TEKNOCRYL AQUA 2935-20

All variants

### [Notice to reader](#)

The information in this SDS is based on the present state of our knowledge and on current laws. The product is not to be used for purposes other than those specified under section 1 without first obtaining written handling instructions. It is always the responsibility of the user to take all necessary steps to fulfil the demands set out in the local rules and legislation. The information in this SDS is meant to be a description of the safety requirements for our product. It is not to be considered a guarantee of the product's properties.

**Date of issue/Date of revision** : 09/10/2024 **Date of previous issue** : 09/10/2024

**Version** : 1.01 21/22

TEKNOCRYL AQUA 2935-20 - All variants

**Label No** : 40924

