Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2020/878

SAFETY DATA SHEET



TEKNOFLOOR 200F - All variants

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

Product name

: TEKNOFLOOR 200F - All variants

1.2 Relevant identified uses of the substance or mixture and uses advised against **Product use** : Paint.

1.3 Details of the supplier of the safety data sheet

Teknos Group Oy, Takkatie 3, FI-00370 HELSINKI, FINLAND. Tel. +358 9 506 091. e-mail address of person : Prod-safe@teknos.com responsible for this SDS

National contact

Teknos Group Oy, Takkatie 3, FI-00370 HELSINKI, FINLAND. Tel. +358 9 506 091.

1.4 Emergency telephone number

National advisory body/Poison Centre

: In an emergency, call 112 **Telephone number**

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Repr. 1B, H360F Aquatic Chronic 2, H411

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Hazard pictograms



Signal word	anger	
Hazard statements	315 - Causes skin irritation. 317 - May cause an allergic skin reaction. 319 - Causes serious eye irritation. 360F - May damage fertility. 411 - Toxic to aquatic life with long lasting effects.	
Precautionary statements		
Prevention	201 - Obtain special instructions before use. 280 - Wear protective gloves, protective clothing, eye protection, face prot r hearing protection. 273 - Avoid release to the environment.	tection,

Date of issue/Date of revision	: 10/10/2024	Date of previous issue	:10/11/2022	Version	:5	1/20
TEKNOFLOOR 200F - All variants				Label No	: <mark>8</mark> 602	21

SECTION 2: Hazards identification

Response	:	₱391 - Collect spillage. P308 + P313 - IF exposed or concerned: Get medical advice or attention.
Storage	1	Not applicable.
Disposal	:	P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.
Hazardous ingredients	:	Contains: Bis[4-(2,3-epoxypropoxy)phenyl]propane; Reaction mass of 2,2'- [methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis (4,1-phenyleneoxymethylene)]bis(oxirane) and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl] phenoxy}methyl)oxirane and Oxirane, mono[(C12-14-alkyloxy)methyl]derivs.
Supplemental label elements	:	Contains epoxy constituents. May produce an allergic reaction. Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	:	Restricted to professional users.
2.3 Other hazards		
Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII	:	This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

Other hazards which do : None known. not result in classification

SECTION 3: Composition/information on ingredients

3.2 Mixtures	: Mixture				
Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Туре
Bis[4-(2,3-epoxypropoxy) phenyl]propane	REACH #: 01-2119456619-26 EC: 216-823-5 CAS: 1675-54-3 Index: 603-073-00-2	≥25 - ≤50	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 2, H411	Skin Irrit. 2, H315: C ≥ 5% Eye Irrit. 2, H319: C ≥ 5%	[1]
Reaction mass of 2,2'- [methylenebis (2,1-phenyleneoxymethylene)] bis(oxirane) and 2,2'- [methylenebis (4,1-phenyleneoxymethylene)] bis(oxirane) and 2-({2-[4- (oxiran-2-ylmethoxy)benzyl] phenoxy}methyl)oxirane	CAS: 9003-36-5	≥10 - ≤25	Skin Irrit. 2, H315 Skin Sens. 1, H317 Aquatic Chronic 2, H411	-	[1]
titanium dioxide	REACH #: 01-2119489379-17 EC: 236-675-5 CAS: 13463-67-7	≥10 - ≤25	Carc. 2, H351 (inhalation)	-	[1] [*]
Oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	REACH #: 01-2119485289-22 EC: 271-846-8 CAS: 68609-97-2 Index: 603-103-00-4	≤10	Skin Irrit. 2, H315 Skin Sens. 1, H317 Repr. 1B, H360F	-	[1]
Date of issue/Date of revision		e of previous is	sue : 10/11/2022	Version : 5	2/20
TEKNOFLOOR 200F - All variants Label No : 6021					

SECTION 3: Composition/information on ingredients See Section 16 for the full text of the H statements declared above.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

<u>Type</u>

[1] Substance classified with a health or environmental hazard

[*] The classification as a carcinogen by inhalation applies only to mixtures placed on the market in powder form containing 1% or more of titanium dioxide particles with aerodynamic diameter \leq 10 µm not bound within a matrix.

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid n	neasures
Eye contact	: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Skin contact	: Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	: Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Protection of first-aiders	■ No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

Over-exposure signs/symptoms				
Eye contact	: Adverse symptoms may include the following: pain or irritation watering redness			
Inhalation	 Koverse symptoms may include the following: reduced foetal weight increase in foetal deaths skeletal malformations 			
Skin contact	: Adverse symptoms may include the following: irritation redness reduced foetal weight increase in foetal deaths skeletal malformations			

SECTION 4: First aid	
Ingestion	 Adverse symptoms may include the following: reduced foetal weight
	increase in foetal deaths
	skeletal malformations
4.3 Indication of any immedi	ate medical attention and special treatment needed
Notes to physician	 Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments	: No specific treatment.
SECTION 5: Firefigh	ting measures
5.1 Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
5.2 Special hazards arising f	rom the substance or mixture
Hazards from the substance or mixture	: In a fire or if heated, a pressure increase will occur and the container may burst. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
Hazardous combustion products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide halogenated compounds metal oxide/oxides
5.3 Advice for firefighters	
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident in there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.
SECTION 6: Acciden	ital release measures
6.1 Personal precautions, pr	otective equipment and emergency procedures
For non-emergency personnel	: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. But on appropriate personal protective equipment.

		inadequate. Put on appropriate personal protective equipment.
For emergency responders	1	If specialised clothing is required to deal with the spillage, take note of any
		information in Section 8 on suitable and unsuitable materials. See also the
		information in "For non-emergency personnel".

6.2 Environmental precautions
 Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

6.3 Methods and material for containment and cleaning up

SECTION 6: Accidental release measures

Small spill	: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	: Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product.
6.4 Reference to other sections	: See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

Protective measures	: Fut on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapour or mist. Avoid release to the environment. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

Seveso Directive - Reporting thresholds

Danger criteria			
	Notification and MAPP threshold	Safety report threshold	
E2	200 tonne	500 tonne	

7.3 Specific end use(s) Recommendations

: Not available.

Industrial sector specific solutions

: Not available.

: 10/10/2024 Date of previous issue

:10/11/2022

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

8.1 Control parameters

Occupational exposure limits

Product/ingredient name	Exposure limit values
₿īs[4-(2,3-epoxypropoxy)phenyl]propane Oxirane, mono[(C12-14-alkyloxy)methyl]derivs.	 Regulation on Limit Values - MAC (Austria, 4/2021). [1,2-Epoxy- 3-(tolyloxy)propane (all isomers)] TWA: 10 ppm 8 hours. TWA: 70 mg/m³ 8 hours. PEAK: 20 ppm, 4 times per shift, 15 minutes. PEAK: 140 mg/m³, 4 times per shift, 15 minutes. Regulation on Limit Values - MAC (Austria, 4/2021). [1,2-Epoxy- 3-(tolyloxy)propane (all isomers)] TWA: 10 ppm 8 hours. TWA: 70 mg/m³ 8 hours. PEAK: 20 ppm, 4 times per shift, 15 minutes. PEAK: 20 ppm, 4 times per shift, 15 minutes. PEAK: 20 ppm, 4 times per shift, 15 minutes. PEAK: 140 mg/m³, 4 times per shift, 15 minutes.
No exposure limit value known.	
Bis[4-(2,3-epoxypropoxy)phenyl]propane	DFG MAC-values list (Germany, 7/2022). Skin sensitiser.
No exposure limit value known.	
http://www.late.of.revision	to of providuo inque (10/11/2022)

Date of issue/Date of revision TEKNOFLOOR 200F - All variants

: 10/10/2024 Date of previous issue

:10/11/2022

• •	•
2-Methoxy-1-methylethyl acetate	EH40/2005 WELs (United Kingdom (UK), 1/2020). Absorbed
	through skin.
	STEL: 548 mg/m ³ 15 minutes.
	TWA: 50 ppm 8 hours.
	TWA: 274 mg/m ³ 8 hours.
	STEL: 100 ppm 15 minutes.

Biological exposure indices Product/ingredient name Exposure indices No exposure indices known. : Reference should be made to monitoring standards, such as the following: **Recommended monitoring** European Standard EN 689 (Workplace atmospheres - Guidance for the procedures assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures

 for the measurement of chemical agents) Reference to national guidance

 Date of issue/Date of revision
 : 10/10/2024
 Date of previous issue
 : 10/11/2022
 Version
 : 5
 7/20

 TEKNOFLOOR 200F - All variants
 Label No : \$6021

documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

Product/ingredient name	Туре	Exposure	Value	Population	Effects
Sis[4-(2,3-epoxypropoxy)phenyl] propane	DNEL	Long term Dermal	89.3 µg/kg bw/day	General population	Systemic
	DNEL	Long term Oral	0.5 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	0.75 mg/ kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	0.87 mg/m ³	General population	Systemic
	DNEL	Long term Inhalation	4.93 mg/m ³		Systemic
Reaction mass of 2,2'-[methylenebis (2,1-phenyleneoxymethylene)]bis (oxirane) and 2,2'-[methylenebis (4,1-phenyleneoxymethylene)]bis (oxirane) and 2-({2-[4-(oxiran- 2-ylmethoxy)benzyl]phenoxy}methyl) oxirane	DMEL	Short term Dermal	8.3 µg/cm²	Workers	Local
UNITATIO	DNEL	Long term Oral	6.25 mg/ kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	8.7 mg/m ³	General population	Systemic
	DNEL	Long term Inhalation	29.39 mg/ m³	Workers	Systemic
	DNEL	Long term Dermal	62.5 mg/ kg bw/day	General population	Systemic
	DNEL	Long term Dermal	104.15 mg/ kg bw/day	Workers	Systemic
Oxirane, mono[(C12-14-alkyloxy) methyl]derivs.	DNEL	Long term Oral	0.5 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	0.5 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	0.87 mg/m ³	General population	Systemic
	DNEL	Long term Dermal	1 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	3.6 mg/m ³	Workers	Systemic

PNECs

Product/ingredient name	Compartment Detail	Value	Method Detail
Reaction mass of 2,2'-[methylenebis (2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis (4,1-phenyleneoxymethylene)]bis(oxirane) and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl] phenoxy}methyl)oxirane	Fresh water	0.003 mg/l	-
	Fresh water sediment	0.294 mg/kg	-
	Marine water sediment	0.029 mg/kg	-
	Sewage Treatment Plant	10 mg/l	-
	Soil	0.237 mg/kg	-

8.2 Exposure controls

```
Appropriate engineering controls
```

: Fuser operations generate dust, fumes, gas, vapour or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Individual protection measures

Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.
Skin protection	
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
	Recommendations : Wear suitable gloves tested to EN374.
	< 1 hour (breakthrough time): Nitrile gloves. thickness > 0.3 mm
	> 8 hours (breakthrough time): 4H / Silver Shield® gloves.
	Wash hands before breaks and immediately after handling the product.
Body protection	 Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	 Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.
	Filter type: A
	Filter type (spray application): A P
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

<u>Appearance</u>	
Physical state	: Liquid.
Colour	: Various
Odour	: Slight
Odour threshold	: Not available.
Melting point/freezing point	: Not available.
Initial boiling point and boiling range	: Not available.
Flammability	: Not available.
Lower and upper explosion limit	: Lower: Not applicable. Upper: Not applicable.
Flash point	:

: 10/10/2024 Date of previous issue

		Closed cup			Open cup		
Ingredient name	°C	°F	Method	°C	°F	Method	
₿ſs[4-(2,3-epoxypropoxy)phenyl] propane				79	174.2		
Reaction mass of 2,2'- [methylenebis (2,1-phenyleneoxymethylene)]bis (oxirane) and 2,2'-[methylenebis (4,1-phenyleneoxymethylene)]bis (oxirane) and 2-({2-[4-(oxiran- 2-ylmethoxy)benzyl] phenoxy}methyl)oxirane	>93	>199.4	EU A.9				
uto-ignition temperature		ot available.					
ecomposition temperature		ot available.					
н	: 🕅	ot available.					
iscosity	: No	ot available.					
olubility(ies) Not available.	:						
olubility in water	: No	ot available.					
Partition coefficient: n-octa vater	nol/ : No	ot applicable.					

Vapour pressure

	Vapour Pressure at 20°C			Vapour pressure at 50°C		
Ingredient name	mm Hg	kPa	Method	mm Hg	kPa	Method
Reaction mass of 2,2'- [methylenebis (2,1-phenyleneoxymethylene)]bis (oxirane) and 2,2'-[methylenebis (4,1-phenyleneoxymethylene)]bis (oxirane) and 2-({2-[4-(oxiran- 2-ylmethoxy)benzyl] phenoxy}methyl)oxirane	0.62	0.083	EU A.4			
Oxirane, mono[(C12-14-alkyloxy) methyl]derivs.	0.00013	0.000017	OECD 104			

:	1.5 g/cm³
1	Not available.
1	Not available.
1	Not available.
1	Not applicable.
	: : :

1

9.2 Other information

No additional information.

SECTION 10: Stability and reactivity

10.1 Reactivity	: No specific test data related to react	tivity available for this	product or its ingred	lients.
10.2 Chemical stability	: The product is stable.			
10.3 Possibility of hazardous reactions	: Under normal conditions of storage	and use, hazardous r	eactions will not occ	xur.
10.4 Conditions to avoid	: No specific data.			
Date of issue/Date of revision	: 10/10/2024 Date of previous issue	: 10/11/2022	Version : 5	10/20

SECTION 10: Stability and reactivity

10.5 Incompatible materials : No specific data.

10.6 Hazardous decomposition products

: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
₿is[4-(2,3-epoxypropoxy) phenyl]propane	LD50 Dermal	Rabbit	20 g/kg	-
Reaction mass of 2,2'- [methylenebis (2,1-phenyleneoxymethylene)] bis(oxirane) and 2,2'- [methylenebis (4,1-phenyleneoxymethylene)] bis(oxirane) and 2-({2-[4- (oxiran-2-ylmethoxy)benzyl] phenoxy}methyl)oxirane	LD50 Dermal	Rat	>2000 mg/kg	-
Oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	LD50 Oral LD50 Oral	Rat Rat	>5000 mg/kg 17100 mg/kg	-
Conclusion/Summary	: Based on available data, th	e classification crite	eria are not met.	

Acute toxicity estimates

Route	ATE value
Not available.	

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
₿ı́s[4-(2,3-epoxypropoxy)	Eyes - Severe irritant	Rabbit	-	24 hours 2	-
phenyl]propane				mg	
	Skin - Mild irritant	Rabbit	-	500 mg	-
Reaction mass of 2,2'-	Skin - Mild irritant	Rabbit	-	24 hours 500	-
[methylenebis				uL	
(2,1-phenyleneoxymethylene)]					
bis(oxirane) and 2,2'-					
[methylenebis (4,1-phenyleneoxymethylene)]					
bis(oxirane) and 2-({2-[4-					
(oxiran-2-ylmethoxy)benzyl]					
phenoxy}methyl)oxirane					
titanium dioxide	Skin - Mild irritant	Human	-	72 hours 300	-
				ug l	
Oxirane, mono[Skin - Moderate irritant	Rabbit	-	24 hours 500	-
(C12-14-alkyloxy)methyl]				uL	
derivs.					
Conclusion/Summary	: Causes skin irritation.			·	
Sensitisation					
Conclusion/Summary	: May cause an allergic skin rea	action.			

Conclusion/Summary : Based on available data, the classification criteria are not met.

Carcinogenicity

Mutagenicity

It has been observed that the carcinogenic hazard of this product arises when respirable dust is inhaled in quantities leading to significant impairment of particle clearance mechanisms in the lung.

Conclusion/Summary : Based on available data, the classification criteria are not met.

Date of issue/Date of revision	: 10/10/2024	Date of previous issue	: 10/11/2022	Version :	5 11/20	,
TEKNOFLOOR 200F - All variants				Label No :8	6021	

Reproductive toxicity Conclusion/Summary : May damage fertility. Teratogenicity
Specific target organ toxicity (repeated exposure) Not available. Aspiration hazard Not available. Information on likely routes of exposure : Not available. Potential acute health effects Eye contact : Causes serious eye irritation. Inhalation : No known significant effects or critical hazards. Skin contact : Causes skin irritation. May cause an allergic skin reaction. Ingestion : No known significant effects or critical hazards. Symptoms related to the physical, chemical and toxicological characteristics Eye contact : Adverse symptoms may include the following: pain or irritation watering redness
Not available. Aspiration hazard Not available. Information on likely routes : Not available. of exposure Potential acute health effects Eye contact : Causes serious eye irritation. Inhalation : No known significant effects or critical hazards. Skin contact : Causes skin irritation. May cause an allergic skin reaction. Ingestion : No known significant effects or critical hazards. Symptoms related to the physical. chemical and toxicological characteristics Eye contact : Adverse symptoms may include the following: pain or irritation watering redness
Not available. Information on likely routes of exposure : Not available. Potential acute health effects Eye contact : Causes serious eye irritation. Inhalation : No known significant effects or critical hazards. Skin contact : Causes skin irritation. May cause an allergic skin reaction. Ingestion : No known significant effects or critical hazards. Symptoms related to the physical. chemical and toxicological characteristics Eye contact : Adverse symptoms may include the following: pain or irritation watering redness
of exposure Potential acute health effects Eye contact : Causes serious eye irritation. Inhalation : No known significant effects or critical hazards. Skin contact : Causes skin irritation. May cause an allergic skin reaction. Ingestion : No known significant effects or critical hazards. Symptoms related to the physical. chemical and toxicological characteristics Eye contact : Adverse symptoms may include the following: pain or irritation watering redness
Eye contact: Causes serious eye irritation.Inhalation: No known significant effects or critical hazards.Skin contact: Causes skin irritation. May cause an allergic skin reaction.Ingestion: No known significant effects or critical hazards.Symptoms related to the physical, chemical and toxicological characteristicsEye contact: Adverse symptoms may include the following: pain or irritation watering redness
Inhalation: No known significant effects or critical hazards.Skin contact: Causes skin irritation. May cause an allergic skin reaction.Ingestion: No known significant effects or critical hazards.Symptoms related to the physical, chemical and toxicological characteristicsEye contact: Adverse symptoms may include the following: pain or irritation watering redness
Skin contact : Causes skin irritation. May cause an allergic skin reaction. Ingestion : No known significant effects or critical hazards. Symptoms related to the physical, chemical and toxicological characteristics Eye contact : Adverse symptoms may include the following: pain or irritation watering redness
Ingestion : No known significant effects or critical hazards. Symptoms related to the physical, chemical and toxicological characteristics Eye contact : Adverse symptoms may include the following: pain or irritation watering redness
Symptoms related to the physical, chemical and toxicological characteristics Eye contact : Adverse symptoms may include the following: pain or irritation watering redness
Eye contact : Adverse symptoms may include the following: pain or irritation watering redness
pain or irritation watering redness
Inhalation : K dverse symptoms may include the following:
reduced foetal weight increase in foetal deaths skeletal malformations
Skin contact : Adverse symptoms may include the following: irritation redness reduced foetal weight increase in foetal deaths skeletal malformations
Ingestion : Adverse symptoms may include the following: reduced foetal weight increase in foetal deaths skeletal malformations
Delayed and immediate effects as well as chronic effects from short and long-term exposure
Short term exposure
Potential immediate : Not available. effects
Potential delayed effects : Not available.
Long term exposure
Potential immediate : Not available. effects
Potential delayed effects : Not available.
Potential chronic health effects Not available.
Conclusion/Summary : Not available.
General : Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
Date of issue/Date of revision : 10/10/2024 Date of previous issue : 10/11/2022 Version : 5 12/20 TEKNOFLOOR 200F - All variants Label No : \$6021

SECTION 11: Toxicological information

Carcinogenicity

Mutagenicity

- : No known significant effects or critical hazards.
- : No known significant effects or critical hazards.

Reproductive toxicity

: May damage fertility.

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

Not available.

11.2.2 Other information

Not available.

SECTION 12: Ecological information

12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
Reaction mass of 2,2'- [methylenebis (2,1-phenyleneoxymethylene)] bis(oxirane) and 2,2'- [methylenebis (4,1-phenyleneoxymethylene)] bis(oxirane) and 2-({2-[4- (oxiran-2-ylmethoxy)benzyl] phenoxy}methyl)oxirane		Algae	72 hours
priorioxyjiriotrijijoxilario	EC50 2.55 mg/l	Daphnia - Daphnia magna	48 hours
	Chronic LC50 2.54 mg/l	Fish	96 hours
titanium dioxide	Acute LC50 3 mg/l Fresh water	Crustaceans - Ceriodaphnia dubia - Neonate	48 hours
	Acute LC50 6.5 mg/l Fresh water	Daphnia - <i>Daphnia pulex</i> - Neonate	48 hours
	Acute LC50 >1000000 μg/l Marine water	Fish - Fundulus heteroclitus	96 hours

Conclusion/Summary : Toxic to aquatic life with long lasting effects.

12.2 Persistence and degradability

Conclusion/Summary : This product has not been tested for biodegradation.

12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
Reaction mass of 2,2'- [methylenebis (2,1-phenyleneoxymethylene)] bis(oxirane) and 2,2'- [methylenebis (4,1-phenyleneoxymethylene)] bis(oxirane) and 2-({2-[4- (oxiran-2-ylmethoxy)benzyl]		-	Low
phenoxy}methyl)oxirane Oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	3.77	160 to 263	Low

12.4 Mobility in soil

Soil/water partition coefficient (Koc)	: Not available.
Mobility	: Not available.

12.5 Results of PBT and vPvB assessment

Date of issue/Date of revision : 10/10/2024

D24 Date of previous issue

:10/11/2022

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Endocrine disrupting properties

Not available.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

13.1 Waste treatment meth	ods
Product	
Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
European waste catalogue (EWC)	: 080111*, 200127*
Packaging	
Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.
Special precautions	This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

	-			
	ADR/RID	ADN	IMDG	ΙΑΤΑ
14.1 UN number or ID number	UN3082	UN3082	UN3082	UN3082
14.2 UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy resin)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy resin)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy Resin)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy Resin)
14.3 Transport hazard class(es)	9	9	9	9
14.4 Packing group	111	111	111	111
14.5 Environmental hazards	Yes.	Yes.	Yes.	Yes.

Additional information

ADR/RID

This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.
 Tunnel code (-)

SECTION 14: Transp	t information	
ADN	This product is not regulated as a dangerous good when transported in sizes of \leq or \leq 5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.	
IMDG	This product is not regulated as a dangerous good when transported in sizes of \leq or \leq 5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.	
ΙΑΤΑ	This product is not regulated as a dangerous good when transported in sizes of \leq or \leq 5 kg, provided the packagings meet the general provisions of 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8.	:5 L
14.6 Special precautions for user	Transport within user's premises: always transport in closed containers that ar upright and secure. Ensure that persons transporting the product know what to do the event of an accident or spillage.	
14.7 Maritime transport in bulk according to IMO instruments	Not relevant/applicable due to nature of the product.	
SECTION 15: Regula	ry information	

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Product/ingredient name		%	Designation [Usage]			
KNOFLOOR 200F		≥90	3			
Oxirane, mono[(C12-14-alky	yloxy)methyl]	≤10	30 30			
Labelling	: Restricted to	o profession	al users.			
Other EU regulations						
Industrial emissions (integrated pollution prevention and control) - Air	: Not listed					
Industrial emissions (integrated pollution prevention and control) - Water	: Not listed					
Explosive precursors	: Not applicat	ole.				
Ozone depleting substanc Not listed.	<u>es (1005/2009/I</u>	<u>EU)</u>				
Prior Informed Consent (P Not listed.	<u>IC) (649/2012/E</u>	<u>U)</u>				
Persistent Organic Polluta Not listed.	<u>nts</u>					
Seveso Directive						
This product is controlled un Danger criteria	der the Seveso	Directive.				
te of issue/Date of revision	: 10/10/2024	Date of prev	ious issue : 10/11/2022	Version	:5	15/20
EKNOFLOOR 200F - All varia	ants			Label No	: 86021	1

S

ECTION 15: Regula	tory information				
Category					
E2					
ational regulations Austria	. Downsitted				
Limitation of the use of organic solvents	: Permitted.				
<u>Czech Republic</u> Storage code <u>Denmark</u>	: 🕅				
Executive Order No. 1795/2	<u>2015</u>				
Ingredient name		Annex I Section A	Annex I Section B		
titanium dioxide		Listed	-		
MAL-code	: 3-5				
Protection based on MAL	: According to the regulations on stipulations apply to the use of General: Gloves must be worn for coveralls/protective clothing must	personal protective equi or all work that may result i be worn when soiling is so	pment: n soiling. Apron/ great that regular work		
	clothes do not adequately protect skin against contact with the product. A face shield must be worn in work involving spattering if a full mask is not required. In this case, other recommended use of eye protection is not required. In all spraying operations in which there is return spray, the following must be worn: respiratory protection and arm protectors/apron/coveralls/protective clothing as appropriate or as instructed.				
	MAL-code: 3-5 Application: When using scraper or knife, brush, roller etc. for pre- and post- treatments in a spray booth where the operator is outside the spray zone and when working in similar new* facilities of the combined-cabin, spray-cabin and spray-booth type where the operator is working inside the spray zone. When spraying in new* booths and cabins with non-atomizing guns.				
	- Protective clothing must be worn				
	During downtimes, cleaning and re there is a risk of contact with wet p knife, brush, roller, etc, for pre- an existing* facility type, if the operate knife, brush, roller, etc. for pre- an booth or spray cabin.	paint or organic solvents. d post-treatments in cabin or is inside the spray zone.	When using scraper or s or booths of the When using scraper o		
	- Air-supplied half mask, protective	e clothing and eye protection	on must be worn.		
	When spraying in new* booths if the operator is outside the spray zone.				
	- Air-supplied half mask and eye protection must be worn.				
	When spraying in existing* spray b During non-atomising spraying in cabin and spray-booth type where	existing* facilities of the co	mbined-cabin, spray-		
	- Air-supplied full mask and protec	tive clothing must be worr	1.		
	During all spraying where atomisa operator is inside the spray zone a or booth.				

Drying: Items for drying/drying ovens that are temporarily placed on such things as rack trolleys, etc, must be equipped with a mechanical exhaust system to prevent fumes from wet items from passing through workers' inhalation zone. **Polishing:** When polishing treated surfaces, a mask with dust filter must be worn. When machine grinding, eye protection must be worn. Work gloves must always be worn. **Caution** The regulations contain other stipulations in addition to the above. *See Regulations. **Restrictions on use** : Not to be used by professional users below 18 years of age. See the National Working Environment Authorities Executive Order regarding Young People At Work. : Not listed List of undesirable substances : Waste containers must be labeled: Contains a substance or substances regulated Carcinogenic waste by Danish working environment legislation on cancer risks. The product is covered by the rules for epoxy resins and isocyanates in Executive Epoxy/lsocyanate 5 Order no. 1793 of 18/12/2015 on working with substances and materials (chemical agents). Pay attention to the rules, for example: the user of the product must have undergone special training and waste must be labelled. This requirement is in addition to the training requirement described in the REACH regulation, Annex XVII, entry 74 (COMMISSION REGULATION (EU) 2020/1149). **Finland** France : Øxirane, mono[(C12-14-alkyloxy)methyl]derivs. RG 84 Social Security Code, Articles L 461-1 to L 461-7 **Reinforced medical** : Act of July 11, 1977 determining the list of activities which require reinforced medical surveillance: not applicable surveillance Germany Storage class (TRGS 510) : 6.1D

- Air-supplied full mask, protective clothing and hood must be worn.

Hazardous incident ordinance

This product is controlled under the Germany Hazardous Incident Ordinance.

Danger criteria

Category		Reference number
E2		1.3.2
Hazard class for water	: 2	
Technical instruction on air quality control	: TA-Luft Number 5.2.5: 57.1%	
ΑΟΧ	: The product contains organically bound halogens a value in waste water.	and can contribute to the AOX
<u>Italy</u>		
D.Lgs. 152/06	: Not determined.	
Netherlands		
Ministry of Social Affairs a reprotoxic substances	nd Employment (SZW) - Carcinogenic substances	and processes, mutagenic o

: 10/10/2024 Date of previous issue

Ingredient name	Carcinogen	Mutagen	Reproductive toxicity - Fertility	Reproductive toxicity - Development	Harmful via breastfeeding
Solvent naphtha (petroleum), light arom.	Listed	Listed	-	-	-
Water Discharge Po (ABM)	environm	nent (carcinogeni	ubstances with haza city/ mutagenicity/ re econtamination effort	protoxicity/ bioacun	
<u>Norway</u>	-				
<u>Sweden</u>					
Epoxy/Isocyanate	allergeni Working of under be labell addition	c chemical produ Environment. Pa gone necessary t ed with named su to the training red	y the specific rules for acts in provision AFS ay attention to that ha craining and can requi ubstance and as Haz quirement described in REGULATION (EU) 2	2011:19 Chemical ndling the product i ire medical examin ardous waste. This in the REACH regu	Hazards in the requires certificat ation. Waste mus requirement is ir
Switzerland				·	
VOC content	: Exempt.				
nternational regulation	<u>ons</u>				
hemical Weapon Co Not listed.	onvention List Sch	edules I, II & III (<u>Chemicals</u>		
Iontreal Protocol Not listed.					
itockholm Conventic Not listed.	on on Persistent O	rganic Pollutant	<u>ts</u>		
Rotterdam Convention Not listed.	on on Prior Informe	ed Consent (PIC	1		
INECE Aarhus Proto Not listed.	col on POPs and I	<u>leavy Metals</u>			
.2 Chemical safety sessment	: This proc required.		ostances for which Ch	nemical Safety Ass	essments are stil
ECTION 16: Ot	her informati	on			
Indicates information	n that has changed	from previously i	ssued version.		
obreviations and cronyms			mate elling and Packaging	Regulation [Regulation]	ation (EC) No.
	1212/200				

Abbreviations and acronyms	 ATE = Acute Toxicity Estimate CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008] DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level EUH statement = CLP-specific Hazard statement N/A = Not available PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration RRN = REACH Registration Number SGG = Segregation Group
	vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

SECTION 16: Other information			
Classification		Justification	
Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Repr. 1B, H360F Aquatic Chronic 2, H411		Calculation method Calculation method Calculation method Calculation method Calculation method	
Full text of abbreviated H statements			
H317 May o H319 Caus H351 Susp H360F May o	317May cause an allergic skin reaction.319Causes serious eye irritation.351Suspected of causing cancer.360FMay damage fertility.		
Full text of classifications [CLP/GHS]			
Aquatic Chronic 2 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2 Carc. 2 CARCINOGENICITY - Category 2 Eye Irrit. 2 SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2 Repr. 1B REPRODUCTIVE TOXICITY - Category 1B Skin Irrit. 2 SKIN CORROSION/IRRITATION - Category 2 Skin Sens. 1 SKIN SENSITISATION - Category 1			
Date of issue/ Date of : 10/10/2024 revision			
Date of previous issue	e : 10/11/2022		
Version	: 5 TEKNOFLOOR 200F		

Notice to reader

The information in this SDS is based on the present state of our knowledge and on current laws. The product is not to be used for purposes other than those specified under section 1 without first obtaining written handling instructions. It is always the responsibility of the user to take all necessary steps to fulfil the demands set out in the local rules and legislation. The information in this SDS is meant to be a description of the safety requirements for our product. It is not to be considered a guarantee of the product's properties.

Date of issue/Date of revision TEKNOFLOOR 200F - All variants

: 10/10/2024 Date of previous issue