

SAFETY DATA SHEET



TEKNOFLOOR 300F - All variants

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : TEKNOFLOOR 300F - All variants

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Paint.

1.3 Details of the supplier of the safety data sheet

Teknos Group Oy, Takkatie 3, FI-00370 HELSINKI, FINLAND. Tel. +358 9 506 091.

e-mail address of person responsible for this SDS : Prod-safe@teknos.com

National contact

Teknos Group Oy, Takkatie 3, FI-00370 HELSINKI, FINLAND. Tel. +358 9 506 091.

1.4 Emergency telephone number

National advisory body/Poison Centre

Telephone number : National Poisons Information Centre: 01 809 2566

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

☑ Skin Irrit. 2, H315
Eye Irrit. 2, H319
Skin Sens. 1, H317
Repr. 1B, H360F
Aquatic Chronic 2, H411

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Hazard pictograms :



Signal word : ☑ Danger

Hazard statements : ☑ H315 - Causes skin irritation.
H317 - May cause an allergic skin reaction.
H319 - Causes serious eye irritation.
H360F - May damage fertility.
H411 - Toxic to aquatic life with long lasting effects.

Precautionary statements

Prevention : ☑ P201 - Obtain special instructions before use.
P280 - Wear protective gloves, protective clothing, eye protection, face protection, or hearing protection.
P273 - Avoid release to the environment.

SECTION 2: Hazards identification

Response	: P391 - Collect spillage. P308 + P313 - IF exposed or concerned: Get medical advice or attention.
Storage	: Not applicable.
Disposal	: P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.
Hazardous ingredients	: Contains: Bis[4-(2,3-epoxypropoxy)phenyl]propane; Oxirane, mono[(C12-14-alkyloxy)methyl]derivs.; Benzyl alcohol and Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy)methyl}oxirane
Supplemental label elements	: Contains epoxy constituents. May produce an allergic reaction.
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	: Restricted to professional users.

2.3 Other hazards

Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII	: This mixture does not contain any substances that are assessed to be a PBT or a vPvB.
Other hazards which do not result in classification	: None known.

SECTION 3: Composition/information on ingredients

3.2 Mixtures : Mixture

Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Type
Bis[4-(2,3-epoxypropoxy)phenyl]propane	REACH #: 01-2119456619-26 EC: 216-823-5 CAS: 1675-54-3 Index: 603-073-00-2	≥50 - ≤75	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 2, H411	Skin Irrit. 2, H315: C ≥ 5% Eye Irrit. 2, H319: C ≥ 5%	[1]
Oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	REACH #: 01-2119485289-22 EC: 271-846-8 CAS: 68609-97-2 Index: 603-103-00-4	≥10 - ≤25	Skin Irrit. 2, H315 Skin Sens. 1, H317 Repr. 1B, H360F	-	[1]
Benzyl alcohol	REACH #: 01-2119492630-38 EC: 202-859-9 CAS: 100-51-6 Index: 603-057-00-5	≤10	Acute Tox. 4, H302 Eye Irrit. 2, H319 Skin Sens. 1B, H317	ATE [Oral] = 1200 mg/kg	[1]
Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy)methyl}oxirane	REACH #: 01-2119454392-40 EC: 500-006-8 CAS: 9003-36-5	≤5	Skin Irrit. 2, H315 Skin Sens. 1, H317 Aquatic Chronic 2, H411	-	[1]

SECTION 3: Composition/information on ingredients

See Section 16 for the full text of the H statements declared above.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

[1] Substance classified with a health or environmental hazard

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Skin contact** : Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:
pain or irritation
watering
redness
- Inhalation** : Adverse symptoms may include the following:
reduced foetal weight
increase in foetal deaths
skeletal malformations
- Skin contact** : Adverse symptoms may include the following:
irritation
redness
reduced foetal weight
increase in foetal deaths
skeletal malformations

SECTION 4: First aid measures

- Ingestion** : Adverse symptoms may include the following:
reduced foetal weight
increase in foetal deaths
skeletal malformations

4.3 Indication of any immediate medical attention and special treatment needed

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media** : Use an extinguishing agent suitable for the surrounding fire.
- Unsuitable extinguishing media** : None known.

5.2 Special hazards arising from the substance or mixture

- Hazards from the substance or mixture** : In a fire or if heated, a pressure increase will occur and the container may burst. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
- Hazardous combustion products** : Decomposition products may include the following materials:
carbon dioxide
carbon monoxide
halogenated compounds

5.3 Advice for firefighters

- Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions

- : Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

6.3 Methods and material for containment and cleaning up

- Small spill** : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

SECTION 6: Accidental release measures

- Large spill** : Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product.
- 6.4 Reference to other sections** : See Section 1 for emergency contact information.
See Section 8 for information on appropriate personal protective equipment.
See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapour or mist. Avoid release to the environment. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

Seveso Directive - Reporting thresholds

Danger criteria

Category	Notification and MAPP threshold	Safety report threshold
E2	200 tonne	500 tonne

7.3 Specific end use(s)

- Recommendations** : Not available.
- Industrial sector specific solutions** : Not available.

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

8.1 Control parameters

Occupational exposure limits

SECTION 8: Exposure controls/personal protection

Product/ingredient name	Exposure limit values
No exposure limit value known.	

Biological exposure indices

Product/ingredient name	Exposure indices
No exposure indices known.	

Recommended monitoring procedures : Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

Product/ingredient name	Type	Exposure	Value	Population	Effects
Bis[4-(2,3-epoxypropoxy)phenyl]propane	DNEL	Long term Dermal	89.3 µg/kg bw/day	General population	Systemic
	DNEL	Long term Oral	0.5 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	0.75 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	0.87 mg/m ³	General population	Systemic
	DNEL	Long term Inhalation	4.93 mg/m ³	Workers	Systemic
Oxirane, mono[(C12-14-alkyloxy)methyl]derivs.	DNEL	Long term Oral	0.5 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	0.5 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	0.87 mg/m ³	General population	Systemic
	DNEL	Long term Dermal	1 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	3.6 mg/m ³	Workers	Systemic
Benzyl alcohol	DNEL	Long term Oral	4 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	4 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	5.4 mg/m ³	General population	Systemic
	DNEL	Long term Dermal	8 mg/kg bw/day	Workers	Systemic
	DNEL	Short term Oral	20 mg/kg bw/day	General population	Systemic
	DNEL	Short term Dermal	20 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	22 mg/m ³	Workers	Systemic
	DNEL	Short term Inhalation	27 mg/m ³	General population	Systemic
	DNEL	Short term Dermal	40 mg/kg bw/day	Workers	Systemic
	DNEL	Short term Inhalation	110 mg/m ³	Workers	Systemic
	DMEL	Short term Dermal	8.3 µg/cm ²	Workers	Local

SECTION 8: Exposure controls/personal protection

(oxirane) and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy)methyl}oxirane	DNEL	Long term Oral	6.25 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	8.7 mg/m ³	General population	Systemic
	DNEL	Long term Inhalation	29.39 mg/m ³	Workers	Systemic
	DNEL	Long term Dermal	62.5 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	104.15 mg/kg bw/day	Workers	Systemic

PNECs

Product/ingredient name	Compartment Detail	Value	Method Detail
Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy)methyl}oxirane	Fresh water	0.003 mg/l	-
	Fresh water sediment	0.294 mg/kg	-
	Marine water sediment	0.029 mg/kg	-
	Sewage Treatment Plant	10 mg/l	-
	Soil	0.237 mg/kg	-

8.2 Exposure controls

Appropriate engineering controls

- If user operations generate dust, fumes, gas, vapour or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Individual protection measures

Hygiene measures

- Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

- Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

Skin protection

Hand protection

- Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Recommendations : Wear suitable gloves tested to EN374.

< 1 hour (breakthrough time): Nitrile gloves. thickness > 0.3 mm

> 8 hours (breakthrough time): 4H / Silver Shield® gloves.

Wash hands before breaks and immediately after handling the product.

Body protection

- Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

SECTION 8: Exposure controls/personal protection

- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.
Filter type: A
Filter type (spray application): A P
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

Appearance

- Physical state** : Liquid.
- Colour** : Various
- Odour** : Slight
- Odour threshold** : Not available.
- Melting point/freezing point** : Not available.
- Initial boiling point and boiling range** :

Ingredient name	°C	°F	Method
Benzyl alcohol	205.3	401.5	

- Flammability** : Not available.
- Lower and upper explosion limit** : Lower: 1.3% (benzyl alcohol)
Upper: 13% (benzyl alcohol)
- Flash point** : Closed cup: 101°C (213.8°F)
- Auto-ignition temperature** :

Ingredient name	°C	°F	Method
Benzyl alcohol	436	816.8	

- Decomposition temperature** : Not available.
- pH** : Not applicable.
- Viscosity** : Not available.
- Solubility(ies)** :
Not available.
- Solubility in water** : Not available.
- Partition coefficient: n-octanol/ water** : Not applicable.
- Vapour pressure** :

SECTION 9: Physical and chemical properties

Ingredient name	Vapour Pressure at 20°C			Vapour pressure at 50°C		
	mm Hg	kPa	Method	mm Hg	kPa	Method
Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy)methyl}oxirane	0.62	0.083	EU A.4			
Benzyl alcohol	0.05	0.0067				

Relative density	: Not available.
Density	: 1.1 g/cm ³
Vapour density	: Not available.
Explosive properties	: Not available.
Oxidising properties	: Not available.
Particle characteristics	
Median particle size	: Not applicable.

9.2 Other information

No additional information.

SECTION 10: Stability and reactivity

10.1 Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	: The product is stable.
10.3 Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
10.4 Conditions to avoid	: No specific data.
10.5 Incompatible materials	: No specific data.
10.6 Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Bis[4-(2,3-epoxypropoxy)phenyl]propane Oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	LD50 Dermal	Rabbit	20 g/kg	-
	LD50 Oral	Rat	17100 mg/kg	-
Benzyl alcohol	LC50 Inhalation Dusts and mists	Rat - Male, Female	4200 mg/m ³	4 hours
	LD50 Dermal	Rabbit	2000 mg/kg	-
	LD50 Oral	Rat	1230 mg/kg	-
	LD50 Dermal	Rat	>2000 mg/kg	-
	LD50 Dermal	Rat	>2000 mg/kg	-
Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-({2-[4-				

Date of issue/Date of revision : 10/10/2024 Date of previous issue : 10/11/2022 Version : 2 9/16

TEKNOFLOOR 300F - All variants

Label No : 86019

SECTION 11: Toxicological information

(oxiran-2-ylmethoxy)benzyl] phenoxy)methyl)oxirane	LD50 Oral	Rat	>5000 mg/kg	-
--	-----------	-----	-------------	---

Conclusion/Summary : Based on available data, the classification criteria are not met.

Acute toxicity estimates

Route	ATE value
Oral	13957.25 mg/kg

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Bis[4-(2,3-epoxypropoxy) phenyl]propane	Eyes - Severe irritant	Rabbit	-	24 hours 2 mg	-
	Skin - Mild irritant	Rabbit	-	500 mg	-
Oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	Skin - Moderate irritant	Rabbit	-	24 hours 500 uL	-
	Skin - Mild irritant	Man	-	48 hours 16 mg	-
Benzyl alcohol	Skin - Moderate irritant	Pig	-	100 %	-
	Skin - Moderate irritant	Rabbit	-	24 hours 100 mg	-
Reaction mass of 2,2'- [methylenebis (2,1-phenyleneoxymethylene)] bis(oxirane) and 2,2'- [methylenebis (4,1-phenyleneoxymethylene)] bis(oxirane) and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl] phenoxy)methyl)oxirane	Skin - Mild irritant	Rabbit	-	24 hours 500 uL	-

Conclusion/Summary : Causes skin irritation.

Sensitisation

Conclusion/Summary : May cause an allergic skin reaction.

Mutagenicity

Conclusion/Summary : Based on available data, the classification criteria are not met.

Carcinogenicity

Conclusion/Summary : Based on available data, the classification criteria are not met.

Reproductive toxicity

Conclusion/Summary : May damage fertility.

Teratogenicity

Conclusion/Summary : Based on available data, the classification criteria are not met.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.

Information on likely routes of exposure : Not available.

Potential acute health effects

Eye contact : Causes serious eye irritation.

Inhalation : No known significant effects or critical hazards.

Date of issue/Date of revision : 10/10/2024 **Date of previous issue** : 10/11/2022

Version : 2 **10/16**

TEKNOFLOOR 300F - All variants

Label No : 86019

SECTION 11: Toxicological information

- Skin contact** : Causes skin irritation. May cause an allergic skin reaction.
Ingestion : No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

- Eye contact** : Adverse symptoms may include the following:
pain or irritation
watering
redness
- Inhalation** : Adverse symptoms may include the following:
reduced foetal weight
increase in foetal deaths
skeletal malformations
- Skin contact** : Adverse symptoms may include the following:
irritation
redness
reduced foetal weight
increase in foetal deaths
skeletal malformations
- Ingestion** : Adverse symptoms may include the following:
reduced foetal weight
increase in foetal deaths
skeletal malformations

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Short term exposure

- Potential immediate effects** : Not available.
Potential delayed effects : Not available.

Long term exposure

- Potential immediate effects** : Not available.
Potential delayed effects : Not available.

Potential chronic health effects

Not available.

- Conclusion/Summary** : Not available.
General : Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
Carcinogenicity : No known significant effects or critical hazards.
Mutagenicity : No known significant effects or critical hazards.
Reproductive toxicity : May damage fertility.

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

Not available.

11.2.2 Other information

Not available.

SECTION 12: Ecological information

12.1 Toxicity

SECTION 12: Ecological information

Product/ingredient name	Result	Species	Exposure
Benzyl alcohol Reaction mass of 2,2'- [methylenebis (2,1-phenyleneoxymethylene)] bis(oxirane) and 2,2'- [methylenebis (4,1-phenyleneoxymethylene)] bis(oxirane) and 2-({2-[4- (oxiran-2-ylmethoxy)benzyl] phenoxy}methyl)oxirane	Acute LC50 10000 µg/l Fresh water EC50 1.8 mg/l	Fish - <i>Lepomis macrochirus</i> Algae	96 hours 72 hours
	EC50 2.55 mg/l Chronic LC50 2.54 mg/l	Daphnia - <i>Daphnia magna</i> Fish	48 hours 96 hours

Conclusion/Summary : Toxic to aquatic life with long lasting effects.

12.2 Persistence and degradability

Conclusion/Summary : This product has not been tested for biodegradation.

12.3 Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
Oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	3.77	160 to 263	Low
Benzyl alcohol Reaction mass of 2,2'- [methylenebis (2,1-phenyleneoxymethylene)] bis(oxirane) and 2,2'- [methylenebis (4,1-phenyleneoxymethylene)] bis(oxirane) and 2-({2-[4- (oxiran-2-ylmethoxy)benzyl] phenoxy}methyl)oxirane	0.87 2.7	- -	Low Low

12.4 Mobility in soil

Soil/water partition coefficient (K_{oc}) : Not available.

Mobility : Not available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Endocrine disrupting properties

Not available.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations





13.1 Waste treatment methods

Product

SECTION 13: Disposal considerations

- Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
- European waste catalogue (EWC)** : 080111*, 200127*
- Packaging**
- Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.
- Special precautions** : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spill material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

	ADR/RID	ADN	IMDG	IATA
14.1 UN number or ID number	UN3082	UN3082	UN3082	UN3082
14.2 UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy resin)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy resin)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy Resin)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy Resin)
14.3 Transport hazard class(es)	9 	9 	9 	9 
14.4 Packing group	III	III	III	III
14.5 Environmental hazards	Yes.	Yes.	Yes.	Yes.

Additional information

- ADR/RID** : This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.
Tunnel code (-)
- ADN** : This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.
- IMDG** : This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.
- IATA** : This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8.

- 14.6 Special precautions for user** : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

SECTION 14: Transport information

14.7 Maritime transport in bulk according to IMO instruments : Not relevant/applicable due to nature of the product.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Product/ingredient name	%	Designation [Usage]
<input checked="" type="checkbox"/> TEKNOFLOOR 300F	≥90	3
Oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	≥10 - ≤25	30 30

Labelling : Restricted to professional users.

Other EU regulations

Industrial emissions (integrated pollution prevention and control) - Air : Not listed

Industrial emissions (integrated pollution prevention and control) - Water : Not listed

Explosive precursors : Not applicable.

Ozone depleting substances (1005/2009/EU)

Not listed.

Prior Informed Consent (PIC) (649/2012/EU)

Not listed.

Persistent Organic Pollutants

Not listed.

Seveso Directive

This product is controlled under the Seveso Directive.

Danger criteria

Category
E2

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

SECTION 15: Regulatory information

Not listed.

[UNECE Aarhus Protocol on POPs and Heavy Metals](#)

Not listed.

15.2 Chemical safety assessment : This product contains substances for which Chemical Safety Assessments are still required.

SECTION 16: Other information

✔ Indicates information that has changed from previously issued version.

Abbreviations and acronyms :

- ATE = Acute Toxicity Estimate
- CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
- DMEL = Derived Minimal Effect Level
- DNEL = Derived No Effect Level
- EUH statement = CLP-specific Hazard statement
- N/A = Not available
- PBT = Persistent, Bioaccumulative and Toxic
- PNEC = Predicted No Effect Concentration
- RRN = REACH Registration Number
- SGG = Segregation Group
- vPvB = Very Persistent and Very Bioaccumulative

[Procedure used to derive the classification according to Regulation \(EC\) No. 1272/2008 \[CLP/GHS\]](#)

Classification	Justification
✔ Skin Irrit. 2, H315	Calculation method
Eye Irrit. 2, H319	Calculation method
Skin Sens. 1, H317	Calculation method
Repr. 1B, H360F	Calculation method
Aquatic Chronic 2, H411	Calculation method

[Full text of abbreviated H statements](#)

✔ H302	Harmful if swallowed.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H360F	May damage fertility.
H411	Toxic to aquatic life with long lasting effects.

[Full text of classifications \[CLP/GHS\]](#)

✔ Acute Tox. 4	ACUTE TOXICITY - Category 4
Aquatic Chronic 2	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2
Eye Irrit. 2	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2
Repr. 1B	REPRODUCTIVE TOXICITY - Category 1B
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2
Skin Sens. 1	SKIN SENSITISATION - Category 1
Skin Sens. 1B	SKIN SENSITISATION - Category 1B

Date of issue/ Date of revision : 10/10/2024

Date of previous issue : 10/11/2022

Version : 2

TEKNOFLOOR 300F

All variants

[Notice to reader](#)

The information in this SDS is based on the present state of our knowledge and on current laws. The product is not to be used for purposes other than those specified under section 1 without first obtaining written handling instructions. It is always the responsibility of the user to take all necessary steps to fulfil the demands set out in the local rules and legislation. The information in this SDS is meant to be a description of the safety requirements for our product. It is not to be considered a guarantee of the product's properties.

