## SAFETY DATA SHEET



#### **TEKNOPLAST PRIMER 7**

## SECTION 1: Identification of the substance/mixture and of the company/ undertaking

#### 1.1 Product identifier

: TEKNOPLAST PRIMER 7 **Product name** 

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Product use** : Paint.

#### 1.3 Details of the supplier of the safety data sheet

Teknos Group Oy, Takkatie 3, FI-00370 HELSINKI, FINLAND. Tel. +358 9 506 091.

e-mail address of person : Prod-safe@teknos.com

responsible for this SDS

**National contact** 

Teknos Group Oy, Takkatie 3, FI-00370 HELSINKI, FINLAND. Tel. +358 9 506 091.

#### 1.4 Emergency telephone number

**National advisory body/Poison Centre** 

: In an emergency, call 112 Telephone number

#### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

**Product definition** : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Flam. Liq. 3, H226 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 **STOT RE 2, H373** 

Aquatic Chronic 3, H412

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

#### 2.2 Label elements

**Hazard pictograms** 







: Warning Signal word

**Hazard statements** : H226 - Flammable liquid and vapour.

H315 - Causes skin irritation.

H317 - May cause an allergic skin reaction.

H319 - Causes serious eye irritation.

H373 - May cause damage to organs through prolonged or repeated exposure.

H412 - Harmful to aquatic life with long lasting effects.

**Precautionary statements** 

Date of issue/Date of revision · 07/02/2025 Version : 20 1/37 : 10/02/2025 Date of previous issue Label No : 100297

### **SECTION 2: Hazards identification**

**Prevention** 

: P280 - Wear protective gloves. Wear eye or face protection.

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P273 - Avoid release to the environment.

P260 - Do not breathe vapour.

Response

: P314 - Get medical advice/attention if you feel unwell.

**Storage** 

: Not applicable.

**Disposal** 

: P501 - Dispose of contents and container in accordance with all local, regional,

national and international regulations.

**Hazardous ingredients** 

: Contains: Phenol, methylstyrenated; Xylene; Bis[4-(2,3-epoxypropoxy)phenyl] propane and reaction product: bisphenol-A-(epichlorhydrin); epoxy resin

Supplemental label elements

: Contains epoxy constituents. May produce an allergic reaction.

Warning! Hazardous respirable droplets may be formed when sprayed. Do not

breathe spray or mist.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

2.3 Other hazards

Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII  This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

Other hazards which do not result in classification

: None known.

## **SECTION 3: Composition/information on ingredients**

3.2 Mixtures : Mixture

Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Туре
Phenol, methylstyrenated	REACH #: 01-2119555274-38 EC: 700-960-7 CAS: 68512-30-1	≥10 - ≤25	Skin Irrit. 2, H315 Skin Sens. 1, H317 Aquatic Chronic 3, H412	-	[1]
Xylene	REACH #: 01-2119488216-32 EC: 215-535-7 CAS: 1330-20-7 Index: 601-022-00-9	≥10 - <20	Flam. Liq. 3, H226 Acute Tox. 4, H312 Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 STOT RE 2, H373 (oral, inhalation) Asp. Tox. 1, H304	ATE [Dermal] = 1100 mg/kg ATE [Inhalation (vapours)] = 11 mg/ I	[1] [2]
titanium dioxide	REACH #: 01-2119489379-17 EC: 236-675-5 CAS: 13463-67-7	≤10	Carc. 2, H351 (inhalation)	-	[1] [*]
Bis[4-(2,3-epoxypropoxy) phenyl]propane	REACH #: 01-2119456619-26 EC: 216-823-5 CAS: 1675-54-3 Index: 603-073-00-2	≤10	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 2, H411	Skin Irrit. 2, H315: C ≥ 5% Eye Irrit. 2, H319: C ≥ 5%	[1]
reaction product: bisphenol-	EC: 500-033-5	≤10	Skin Irrit. 2, H315	-	[1]

 Date of issue/Date of revision
 : 10/02/2025
 Date of previous issue
 : 07/02/2025
 Version
 : 20
 2/37

 TEKNOPLAST PRIMER 7
 Label No : 1/00297

## **SECTION 3: Composition/information on ingredients**

A-(epichlorhydrin); epoxy resin	CAS: 25068-38-6		Eye Irrit. 2, H319 Skin Sens. 1, H317		
Ethylbenzene	REACH #: 01-2119489370-35 EC: 202-849-4 CAS: 100-41-4 Index: 601-023-00-4	≤3	Flam. Liq. 2, H225 Acute Tox. 4, H332 STOT RE 2, H373 (hearing organs) (oral, inhalation) Asp. Tox. 1, H304	ATE [Inhalation (vapours)] = 11 mg/	[1] [2]
1-Methoxy 2-propanol	REACH #: 01-2119457435-35 EC: 203-539-1 CAS: 107-98-2 Index: 603-064-00-3	≤3	Flam. Liq. 3, H226 STOT SE 3, H336	-	[1] [2]
Octadecanoic acid, 12-hydroxy-, reaction products with ethylenediamine	REACH #: 01-2119979085-27 EC: 309-629-8 CAS: 100545-48-0	≤0.3	Skin Sens. 1B, H317 Aquatic Chronic 3, H412	-	[1]
			See Section 16 for the full text of the H statements declared above.		

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

#### Type

- [1] Substance classified with a health or environmental hazard
- [2] Substance with a workplace exposure limit
- [\*] The classification as a carcinogen by inhalation applies only to mixtures placed on the market in powder form containing 1% or more of titanium dioxide particles with aerodynamic diameter ≤ 10 µm not bound within a matrix.

Occupational exposure limits, if available, are listed in Section 8.

#### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

**Eye contact** 

: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.

Inhalation

: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention following exposure or if feeling unwell. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

**Skin contact** 

Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Ingestion

: Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention following exposure or if feeling unwell. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Date of issue/Date of revision : 10/02/2025 · 07/02/2025 Version : 20 3/37 Date of previous issue Label No : 100297

#### **SECTION 4: First aid measures**

#### Protection of first-aiders

: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

#### 4.2 Most important symptoms and effects, both acute and delayed

#### Over-exposure signs/symptoms

Eye contact : Adverse symptoms may include the following:

> pain or irritation watering redness

Inhalation : No specific data.

Skin contact : Adverse symptoms may include the following:

> irritation redness

: No specific data. Ingestion

#### 4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician : Treat symptomatically. Contact poison treatment specialist immediately if large

quantities have been ingested or inhaled.

: No specific treatment. **Specific treatments** 

## SECTION 5: Firefighting measures

#### 5.1 Extinguishing media

Suitable extinguishing

media

Use dry chemical, CO<sub>2</sub> water spray (fog) or foam.

**Unsuitable extinguishing** 

media

: Do not use water jet.

#### 5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture : Flammable liquid and vapour. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

**Hazardous combustion** products

: Decomposition products may include the following materials:

carbon dioxide carbon monoxide sulfur oxides

halogenated compounds metal oxide/oxides

#### 5.3 Advice for firefighters

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

**Special protective** equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

Date of issue/Date of revision · 07/02/2025 Version : 20 4/37 : 10/02/2025 Date of previous issue Label No : 100297

#### SECTION 6: Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

#### For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

#### For emergency responders:

If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

#### 6.2 Environmental precautions

: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

#### 6.3 Methods and material for containment and cleaning up

#### **Small spill**

: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

#### Large spill

: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

#### 6.4 Reference to other sections

: See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

## SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

#### 7.1 Precautions for safe handling

#### **Protective measures**

: Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not breathe vapour or mist. Do not ingest. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.

#### Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

#### 7.2 Conditions for safe storage, including any incompatibilities

Date of issue/Date of revision · 10/02/2025 · 07/02/2025 Version : 20 5/37 Date of previous issue Label No : 100297

## **SECTION 7: Handling and storage**

Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Eliminate all ignition sources. Separate from oxidising materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

### **Seveso Directive - Reporting thresholds**

#### **Danger criteria**

Category	Notification and MAPP threshold	Safety report threshold
P5c	5000 tonnes	50000 tonnes

#### 7.3 Specific end use(s)

Recommendations : Not available.

Industrial sector specific : Not available.

solutions

## **SECTION 8: Exposure controls/personal protection**

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

#### 8.1 Control parameters

#### **Occupational exposure limits**

Product/ingredient name	Exposure limit values
Kylene	Regulation on Limit Values - MAC (Austria, 4/2021) [Xylol (alle Isomeren, rein)] PEAK 15 minutes: 442 mg/m³ 4 times per shift. TWA 8 hours: 50 ppm. PEAK 15 minutes: 100 ppm 4 times per shift. TWA 8 hours: 221 mg/m³.
Bis[4-(2,3-epoxypropoxy)phenyl]propane	Regulation on Limit Values - MAC (Austria, 4/2021) [1,2-Epoxy-3-(tolyloxy)propan (alle Isomeren)] Carc B.  TWA 8 hours: 10 ppm.  TWA 8 hours: 70 mg/m³.  PEAK 15 minutes: 20 ppm 4 times per shift.  PEAK 15 minutes: 140 mg/m³ 4 times per shift.
Ethylbenzene	Regulation on Limit Values - MAC (Austria, 4/2021) Absorbed through skin.  TWA 8 hours: 100 ppm.  TWA 8 hours: 440 mg/m³.  CEIL 5 minutes: 200 ppm 8 times per shift.  CEIL 5 minutes: 880 mg/m³ 8 times per shift.
1-Methoxy 2-propanol	Regulation on Limit Values - MAC (Austria, 4/2021) Absorbed through skin.  TWA 8 hours: 50 ppm.  TWA 8 hours: 187 mg/m³.  CEIL: 50 ppm.  CEIL: 187 mg/m³.
Xylene	Limit values (Belgium, 12/2023) [Xyleen] Absorbed through skin. TWA 8 hours: 50 ppm. TWA 8 hours: 221 mg/m³. STEL 15 minutes: 100 ppm. STEL 15 minutes: 442 mg/m³.
Ethylbenzene	Limit values (Belgium, 12/2023) Absorbed through skin. TWA 8 hours: 20 ppm. TWA 8 hours: 87 mg/m³. STEL 15 minutes: 125 ppm. STEL 15 minutes: 551 mg/m³.

Date of issue/Date of revision: 10/02/2025Date of previous issue: 07/02/2025Version: 206/37TEKNOPLAST PRIMER 7Label No: 1/00297

1-Methoxy 2-propanol Limit values (Belgium, 12/2023) Absorbed through skin.

TWA 8 hours: 50 ppm. TWA 8 hours: 184 mg/m³. STEL 15 minutes: 100 ppm. STEL 15 minutes: 369 mg/m³.

Xylene Ministry of Labour and Social Policy and the Ministry of

Health - Ordinance No 13/2003. (Bulgaria, 4/2024) [Xylene]

Absorbed through skin.

Limit value 8 hours: 221 mg/m³. Limit value 15 minutes: 442 mg/m³. Limit value 15 minutes: 100 ppm. Limit value 8 hours: 50 ppm.

Ethylbenzene Ministry of Labour and Social Policy and the Ministry of

Health - Ordinance No 13/2003. (Bulgaria, 4/2024) Absorbed

through skin.

Limit value 8 hours: 435 mg/m³. Limit value 15 minutes: 545 mg/m³.

1-Methoxy 2-propanol Ministry of Labour and Social Policy and the Ministry of

Health - Ordinance No 13/2003. (Bulgaria, 4/2024) Absorbed

through skin.

Limit value 8 hours: 375 mg/m³. Limit value 15 minutes: 568 mg/m³. Limit value 15 minutes: 150 ppm. Limit value 8 hours: 100 ppm.

Xylene Ordinance on the protection of workers from exposure to

hazardous chemicals at work, exposure limit values (Annex I)

(Croatia, 12/2023) [ksilen] Absorbed through skin.

STELV 15 minutes: 442 mg/m³. STELV 15 minutes: 100 ppm. ELV 8 hours: 221 mg/m³. ELV 8 hours: 50 ppm.

Ethylbenzene Ordinance on the protection of workers from exposure to

hazardous chemicals at work, exposure limit values (Annex I)

(Croatia, 12/2023) Absorbed through skin.

STELV 15 minutes: 884 mg/m³. STELV 15 minutes: 200 ppm. ELV 8 hours: 442 mg/m³. ELV 8 hours: 100 ppm.

1-Methoxy 2-propanol Ordinance on the protection of workers from exposure to

hazardous chemicals at work, exposure limit values (Annex I)

(Croatia, 12/2023)

STELV 15 minutes: 568 mg/m³. STELV 15 minutes: 150 ppm. ELV 8 hours: 375 mg/m³. ELV 8 hours: 100 ppm.

Xylene Department of labour inspection (Cyprus, 7/2021) [Ξυλένιο,

μικτά ισομερή, καθαρά] Absorbed through skin.

STEL 15 minutes: 100 ppm. STEL 15 minutes: 442 mg/m³. TWA 8 hours: 50 ppm. TWA 8 hours: 221 mg/m³.

Ethylbenzene Department of labour inspection (Cyprus, 7/2021) Absorbed

through skin.

STEL 15 minutes: 884 mg/m³. TWA 8 hours: 100 ppm. TWA 8 hours: 442 mg/m³. STEL 15 minutes: 200 ppm.

1-Methoxy 2-propanol Department of labour inspection (Cyprus, 7/2021) Absorbed

through skin.

STEL 15 minutes: 150 ppm. STEL 15 minutes: 568 mg/m³. TWA 8 hours: 100 ppm.

Date of issue/Date of revision : 10/02/2025 Date of previous issue : 07/02/2025 Version : 20 7/37

TEKNOPLAST PRIMER 7

TWA 8 hours: 375 mg/m<sup>3</sup>. **Xylene** 

Government regulation of Czech Republic PEL/NPK-P (Czech

Republic, 12/2023) [xylen] Absorbed through skin.

TWA 8 hours: 200 mg/m<sup>3</sup>. TWA 8 hours: 45.33 ppm. STEL 15 minutes: 400 mg/m<sup>3</sup>. STEL 15 minutes: 90.66 ppm.

Ethylbenzene Government regulation of Czech Republic PEL/NPK-P (Czech

Republic, 12/2023) Absorbed through skin.

TWA 8 hours: 200 mg/m<sup>3</sup>. TWA 8 hours: 45.33 ppm. STEL 15 minutes: 500 mg/m<sup>3</sup>. STEL 15 minutes: 113.32 ppm.

Government regulation of Czech Republic PEL/NPK-P (Czech 1-Methoxy 2-propanol

Republic, 12/2023) Absorbed through skin.

TWA 8 hours: 270 mg/m<sup>3</sup>. TWA 8 hours: 72.09 ppm. STEL 15 minutes: 550 mg/m<sup>3</sup>. STEL 15 minutes: 146.84 ppm.

**Xylene** Working Environment Authority (Denmark, 3/2024) [xylen, alle

isomere] Absorbed through skin.

TWA 8 hours: 25 ppm. TWA 8 hours: 109 mg/m<sup>3</sup>. STEL 15 minutes: 442 mg/m<sup>3</sup>. STEL 15 minutes: 100 ppm.

Ethylbenzene Working Environment Authority (Denmark, 3/2024) K. Absorbed

through skin.

TWA 8 hours: 50 ppm. TWA 8 hours: 217 mg/m<sup>3</sup>. STEL 15 minutes: 434 mg/m<sup>3</sup>. STEL 15 minutes: 100 ppm.

1-Methoxy 2-propanol Working Environment Authority (Denmark, 3/2024) [1-methoxy-

**2-propanol**] Absorbed through skin.

TWA 8 hours: 50 ppm. TWA 8 hours: 185 mg/m<sup>3</sup>. STEL 15 minutes: 568 mg/m<sup>3</sup>. STEL 15 minutes: 150 ppm.

**Xylene** Occupational exposure limits, Regulation No. 293 (Estonia,

4/2024) [ksüleen] Absorbed through skin.

TWA 8 hours: 50 ppm. STEL 15 minutes: 100 ppm. STEL 15 minutes: 450 mg/m<sup>3</sup>. TWA 8 hours: 200 mg/m<sup>3</sup>.

Occupational exposure limits, Regulation No. 293 (Estonia, Ethylbenzene

4/2024) Absorbed through skin, Sensitiser.

TWA 8 hours: 442 mg/m<sup>3</sup>. TWA 8 hours: 100 ppm. STEL 15 minutes: 884 mg/m<sup>3</sup>. STEL 15 minutes: 200 ppm.

Occupational exposure limits, Regulation No. 293 (Estonia, 1-Methoxy 2-propanol

4/2024) Absorbed through skin, Sensitiser.

TWA 8 hours: 375 mg/m<sup>3</sup>. TWA 8 hours: 100 ppm. STEL 15 minutes: 568 mg/m<sup>3</sup>. STEL 15 minutes: 150 ppm.

**Xylene** EU OEL (Europe, 1/2022) [xylene, mixed isomers] Absorbed

through skin.

TWA 8 hours: 50 ppm. TWA 8 hours: 221 mg/m<sup>3</sup>. STEL 15 minutes: 100 ppm. STEL 15 minutes: 442 mg/m<sup>3</sup>.

Ethylbenzene EU OEL (Europe, 1/2022) Absorbed through skin.

Date of issue/Date of revision : 07/02/2025 Version : 20 8/37 : 10/02/2025 Date of previous issue **TEKNOPLAST PRIMER 7** Label No : 100297

TWA 8 hours: 100 ppm. TWA 8 hours: 442 ma/m<sup>3</sup>. STEL 15 minutes: 200 ppm. STEL 15 minutes: 884 mg/m<sup>3</sup>.

1-Methoxy 2-propanol EU OEL (Europe, 1/2022) Absorbed through skin.

> TWA 8 hours: 100 ppm. TWA 8 hours: 375 mg/m<sup>3</sup>. STEL 15 minutes: 150 ppm. STEL 15 minutes: 568 mg/m<sup>3</sup>.

**Xylene** Institute of Occupational Health, Ministry of Social Affairs (Finland, 10/2021) [Ksyleeni] Absorbed through skin.

> STEL 15 minutes: 440 mg/m<sup>3</sup>. TWA 8 hours: 220 mg/m<sup>3</sup>. TWA 8 hours: 50 ppm. STEL 15 minutes: 100 ppm.

Ethylbenzene Institute of Occupational Health, Ministry of Social Affairs

(Finland, 10/2021) Absorbed through skin.

TWA 8 hours: 50 ppm. TWA 8 hours: 220 mg/m<sup>3</sup>. STEL 15 minutes: 200 ppm. STEL 15 minutes: 880 mg/m<sup>3</sup>.

Institute of Occupational Health, Ministry of Social Affairs 1-Methoxy 2-propanol

(Finland, 10/2021) Absorbed through skin.

TWA 8 hours: 100 ppm. TWA 8 hours: 370 mg/m<sup>3</sup>. STEL 15 minutes: 150 ppm. STEL 15 minutes: 560 mg/m<sup>3</sup>.

**Xylene** Ministry of Labor (France, 6/2024) [xylènes, isomères mixtes, purs] Absorbed through skin.

> STEL 15 minutes: 442 mg/m³. Notes: Binding regulatory limit values (article R. 4412-149 of the Labor Code)

STEL 15 minutes: 100 ppm. Notes: Binding regulatory limit values (article R. 4412-149 of the Labor Code)

TWA 8 hours: 221 mg/m³. Notes: Binding regulatory limit values

(article R. 4412-149 of the Labor Code) TWA 8 hours: 50 ppm. Notes: Binding regulatory limit values

(article R. 4412-149 of the Labor Code)

Ethylbenzene Ministry of Labor (France, 6/2024) Absorbed through skin.

TWA 8 hours: 20 ppm. Notes: Binding regulatory limit values (article R. 4412-149 of the Labor Code)

TWA 8 hours: 88.4 mg/m<sup>3</sup>. Notes: Binding regulatory limit values

(article R. 4412-149 of the Labor Code) STEL 15 minutes: 442 mg/m³. Notes: Binding regulatory limit

values (article R. 4412-149 of the Labor Code)

STEL 15 minutes: 100 ppm. Notes: Binding regulatory limit values (article R. 4412-149 of the Labor Code)

1-Methoxy 2-propanol Ministry of Labor (France, 6/2024) Absorbed through skin.

> TWA 8 hours: 50 ppm. Notes: Binding regulatory limit values (article R. 4412-149 of the Labor Code)

TWA 8 hours: 188 mg/m<sup>3</sup>. Notes: Binding regulatory limit values (article R. 4412-149 of the Labor Code)

STEL 15 minutes: 375 mg/m³. Notes: Binding regulatory limit values (article R. 4412-149 of the Labor Code)

STEL 15 minutes: 100 ppm. Notes: Binding regulatory limit values (article R. 4412-149 of the Labor Code)

TRGS 900 OEL (Germany, 6/2024) [Xylol] Absorbed through skin.

TWA 8 hours: 220 mg/m<sup>3</sup>. PEAK 15 minutes: 440 mg/m<sup>3</sup>. TWA 8 hours: 50 ppm. PEAK 15 minutes: 100 ppm.

DFG MAC-values list (Germany, 7/2023) [Xylene] Develop D.

Absorbed through skin.

Date of issue/Date of revision : 07/02/2025 Version : 20 9/37 : 10/02/2025 Date of previous issue Label No : 100297

**X**ylene

TWA 8 hours: 50 ppm. PEAK 15 minutes: 100 ppm 4 times per shift [Interval: 1 hour]. TWA 8 hours: 220 mg/m<sup>3</sup>. PEAK 15 minutes: 440 mg/m<sup>3</sup> 4 times per shift [Interval: 1 hour]. Bis[4-(2,3-epoxypropoxy)phenyl]propane DFG MAC-values list (Germany, 7/2023) Skin sensitiser. Ethylbenzene TRGS 900 OEL (Germany, 6/2024) Absorbed through skin. TWA 8 hours: 88 mg/m<sup>3</sup>. PEAK 15 minutes: 176 mg/m<sup>3</sup>. TWA 8 hours: 20 ppm. PEAK 15 minutes: 40 ppm. DFG MAC-values list (Germany, 7/2023) Carc 4, Develop C. Absorbed through skin. PEAK 15 minutes: 40 ppm 4 times per shift [Interval: 1 hour]. PEAK 15 minutes: 176 mg/m<sup>3</sup> 4 times per shift [Interval: 1 hour]. TWA 8 hours: 88 mg/m<sup>3</sup>. TWA 8 hours: 20 ppm. 1-Methoxy 2-propanol TRGS 900 OEL (Germany, 6/2024) TWA 8 hours: 370 mg/m<sup>3</sup>. PEAK 15 minutes: 740 mg/m<sup>3</sup>. TWA 8 hours: 100 ppm. PEAK 15 minutes: 200 ppm. DFG MAC-values list (Germany, 7/2023) Develop C. TWA 8 hours: 100 ppm. PEAK 15 minutes: 200 ppm 4 times per shift [Interval: 1 hour]. TWA 8 hours: 370 mg/m<sup>3</sup>. PEAK 15 minutes: 740 mg/m<sup>3</sup> 4 times per shift [Interval: 1 hour]. **Xylene** Presidential Decree 307/1986: Occupational exposure limit values (Greece, 9/2021) [ξυλόλια (όλα τα ισομερή)] Absorbed through skin. TWA 8 hours: 100 ppm. TWA 8 hours: 435 mg/m<sup>3</sup>. STEL 15 minutes: 150 ppm. STEL 15 minutes: 650 mg/m<sup>3</sup>. Presidential Decree 307/1986: Occupational exposure limit Ethylbenzene values (Greece, 9/2021) TWA 8 hours: 100 ppm. TWA 8 hours: 435 mg/m<sup>3</sup>. STEL 15 minutes: 125 ppm. STEL 15 minutes: 545 mg/m<sup>3</sup>. 1-Methoxy 2-propanol Presidential Decree 307/1986: Occupational exposure limit values (Greece, 9/2021) Absorbed through skin. TWA 8 hours: 100 ppm. TWA 8 hours: 360 mg/m<sup>3</sup>. STEL 15 minutes: 300 ppm. STEL 15 minutes: 1080 mg/m<sup>3</sup>. 5/2020. (II. 6.) ITM Decree (Hungary, 12/2023) [xilol izomerek **Xylene** keveréke] Absorbed through skin. TWA 8 hours: 221 mg/m<sup>3</sup>. PEAK 15 minutes: 442 mg/m<sup>3</sup>. PEAK 15 minutes: 100 ppm. TWA 8 hours: 50 ppm. Ethylbenzene 5/2020. (II. 6.) ITM Decree (Hungary, 12/2023) Absorbed through TWA 8 hours: 442 mg/m<sup>3</sup>. PEAK 15 minutes: 884 mg/m<sup>3</sup>. PEAK 15 minutes: 200 ppm. TWA 8 hours: 100 ppm. 5/2020. (II. 6.) ITM Decree (Hungary, 12/2023) Absorbed through 1-Methoxy 2-propanol

Date of issue/Date of revision · 07/02/2025 Version : 20 10/37 : 10/02/2025 Date of previous issue Label No : 100297

TWA 8 hours: 375 mg/m<sup>3</sup>. PEAK 15 minutes: 568 mg/m<sup>3</sup>. PEAK 15 minutes: 150 ppm. TWA 8 hours: 100 ppm.

skin.

Xylene Ministry of Welfare, List of Exposure Limits (Iceland, 11/2023)

[Xýlen, allir ísómerar] Absorbed through skin.

STEL 15 minutes: 442 mg/m³. STEL 15 minutes: 100 ppm. TWA 8 hours: 109 mg/m³. TWA 8 hours: 25 ppm.

Ethylbenzene Ministry of Welfare, List of Exposure Limits (Iceland, 11/2023)

Absorbed through skin.

STEL 15 minutes: 884 mg/m³. STEL 15 minutes: 200 ppm. TWA 8 hours: 200 mg/m³. TWA 8 hours: 50 ppm.

1-Methoxy 2-propanol Ministry of Welfare, List of Exposure Limits (Iceland, 11/2023)

Absorbed through skin.

STEL 15 minutes: 568 mg/m³. STEL 15 minutes: 150 ppm. TWA 8 hours: 185 mg/m³. TWA 8 hours: 50 ppm.

Xylene NAOSH (Ireland, 4/2024) [xylene] Absorbed through skin. Notes:

EU derived Occupational Exposure Limit Values

OELV 8 hours: 50 ppm.
OELV 8 hours: 221 mg/m³.
OELV 15 minutes: 100 ppm.
OELV 15 minutes: 442 mg/m³.

Ethylbenzene NAOSH (Ireland, 4/2024) Absorbed through skin. Notes: EU

derived Occupational Exposure Limit Values

OELV 8 hours: 100 ppm. OELV 8 hours: 442 mg/m³. OELV 15 minutes: 200 ppm. OELV 15 minutes: 884 mg/m³.

1-Methoxy 2-propanol NAOSH (Ireland, 4/2024) Notes: EU derived Occupational

Exposure Limit Values
OELV 8 hours: 100 ppm.
OELV 8 hours: 375 mg/m³.
OELV 15 minutes: 150 ppm.
OELV 15 minutes: 568 mg/m³.

Xylene Legislative Decree No. 81/2008. Title IX. Protection from chemical agents, carcinogens and mutagens (Italy, 6/2020)

[Xilene, isomeri misti, puro] Absorbed through skin.

Limit value 8 hours: 50 ppm. Limit value 8 hours: 221 mg/m³. Short Term 15 minutes: 100 ppm. Short Term 15 minutes: 442 mg/m³.

Ethylbenzene Legislative Decree No. 81/2008. Title IX. Protection from chemical agents, carcinogens and mutagens (Italy, 6/2020)

Absorbed through skin.

Limit value 8 hours: 100 ppm. Limit value 8 hours: 442 mg/m³. Short Term 15 minutes: 200 ppm. Short Term 15 minutes: 884 mg/m³.

1-Methoxy 2-propanol Legislative Decree No. 81/2008. Title IX. Protection from chemical agents, carcinogens and mutagens (Italy, 6/2020)

Absorbed through skin.

Limit value 8 hours: 100 ppm. Limit value 8 hours: 375 mg/m³. Short Term 15 minutes: 150 ppm. Short Term 15 minutes: 568 mg/m³.

Label No : 100297

Date of issue/Date of revision : 10/02/2025 Date of previous issue : 07/02/2025 Version : 20 11/37

Xylene Ministers Cabinet Regulations Nr.325 - AER (Latvia, 3/2024)

[Ksilols] Absorbed through skin. TWA 8 hours: 221 mg/m³. TWA 8 hours: 50 ppm. STEL 15 minutes: 100 ppm. STEL 15 minutes: 442 mg/m³.

Ethylbenzene Ministers Cabinet Regulations Nr.325 - AER (Latvia, 3/2024)

Absorbed through skin.
TWA 8 hours: 442 mg/m³.
TWA 8 hours: 100 ppm.
STEL 15 minutes: 200 ppm.
STEL 15 minutes: 884 mg/m³.

1-Methoxy 2-propanol Ministers Cabinet Regulations Nr.325 - AER (Latvia, 3/2024)

Absorbed through skin.
TWA 8 hours: 100 ppm.
STEL 15 minutes: 568 mg/m³.
TWA 8 hours: 375 mg/m³.
STEL 15 minutes: 150 ppm.

Xylene Lithuanian Hygiene Standard HN 23 (Lithuania, 1/2024)

[ksilenas, mišrūs izomerai, grynas] Absorbed through skin.

STEL 15 minutes: 442 mg/m³. TWA 8 hours: 50 ppm. STEL 15 minutes: 100 ppm. TWA 8 hours: 221 mg/m³.

Ethylbenzene Lithuanian Hygiene Standard HN 23 (Lithuania, 1/2024)

Absorbed through skin.
TWA 8 hours: 442 mg/m³.
TWA 8 hours: 100 ppm.
STEL 15 minutes: 884 mg/m³.
STEL 15 minutes: 200 ppm.

1-Methoxy 2-propanol Lithuanian Hygiene Standard HN 23 (Lithuania, 1/2024)

Absorbed through skin.
TWA 8 hours: 190 mg/m³.
TWA 8 hours: 50 ppm.
STEL 15 minutes: 300 mg/m³.
STEL 15 minutes: 75 ppm.

Xylene Grand-Duchy Regulation 2016. Chemical agents. Annex I

(Luxembourg, 3/2021) [xylène Isomères mixtes, pures]

Absorbed through skin.
TWA 8 hours: 50 ppm.
TWA 8 hours: 221 mg/m³.
STEL 15 minutes: 100 ppm.
STEL 15 minutes: 442 mg/m³.

Ethylbenzene Grand-Duchy Regulation 2016. Chemical agents. Annex I

(Luxembourg, 3/2021) Absorbed through skin.

TWA 8 hours: 100 ppm. TWA 8 hours: 442 mg/m³. STEL 15 minutes: 200 ppm. STEL 15 minutes: 884 mg/m³.

1-Methoxy 2-propanol Grand-Duchy Regulation 2016. Chemical agents. Annex I

(Luxembourg, 3/2021) Absorbed through skin.

TWA 8 hours: 100 ppm. TWA 8 hours: 375 mg/m³. STEL 15 minutes: 150 ppm. STEL 15 minutes: 568 mg/m³.

Xylene | EU OEL (Europe, 1/2022) [xylene, mixed isomers] Absorbed

through skin.

TWA 8 hours: 50 ppm. TWA 8 hours: 221 mg/m³. STEL 15 minutes: 100 ppm. STEL 15 minutes: 442 mg/m³.

Ethylbenzene EU OEL (Europe, 1/2022) Absorbed through skin.

 Date of issue/Date of revision
 : 10/02/2025
 Date of previous issue
 : 07/02/2025
 Version
 : 20
 12/37

 TEKNOPLAST PRIMER 7
 Label No : 10/02/2027
 Label No : 10/02/2027

TWA 8 hours: 100 ppm. TWA 8 hours: 442 ma/m<sup>3</sup>. STEL 15 minutes: 200 ppm. STEL 15 minutes: 884 mg/m<sup>3</sup>.

1-Methoxy 2-propanol

EU OEL (Europe, 1/2022) Absorbed through skin.

TWA 8 hours: 100 ppm. TWA 8 hours: 375 mg/m<sup>3</sup>. STEL 15 minutes: 150 ppm. STEL 15 minutes: 568 mg/m<sup>3</sup>.

**Xylene** 

Ministry of Social Affairs and Employment, Legal limit values (Netherlands, 5/2024) [xyleen, o-, m-, p-isomeren] Absorbed

through skin.

TWA 8 hours: 210 mg/m<sup>3</sup>. STEL 15 minutes: 442 mg/m<sup>3</sup>. STEL 15 minutes: 100 ppm. TWA 8 hours: 47.5 ppm.

Ethylbenzene

Ministry of Social Affairs and Employment, Legal limit values (Netherlands, 5/2024) Absorbed through skin.

TWA 8 hours: 215 mg/m<sup>3</sup>. STEL 15 minutes: 430 mg/m<sup>3</sup>. STEL 15 minutes: 97.3 ppm. TWA 8 hours: 48.6 ppm.

1-Methoxy 2-propanol

Ministry of Social Affairs and Employment, Legal limit values (Netherlands, 5/2024) Absorbed through skin.

TWA 8 hours: 375 mg/m<sup>3</sup>. STEL 15 minutes: 563 mg/m<sup>3</sup>. TWA 8 hours: 100 ppm. STEL 15 minutes: 150 ppm.

**Xylene** 

FOR-2011-12-06-1358 (Norway, 12/2022) [xylen] Absorbed

through skin.

TWA 8 hours: 25 ppm. TWA 8 hours: 108 mg/m<sup>3</sup>.

Ethylbenzene

FOR-2011-12-06-1358 (Norway, 12/2022) Carc. Absorbed through

TWA 8 hours: 5 ppm. TWA 8 hours: 20 mg/m<sup>3</sup>.

1-Methoxy 2-propanol

FOR-2011-12-06-1358 (Norway, 12/2022) Absorbed through skin.

TWA 8 hours: 50 ppm. TWA 8 hours: 180 mg/m<sup>3</sup>.

**Xylene** 

Regulation of the Minister of Family, Labor and Social Policy of June 12, 2018 on the maximum permissible concentrations and intensities of factors harmful to health in the work environment (Journal of Laws of 2018, item 1286) (Poland, 8/2023) [xylene - mixed isomers (1,2-, 1,3-, 1,4-)] Absorbed

through skin.

TWA 8 hours: 100 mg/m<sup>3</sup>. STEL 15 minutes: 200 mg/m<sup>3</sup>.

Ethylbenzene

Regulation of the Minister of Family, Labor and Social Policy of June 12, 2018 on the maximum permissible concentrations and intensities of factors harmful to health in the work environment (Journal of Laws of 2018, item 1286) (Poland, 8/2023) Absorbed through skin.

TWA 8 hours: 200 mg/m<sup>3</sup>. STEL 15 minutes: 400 mg/m<sup>3</sup>.

1-Methoxy 2-propanol

Regulation of the Minister of Family, Labor and Social Policy of June 12, 2018 on the maximum permissible concentrations and intensities of factors harmful to health in the work environment (Journal of Laws of 2018, item 1286) (Poland, 8/2023) Absorbed through skin.

TWA 8 hours: 180 mg/m<sup>3</sup>. STEL 15 minutes: 360 mg/m<sup>3</sup>.

Date of issue/Date of revision · 07/02/2025 Version : 20 13/37 : 10/02/2025 Date of previous issue Label No : 100297

Xylene Portuguese Institute of Quality (Portugal, 11/2014) [xileno

(isómeros o, m & p)] A4. TWA 8 hours: 100 ppm. STEL 15 minutes: 150 ppm.

Ethylbenzene Portuguese Institute of Quality (Portugal, 11/2014) A3.

TWA 8 hours: 20 ppm.

1-Methoxy 2-propanol Portuguese Institute of Quality (Portugal, 11/2014) A4.

TWA 8 hours: 50 ppm. STEL 15 minutes: 100 ppm.

Xylene HG 1218/2006, Annex 1, with subsequent modifications and additions (Romania, 3/2024) [xilen] Absorbed through skin.

VLA 8 hours: 221 mg/m³.
VLA 8 hours: 50 ppm.

Short term 15 minutes: 442 mg/m³. Short term 15 minutes: 100 ppm.

Ethylbenzene HG 1218/2006, Annex 1, with subsequent modifications and

additions (Romania, 3/2024) Absorbed through skin.

VLA 8 hours: 442 mg/m<sup>3</sup>. VLA 8 hours: 100 ppm.

Short term 15 minutes: 884 mg/m<sup>3</sup>. Short term 15 minutes: 200 ppm.

1-Methoxy 2-propanol HG 1218/2006, Annex 1, with subsequent modifications and

additions (Romania, 3/2024) Absorbed through skin.

VLA 8 hours: 375 mg/m<sup>3</sup>. VLA 8 hours: 100 ppm.

Short term 15 minutes: 568 mg/m³. Short term 15 minutes: 150 ppm.

Xylene Government regulation SR c. 355/2006 (Slovakia, 7/2024)

[xylén, zmiešané izoméry] Absorbed through skin, Inhalation

sensitiser.

TWA 8 hours: 221 mg/m³ (xylene, mixed isomers). TWA 8 hours: 50 ppm (xylene, mixed isomers). STEL 15 minutes: 442 mg/m³ (xylene, mixed isomers). STEL 15 minutes: 100 ppm (xylene, mixed isomers).

Ethylbenzene | Government regulation SR c. 355/2006 (Slovakia, 7/2024)

Absorbed through skin, Inhalation sensitiser.

TWA 8 hours: 442 mg/m³. TWA 8 hours: 100 ppm. STEL 15 minutes: 884 mg/m³. STEL 15 minutes: 200 ppm.

1-Methoxy 2-propanol Government regulation SR c. 355/2006 (Slovakia, 7/2024)

Absorbed through skin, Inhalation sensitiser.

TWA 8 hours: 375 mg/m³. TWA 8 hours: 100 ppm. STEL 15 minutes: 568 mg/m³. STEL 15 minutes: 150 ppm.

Xylene Regulation on protection of workers from the risks related to

exposure to chemical substances at work (Slovenia, 4/2024)

**[ksilen]** Absorbed through skin. TWA 8 hours: 221 mg/m³.

TWA 8 hours: 50 ppm.

KTV 15 minutes: 442 mg/m³ 4 times per shift [time between two exposure events at this concentration must be at least 60 minutes]. KTV 15 minutes: 100 ppm 4 times per shift [time between two exposure events at this concentration must be at least 60 minutes].

Ethylbenzene Regulation on protection of workers from the risks related to exposure to chemical substances at work (Slovenia, 4/2024)

Absorbed through skin.
TWA 8 hours: 442 mg/m³.
TWA 8 hours: 100 ppm.

KTV 15 minutes: 884 mg/m³ 4 times per shift [time between two exposure events at this concentration must be at least 60 minutes].

Date of issue/Date of revision : 10/02/2025 Date of previous issue : 07/02/2025 Version : 20

TEKNOPLAST PRIMER 7

Label No : 100297

14/37

1-Methoxy 2-propanol

KTV 15 minutes: 200 ppm 4 times per shift [time between two exposure events at this concentration must be at least 60 minutes].

Regulation on protection of workers from the risks related to exposure to chemical substances at work (Slovenia, 4/2024)

Absorbed through skin. TWA 8 hours: 375 mg/m<sup>3</sup>. TWA 8 hours: 100 ppm.

KTV 15 minutes: 568 mg/m<sup>3</sup> 4 times per shift [time between two exposure events at this concentration must be at least 60 minutes]. KTV 15 minutes: 150 ppm 4 times per shift [time between two exposure events at this concentration must be at least 60 minutes].

**Xylene** 

National institute of occupational safety and health (Spain, 1/2024) [xileno, mezcla isómeros] Absorbed through skin.

TWA 8 hours: 50 ppm. TWA 8 hours: 221 mg/m<sup>3</sup>. STEL 15 minutes: 100 ppm. STEL 15 minutes: 442 mg/m<sup>3</sup>.

Ethylbenzene

National institute of occupational safety and health (Spain,

1/2024) Absorbed through skin. TWA 8 hours: 100 ppm. TWA 8 hours: 441 mg/m<sup>3</sup>. STEL 15 minutes: 200 ppm. STEL 15 minutes: 884 mg/m<sup>3</sup>.

1-Methoxy 2-propanol

National institute of occupational safety and health (Spain,

1/2024) Absorbed through skin. TWA 8 hours: 100 ppm.

TWA 8 hours: 375 mg/m<sup>3</sup>. STEL 15 minutes: 150 ppm. STEL 15 minutes: 568 mg/m<sup>3</sup>.

**Xylene** 

Work environment authority Regulation 2018:1 (Sweden,

11/2022) [xylene] Absorbed through skin.

TWA 8 hours: 50 ppm. TWA 8 hours: 221 mg/m<sup>3</sup>. STEL 15 minutes: 100 ppm. STEL 15 minutes: 442 mg/m<sup>3</sup>.

Ethylbenzene

Work environment authority Regulation 2018:1 (Sweden,

11/2022) Absorbed through skin.

TWA 8 hours: 50 ppm. TWA 8 hours: 220 mg/m<sup>3</sup>. STEL 15 minutes: 200 ppm. STEL 15 minutes: 884 mg/m<sup>3</sup>.

1-Methoxy 2-propanol

Work environment authority Regulation 2018:1 (Sweden,

11/2022) Absorbed through skin. STEL 15 minutes: 150 ppm. STEL 15 minutes: 568 mg/m<sup>3</sup>. TWA 8 hours: 190 mg/m<sup>3</sup>. TWA 8 hours: 50 ppm.

**Xylene** 

SUVA (Switzerland, 1/2024) [Xylol] Absorbed through skin.

· 07/02/2025

TWA 8 hours: 50 ppm. TWA 8 hours: 220 mg/m<sup>3</sup>. STEL 15 minutes: 100 ppm. STEL 15 minutes: 440 mg/m<sup>3</sup>.

Ethylbenzene

SUVA (Switzerland, 1/2024) Absorbed through skin, Ototoxicant.

TWA 8 hours: 50 ppm. TWA 8 hours: 220 mg/m<sup>3</sup>. STEL 15 minutes: 50 ppm. STEL 15 minutes: 220 mg/m<sup>3</sup>. SUVA (Switzerland, 1/2024)

1-Methoxy 2-propanol

TWA 8 hours: 100 ppm. TWA 8 hours: 360 mg/m<sup>3</sup>.

STEL 15 minutes: 200 ppm. STEL 15 minutes: 720 mg/m<sup>3</sup>.

Date of issue/Date of revision TEKNOPLAST PRIMER 7 : 10/02/2025 Date of previous issue Version : 20

Label No : 100297

15/37

Xylene	EH40/2005 WELs (United Kingdom (UK), 1/2020) [xylene, o-,m-,
	p- or mixed isomers] Absorbed through skin.
	STEL 15 minutes: 441 mg/m³.
	TWA 8 hours: 50 ppm.
	TWA 8 hours: 220 mg/m³.
	STEL 15 minutes: 100 ppm.
Ethylbenzene	EH40/2005 WELs (United Kingdom (UK), 1/2020) Absorbed
	through skin.
	STEL 15 minutes: 552 mg/m³.
	STEL 15 minutes: 125 ppm.
	TWA 8 hours: 100 ppm.
	TWA 8 hours: 441 mg/m³.
1-Methoxy 2-propanol	EH40/2005 WELs (United Kingdom (UK), 1/2020) Absorbed
	through skin.
	STEL 15 minutes: 560 mg/m³.
	STEL 15 minutes: 150 ppm.
	TWA 8 hours: 375 mg/m³.
	TWA 8 hours: 100 ppm.

## **Biological exposure indices**

Product/ingredient name	Exposure indices
Xylene	VGU BEI (Austria, 9/2020) [xylenes]  BEI Fitness: 1000 μg/l, xylene [in blood]. Sampling time: one year.  BEI Fitness: 1.5 g/l, methylhippuricacid [in urine]. Sampling time: one year.
No exposure indices known.	
Ethylbenzene	Ministry of Labour and Social Policy and the Ministry of Health - Ordinance No 13/2003. (Bulgaria, 4/2024) Notes: significant skin resorption possible BLV: 2000 mg/g creatinine, mandelic acid and phenylglyoxylic acid – in total [in urine]. Sampling time: at the end of the exposure or at the end of the work shift.
Xylene	Ordinance on the protection of workers from exposure to hazardous chemicals at work, biological limit values (Annex IV) (Croatia, 12/2023) [xylene]  BEI: 1.5 mg/l, xylene [in blood]. Sampling time: at the end of the work shift.  BEI: 14.13 µmol/l, xylene [in blood]. Sampling time: at the end of the work shift.  BEI: 0.88 mol/mol creatinine, methylhippuric acid [in urine]. Sampling time: at the end of the work shift.  BEI: 1.5 g/g creatinine, methylhippuric acid [in urine]. Sampling time: at the end of the work shift.
Ethylbenzene	Ordinance on the protection of workers from exposure to hazardous chemicals at work, biological limit values (Annex IV) (Croatia, 12/2023)  BEI: 1.5 mg/l, ethylbenzene [in blood]. Sampling time: during exposure.  BEI: 14.1 µmol/l, ethylbenzene [in blood]. Sampling time: during exposure.  BEI: 1.12 mol/mol creatinine, almond acid [in urine]. Sampling time: at the end of the work shift and at the end of the working week.  BEI: 1.5 g/g creatinine, almond acid [in urine]. Sampling time: at the end of the work shift and at the end of the working week.
No exposure indices known.	

 Date of issue/Date of revision
 : 10/02/2025
 Date of previous issue
 : 07/02/2025
 Version
 : 20
 16/37

 TEKNOPLAST PRIMER 7
 Label No : ₹00297

**Xvlene** 

Government regulation of Czech Republic Limit Values of Biological Exposure Tests (Czech Republic, 9/2015) [Xylene]

Biological limit values: 820 µmol/mmol creatinine, methylhippuric acid [in urine]. Sampling time: end of the shift.

Biological limit values: 1400 mg/g creatinine, methylhippuric acid [in urine]. Sampling time: end of the shift.

Ethylbenzene

Government regulation of Czech Republic Limit Values of Biological Exposure Tests (Czech Republic, 9/2015)

Biological limit values: 1100 µmol/mmol creatinine, almond acid [in urine]. Sampling time: end of the shift.

Biological limit values: 1500 mg/g creatinine, almond acid [in urine]. Sampling time: end of the shift.

No exposure indices known.

No exposure indices known.

No exposure indices known.

**Xylene** 

Ethylbenzene

No exposure indices known.

**Xylene** 

Ethylbenzene

1-Methoxy 2-propanol

No exposure indices known.

**Xylene** 

Ethylbenzene

Institute of Occupational Health, Ministry of Social Affairs (Finland, 9/2020) [Xylene]

BEI: 5 mmol/l, methylhippuricacid [in urine]. Sampling time: at the end of the work shift.

Institute of Occupational Health, Ministry of Social Affairs (Finland, 9/2020)

BEI: 5.2 mmol/l, mandelic acid [in urine]. Sampling time: after work shift at the end of the working week or exposure period.

DFG BEI-values list (Germany, 7/2023) [Xylene (all isomers)]

Notes: danger from percutaneous absorption (see p. 211 and p.

BEI: 2000 mg/l, methylhippuric acid (toluric acid) (all isomers) [in urine]. Sampling time: end of exposure or end of shift.

TRGS 903 - BEI Values (Germany, 2/2024) [Xylene (all isomers)] BEI: 2000 mg/l, methylhippuric acid [in urine]. Sampling time: end of exposure or end of shift.

DFG BEI-values list (Germany, 7/2023) Notes: danger from percutaneous absorption (see p. 211 and p. 228).

BEI: 250 mg/g creatinine, mandelic acid plus phenyl glyoxylic acid [in urine]. Sampling time: end of exposure or end of shift.

TRGS 903 - BEI Values (Germany, 2/2024)

BEI: 250 mg/g creatinine, mandelic acid plus phenylglyoxylic acid [in urine]. Sampling time: end of exposure or end of shift.

DFG BEI-values list (Germany, 7/2023)

BEI: 15 mg/l, propylene glycol 1-methyl ether [in urine]. Sampling time: end of exposure or end of shift.

TRGS 903 - BEI Values (Germany, 2/2024)

BEI: 15 mg/l, 1-methoxypropan-2-ol [in urine]. Sampling time: end of exposure or end of shift.

5/2020. (II. 6.) ITM Decree (Hungary, 12/2023) [xylene]

BEI: 1500 mg/g creatinine, methylhippuric acid [in urine].

Sampling time: at the end of the shift.

BEI: 860 µmol/mmol creatinine, methylhippuric acid [in urine]. Sampling time: at the end of the shift.

5/2020. (II. 6.) ITM Decree (Hungary, 12/2023)

BEI: 1500 mg/g creatinine, mandelic acid [in urine]. Sampling time: at the end of the working week; at the end of the shift.

BEI: 1110 µmol/mmol creatinine, mandelic acid [in urine]. Sampling time: at the end of the working week; at the end of the

: 07/02/2025 Date of issue/Date of revision · 10/02/2025 Version : 20 17/37 Date of previous issue Label No : 100297

No exposure indices known.

**Xylene** 

Ethylbenzene

No exposure indices known.

**Xylene** 

No exposure indices known.

**Xylene** 

Ethylbenzene

**Xylene** 

Ethylbenzene

**Xylene** 

shift.

#### NAOSH (Ireland, 1/2011) [Xylene]

BMGV: 1.5 g/g creatinine, methylhippuric acids [in urine]. Sampling time: end of shift - As soon as possible after exposure ceases.

#### NAOSH (Ireland, 1/2011)

BMGV: Semi-quantitative, the biological analyte is an indicator of exposure to the substance but the quantitative interpretation of the measurement is ambiguous. These analytes should be used as a screening test if a quantitative test is not practical; or as a confirmatory test if the quantitative test is not specific and the origin of the determinant is in question., ethylbenzene [in endexhaled air]. Sampling time: not critical.

BMGV: 0.7 g/g creatinine [Semi-quantitative, the biological analyte is an indicator of exposure to the substance but the quantitative interpretation of the measurement is ambiguous. These analytes should be used as a screening test if a quantitative test is not practical; or as a confirmatory test if the quantitative test is not specific and the origin of the determinant is in question.], mandelic acid and phenylglyoxylic acid [in urine]. Sampling time: end of shift at end of workweek.

## Minister Cabinet Regulations No.325 - BEI (Latvia, 3/2024) [xylenes (all isomers)]

BEI: 2000 mg/l, methylhippuric (toluric) acid (all isomers) [in urine]. Sampling time: at the end of the exposure or at the end of the shift.

## Portuguese Institute of Quality (Portugal, 11/2014) [Xylenes]

BEI: 1.5 g/g creatinine, (o, m, p) -methyl-boronic acids [in urine]. Sampling time: end of shift.

#### Portuguese Institute of Quality (Portugal, 11/2014)

BEI: 0.7 g/g creatinine, sum of mandelic acid and phenylglyoxylic acid [in urine]. Sampling time: end of shift.

## HG 1218/2006, Annex 2, with subsequent modifications and additions (Romania, 3/2024) [Xylene]

OBLV: 3 g/l, methylhippuric acid [in urine]. Sampling time: end of shift.

## HG 1218/2006, Annex 2, with subsequent modifications and additions (Romania, 3/2024)

OBLV: 1.5 g/g creatinine, mandelic acid [in urine]. Sampling time: end of the week.

## Government regulation SR c. 355/2006 (Slovakia, 5/2024) [xylene, all isomers]

BLV: 781 µmol/mmol creatinine, as sum of 2,3,4-methylhippuroic acids [in urine]. Sampling time: at the end of exposure or work shift. BLV: 1334 mg/g creatinine, as sum of 2,3,4-methylhippuroic acids [in urine]. Sampling time: at the end of exposure or work shift.

BLV: 10355 µmol/l, as sum of 2,3,4-methylhippuroic acids [in urine]. Sampling time: at the end of exposure or work shift.

: 07/02/2025

BLV: 14.6 µmol/l, as xylene [in blood]. Sampling time: at the end

Date of previous issue

: 10/02/2025

Date of issue/Date of revision
TEKNOPLAST PRIMER 7

**Label No** : 100297

Version : 20

18/37

of exposure or work shift.

BLV: 2000 mg/l, as sum of 2,3,4-methylhippuroic acids [in urine]. Sampling time: at the end of exposure or work shift.

BLV: 1.5 mg/l, as xylene [in blood]. Sampling time: at the end of exposure or work shift.

Ethylbenzene

#### Government regulation SR c. 355/2006 (Slovakia, 5/2024)

BLV: 799 µmol/mmol creatinine, as mandelic acid and phenylglyoxylic acid [in urine]. Sampling time: at the end of exposure or work shift; long-term exposure: after several work shifts.

BLV: 7.44 µmol/mmol creatinine, as 2 or 4-etylfenol [in urine]. Sampling time: at the end of exposure or work shift; long-term exposure: after several work shifts.

BLV: 1067 mg/g creatinine, as mandelic acid and phenylglyoxylic acid [in urine]. Sampling time: at the end of exposure or work shift; long-term exposure: after several work shifts.

BLV: 8.03 mg/g creatinine, as 2 or 4-etylfenol [in urine]. Sampling time: at the end of exposure or work shift; long-term exposure: after several work shifts.

BLV: 10590 µmol/l, as mandelic acid and phenylglyoxylic acid [in urine]. Sampling time: at the end of exposure or work shift; long-term exposure: after several work shifts.

BLV: 98.6 µmol/l, as 2 or 4-etylfenol [in urine]. Sampling time: at the end of exposure or work shift; long-term exposure: after several work shifts.

BLV: 1600 mg/l, as mandelic acid and phenylglyoxylic acid [in urine]. Sampling time: at the end of exposure or work shift; long-term exposure: after several work shifts.

BLV: 12 mg/l, as 2 or 4-etylfenol [in urine]. Sampling time: at the end of exposure or work shift; long-term exposure: after several work shifts.

**Xylene** 

# Regulation on protection of workers from the risks related to exposure to chemical substances at work (Slovenia, 4/2024) [xylene (all isomers)]

BAT: 2 g/l, methylhippuric acid (all isomers) [in urine]. Sampling time: at the end of the work shift.

#### Ethylbenzene

## Regulation on protection of workers from the risks related to exposure to chemical substances at work (Slovenia, 4/2024)

BAT: 250 mg/g creatinine, mandelic acid and phenylglyoxylic acid [in urine]. Sampling time: at the end of the work shift.

1-Methoxy 2-propanol

## Regulation on protection of workers from the risks related to exposure to chemical substances at work (Slovenia, 4/2024)

BAT: 15 mg/l, 1-methoxypropan-2-ol [in urine]. Sampling time: at the end of the work shift.

#### **Xylene**

## National institute of occupational safety and health (Spain, 1/2024) [Xylenes]

VLB: 1 g/g creatinine, methylhippuric acids [in urine]. Sampling time: end of shift.

#### Ethylbenzene

## National institute of occupational safety and health (Spain, 1/2024)

No exposure indices known.

VLB: 700 mg/g creatinine, sum of mandelic acid and acid and phenylglyoxylic acid [in urine]. Sampling time: end of workweek.

Label No : 100297

Date of issue/Date of revision : 10/02/2025 Date of previous issue : 07/02/2025 Version : 20 19/37

Xylene SUVA (Switzerland, 1/2024) [Xylene, all isomers]

BEI: 2 g/l, methyl hippuric acid [in urine]. Sampling time: immediately after exposure or after working hours.

Ethylbenzene SUVA (Switzerland, 1/2024)

BEI: 600 mg/g creatinine, mandelic acid + phenylglyoxylic acid [in urine]. Sampling time: immediately after exposure or after working

hours.

1-Methoxy 2-propanol SUVA (Switzerland, 1/2024)

BEI: 20 mg/l, 1-methoxypropanol-2 [in urine]. Sampling time:

immediately after exposure or after working hours.

BEI: 221.9 µmol/l, 1-methoxypropanol-2 [in urine]. Sampling time:

immediately after exposure or after working hours.

EH40/2005 BMGVs (United Kingdom (UK), 1/2020) [Xylene, o-,

m-, p- or mixed isomers]

BGV: 650 mmol/mol creatinine, methyl hippuric acid [in urine].

Sampling time: post shift.

Recommended monitoring procedures

: Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

### **DNELs/DMELs**

**Xylene** 

**Xylene** 

#### **Product/ingredient name**

Phenol, methylstyrenated

#### Result

DNEL - General population - Long term - Oral

0.2 mg/kg bw/day Effects: Systemic

DNEL - General population - Long term - Inhalation

0.348 mg/m³ Effects: Systemic

**DNEL - Workers - Long term - Inhalation** 

1.41 mg/m³ Effects: Systemic

DNEL - General population - Long term - Dermal

1.67 mg/kg bw/day <u>Effects</u>: Systemic

**DNEL - Workers - Long term - Dermal** 

3.5 mg/kg bw/day Effects: Systemic

**DNEL - General population - Long term - Oral** 

5 mg/kg bw/day Effects: Systemic

DNEL - General population - Long term - Inhalation

65.3 mg/m³ Effects: Local

DNEL - General population - Long term - Inhalation

65.3 mg/m³ <u>Effects</u>: Systemic

DNEL - General population - Long term - Dermal

125 mg/kg bw/day

Date of issue/Date of revision : 10/02/2025 Date of previous issue : 07/02/2025 Version : 20 20/37

TEKNOPLAST PRIMER 7

Effects: Systemic

**DNEL - Workers - Long term - Dermal** 

212 mg/kg bw/day Effects: Systemic

**DNEL - Workers - Long term - Inhalation** 

221 mg/m<sup>3</sup> Effects: Local

**DNEL - Workers - Long term - Inhalation** 

221 mg/m<sup>3</sup> Effects: Systemic

DNEL - General population - Short term - Inhalation

260 mg/m<sup>3</sup> Effects: Local

DNEL - General population - Short term - Inhalation

260 mg/m<sup>3</sup> Effects: Systemic

**DNEL - Workers - Short term - Inhalation** 

442 mg/m<sup>3</sup> Effects: Local

**DNEL - Workers - Short term - Inhalation** 

442 ma/m<sup>3</sup> Effects: Systemic

DNEL - General population - Long term - Inhalation

28 µg/m<sup>3</sup> Effects: Local

**DNEL - Workers - Long term - Inhalation** 

170 µg/m<sup>3</sup> Effects: Local

Bis[4-(2,3-epoxypropoxy)phenyl]propane DNEL - General population - Long term - Dermal

> 89.3 µg/kg bw/day Effects: Systemic

DNEL - General population - Long term - Oral

0.5 mg/kg bw/day Effects: Systemic

**DNEL - Workers - Long term - Dermal** 

0.75 mg/kg bw/day Effects: Systemic

DNEL - General population - Long term - Inhalation

0.87 mg/m<sup>3</sup> Effects: Systemic

**DNEL - Workers - Long term - Inhalation** 

4.93 ma/m3 Effects: Systemic

Ethylbenzene DMEL - Workers - Long term - Inhalation

> 442 mg/m<sup>3</sup> Effects: Local

DMEL - Workers - Short term - Inhalation

21/37

884 mg/m<sup>3</sup> Effects: Systemic

Date of issue/Date of revision : 07/02/2025 : 10/02/2025 Date of previous issue

Version : 20 TEKNOPLAST PRIMER 7 Label No : 100297

titanium dioxide

DNEL - General population - Long term - Oral

1.6 mg/kg bw/day Effects: Systemic

DNEL - General population - Long term - Inhalation

15 mg/m<sup>3</sup>

Effects: Systemic

**DNEL - Workers - Long term - Inhalation** 

77 mg/m<sup>3</sup>

Effects: Systemic

**DNEL - Workers - Long term - Dermal** 

180 mg/kg bw/day Effects: Systemic

**DNEL - Workers - Short term - Inhalation** 

293 mg/m³ Effects: Local

DNEL - General population - Long term - Oral

33 mg/kg bw/day Effects: Systemic

DNEL - General population - Long term - Inhalation

43.9 mg/m³ Effects: Systemic

**DNEL - General population - Long term - Dermal** 

78 mg/kg bw/day Effects: Systemic

**DNEL - Workers - Long term - Dermal** 

183 mg/kg bw/day Effects: Systemic

**DNEL - Workers - Long term - Inhalation** 

369 mg/m³ Effects: Systemic

**DNEL - Workers - Short term - Inhalation** 

553.5 mg/m³ Effects: Local

**DNEL - Workers - Short term - Inhalation** 

553.5 mg/m³ Effects: Systemic

DNEL - General population - Long term - Inhalation

Label No : 100297

0.055 mg/m³ Effects: Local

DNEL - Workers - Long term - Inhalation

0.308 mg/m³ Effects: Local

Octadecanoic acid, 12-hydroxy-, reaction products with ethylenediamine

#### **PNECs**

Not available.

#### 8.2 Exposure controls

1-Methoxy 2-propanol

Date of issue/Date of revision : 10/02/2025 Date of previous issue : 07/02/2025 Version : 20 22/37

#### Appropriate engineering controls

: Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

#### **Individual protection measures**

#### **Hygiene measures**

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

#### Eye/face protection

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

#### **Skin protection**

#### **Hand protection**

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Recommendations: Wear suitable gloves tested to EN374.

< 1 hour (breakthrough time): Nitrile gloves. thickness > 0.3 mm

> 8 hours (breakthrough time): 4H / Silver Shield® gloves.

Wash hands before breaks and immediately after handling the product.

#### **Body protection**

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves. Refer to European Standard EN 1149 for further information on material and design requirements and test methods.

#### Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

#### Respiratory protection

: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Filter type:

Filter type (spray application):

#### **Environmental exposure** controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

## SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

#### 9.1 Information on basic physical and chemical properties

#### **Appearance**

**Physical state** : Liquid. Colour : Various **Odour** : Slight

Date of issue/Date of revision : 10/02/2025 Version : 20 23/37 Date of previous issue

TEKNOPLAST PRIMER 7

: 07/02/2025

## **SECTION 9: Physical and chemical properties**

Odour threshold : Not available.

Melting point/freezing point : Not available.

Initial boiling point and boiling range

Ingredient name

•

°F

Method

 1-Methoxy 2-propanol
 120.17
 248.3
 OECD 103

 Ethylbenzene
 136.1
 277
 OECD 104

°C

Flammability : Not available.

Lower and upper explosion : Lower: 0.8% (xylene) | Upper: 6.7% (xylene)

Flash point : Closed cup: 30°C (86°F)

Auto-ignition temperature :

Ingredient name	°C	°F	Method
1-Methoxy 2-propanol	270	518	
Phenol, methylstyrenated	>385	>725	DIN 51794

Decomposition temperature : Not available.pH : Not applicable.

Viscosity : Kinematic (40°C): >20.5 mm<sup>2</sup>/s

Solubility(ies) :

Not available.

Solubility in water : Not available.

Partition coefficient: n-octanol/ : Not applicable.

water

Vapour pressure

	Vapour Pressure at 20°C			Va	oour pressu	re at 50°C
Ingredient name	mm Hg	kPa	Method	mm Hg	kPa	Method
Ethylbenzene	9.30076	1.2				
1-Methoxy 2-propanol	8.5	1.1				

Relative density : Not available.

Density : 1.6 g/cm³

Vapour density : Not available.

**Particle characteristics** 

Median particle size : Not applicable.

#### 9.2 Other information

9.2.1 Information with regard to physical hazard classes

Explosive properties : Not available.

Oxidising properties : Not available.

9.2.2 Other safety characteristics

Not applicable.

## **SECTION 10: Stability and reactivity**

**10.1 Reactivity** : No specific test data related to reactivity available for this product or its ingredients.

**10.2 Chemical stability** : The product is stable.

10.3 Possibility of : Under normal conditions of storage and use, hazardous reactions will not occur.

Date of issue/Date of revision: 10/02/2025Date of previous issue: 07/02/2025Version: 2024/37TEKNOPLAST PRIMER 7Label No: 10/02/2027

## **SECTION 10: Stability and reactivity**

10.4 Conditions to avoid

: Avoid all possible sources of ignition (spark or flame). Do not pressurise, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.

10.5 Incompatible materials

: Reactive or incompatible with the following materials:

oxidising materials

10.6 Hazardous decomposition products

: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## **SECTION 11: Toxicological information**

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

**Acute toxicity** 

Xylene

Product/ingredient name

Rat - Oral - LD50

4300 mg/kg

Result

Toxic effects: Liver - Other changes Kidney, Ureter, and

Bladder - Other changes

Rat - Inhalation - LC50 Vapour

21.7 mg/l [4 hours]

Bis[4-(2,3-epoxypropoxy)phenyl]propane

Rabbit - Dermal - LD50

20 g/kg

<u>Toxic effects</u>: Behavioral - Somnolence (general depressed activity) Gastrointestinal - Hypermotility, diarrhea Gross Metabolite Changes - Weight loss or decreased weight gain

Ethylbenzene

Rat - Oral - LD50

3500 mg/kg

Rabbit - Dermal - LD50

15400 mg/kg

Rat - Inhalation - LC50 Dusts and mists

29000 mg/l [4 hours]

1-Methoxy 2-propanol

Rabbit - Dermal - LD50

13 g/kg

Rat - Oral - LD50

6600 mg/kg

<u>Toxic effects</u>: Brain and Coverings - Other degenerative changes Behavioral - General anesthetic Lung, Thorax, or

Respiration - Dyspnea

Conclusion/Summary [Product] : Not available.

#### **Acute toxicity estimates**

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
FEKNOPLAST PRIMER 7	N/A	9907.1	N/A	81.3	N/A
Xylene	4300	1100	N/A	11	N/A
Bis[4-(2,3-epoxypropoxy)phenyl]propane	N/A	20000	N/A	N/A	N/A
Ethylbenzene	3500	15400	N/A	11	29000
1-Methoxy 2-propanol	6600	13000	N/A	N/A	N/A

#### Skin corrosion/irritation

Date of issue/Date of revision: 10/02/2025Date of previous issue: 07/02/2025Version: 2025/37TEKNOPLAST PRIMER 7Label No: 1700297

## **SECTION 11: Toxicological information**

Product/ingredient name Re

**⋉**ylene **Rat - Skin - Mild irritant** 

<u>Duration of treatment/exposure</u>: 8 hours Amount/concentration applied: 60 uL

Rabbit - Skin - Moderate irritant

<u>Duration of treatment/exposure</u>: 24 hours <u>Amount/concentration applied</u>: 500 mg

Rabbit - Skin - Moderate irritant Amount/concentration applied: 100 %

titanium dioxide Human - Skin - Mild irritant

<u>Duration of treatment/exposure</u>: 72 hours <u>Amount/concentration applied</u>: 300 ug I

Bis[4-(2,3-epoxypropoxy)phenyl]propane Rabbit - Skin - Mild irritant

Amount/concentration applied: 500 mg

reaction product: bisphenol-A- Rabbit - Skin - Moderate irritant

<u>Duration of treatment/exposure</u>: 24 hours <u>Amount/concentration applied</u>: 500 uL

Rabbit - Skin - Severe irritant

<u>Duration of treatment/exposure</u>: 24 hours <u>Amount/concentration applied</u>: 2 mg

Ethylbenzene Rabbit - Skin - Mild irritant

<u>Duration of treatment/exposure</u>: 24 hours <u>Amount/concentration applied</u>: 15 mg

1-Methoxy 2-propanol Rabbit - Skin - Mild irritant

Amount/concentration applied: 500 mg

**Conclusion/Summary [Product]**: Not available.

Serious eye damage/eye irritation

(epichlorhydrin); epoxy resin

Product/ingredient name Result

**⋉**ylene **Rabbit - Eyes - Mild irritant** 

Amount/concentration applied: 87 mg

Rabbit - Eyes - Severe irritant

<u>Duration of treatment/exposure</u>: 24 hours <u>Amount/concentration applied</u>: 5 mg

Bis[4-(2,3-epoxypropoxy)phenyl]propane Rabbit - Eyes - Severe irritant

<u>Duration of treatment/exposure</u>: 24 hours <u>Amount/concentration applied</u>: 2 mg

reaction product: bisphenol-A- Rabbit - Eyes - Mild irritant

(epichlorhydrin); epoxy resin <u>Amount/concentration applied</u>: 100 mg

Ethylbenzene Rabbit - Eyes - Severe irritant

Amount/concentration applied: 500 mg

1-Methoxy 2-propanol Rabbit - Eyes - Mild irritant

<u>Duration of treatment/exposure</u>: 24 hours <u>Amount/concentration applied</u>: 500 mg

Conclusion/Summary [Product] : Not available.

Respiratory corrosion/irritation

Not available.

Date of issue/Date of revision : 10/02/2025 Date of previous issue : 07/02/2025 Version : 20 26/37

TEKNOPLAST PRIMER 7

## **SECTION 11: Toxicological information**

**Conclusion/Summary [Product]**: Not available.

#### Respiratory or skin sensitization

Not available.

Skin

**Conclusion/Summary [Product]**: Not available.

Respiratory

**Conclusion/Summary [Product]**: Not available.

#### **Germ cell mutagenicity**

Not available.

**Conclusion/Summary [Product]**: Not available.

#### Carcinogenicity

It has been observed that the carcinogenic hazard of this product arises when respirable dust is inhaled in quantities leading to significant impairment of particle clearance mechanisms in the lung.

Not available.

Conclusion/Summary [Product] : Not available.

#### Reproductive toxicity

Not available.

Conclusion/Summary [Product] : Not available.

#### Specific target organ toxicity (single exposure)

Product/ingredient name Result

Xylene STOT SE 3, H335 (Respiratory tract irritation)

1-Methoxy 2-propanol STOT SE 3, H336 (Narcotic effects)

#### Specific target organ toxicity (repeated exposure)

Product/ingredient name Result

Xylene STOT RE 2, H373 (oral, inhalation)

Ethylbenzene STOT RE 2, H373 (hearing organs) (oral, inhalation)

**Aspiration hazard** 

Product/ingredient name Result

Xylene ASPIRATION HAZARD - Category 1
Ethylbenzene ASPIRATION HAZARD - Category 1

Information on likely routes of exposure

Not available.

Potential acute health effects

**Eye contact** : Causes serious eye irritation.

**Inhalation** : No known significant effects or critical hazards.

**Skin contact**: Causes skin irritation. May cause an allergic skin reaction.

Ingestion : No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Date of issue/Date of revision : 10/02/2025 Date of previous issue : 07/02/2025 Version : 20 27/37

**TEKNOPLAST PRIMER 7** 

## **SECTION 11: Toxicological information**

**Eye contact**: Adverse symptoms may include the following:

pain or irritation watering

redness

Inhalation : No specific data.

**Skin contact**: Adverse symptoms may include the following:

irritation redness

**Ingestion**: No specific data.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Short term exposure

**Potential immediate** 

: Not available.

effects

Potential delayed effects : Not available.

**Long term exposure** 

Potential immediate : Not available.

effects

Potential delayed effects : Not available.

Potential chronic health effects

Not available.

**Conclusion/Summary [Product]**: Not available.

General: May cause damage to organs through prolonged or repeated exposure. Once

sensitized, a severe allergic reaction may occur when subsequently exposed to

very low levels.

Carcinogenicity : No known significant effects or critical hazards.
 Mutagenicity : No known significant effects or critical hazards.
 Reproductive toxicity : No known significant effects or critical hazards.

#### 11.2 Information on other hazards

### 11.2.1 Endocrine disrupting properties

Not available.

**Conclusion/Summary [Product]**: The product does not meet the criteria to be considered as having endocrine

disrupting properties according to the criteria set out in either Regulation (EC)

No. 1907/2006 or Regulation (EC) No 1272/2008.

#### 11.2.2 Other information

Not available.

## **SECTION 12: Ecological information**

#### 12.1 Toxicity

Product/ingredient name Result

Phenol, methylstyrenated Acute - LC50

Fish

25.8 mg/l [96 hours]

Acute - EC50

Daphnia

14 mg/l [48 hours]

Acute - EC50

Algae

15 mg/l [72 hours]

titanium dioxide Acute - LC50 - Marine water

Fish - Mummichog - Fundulus heteroclitus

>1000000 µg/l [96 hours]

Effect: Mortality

Acute - LC50 - Fresh water

Date of issue/Date of revision : 10/02/2025 Date of previous issue : 07/02/2025 Version : 20 28/37

TEKNOPLAST PRIMER 7

## **SECTION 12: Ecological information**

Crustaceans - Water flea - Ceriodaphnia dubia - Neonate

Age: <24 hours 3 mg/l [48 hours] Effect: Mortality

Conclusion/Summary [Product] : Not available.

### 12.2 Persistence and degradability

Not available.

Conclusion/Summary [Product] : Not available.

### 12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
Phenol, methylstyrenated	3.627	-	Low
Xylene	3.12	8.1 to 25.9	Low
reaction product: bisphenol-	2.64 to 3.78	31	Low
A-(epichlorhydrin); epoxy			
resin			
Ethylbenzene	3.6	-	Low
1-Methoxy 2-propanol	<1	-	Low

#### 12.4 Mobility in soil

#### Soil/water partition coefficient

Product/ingredient name	logKoc	Koc
<b>B</b> is[4-(2,3-epoxypropoxy)phenyl]propane	4.02	10465.7
Ethylbenzene	2.23	170.406
1-Methoxy 2-propanol	1.02	10.447

#### Results of PMT and vPvM assessment

Product/ingredient name	PMT	Р	M	T	vPvM	vP	vM
Phenol, methylstyrenated	No	No	No	No	No	No	No
Xylene	No	No	No	No	No	No	No
titanium dioxide	No	No	No	No	No	No	No
Bis[4-(2,3-epoxypropoxy) phenyl]propane	No	No	No	No	No	No	No
reaction product: bisphenol-A-(epichlorhydrin); epoxy resin	No	No	No	No	No	No	No
Ethylbenzene	No	No	No	No	No	No	No
1-Methoxy 2-propanol	No	No	No	No	No	No	No
Octadecanoic acid, 12-hydroxy-, reaction products with ethylenediamine	No	No	No	No	No	No	No

**Mobility** : Not available.

**Conclusion/Summary** : The product does not meet the criteria to be considered as a PMT or vPvM.

12.5 Results of PBT and vPvB assessment Regulation (EC) No. 1907/2006 [REACH]

Version : 20 Date of issue/Date of revision : 10/02/2025 Date of previous issue : 07/02/2025 29/37 Label No : 100297

## **SECTION 12: Ecological information**

Product/ingredient name	PBT	P	В	Т	vPvB	νP	vB	
Phenol, methylstyrenated	No	No	No	No	No	No	No	
Xylene	No	No	No	No	No	No	No	
titanium dioxide	No	No	No	No	No	No	No	
Bis[4-(2,3-epoxypropoxy)	No	No	No	No	No	No	No	
phenyl]propane								
reaction product: bisphenol-	No	No	No	No	No	No	No	
A-(epichlorhydrin); epoxy								
resin								
Ethylbenzene	No	No	No	No	No	No	No	
1-Methoxy 2-propanol	No	No	No	No	No	No	No	
Octadecanoic acid,	No	No	No	No	No	No	No	
12-hydroxy-, reaction								
products with								
ethylenediamine								

#### **Regulation (EC) No. 1272/2008 [CLP]**

Product/ingredient name	PBT	Р	В	Т	vPvB	vP	vB
Phenol, methylstyrenated	No	No	No	No	No	No	No
Xylene	No	No	No	No	No	No	No
titanium dioxide	No	No	No	No	No	No	No
Bis[4-(2,3-epoxypropoxy) phenyl]propane	No	No	No	No	No	No	No
reaction product: bisphenol-A-(epichlorhydrin); epoxy resin	No	No	No	No	No	No	No
Ethylbenzene	No	No	No	No	No	No	No
1-Methoxy 2-propanol	No	No	No	No	No	No	No
Octadecanoic acid, 12-hydroxy-, reaction products with ethylenediamine	No	No	No	No	No	No	No

Conclusion/Summary Regulation (EC) No. 1272/2008 [CLP]

: The product does not meet the criteria to be considered as a PBT or vPvB.

#### 12.6 Endocrine disrupting properties

Not available.

**Conclusion/Summary [Product]** 

: The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

#### 12.7 Other adverse effects

No known significant effects or critical hazards.

## **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

#### **Product**

**Methods of disposal** 

The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

**European waste** catalogue (EWC)

: 080111\*, 200127\*

**Packaging** 

Date of issue/Date of revision: 10/02/2025Date of previous issue: 07/02/2025Version: 2030/37TEKNOPLAST PRIMER 7Label No : №0297

## SECTION 13: Disposal considerations

**Methods of disposal** 

: The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

#### **Special precautions**

: This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapour from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

## **SECTION 14: Transport information**

	ADR/RID	ADN	IMDG	IATA
14.1 UN number or ID number	UN1263	UN1263	UN1263	UN1263
14.2 UN proper shipping name	PAINT	PAINT	PAINT	PAINT
14.3 Transport hazard class(es)	3	3	3	3
14.4 Packing group	III	III	III	III
14.5 Environmental hazards	No.	No.	No.	No.

#### **Additional information**

ADR/RID

: Viscous liquid exception This class 3 viscous liquid is not subject to regulation in packagings up to 450 L according to 2.2.3.1.5.1. Tunnel code (D/E)

**ADN** 

: Viscous liquid exception This class 3 viscous liquid is not subject to regulation in packagings up to 450 L according to 2.2.3.1.5.1.

**IMDG** 

: Viscous liquid exception This class 3 viscous liquid is not subject to regulation in packagings up to 450 L according to 2.3.2.5.

user

14.6 Special precautions for : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Maritime transport in bulk according to IMO instruments

: Not relevant/applicable due to nature of the product.

## **SECTION 15: Regulatory information**

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

**Annex XIV** 

None of the components are listed.

Substances of very high concern

Date of issue/Date of revision · 07/02/2025 Version : 20 31/37 : 10/02/2025 Date of previous issue Label No : 100297

Intrinsic property	Ingredient name		Reference number	Date of revision
vPvB	Phenol, methylstyrenated	Candidate	D(2023) 8585-DC	-

## <u>Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles</u>

Product/ingredient name	%	Designation [Usage]
TEKNOPLAST PRIMER 7	≥90	3

Labelling :

**Other EU regulations** 

Industrial emissions : Not listed

(integrated pollution prevention and control) -

**Air** 

Industrial emissions : Not listed

(integrated pollution prevention and control) -

Water

Explosive precursors : Not applicable.

Ozone depleting substances (EU 2024/590)

Not listed

Prior Informed Consent (PIC) (649/2012/EU)

Not listed.

**Persistent Organic Pollutants** 

Not listed.

**Seveso Directive** 

This product is controlled under the Seveso Directive.

**Danger criteria** 

**Category** 

P5c

**National regulations** 

**Austria** 

**Limitation of the use of :** Permitted.

organic solvents

**Belgium** 

Book VI carcinogenic agents annex VI.2-1 - VI.2-3

Ingredient name	Status
Silice	Listed
Silice	Listed

**Czech Republic** 

Storage code : II

**Denmark** 

Fire class : II-1 Executive Order No. 1795/2015

Ingredient name	Annex I Section A	Annex I Section B
titanium dioxide	Listed	-
Ethylbenzene	Listed	-

MAL-code : 3-6

Date of issue/Date of revision: 10/02/2025Date of previous issue: 07/02/2025Version: 2032/37TEKNOPLAST PRIMER 7Label No: \$100297

Protection based on MAL : According to the regulations on work involving coded products, the following stipulations apply to the use of personal protective equipment:

> **General:** Gloves must be worn for all work that may result in soiling. Apron/ coveralls/protective clothing must be worn when soiling is so great that regular work clothes do not adequately protect skin against contact with the product. A face shield must be worn in work involving spattering if a full mask is not required. In this case, other recommended use of eye protection is not required.

> In all spraying operations in which there is return spray, the following must be worn: respiratory protection and arm protectors/apron/coveralls/protective clothing as appropriate or as instructed.

MAL-code: 3-6

Application: When using scraper or knife, brush, roller etc. for pre- and posttreatments in a spray booth where the operator is outside the spray zone and when working in similar new\* facilities of the combined-cabin, spray-cabin and spray-booth type where the operator is working inside the spray zone. When spraying in new\* booths and cabins with non-atomizing guns.

- Protective clothing must be worn.

During downtimes, cleaning and repair in closed facilities, spray booths or cabins, if there is a risk of contact with wet paint or organic solvents. When using scraper or knife, brush, roller, etc, for pre- and post-treatments in cabins or booths of the existing\* facility type, if the operator is inside the spray zone. When using scraper or knife, brush, roller, etc. for pre- and post-treatments outside a closed facility, spray booth or spray cabin.

Air-supplied half mask, protective clothing and eye protection must be worn.

When spraying in new\* booths if the operator is outside the spray zone.

- Air-supplied half mask and eye protection must be worn.

When spraying in existing\* spray booths, if the operator is outside the spray zone. During non-atomising spraying in existing\* facilities of the combined-cabin, spraycabin and spray-booth type where the operator is working inside the spray zone.

- Air-supplied full mask and protective clothing must be worn.

During all spraying where atomisation occurs in cabins or spray booths where the operator is inside the spray zone and during spraying outside a closed facility, cabin or booth.

- Air-supplied full mask, protective clothing and hood must be worn.

Drying: Items for drying/drying ovens that are temporarily placed on such things as rack trolleys, etc, must be equipped with a mechanical exhaust system to prevent fumes from wet items from passing through workers' inhalation zone.

**Polishing:** When polishing treated surfaces, a mask with dust filter must be worn. When machine grinding, eye protection must be worn. Work gloves must always be worn.

**Caution** The regulations contain other stipulations in addition to the above.

\*See Regulations.

Restrictions on use

Not to be used by professional users below 18 years of age. See the National Working Environment Authorities Executive Order regarding Young People At Work.

Date of issue/Date of revision · 07/02/2025 Version : 20 33/37 : 10/02/2025 Date of previous issue TEKNOPLAST PRIMER 7 Label No : 100297

List of undesirable substances

: Not listed

Carcinogenic waste

: Waste containers must be labeled: Contains a substance or substances regulated by Danish working environment legislation on cancer risks.

**Epoxy/Isocyanate** 

: The product is covered by the rules for epoxy resins and isocyanates in Executive Order no. 1793 of 18/12/2015 on working with substances and materials (chemical agents). Pay attention to the rules, for example: the user of the product must have undergone special training and waste must be labelled. This requirement is in addition to the training requirement described in the REACH regulation, Annex XVII, entry 74 (COMMISSION REGULATION (EU) 2020/1149).

Finland France

Social Security Code, Articles L 461-1 to L 461-7 ▼ylene RG 4bis, RG 84

Bis[4-(2,3-epoxypropoxy)phenyl]propane RG 84
Ethylbenzene RG 84
1-Methoxy 2-propanol RG 84

Reinforced medical surveillance

Act of July 11, 1977 determining the list of activities which require reinforced

medical surveillance: not applicable

**Germany** 

Storage class (TRGS 510) : 3 Hazardous incident ordinance

This product is controlled under the Germany Hazardous Incident Ordinance.

#### **Danger criteria**

Category	Reference number
P5c	1.2.5.3

Hazard class for water : 2

Technical instruction on air quality control (TA Luft)

Number [Class]	Description	%
5.2.1	Total dust	53.6
5.2.5	Organic substances	46.3
5.2.5 [I]	Organic substances	16

**AOX** 

: The product contains organically bound halogens and can contribute to the AOX value in waste water.

Italy

D.Lgs. 152/06 : Not determined.

**Netherlands** 

## Ministry of Social Affairs and Employment (SZW) - Carcinogenic substances and processes, mutagenic or reprotoxic substances

Ingredient name	Carcinogen	•	Reproductive toxicity - Fertility	•	Harmful via breastfeeding
xylene ethanol silica, crystalline (NL- carcinogen specific)	Listed Listed	- - -	- Fertility 1A -	Development 2 Development 1A	Listed

Water Discharge Policy (ABM)

Z(1) Non biodegradable substances with hazardous properties for humans and the environment (carcinogenicity/ mutagenicity/ reprotoxicity/ bioacumulative potential/ toxicity or persistence). Decontamination effort: Z

Norway Sweden

Flammable liquid class

(SRVFS 2005:10)

: 2a

Date of issue/Date of revision: 10/02/2025Date of previous issue: 07/02/2025Version: 2034/37TEKNOPLAST PRIMER 7Label No: 10/02/2027

#### **Epoxy/Isocyanate**

: The product is covered by the specific rules for epoxy resins and isocyanates, allergenic chemical products in provision AFS 2011:19 Chemical Hazards in the Working Environment, Pay attention to that handling the product requires certificate of undergone necessary training and can require medical examination. Waste must be labelled with named substance and as Hazardous waste. This requirement is in addition to the training requirement described in the REACH regulation, Annex XVII, entry 74 (COMMISSION REGULATION (EU) 2020/1149).

**Switzerland** 

**VOC** content : VOC (w/w): 16%

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

**Montreal Protocol** 

Not listed.

**Stockholm Convention on Persistent Organic Pollutants** 

Not listed.

**Rotterdam Convention on Prior Informed Consent (PIC)** 

Not listed.

**UNECE Aarhus Protocol on POPs and Heavy Metals** 

Not listed.

15.2 Chemical safety

assessment

: This product contains substances for which Chemical Safety Assessments are still required.

#### SECTION 16: Other information

Indicates information that has changed from previously issued version.

**Abbreviations and** acronyms

: ATE = Acute Toxicity Estimate

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No.

1272/2008]

DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level

EUH statement = CLP-specific Hazard statement

N/A = Not available

PBT = Persistent. Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration

RRN = REACH Registration Number

SGG = Segregation Group

vPvB = Very Persistent and Very Bioaccumulative

#### Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Flam. Liq. 3, H226	On basis of test data
Skin Irrit. 2, H315	Calculation method
Eye Irrit. 2, H319	Calculation method
Skin Sens. 1, H317	Calculation method
STOT RE 2, H373	Calculation method
Aquatic Chronic 3, H412	Calculation method

Full text of abbreviated H statements

Date of issue/Date of revision · 07/02/2025 Version : 20 35/37 : 10/02/2025 Date of previous issue Label No : 100297

## **SECTION 16: Other information**

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

#### Full text of classifications [CLP/GHS]

Acute Tox. 4	ACUTE TOXICITY - Category 4
Aquatic Chronic 2	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2
Aquatic Chronic 3	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3
Asp. Tox. 1	ASPIRATION HAZARD - Category 1
Carc. 2	CARCINOGENICITY - Category 2
Eye Irrit. 2	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2
Flam. Liq. 2	FLAMMABLE LIQUIDS - Category 2
Flam. Liq. 3	FLAMMABLE LIQUIDS - Category 3
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2
Skin Sens. 1	SKIN SENSITISATION - Category 1
Skin Sens. 1B	SKIN SENSITISATION - Category 1B
STOT RE 2	SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 2
STOT SE 3	SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3

Date of issue/ Date of : 10/02/2025

revision

Date of previous issue : 07/02/2025

Version : 20

### **Notice to reader**

The information in this SDS is based on the present state of our knowledge and on current laws. The product is not to be used for purposes other than those specified under section 1 without first obtaining written handling instructions. It is always the responsibility of the user to take all necessary steps to fulfil the demands set out in the local rules and legislation. The information in this SDS is meant to be a description of the safety requirements for our product. It is not to be considered a guarantee of the product's properties.

Date of issue/Date of revision : 10/02/2025 Date of previous issue : 07/02/2025 Version : 20 36/37 Label No : 100297

 Date of issue/Date of revision
 : 10/02/2025
 Date of previous issue
 : 07/02/2025
 Version
 : 20
 37/37

 TEKNOPLAST PRIMER 7
 Label No : ₹00297