Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2020/878 - United Kingdom: Northern Ireland

SAFETY DATA SHEET



UVILUX FILLER 1806-00 - All variants

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product ident	ifier
-------------------	-------

Product name : UVILUX FILLER 1806-00 - All variants

1.2 Relevant identified uses of the substance or mixture and uses advised againstProduct use: Paint.

1.3 Details of the supplier of the safety data sheet

Teknos Group Oy, Takkatie 3, FI-00370 HELSINKI, FINLAND. Tel. +358 9 506 091.

e-mail address of person : Prod-safe@teknos.com responsible for this SDS

National contact

Teknos Ireland Limited, 52 Ballymoughan Road, Magherafelt, BT45 6HN, UK. Tel. +44 (0) 2879 301 472.

1.4 Emergency telephone number

National advisory body/Poison Centre

Telephone number : NHS: 111

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 STOT SE 3, H335 Aquatic Chronic 2, H411

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Hazard pictograms



Signal word	: Warning
Hazard statements	 F315 - Causes skin irritation. H317 - May cause an allergic skin reaction. H319 - Causes serious eye irritation. H335 - May cause respiratory irritation. H411 - Toxic to aquatic life with long lasting effects.
Precautionary statements	
Prevention	 P280 - Wear protective gloves. Wear eye or face protection. P273 - Avoid release to the environment. P261 - Avoid breathing vapour.
Response	: P391 - Collect spillage.
Dete of issue (Dete of models is	

SECTION 2: Hazards	identification
Storage	: P403 + P233 - Store in a well-ventilated place. Keep container tightly closed.
Disposal	: P501 - Dispose of contents and container in accordance with all local, regiona national and international regulations.
Hazardous ingredients	: Contains: (1-methyl-1,2-ethanediyl)bis[oxy(methyl-2,1-ethanediyl)] diacrylate; (5-ethyl-1,3-dioxan-5-yl)methyl acrylate and Phosphine oxide, phenylbis (2,4,6-trimethylbenzoyl)-
Supplemental label elements	:
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	:

2.3 Other hazards	
Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII	: This mixture does not contain any substances that are assessed to be a PBT or a vPvB.
Other hazards which do not result in classification	: None known.

SECTION 3: Composition/information on ingredients

3.2 Mixtures	: Mixture				
Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Туре
-methyl-1,2-ethanediyl)bis [oxy(methyl-2,1-ethanediyl)] diacrylate	REACH #: 01-2119484613-34 EC: 256-032-2 CAS: 42978-66-5 Index: 607-249-00-X	≥10 - ≤25	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 STOT SE 3, H335 Aquatic Chronic 2, H411	STOT SE 3, H335: C ≥ 10%	[1]
Ethanol, 2-amino-, reaction products with polyethylene- polypropylene glycol ether with trimethylolpropane (3: 1) acrylate	CAS: 119327-83-2	≥10 - ≤25	Aquatic Chronic 2, H411	-	[1]
(5-ethyl-1,3-dioxan-5-yl) methyl acrylate	REACH #: 01-2119976303-36 EC: 266-380-7 CAS: 66492-51-1	≤10	Skin Irrit. 2, H315 Skin Sens. 1B, H317 Aquatic Chronic 2, H411	-	[1]
2-hydroxy- 2-methylpropiophenone	REACH #: 01-2119472306-39 EC: 231-272-0 CAS: 7473-98-5	≤3	Acute Tox. 4, H302 Aquatic Chronic 3, H412	ATE [Oral] = 1694 mg/kg	[1]
Phosphine oxide, phenylbis (2,4,6-trimethylbenzoyl)-	REACH #: 01-2119489401-38 EC: 423-340-5 CAS: 162881-26-7 Index: 015-189-00-5	<1	Skin Sens. 1A, H317 Aquatic Chronic 4, H413	-	[1]
			See Section 16 for the full text of the H statements declared above.		

: 20/02/2025 Date of previous issue

: 19/12/2023

SECTION 3: Composition/information on ingredients

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

<u>Type</u>

[7] Substance classified with a health or environmental hazard

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid n	neasures
Eye contact	: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Skin contact	: Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	: Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

Over-exposure signs/symptoms

Eye contact	: Adverse symptoms may include the following: pain or irritation watering redness
Inhalation	: Adverse symptoms may include the following: respiratory tract irritation coughing
Skin contact	: Adverse symptoms may include the following: irritation redness
Ingestion	: No specific data.
4.3 Indication of any im	mediate medical attention and special treatment needed

the interoducion of any initia	
Notes to physician	: Treat symptomatically. Contact poison treatment specialist immediately if large
	quantities have been ingested or inhaled.
Specific treatments	: No specific treatment.

Date of issue/Date of revision	: 20/02/2025	Date of previous issue	: 19/12/2023	Version	: 1.01

SECTION 5: Firefighting measures

SECTION 5. Fileligi	ny measures	
5.1 Extinguishing media		
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.	
Unsuitable extinguishing media	: None known.	
5.2 Special hazards arising	m the substance or mixture	
Hazards from the substance or mixture	: In a fire or if heated, a pressure increase will occur and the container may burst. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.	
Hazardous combustion products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide metal oxide/oxides	
5.3 Advice for firefighters		
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incide there is a fire. No action shall be taken involving any personal risk or without suitable training.	ənt if
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection chemical incidents.)

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	:	If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
6.2 Environmental precautions	:	Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.
6.3 Methods and material for	со	ntainment and cleaning up
Small spill	:	Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	:	Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spill product. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.
6.4 Reference to other sections	:	See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.
Date of issue/Date of revision		: 20/02/2025 Date of previous issue : 19/12/2023 Version : 1.01 4/18

UVILUX FILLER 1806-00 - All variants

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

Protective measures	: Fut on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapour or mist. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Seveso Directive - Reporting thresholds

Danger criteria

	Notification and MAPP threshold	Safety report threshold
₽2	200 tonnes	500 tonnes

7.3 Specific end use(s)

Recommendations

: Not available.

Industrial sector specific solutions

: Not available.

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

8.1 Control parameters

Occupational exposure limits

Product/ingredient name		Exposure limit values
No exposure limit value known.		
Biological exposure indices		
Product/ingredient r	name	Exposure indices
No exposure indices known.		
Recommended monitoring : procedures	European Stand assessment of e values and mea atmospheres - C of exposure to c (Workplace atm for the measure	Id be made to monitoring standards, such as the following: dard EN 689 (Workplace atmospheres - Guidance for the exposure by inhalation to chemical agents for comparison with limit isurement strategy) European Standard EN 14042 (Workplace Guide for the application and use of procedures for the assessment chemical and biological agents) European Standard EN 482 tospheres - General requirements for the performance of procedures ment of chemical agents) Reference to national guidance nethods for the determination of hazardous substances will also be

Date of issue/Date of revision	: 20/02/2025	Date of previous issue	: 19/12/2023	Version :1	.01 5/18
UVILUX FILLER 1806-00 - All v	variants			Label No :10	0497

SECTION 8: Exposure controls/personal protection

DNELs/DMELs

Product/ingredient name

-methyl-1,2-ethanediyl)bis[oxy(methyl-2,1-ethanediyl)] diacrylate

2-hydroxy-2-methylpropiophenone

Result

DNEL - Workers - Long term - Dermal 1.7 mg/kg bw/day <u>Effects</u>: Systemic

DNEL - Workers - Long term - Inhalation 2.35 mg/m³ Effects: Systemic

DNEL - General population - Long term - Oral 0.4 mg/kg bw/day <u>Effects</u>: Systemic

DNEL - General population - Long term - Dermal 0.5 mg/kg bw/day <u>Effects</u>: Systemic

DNEL - General population - Long term - Inhalation 0.9 mg/m³ Effects: Systemic

DNEL - Workers - Long term - Dermal 1 mg/kg bw/day <u>Effects</u>: Systemic

DNEL - Workers - Long term - Inhalation 3.5 mg/m³ Effects: Systemic

DNEL - Workers - Long term - Inhalation 21 mg/m³ <u>Effects</u>: Systemic

DNEL - Workers - Short term - Inhalation 21 mg/m³ <u>Effects</u>: Systemic

DNEL - Workers - Long term - Dermal 3.3 mg/kg <u>Effects</u>: Systemic

DNEL - Workers - Short term - Dermal 3.3 mg/kg Effects: Systemic

DNEL - General population - Consumers - Long term -Inhalation 5.2 mg/m³ Effects: Systemic

DNEL - General population - Consumers - Long term -Dermal 1.5 mg/kg <u>Effects</u>: Systemic

DNEL - General population - Consumers - Long term - Oral 1.5 mg/kg <u>Effects</u>: Systemic

DNEL - General population - Short term - Oral 1.67 ng/kg bw/day <u>Effects</u>: Systemic

DNEL - General population - Long term - Oral

Date of issue/Date of revision: 20/02/2025Date of previous issue: 19/12/2023Version: 1.016/18UVILUX FILLER 1806-00 - All variantsLabel No : 100497

Phosphine oxide, phenylbis (2,4,6-trimethylbenzoyl)-

SECTION 8: Exposure controls/personal protection

1.5 mg/kg bw/day Effects: Systemic

DNEL - General population - Long term - Dermal 1.5 mg/kg bw/day <u>Effects</u>: Systemic

DNEL - General population - Short term - Dermal 1.67 mg/kg bw/day <u>Effects</u>: Systemic

DNEL - General population - Short term - Inhalation 1.93 mg/m³ <u>Effects</u>: Systemic

DNEL - General population - Long term - Inhalation 1.93 mg/m³ Effects: Systemic

DNEL - Workers - Long term - Dermal 3 mg/kg bw/day <u>Effects</u>: Systemic

DNEL - Workers - Short term - Dermal 3.33 mg/kg bw/day <u>Effects</u>: Systemic

DNEL - Workers - Short term - Inhalation 7.84 mg/m³ <u>Effects</u>: Systemic

DNEL - Workers - Long term - Inhalation 7.84 mg/m³ <u>Effects</u>: Systemic

PNECs

Not available.

8.2 Exposure controls	
Appropriate engineering controls	: Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapour or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.
Individual protection measur	<u>es</u>
Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.
Skin protection	

: 20/02/2025 Date of previous issue

SECTION 8: Exposure controls/personal protection

p	-	
Hand protection	:	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
		Recommendations : Wear suitable gloves tested to EN374.
		< 1 hour (breakthrough time): Nitrile gloves. thickness > 0.3 mm
		1 - 4 hours (breakthrough time): 4H / Silver Shield® gloves.
Body protection	:	Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	:	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	:	Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.
		Filter type: A
		Filter type (spray application): A P
Environmental exposure controls	:	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

Appearance	
Physical state	: Liquid.
Colour	: Various
Odour	: Slight
Odour threshold	: Not available.
Melting point/freezing point	: Not available.
Initial boiling point and boiling range	:

Ingredient name		°C	°F	Method	
-methyl-1,2-ethanediyl)bis[oxy(methyl- 2,1-ethanediyl)] diacrylate		>120	>248		
(5-ethyl-1,3-dioxan-5-yl)methyl acrylate		>200	>392		
Flammability	: Not ava	ilable.			
Lower and upper explosion imit		Not applicabl Not applicabl			
Flash point	: Closed cup: >100°C (>212°F)				
Auto-ignition temperature	:				
Ingredient name		°C	°F	Method	
Fethyl-1,3-dioxan-5-yl)methyl acrylate		245	473		
Decomposition temperature	: Not ava	ilable.	Į		
н	: Not app	licable.			
/iscosity	: Not ava	ilable.			
te of issue/Date of revision	: 20/02/2025	Date of prev	ious issue ::	9/12/2023 Version	: 1.01 8/18

UVILUX FILLER 1806-00 - All variants

SECTION 9: Physical and chemical properties

÷.

ŝ,

Not available.

Solubility in water : Not available.

Partition coefficient: n-octanol/ : Not applicable.

water

Vapour pressure

	Vapour Pressure at 20°C			Vapour pressure at 50°C			
Ingredient name	mm Hg	kPa	Method	mm Hg	kPa	Method	
	0.0045	0.0006					
2-hydroxy-2-methylpropiophenone	0.00428	0.00057	OECD 104	0.09751	0.013	OECD 104	
Relative density	: Not a	vailable.	ł		•		
Density	: 1.4 g	/cm³					
Vapour density	: Not a	available.					

vapour density	 Not availa
Particle characteristics	

Median particle size	: Not applicable.
----------------------	-------------------

9.2 Other information

9.2.1 Information with regard to physical hazard classesExplosive properties: Not available.

Oxidising properties : Not available.

9.2.2 Other safety characteristics

Not applicable.

SECTION 10: Stability and reactivity

10.1 Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	: The product is stable.
10.3 Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
10.4 Conditions to avoid	: No specific data.
10.5 Incompatible materials	: No specific data.
10.6 Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined	d in Regulation (EC) No 1272/2008
Acute toxicity	
Product/ingredient name	Result
M-methyl-1,2-ethanediyl)bis[oxy(methyl- 2,1-ethanediyl)] diacrylate	Rat - Oral - LD50 6200 mg/kg <u>Toxic effects</u> : Eye - Ptosis Lung, Thorax, or Respiration - Respiratory depression Other - Hair
2-hydroxy-2-methylpropiophenone	Rat - Oral - LD50 1694 mg/kg <u>Toxic effects</u> : Behavioral - Somnolence (general depressed activity) Behavioral - Tremor Liver - Other changes

Date of issue/Date of revision : 20 UVILUX FILLER 1806-00 - All variants

: 20/02/2025 Date of previous issue

:19/12/2023

Version : 1.01 9/18 Label No : 100497

SECTION 11: Toxicological information

Rat - Dermal - LD50 6929 mg/kg

Phosphine oxide, phenylbis (2,4,6-trimethylbenzoyl)-

Rat - Oral - LD50 >2000 mg/kg OECD [Acute Oral Toxicity]

Conclusion/Summary [Product] : Not available.

Acute toxicity estimates

(mg/kg)	(gases) (ppm)	(vapours) (mg/l)	(dusts and mists) (mg/l)
) N/A N/A	N/A N/A	N/A N/A	N/A N/A N/A
1		N/A N/A	N/A N/A N/A

Skin corrosion/irritation

Product/ingredient name

-methyl-1,2-ethanediyl)bis[oxy(methyl-2,1-ethanediyl)] diacrylate

Result

Rabbit - Skin - Moderate irritant Amount/concentration applied: 500 mg

Conclusion/Summary [Product] : Not available.

Serious eye damage/eye irritation

Product/ingredient name -methyl-1,2-ethanediyl)bis[oxy(methyl-2,1-ethanediyl)] diacrylate

Result

Rabbit - Eyes - Severe irritant Duration of treatment/exposure: 24 hours Amount/concentration applied: 100 uL

Conclusion/Summary [Product] : Not available.

Respiratory corrosion/irritation

Not available.

Conclusion/Summary [Product] : Not available.

Respiratory or skin sensitization

Product/ingredient name

hosphine oxide, phenylbis (2,4,6-trimethylbenzoyl)-

Skin

Conclusion/Summary [Product] : Not available.

Respiratory Conclusion/Summary [Product] : Not available.

Germ cell mutagenicity

Product/ingredient name

Phosphine oxide, phenylbis (2,4,6-trimethylbenzoyl)-

Result

Result

Guinea pig - skin

Result: Sensitising

OECD [Skin Sensitization]

Bacteria <u>Result</u>: Negative

Date of issue/Date of revision: 20/02/2025Date of previous issueUVILUX FILLER 1806-00 - All variants

: 19/12/2023

SECTION 11: Toxicological information

Conclusion/Summary [Product] : Not available.

Carcinogenicity

Not available.

Conclusion/Summary [Product] : Not available. Ingredient name

Phosphine oxide, phenylbis (2,4,6-trimethylbenzoyl)-

Conclusion/Summary No results available.

Result

Reproductive toxicity

Not available.

Conclusion/Summary [Product] : Not available.

Specific target organ toxicity (single exposure)

Product/ingredient name

-methyl-1,2-ethanediyl)bis[oxy(methyl-2,1-ethanediyl)] diacrylate

STOT SE 3, H335 (Respiratory tract irritation)

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard		
Not available.		
Information on likely routes	exposure	
Not available.		
Potential acute health effect		
Eye contact	Causes serious eye irritation.	
Inhalation	May cause respiratory irritation.	
Skin contact	Causes skin irritation. May cause an allergic skin re	eaction.
Ingestion	No known significant effects or critical hazards.	
Symptoms related to the ph	ical, chemical and toxicological characteristics	
Eye contact	Adverse symptoms may include the following: pain or irritation watering redness	
Inhalation	Adverse symptoms may include the following: respiratory tract irritation coughing	
Skin contact	Adverse symptoms may include the following: irritation redness	
Ingestion	No specific data.	
Delayed and immediate effe	as well as chronic effects from short and long-te	<u>exposure</u>
Short term exposure		
Potential immediate effects	Not available.	
Potential delayed effects	Not available.	
Long term exposure		
Potential immediate effects	Not available.	
Potential delayed effects	Not available.	
Date of issue/Date of revision	: 20/02/2025 Date of previous issue : 19/12/2023	Version : 1.01 11/18
JVILUX FILLER 1806-00 - All	iants	Label No :100497

SECTION 11: Toxicological information

Potential chronic health effects

Not available.

Conclusion/Summary [Product] : Not available.

General	: Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
Carcinogenicity	: 📈 known significant effects or critical hazards.
Mutagenicity	: No known significant effects or critical hazards.
Reproductive toxicity	: No known significant effects or critical hazards.

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

Not available.

Conclusion/Summary [Product] : The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

11.2.2 Other information

Not available.

SECTION 12: Ecological information

12.1 Toxicity

Product/ingredient name Phosphine oxide, phenylbis (2,4,6-trimethylbenzoyl)-

Result

Acute - LC50 OECD [Fish, Acute Toxicity Test] Fish - Brachydanio rerio >0.09 mg/l [96 hours]

Acute - EC50

Daphnia sp. Acute Immobilization Test and Reproduction Test Daphnia - Daphnia magna >1.175 mg/l [48 hours]

EC50

Alga, Growth Inhibition Test Aquatic plants - Desmodesmus subspicatus ≥0.26 mg/l [72 hours]

NOEC - Fresh water

OECD [Daphnia Magna Reproduction Test] Daphnia - Daphnia magna ≥0.008 mg/l [21 days]

Conclusion/Summary [Product] : Not available.

12.2 Persistence and degradability

Not available.

Conclusion/Summary [Product] : Not available.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
Phosphine oxide, phenylbis (2,4,6-trimethylbenzoyl)-	-	-	Not readily

12.3 Bioaccumulative potential

SECTION 12: Ecological information						
Product/ingredient name LogPow BCF Potential						
-methyl-1,2-ethanediyl)bis [oxy(methyl-2,1-ethanediyl)] diacrylate	2	-	Low			
2-hydroxy- 2-methylpropiophenone	1.62	-	Low			
Phosphine oxide, phenylbis (2,4,6-trimethylbenzoyl)-	5.77	<5	Low			

12.4 Mobility in soil

Soil/water partition coefficient

Product/ingredient name	logKoc	Кос
-methyl-1,2-ethanediyl)bis[oxy(methyl- 2,1-ethanediyl)] diacrylate	2.9	803.136
(5-ethyl-1,3-dioxan-5-yl)methyl acrylate 2-hydroxy-2-methylpropiophenone	2.01 1.91	102.086 80.7076
Phosphine oxide, phenylbis (2,4,6-trimethylbenzoyl)-	5.04	108908

Results of PMT and vPvM assessment

Product/ingredient name	РМТ	Р	М	Т	vPvM	vP	vM
-methyl-1,2-ethanediyl)bis [oxy(methyl-2,1-ethanediyl)] diacrylate	No	No	No	No	No	No	No
Ethanol, 2-amino-, reaction products with polyethylene- polypropylene glycol ether with trimethylolpropane (3:1) acrylate	No	No	No	No	No	No	No
(5-ethyl-1,3-dioxan-5-yl) methyl acrylate	No	No	No	No	No	No	No
2-hydroxy- 2-methylpropiophenone	No	No	No	No	No	No	No
Phosphine oxide, phenylbis (2,4,6-trimethylbenzoyl)-	No	No	No	No	No	No	No

Mobility

: Not available.

: The product does not meet the criteria to be considered as a PMT or vPvM.

12.5 Results of PBT and vPvB assessment

Conclusion/Summary

Regulation (EC) No. 1907/2006 [REACH]

Product/ingredient name	PBT	Р	В	Т	vPvB	vP	vB
-methyl-1,2-ethanediyl)bis [oxy(methyl-2,1-ethanediyl)] diacrylate	No	No	No	No	No	No	No
Ethanol, 2-amino-, reaction products with polyethylene- polypropylene glycol ether with trimethylolpropane (3:1) acrylate	No	No	No	No	No	No	No
(5-ethyl-1,3-dioxan-5-yl) methyl acrylate	No	No	No	No	No	No	No
2-hydroxy- 2-methylpropiophenone	No	No	No	No	No	No	No
Phosphine oxide, phenylbis (2,4,6-trimethylbenzoyl)-	No	No	No	No	No	No	No

Regulation (EC) No. 1272/2008 [CLP]

: 20/02/2025 Date of previous issue

: 19/12/2023

SECTION 12: Ecological information

Product/ingredient name	PBT	Ρ	В	т	vPvB	vP	vB
-methyl-1,2-ethanediyl)bis [oxy(methyl-2,1-ethanediyl)] diacrylate	No	No	No	No	No	No	No
Ethanol, 2-amino-, reaction products with polyethylene- polypropylene glycol ether with trimethylolpropane (3:1) acrylate	No	No	No	No	No	No	No
(5-ethyl-1,3-dioxan-5-yl) methyl acrylate	No	No	No	No	No	No	No
2-hydroxy- 2-methylpropiophenone	No	No	No	No	No	No	No
Phosphine oxide, phenylbis (2,4,6-trimethylbenzoyl)-	No	No	No	No	No	No	No

Conclusion/Summary Regulation (EC) No. 1272/2008 [CLP] : The product does not meet the criteria to be considered as a PBT or vPvB.

12.6 Endocrine disrupting properties

Not available.

```
Conclusion/Summary [Product]
```

: The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product	
Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
European waste catalogue (EWC)	: 08.01.11
Packaging	
Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.
Special precautions	: This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

	ADR/RID	ADN	IMDG	IATA
14.1 UN number or ID number	UN3082	UN3082	V N3082	₩N3082
14.2 UN proper shipping name	ENVIRONMENT HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (PAINT)	ALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (PAINT)	LY ENVIRONMENTALL HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (PAINT)	Y NVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (PAINT)
14.3 Transport hazard class(es)	9	9		
14.4 Packing group	111	111	W	W
14.5 Environmental hazards	Yes.	Yes.	Y es.	Y es.
Additional informa	tion	•		
ADR/RID	or ≤{ and	product is not regulated as 5 kg, provided the packagir 4.1.1.4 to 4.1.1.8. <u>nel code</u> (-)		transported in sizes of ≤5 L sions of 4.1.1.1, 4.1.1.2
ADN	or ≤	product is not regulated as 5 kg, provided the packagir 4.1.1.4 to 4.1.1.8.		transported in sizes of ≤5 L sions of 4.1.1.1, 4.1.1.2
IMDG	or ≤	product is not regulated as 5 kg, provided the packagir 4.1.1.4 to 4.1.1.8.		transported in sizes of ≤5 L sions of 4.1.1.1, 4.1.1.2
ΙΑΤΑ	or ≤	product is not regulated as 5 kg, provided the packagir 2.6.1.1 and 5.0.2.8.		transported in sizes of ≤5 L sions of 5.0.2.4.1,
14.6 Special precau user	uprię	sport within user's prem wht and secure. Ensure that event of an accident or spill	t persons transporting the	closed containers that are product know what to do in
14.7 Maritime trans bulk according to I instruments		relevant/applicable due to r	nature of the product.	

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture <u>EU Regulation (EC) No. 1907/2006 (REACH)</u>

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Product/ingredient name	%	Designation [Usage]
VILUX FILLER 1806-00	≥90	3

Date of issue/Date of revision

UVILUX FILLER 1806-00 - All variants

:19/12/2023

SECTION 15: Regulatory information

SECTION 15. Regula	tory information
Labelling	: 🖊
Other EU regulations	
Industrial emissions (integrated pollution prevention and control) - Air	: Not listed
Industrial emissions (integrated pollution prevention and control) - Water	: Not listed
Explosive precursors	: Not applicable.
Ozone depleting substanc	<u>es (EU 2024/590)</u>
Not listed.	
Prior Informed Consent (P Not listed.	<u>IC) (649/2012/EU)</u>
Persistent Organic Polluta Not listed.	<u>nts</u>
Seveso Directive	
This product is controlled un	der the Seveso Directive.

Danger criteria

Category

E2

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

15.2 Chemical safety	This product contains substances for which Chemical Safety Assessments are still
assessment	required.

SECTION 16: Other information

Indicates informatic	on that has changed from previously issued version.
Abbreviations and acronyms	 ATE = Acute Toxicity Estimate CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008] DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level EUH statement = CLP-specific Hazard statement N/A = Not available PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration RRN = REACH Registration Number
	vPvB = Very Persistent and Very Bioaccumulative
	SGG = Segregation Group

Date of issue/Date of revision	: 20/02/2025	Date of previous issue	: 19/12/2023	Ve
UVILUX FILLER 1806-00 - All vari	ants			Lab

Procedure used to der	ive the classification according to Re	egulation (EC) No. 1272/2008 [CLP/GHS
Classification		Justification
Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 STOT SE 3, H335 Aquatic Chronic 2, H411		Calculation method Calculation method Calculation method Calculation method Calculation method
ull text of abbreviate	d H statements	
H315 Caus H317 May o H319 Caus H335 May o H411 Toxic H412 Harm	ful if swallowed. es skin irritation. cause an allergic skin reaction. es serious eye irritation. cause respiratory irritation. to aquatic life with long lasting effects. ful to aquatic life with long lasting effect cause long lasting harmful effects to aqu	
ull text of classificati	ons [CLP/GHS]	
Acute Tox. 4 Aquatic Chronic 2 Aquatic Chronic 3 Aquatic Chronic 4 Eye Irrit. 2 Skin Irrit. 2 Skin Sens. 1 Skin Sens. 1A Skin Sens. 1B STOT SE 3	ACUTE TOXICITY - Category 4 LONG-TERM (CHRONIC) AQUATIC H LONG-TERM (CHRONIC) AQUATIC H LONG-TERM (CHRONIC) AQUATIC H SERIOUS EYE DAMAGE/EYE IRRITA SKIN CORROSION/IRRITATION - Cat SKIN SENSITISATION - Category 1 SKIN SENSITISATION - Category 1A SKIN SENSITISATION - Category 1B SPECIFIC TARGET ORGAN TOXICIT	IAZARD - Category 3 IAZARD - Category 4 TION - Category 2 egory 2
Date of issue/ Date of revision	: 20/02/2025	
Date of previous issue	: 19/12/2023	
Version	: 1.01	

Notice to reader

The information in this SDS is based on the present state of our knowledge and on current laws. The product is not to be used for purposes other than those specified under section 1 without first obtaining written handling instructions. It is always the responsibility of the user to take all necessary steps to fulfil the demands set out in the local rules and legislation. The information in this SDS is meant to be a description of the safety requirements for our product. It is not to be considered a guarantee of the product's properties.

: 20/02/2025 Date of previous issue

Date of issue/Date of revision : 20. UVILUX FILLER 1806-00 - All variants

: 20/02/2025 Date of previous issue