# SAFETY DATA SHEET



WOODEX AQUA WOOD OIL - GREY

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : WOODEX AQUA WOOD OIL - GREY

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Paint.

1.3 Details of the supplier of the safety data sheet

Teknos Group Oy, Takkatie 3, FI-00370 HELSINKI, FINLAND. Tel. +358 9 506 091.

e-mail address of person responsible for this SDS

: Prod-safe@teknos.com

**National contact** 

Teknos Group Oy, Takkatie 3, FI-00370 HELSINKI, FINLAND. Tel. +358 9 506 091.

1.4 Emergency telephone number

**National advisory body/Poison Centre** 

Telephone number : In an emergency, call 112

#### **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

**Product definition**: Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Aquatic Chronic 3, H412

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Signal word : No signal word.

**Hazard statements** : H412 - Harmful to aquatic life with long lasting effects.

**Precautionary statements** 

**Prevention**: P273 - Avoid release to the environment.

Response : Not applicable.

Storage : Not applicable.

Disposal : P501 - Dispose of contents and container in accordance with all local, regional,

national and international regulations.

Supplemental label

elements

: Contains 3-iodo-2-propynyl-butyl carbamate, 1,2-benzisothiazol-3(2H)-one and reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1). May produce an allergic reaction. Contains biocidal products for dry film and in-can preservation: IPBC and EGForm and C(M)IT/MIT (3:1). Risk of skin sensitisation.

Label No: 96283

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Date of issue/Date of revision : 14/03/2025 Date of previous issue : 14/11/2023 Version : 7 1/22

# **SECTION 2: Hazards identification**

#### 2.3 Other hazards

**Product meets the criteria** for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII

: This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

Other hazards which do not result in classification : None known.

# **SECTION 3: Composition/information on ingredients**

3.2 Mixtures : Mixture

3.2 Mixtures	: Mixture				
Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Туре
Manium dioxide	REACH #: 01-2119489379-17 EC: 236-675-5 CAS: 13463-67-7	≤1	Carc. 2, H351 (inhalation)	-	[1] [*]
(Z)-9-Octadecen-1-ol ethoxylated	EC: 500-016-2 CAS: 9004-98-2	≤0.3	Skin Irrit. 2, H315 Aquatic Acute 1, H400	M [Acute] = 1	[1]
3-iodo-2-propynyl-butyl carbamate	EC: 259-627-5 CAS: 55406-53-6 Index: 616-212-00-7	≤0.3	Acute Tox. 4, H302 Acute Tox. 3, H331 Eye Dam. 1, H318 Skin Sens. 1, H317 STOT RE 1, H372 (larynx) Aquatic Acute 1, H400 Aquatic Chronic 1, H410	ATE [Oral] = 400 mg/kg ATE [Inhalation (dusts and mists)] = 0.67 mg/l M [Acute] = 10 M [Chronic] = 1	[1]
1,2-benzisothiazol-3(2H)- one	EC: 220-120-9 CAS: 2634-33-5 Index: 613-088-00-6	<0.036	Acute Tox. 4, H302 Acute Tox. 2, H330 Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410	ATE [Oral] = 450 mg/kg ATE [Inhalation (dusts and mists)] = 0.21 mg/l Skin Sens. 1, H317: C ≥ 0.036% M [Acute] = 1 M [Chronic] = 1	[1]
reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	EC: 911-418-6 CAS: 55965-84-9 Index: 613-167-00-5	<0.0015	Acute Tox. 3, H301 Acute Tox. 2, H310 Acute Tox. 2, H330 Skin Corr. 1C, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 EUH071	ATE [Oral] = 53 mg/kg ATE [Dermal] = 50 mg/kg ATE [Inhalation (vapours)] = 0.5 mg/l Skin Corr. 1C, H314: $C \ge 0.6\%$ Eye Dam. 1, H318: $C \ge 0.6\%$ Eye Irrit. 2, H319: $0.06\% \le C < 0.6\%$ Skin Sens. 1, H317: $C \ge 0.0015\%$ M [Acute] = 100 M [Chronic] = 100	[1]
			See Section 16 for the full text of the H statements declared above.	[225]	

Version :7 Date of issue/Date of revision : 14/03/2025 Date of previous issue : 14/11/2023 2/22 Label No : 96283

# SECTION 3: Composition/information on ingredients

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

- [1] Substance classified with a health or environmental hazard
- [\*] The classification as a carcinogen by inhalation applies only to mixtures placed on the market in powder form containing 1% or more of titanium dioxide particles with aerodynamic diameter ≤ 10 µm not bound within a matrix.

Occupational exposure limits, if available, are listed in Section 8.

#### **SECTION 4: First aid measures**

#### 4.1 Description of first aid measures

Eye contact : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower

eyelids. Check for and remove any contact lenses. Get medical attention if irritation

occurs.

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing.

Skin contact Flush contaminated skin with plenty of water. Remove contaminated clothing and

shoes. Get medical attention if symptoms occur.

Ingestion : Wash out mouth with water. If material has been swallowed and the exposed

person is conscious, give small quantities of water to drink. Do not induce vomiting

unless directed to do so by medical personnel.

**Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training.

#### 4.2 Most important symptoms and effects, both acute and delayed

#### Over-exposure signs/symptoms

: No specific data. Eye contact Inhalation : No specific data. Skin contact : No specific data. : No specific data. Ingestion

#### 4.3 Indication of any immediate medical attention and special treatment needed

: Treat symptomatically. Contact poison treatment specialist immediately if large Notes to physician

quantities have been ingested or inhaled.

: No specific treatment. **Specific treatments** 

# **SECTION 5: Firefighting measures**

#### 5.1 Extinguishing media

Suitable extinguishing

media

: Use an extinguishing agent suitable for the surrounding fire.

Unsuitable extinguishing

media

: None known.

#### 5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture : In a fire or if heated, a pressure increase will occur and the container may burst. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

**Hazardous combustion** products

: Decomposition products may include the following materials: carbon dioxide

carbon monoxide

#### 5.3 Advice for firefighters

**Special protective actions** 

for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Date of issue/Date of revision : 14/03/2025 : 14/11/2023 Version :7 3/22 Date of previous issue

WOODEX AQUA WOOD OIL - GREY

Label No: 96283

# SECTION 5: Firefighting measures

#### Special protective equipment for fire-fighters

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

# **SECTION 6: Accidental release measures**

### 6.1 Personal precautions, protective equipment and emergency procedures

#### For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Put on appropriate personal protective equipment.

For emergency responders: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

#### 6.2 Environmental precautions

: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

#### 6.3 Methods and material for containment and cleaning up

#### **Small spill**

: Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

#### Large spill

Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

#### 6.4 Reference to other sections

: See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

# SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

#### 7.1 Precautions for safe handling

#### **Protective measures**

: Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapour or mist. Avoid release to the environment. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Risk of self-ignition of used cleaning rags, paper wipes etc. Contaminated materials should be soaked in water and placed in a closed metal container before disposal.

#### Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

### 7.2 Conditions for safe storage, including any incompatibilities

Date of issue/Date of revision : 14/03/2025 · 14/11/2023 Version: 7 4/22 Date of previous issue Label No: 96283

# **SECTION 7: Handling and storage**

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

#### 7.3 Specific end use(s)

Recommendations : Not available.

Industrial sector specific : Not available.

solutions

# **SECTION 8: Exposure controls/personal protection**

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

#### 8.1 Control parameters

#### **Occupational exposure limits**

4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one (EC no. 220-239-6) (3:1)  No exposure limit value known.  No exposure limit value known.  Propylene glycol  Ordinance on the protection of workers from exposure to hazardous chemicals at work, exposure limit values (Annex (Croatia, 12/2023)  ELV 8 hours: 10 mg/m³. Form: only particles.  ELV 8 hours: 474 mg/m³. Form: total vapour and particles.  ELV 8 hours: 150 ppm. Form: total vapour and particles.  ELV 8 hours: 150 ppm. Form: total vapour and particles.  TRGS 900 OEL (Germany, 6/2024) Skin sensitiser.  PEAK 15 minutes: 0.116 mg/m³.  TWA 8 hours: 0.058 ppm.  DFG MAC-values list (Germany, 7/2023) Skin sensitiser.  DFG MAC-values list (Germany, 7/2023) Skin sensitiser.	Product/ingredient name	Exposure limit values
No exposure limit value known.  Propylene glycol  Ordinance on the protection of workers from exposure to hazardous chemicals at work, exposure limit values (Annex (Croatia, 12/2023)  ELV 8 hours: 10 mg/m³. Form: only particles. ELV 8 hours: 474 mg/m³. Form: total vapour and particles. ELV 8 hours: 150 ppm. Form: total vapour and particles. ELV 8 hours: 150 ppm. Form: total vapour and particles. ELV 8 hours: 150 ppm. Form: total vapour and particles. ELV 8 hours: 150 ppm. Form: total vapour and particles.  TRGS 900 OEL (Germany, 6/2024) Skin sensitiser. PEAK 15 minutes: 0.116 mg/m³. PEAK 15 minutes: 0.01 ppm. TWA 8 hours: 0.005 mg/m³. TWA 8 hours: 0.005 ppm.  DFG MAC-values list (Germany, 7/2023) Develop C. Skin sensitiser. PEAK 15 minutes: 0.116 mg/m³ 4 times per shift [Interval: 1 hour]. TWA 8 hours: 0.005 mg/m³.	4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no.	hydroisothiazol-3-on (Gemisch im Verhältnis 3:1)] Skin sensitiser.
Ordinance on the protection of workers from exposure to hazardous chemicals at work, exposure limit values (Annex (Croatia, 12/2023)  ELV 8 hours: 10 mg/m³. Form: only particles. ELV 8 hours: 150 ppm. Form: total vapour and particles. ELV 8 hours: 150 ppm. Form: total vapour and particles. ELV 8 hours: 150 ppm. Form: total vapour and particles.  No exposure limit value known.  TRGS 900 OEL (Germany, 6/2024) Skin sensitiser. PEAK 15 minutes: 0.016 mg/m³. TWA 8 hours: 0.058 mg/m³. TWA 8 hours: 0.005 ppm. DFG MAC-values list (Germany, 7/2023) Develop C. Skin sensitiser. PEAK 15 minutes: 0.116 mg/m³ 4 times per shift [Interval: 1 hour]. TWA 8 hours: 0.058 mg/m³. TWA 8 hours: 0.058 mg/m³. TWA 8 hours: 0.059 ppm.  1,2-benzisothiazol-3(2H)-one No exposure limit value known. No exposure limit value known. No exposure limit value known.	No exposure limit value known.	
hazardous chemicals at work, exposure limit values (Annex (Croatia, 12/2023)  ELV 8 hours: 10 mg/m³. Form: only particles. ELV 8 hours: 474 mg/m³. Form: total vapour and particles. ELV 8 hours: 150 ppm. Form: total vapour and particles. ELV 8 hours: 150 ppm. Form: total vapour and particles.  No exposure limit value known.  TRGS 900 OEL (Germany, 6/2024) Skin sensitiser. PEAK 15 minutes: 0.116 mg/m³. TWA 8 hours: 0.058 mg/m³. TWA 8 hours: 0.005 ppm.  DFG MAC-values list (Germany, 7/2023) Develop C. Skin sensitiser. PEAK 15 minutes: 0.116 mg/m³ 4 times per shift [Interval: 1 hour]. TWA 8 hours: 0.058 mg/m³. TWA 8 hours: 0.005 ppm.  DFG MAC-values list (Germany, 7/2023) Skin sensitiser.  PEAK 15 minutes: 0.010 ppm 4 times per shift [Interval: 1 hour]. TWA 8 hours: 0.005 ppm.  DFG MAC-values list (Germany, 7/2023) Skin sensitiser.  DFG MAC-values list (Germany, 7/2023) Skin sensitiser.	No exposure limit value known.	
No exposure limit value known.  Fiodo-2-propynyl-butyl carbamate  TRGS 900 OEL (Germany, 6/2024) Skin sensitiser.  PEAK 15 minutes: 0.116 mg/m³.  PEAK 15 minutes: 0.01 ppm.  TWA 8 hours: 0.058 mg/m³.  TWA 8 hours: 0.058 mg/m³.  TWA 8 hours: 0.01 ppm 4 times per shift [Interval: 1 hour].  TWA 8 hours: 0.058 mg/m³.  TWA 8 hours: 0.01 ppm 4 times per shift [Interval: 1 hour].  TWA 8 hours: 0.058 mg/m³.  TWA 8 hours: 0.058 mg/m³.  TWA 8 hours: 0.059 ppm.  DFG MAC-values list (Germany, 7/2023) Skin sensitiser.  PEAK 15 minutes: 0.116 mg/m³ 4 times per shift [Interval: 1 hour].  TWA 8 hours: 0.058 mg/m³.  TWA 8 hours: 0.058 mg/m³.  TWA 8 hours: 0.005 ppm.  DFG MAC-values list (Germany, 7/2023) Skin sensitiser.  PFG MAC-values list (Germany, 7/2023) Skin sensitiser.	Propylene glycol	hazardous chemicals at work, exposure limit values (Annex I) (Croatia, 12/2023)  ELV 8 hours: 10 mg/m³. Form: only particles.  ELV 8 hours: 474 mg/m³. Form: total vapour and particles.
No exposure limit value known.  **Track to minutes: 0.116 mg/m³.  PEAK 15 minutes: 0.01 ppm.  TWA 8 hours: 0.058 mg/m³.  TWA 8 hours: 0.059 ppm.  **DFG MAC-values list (Germany, 7/2023) Develop C. Skin sensitiser.  PEAK 15 minutes: 0.116 mg/m³ 4 times per shift [Interval: 1 hour].  TWA 8 hours: 0.058 mg/m³.  TWA 8 hours: 0.058 mg/m³.  TWA 8 hours: 0.058 mg/m³.  TWA 8 hours: 0.059 ppm.  1,2-benzisothiazol-3(2H)-one No exposure limit value known.  No exposure limit value known.	No exposure limit value known.	
No exposure limit value known.  Fiodo-2-propynyl-butyl carbamate  TRGS 900 OEL (Germany, 6/2024) Skin sensitiser.  PEAK 15 minutes: 0.116 mg/m³.  PEAK 15 minutes: 0.01 ppm.  TWA 8 hours: 0.058 mg/m³.  TWA 8 hours: 0.005 ppm.  DFG MAC-values list (Germany, 7/2023) Develop C. Skin sensitiser.  PEAK 15 minutes: 0.116 mg/m³ 4 times per shift [Interval: 1 hourgeness per shift [Interval: 1	No exposure limit value known.	
No exposure limit value known.  No exposure limit value known.  No exposure limit value known.  TRGS 900 OEL (Germany, 6/2024) Skin sensitiser.  PEAK 15 minutes: 0.116 mg/m³.  PEAK 15 minutes: 0.01 ppm.  TWA 8 hours: 0.058 mg/m³.  TWA 8 hours: 0.005 ppm.  DFG MAC-values list (Germany, 7/2023) Develop C. Skin sensitiser.  PEAK 15 minutes: 0.116 mg/m³ 4 times per shift [Interval: 1 hour peak 15 minutes: 0.01 ppm 4 times per shift [Interval: 1 hour].  TWA 8 hours: 0.058 mg/m³.  TWA 8 hours: 0.058 mg/m³.  TWA 8 hours: 0.058 mg/m³.  TWA 8 hours: 0.059 ppm.  1,2-benzisothiazol-3(2H)-one  No exposure limit value known.  No exposure limit value known.	No exposure limit value known.	
No exposure limit value known.  8-iodo-2-propynyl-butyl carbamate  TRGS 900 OEL (Germany, 6/2024) Skin sensitiser.  PEAK 15 minutes: 0.116 mg/m³.  PEAK 15 minutes: 0.01 ppm.  TWA 8 hours: 0.058 mg/m³.  TWA 8 hours: 0.005 ppm.  DFG MAC-values list (Germany, 7/2023) Develop C. Skin sensitiser.  PEAK 15 minutes: 0.116 mg/m³ 4 times per shift [Interval: 1 hour].  TWA 8 hours: 0.058 mg/m³.  TWA 8 hours: 0.058 mg/m³.  TWA 8 hours: 0.058 mg/m³.  TWA 8 hours: 0.059 ppm.  1,2-benzisothiazol-3(2H)-one  No exposure limit value known.  No exposure limit value known.	No exposure limit value known.	
No exposure limit value known.  TRGS 900 OEL (Germany, 6/2024) Skin sensitiser.  PEAK 15 minutes: 0.116 mg/m³.  PEAK 15 minutes: 0.01 ppm.  TWA 8 hours: 0.005 ppm.  DFG MAC-values list (Germany, 7/2023) Develop C. Skin sensitiser.  PEAK 15 minutes: 0.116 mg/m³ 4 times per shift [Interval: 1 hourgeness per shift sensitiser.  PEAK 15 minutes: 0.116 mg/m³ 4 times per shift [Interval: 1 hourgeness per shift sensitiser.  PEAK 15 minutes: 0.01 ppm 4 times per shift [Interval: 1 hourgeness per shift sensitiser.  TWA 8 hours: 0.058 mg/m³.  TWA 8 hours: 0.005 ppm.  1,2-benzisothiazol-3(2H)-one  No exposure limit value known.  DFG MAC-values list (Germany, 7/2023) Skin sensitiser.	No exposure limit value known.	
TRGS 900 OEL (Germany, 6/2024) Skin sensitiser.  PEAK 15 minutes: 0.116 mg/m³.  PEAK 15 minutes: 0.001 ppm.  TWA 8 hours: 0.058 mg/m³.  TWA 8 hours: 0.005 ppm.  DFG MAC-values list (Germany, 7/2023) Develop C. Skin sensitiser.  PEAK 15 minutes: 0.116 mg/m³ 4 times per shift [Interval: 1 hour].  TWA 8 hours: 0.01 ppm 4 times per shift [Interval: 1 hour].  TWA 8 hours: 0.058 mg/m³.  TWA 8 hours: 0.058 mg/m³.  TWA 8 hours: 0.005 ppm.  1,2-benzisothiazol-3(2H)-one  No exposure limit value known.  DFG MAC-values list (Germany, 7/2023) Skin sensitiser.	No exposure limit value known.	
PEAK 15 minutes: 0.116 mg/m³. PEAK 15 minutes: 0.01 ppm. TWA 8 hours: 0.058 mg/m³. TWA 8 hours: 0.005 ppm.  DFG MAC-values list (Germany, 7/2023) Develop C. Skin sensitiser. PEAK 15 minutes: 0.116 mg/m³ 4 times per shift [Interval: 1 hour]. TWA 8 hours: 0.01 ppm 4 times per shift [Interval: 1 hour]. TWA 8 hours: 0.058 mg/m³. TWA 8 hours: 0.005 ppm.  1,2-benzisothiazol-3(2H)-one No exposure limit value known.  DFG MAC-values list (Germany, 7/2023) Skin sensitiser.  DFG MAC-values list (Germany, 7/2023) Skin sensitiser.	No exposure limit value known.	
No exposure limit value known.  No exposure limit value known.	<b>3</b> -iodo-2-propynyl-butyl carbamate	PEAK 15 minutes: 0.116 mg/m³. PEAK 15 minutes: 0.01 ppm. TWA 8 hours: 0.058 mg/m³. TWA 8 hours: 0.005 ppm.  DFG MAC-values list (Germany, 7/2023) Develop C. Skin sensitiser. PEAK 15 minutes: 0.116 mg/m³ 4 times per shift [Interval: 1 hour]. PEAK 15 minutes: 0.01 ppm 4 times per shift [Interval: 1 hour]. TWA 8 hours: 0.058 mg/m³.
No exposure limit value known.	1,2-benzisothiazol-3(2H)-one	DFG MAC-values list (Germany, 7/2023) Skin sensitiser.
	No exposure limit value known.	
No exposure limit value known.	No exposure limit value known.	
	No exposure limit value known.	

Date of issue/Date of revision: 14/03/2025Date of previous issue: 14/11/2023Version: 75/22WOODEX AQUA WOOD OIL - GREYLabel No : 96283

# **SECTION 8: Exposure controls/personal protection** Propylene glycol Limit Values (OELVs)

NAOSH (Ireland, 4/2024) Notes: Advisory Occupational Exposure

OELV 8 hours: 10 mg/m<sup>3</sup>. Form: particulate.

OELV 8 hours: 470 mg/m³. Form: vapour and particulates. OELV 8 hours: 150 ppm. Form: vapour and particulates.

No exposure limit value known.

Propylene glycol

Ministers Cabinet Regulations Nr.325 - AER (Latvia, 3/2024) TWA 8 hours: 7 mg/m<sup>3</sup>.

Lithuanian Hygiene Standard HN 23 (Lithuania, 1/2024) Propylene glycol

TWA 8 hours: 7 ma/m<sup>3</sup>.

TWA 8 hours: 25 ppm.

No exposure limit value known.

No exposure limit value known.

No exposure limit value known.

Propylene glycol FOR-2011-12-06-1358 (Norway, 12/2022) TWA 8 hours: 79 ma/m<sup>3</sup>.

Regulation of the Minister of Family, Labor and Social Policy of June 12, 2018 on the maximum permissible concentrations and intensities of factors harmful to health in the work environment (Journal of Laws of 2018, item 1286) (Poland,

8/2023)

TWA 8 hours: 100 mg/m<sup>3</sup>. Form: vapor and inhalable fraction.

Propylene glycol

No exposure limit value known.

No exposure limit value known.

No exposure limit value known.

3-iodo-2-propynyl-butyl carbamate

Regulation on protection of workers from the risks related to exposure to chemical substances at work (Slovenia, 4/2024)

KTV 15 minutes: 0.01 ppm 4 times per shift [time between two exposure events at this concentration must be at least 60 minutes]. TWA 8 hours: 0.005 ppm.

KTV 15 minutes: 0.116 mg/m<sup>3</sup> 4 times per shift [time between two exposure events at this concentration must be at least 60 minutes]. TWA 8 hours: 0.058 mg/m<sup>3</sup>.

No exposure limit value known.

No exposure limit value known.

3-iodo-2-propynyl-butyl carbamate

SUVA (Switzerland, 1/2024) Sensitiser.

STEL 15 minutes: 0.24 mg/m<sup>3</sup>. Form: vapour and aerosols. STEL 15 minutes: 0.02 ppm. Form: vapour and aerosols. TWA 8 hours: 0.01 ppm. Form: vapour and aerosols. TWA 8 hours: 0.12 mg/m<sup>3</sup>. Form: vapour and aerosols.

reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and

2-methyl-2H-isothiazol-3-one [EC no.

220-239-6] (3:1)

No exposure limit value known.

SUVA (Switzerland, 1/2024) Sensitiser.

STEL 15 minutes: 0.4 mg/m<sup>3</sup>. Form: Inhalable fraction. TWA 8 hours: 0.2 mg/m<sup>3</sup>. Form: Inhalable fraction.

#### **Biological exposure indices**

Product/ingredient name	Exposure indices
No exposure indices known.	

Date of issue/Date of revision : 14/03/2025 · 14/11/2023 Version :7 6/22 Date of previous issue Label No: 96283

# SECTION 8: Exposure controls/personal protection No exposure indices known. No exposure indices known.

# Recommended monitoring procedures

: Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

#### **DNELs/DMELs**

**Product/ingredient name** 

titanium dioxide

#### **Result**

DNEL - General population - Long term - Inhalation

28 μg/m³ <u>Effects</u>: Local

**DNEL - Workers - Long term - Inhalation** 

170 μg/m³ <u>Effects</u>: Local

(Z)-9-Octadecen-1-ol ethoxylated DNEL - General population - Long term - Oral

2.5 mg/kg bw/day <u>Effects</u>: Systemic

DNEL - General population - Long term - Inhalation

Label No : 96283

Date of issue/Date of revision : 14/03/2025 Date of previous issue : 14/11/2023 Version : 7 7/22

# **SECTION 8: Exposure controls/personal protection**

6.53 mg/m³
Effects: Systemic

**DNEL - Workers - Long term - Inhalation** 

37 mg/m<sup>3</sup>

Effects: Systemic

**DNEL - General population - Long term - Dermal** 

125 mg/kg bw/day Effects: Systemic

**DNEL - Workers - Long term - Dermal** 

350 mg/kg bw/day Effects: Systemic

3-iodo-2-propynyl-butyl carbamate

**DNEL - Workers - Long term - Inhalation** 

0.023 mg/m³ Effects: Systemic

**DNEL - Workers - Short term - Inhalation** 

0.07 mg/m³ Effects: Systemic

**DNEL - Workers - Short term - Inhalation** 

1.16 mg/m³ Effects: Local

**DNEL - Workers - Long term - Inhalation** 

1.16 mg/m³ Effects: Local

**DNEL - Workers - Long term - Dermal** 

2 mg/kg bw/day <u>Effects</u>: Systemic

1,2-benzisothiazol-3(2H)-one

**DNEL - General population - Long term - Dermal** 

0.345 mg/kg bw/day Effects: Systemic

**DNEL - Workers - Long term - Dermal** 

0.966 mg/kg bw/day Effects: Systemic

DNEL - General population - Long term - Inhalation

1.2 mg/m<sup>3</sup>

Effects: Systemic

**DNEL - Workers - Long term - Inhalation** 

6.81 mg/m³ Effects: Systemic

DNEL - General population - Long term - Inhalation

0.02 mg/m³ Effects: Local

**DNEL - Workers - Long term - Inhalation** 

0.02 mg/m³ Effects: Local

DNEL - General population - Short term - Inhalation

0.04 mg/m³ Effects: Local

**DNEL - Workers - Short term - Inhalation** 

0.04 mg/m<sup>3</sup>

Date of issue/Date of revision : 14/03/2025 Date of previous issue : 14/11/2023 Version : 7 8/22

WOODEX AQUA WOOD OIL - GREY

reaction mass of: 5-chloro-2-methyl-

2-methyl-2H-isothiazol-3-one [EC no.

220-239-6] (3:1)

4-isothiazolin-3-one [EC no. 247-500-7] and

Label No : 96283

# **SECTION 8: Exposure controls/personal protection**

Effects: Local

DNEL - General population - Long term - Oral

0.09 mg/kg bw/day Effects: Systemic

DNEL - General population - Short term - Oral

0.11 mg/kg bw/day Effects: Systemic

#### **PNECs**

Not available.

#### 8.2 Exposure controls

# Appropriate engineering controls

: Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

#### **Individual protection measures**

#### Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

#### **Eye/face protection**

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.

# Skin protection Hand protection

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Recommendations: Wear suitable gloves tested to EN374.

> 8 hours (breakthrough time): Nitrile gloves. thickness > 0.3 mm Not recommended polyvinyl alcohol (PVA) gloves

#### **Body protection**

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

#### Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

#### **Respiratory protection**

: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Filter type (spray application): A P

# **Environmental exposure** controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Date of issue/Date of revision : 14/03/2025 Date of previous issue : 14/11/2023 Version : 7 9/22

# **SECTION 9: Physical and chemical properties**

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

#### 9.1 Information on basic physical and chemical properties

**Appearance** 

**Physical state** : Liquid. Colour : Various **Odour** : Slight

: Not available. **Odour threshold** Melting point/freezing point : Not available.

Initial boiling point and

boiling range

Ingredient name	°C	°F	Method
water	100	212	
Propylene glycol	188.2	370.8	

**Flammability** : Not available.

Lower and upper explosion : Lower: 2.6% (propane-1,2-diol) Upper: 12.6% (propane-1,2-diol) limit

Flash point

		Closed cup			Open cup		
Ingredient name	°C	°F	Method	°C	°F	Method	
Propylene glycol	99	210.2					

#### **Auto-ignition temperature** ÷

Ingredient name	°C	°F	Method
Propylene glycol	371	699.8	

: Not available. **Decomposition temperature** 7.5 to 9 pН **Viscosity** : Not available.

Solubility(ies)

Not available.

Solubility in water : Not available. Partition coefficient: n-octanol/ : Not applicable.

water

Vapour pressure

	Va	Vapour Pressure at 20°C			Vapour pressure at 5		
Ingredient name	mm Hg	kPa	Method	mm Hg	kPa	Method	
water	17.5	2.3					
Propylene glycol	0.15	0.02	EU A.4				

**Relative density** : Not available. : 1 g/cm<sup>3</sup> **Density** Vapour density : Not available.

**Particle characteristics** 

Median particle size : Not applicable.

### 9.2 Other information

9.2.1 Information with regard to physical hazard classes

**Explosive properties** : Not available. **Oxidising properties** : Not available.

: 14/03/2025 Date of previous issue Date of issue/Date of revision : 14/11/2023 Version: 7 10/22

Label No : 96283

# SECTION 9: Physical and chemical properties

#### 9.2.2 Other safety characteristics

Not applicable.

# SECTION 10: Stability and reactivity

10.1 Reactivity : No specific test data related to reactivity available for this product or its ingredients.

10.2 Chemical stability : The product is stable.

10.3 Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will not occur.

10.4 Conditions to avoid : No specific data.

10.5 Incompatible materials : No specific data.

10.6 Hazardous decomposition products : Under normal conditions of storage and use, hazardous decomposition products

should not be produced.

# SECTION 11: Toxicological information

#### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### **Acute toxicity**

Product/ingredient name Result

3-iodo-2-propynyl-butyl carbamate Rat - Oral - LD50

400 mg/kg

Rat - Dermal - LD50

>2000 mg/kg

Rat - Inhalation - LC50 Dusts and mists

0.763 mg/l [4 hours]

Rat - Inhalation - LC50 Dusts and mists

0.67 g/m3 [4 hours]

1,2-benzisothiazol-3(2H)-one Rat - Oral - LD50

1020 mg/kg

reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)

Rat - Oral - LD50

53 mg/kg

Toxic effects: Behavioral - Somnolence (general depressed activity) Behavioral - Ataxia Lung, Thorax, or Respiration -

Respiratory depression

**Conclusion/Summary [Product]**: Not available.

#### **Acute toxicity estimates**

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
₩OODEX AQUA WOOD OIL	N/A	N/A	N/A	N/A	338.4
3-iodo-2-propynyl-butyl carbamate	400	N/A	N/A	N/A	0.67
1,2-benzisothiazol-3(2H)-one	450	N/A	N/A	N/A	0.21
reaction mass of: 5-chloro-2-methyl-4-isothiazolin-	53	50	N/A	0.5	N/A
3-one [EC no. 247-500-7] and 2-methyl-2H-					
isothiazol-3-one [EC no. 220-239-6] (3:1)					

#### Skin corrosion/irritation

Date of issue/Date of revision : 14/03/2025 : 14/11/2023 Version :7 11/22 Date of previous issue Label No: 96283

**SECTION 11: Toxicological information** 

Product/ingredient name

titanium dioxide Human - Skin - Mild irritant

> <u>Duration of treatment/exposure</u>: 72 hours Amount/concentration applied: 300 ug I

Rabbit - Skin - Moderate irritant (Z)-9-Octadecen-1-ol ethoxylated

> **Duration of treatment/exposure: 24 hours** Amount/concentration applied: 500 mg

Human - Skin - Mild irritant 1,2-benzisothiazol-3(2H)-one

> Duration of treatment/exposure: 48 hours Amount/concentration applied: 5 %

reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no.

220-239-6] (3:1)

Human - Skin - Severe irritant Amount/concentration applied: 0.01 %

**Conclusion/Summary [Product]**: Not available.

Serious eye damage/eye irritation

**Product/ingredient name** Result

(Z)-9-Octadecen-1-ol ethoxylated Rabbit - Eyes - Moderate irritant

Amount/concentration applied: 100 uL

3-iodo-2-propynyl-butyl carbamate Rabbit - Eyes - Severe irritant

**Conclusion/Summary [Product]**: Not available.

**Respiratory corrosion/irritation** 

Not available.

Conclusion/Summary [Product] : Not available.

Respiratory or skin sensitization

Product/ingredient name Result

3-iodo-2-propynyl-butyl carbamate Guinea pig - skin Result: Not sensitizing

Skin

Conclusion/Summary [Product] : Not available.

Respiratory

Conclusion/Summary [Product] : Not available.

Germ cell mutagenicity

**Product/ingredient name** Result

3-iodo-2-propynyl-butyl carbamate In vitro - Bacteria

Result: Negative

**Conclusion/Summary [Product]**: Not available.

Carcinogenicity

Not available.

**Conclusion/Summary [Product]**: Not available.

Date of issue/Date of revision : 14/03/2025 : 14/11/2023 Version: 7 12/22 Date of previous issue Label No : 96283

# **SECTION 11: Toxicological information**

**Reproductive toxicity** 

Product/ingredient name Result

50 mg/kg [7 days per week] [13 days]

Maternal toxicity: Positive Developmental: Negative

Rabbit - Female - Oral

20 mg/kg [7 days per week] [13 days]

Maternal toxicity: Negative Developmental: Negative

Conclusion/Summary [Product] : Not available.

#### Specific target organ toxicity (single exposure)

Not available.

#### Specific target organ toxicity (repeated exposure)

Product/ingredient name Result

#### **Aspiration hazard**

Not available.

#### Information on likely routes of exposure

Not available.

Potential acute health effects

Eye contact
 Inhalation
 No known significant effects or critical hazards.
 Skin contact
 No known significant effects or critical hazards.
 Ingestion
 No known significant effects or critical hazards.
 Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : No specific data.

Inhalation : No specific data.

Skin contact : No specific data.

Ingestion : No specific data.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Short term exposure** 

Potential immediate : No

effects

: Not available.

Potential delayed effects : Not available.

**Long term exposure** 

Potential immediate : Not available.

effects

Potential delayed effects: Not available.

Potential chronic health effects

Not available.

**Conclusion/Summary [Product]**: Not available.

General : No known significant effects or critical hazards.
 Carcinogenicity : No known significant effects or critical hazards.
 Mutagenicity : No known significant effects or critical hazards.
 Reproductive toxicity : No known significant effects or critical hazards.

#### 11.2 Information on other hazards

Date of issue/Date of revision : 14/03/2025 Date of previous issue : 14/11/2023 Version : 7 13/22

WOODEX AQUA WOOD OIL - GREY

**Label No** : 96283

# **SECTION 11: Toxicological information**

#### 11.2.1 Endocrine disrupting properties

Not available.

**Conclusion/Summary [Product]**: The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

#### 11.2.2 Other information

Not available.

# **SECTION 12: Ecological information**

#### 12.1 Toxicity

#### **Product/ingredient name**

titanium dioxide

#### Result

#### Acute - LC50 - Marine water

Fish - Mummichog - Fundulus heteroclitus

>1000000 µg/l [96 hours]

Effect: Mortality

#### Acute - LC50 - Fresh water

Crustaceans - Water flea - Ceriodaphnia dubia - Neonate

Age: <24 hours 3 mg/l [48 hours] Effect: Mortality

#### 3-iodo-2-propynyl-butyl carbamate

#### Acute - LC50 - Fresh water

Fish - Trout - Oncorhynchus mykiss

0.067 mg/l [96 hours]

#### Acute - NOEC - Fresh water

ΕU

Fish - Trout - Oncorhynchus mykiss

0.049 mg/l [96 hours]

#### Acute - EC50 - Fresh water

Daphnia - Daphnia - Daphnia magna

0.16 mg/l [48 hours]

#### Chronic - NOEC - Fresh water

Daphnia - Daphnia Magna

0.05 mg/l [21 days]

#### Acute - EC50 - Fresh water

Algae - Algae - Scenedemus subspicatus

0.022 mg/l [72 hours]

#### 1,2-benzisothiazol-3(2H)-one

#### Acute - LC50 - Fresh water

OECD [Fish, Acute Toxicity Test] Fish - Trout - Onorhynchus Mykiss

1.9 mg/l [96 hours]

### Acute - EC50

OECD 202 [Daphnia sp. Acute Immobilization Test and

Label No : 96283

Reproduction Test1

Daphnia - Daphnia - Daphnia Magna

3.7 mg/l [48 hours]

#### Acute - EC50 - Marine water

OECD 201 [Alga, Growth Inhibition Test] Algae - Algae - Skeletonema Costatum

0.36 mg/l [72 hours]

Date of issue/Date of revision : 14/11/2023 Version: 7 14/22 : 14/03/2025 Date of previous issue

# **SECTION 12: Ecological information**

Acute - NOEC - Marine water

OECD 201 [Alga, Growth Inhibition Test] Algae - Algae - Skeletonema Costatum

0.15 mg/l [72 hours]

Conclusion/Summary [Product] : Not available.

12.2 Persistence and degradability

**Product/ingredient name** Result 7,2-benzisothiazol-3(2H)-one EU

24% [28 days]

Conclusion/Summary [Product] : Not available.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
3-iodo-2-propynyl-butyl carbamate	-	-	Not readily
1,2-benzisothiazol-3(2H)-one	-	-	Inherent

#### 12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
3-iodo-2-propynyl-butyl	>1	-	Low
carbamate 1,2-benzisothiazol-3(2H)-one	-	3.2	Low

#### 12.4 Mobility in soil

### Soil/water partition coefficient

Product/ingredient name	logKoc	Koc
3-iodo-2-propynyl-butyl carbamate 1,2-benzisothiazol-3(2H)-one	1.13 1.86	13.4558 73.142

#### Results of PMT and vPvM assessment

Product/ingredient name	PMT	Р	M	Т	vPvM	νP	vM
titanium dioxide	No	No	No	No	No	No	No
(Z)-9-Octadecen-1-ol ethoxylated	No	No	No	No	No	No	No
3-iodo-2-propynyl-butyl carbamate	No	No	No	No	No	No	No
1,2-benzisothiazol-3(2H)-one	No	No	No	No	No	No	No
reaction mass of: 5-chloro- 2-methyl-4-isothiazolin- 3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol- 3-one [EC no. 220-239-6] (3: 1)	No	No	No	No	No	No	No

**Mobility** : Not available.

: The product does not meet the criteria to be considered as a PMT or vPvM. **Conclusion/Summary** 

12.5 Results of PBT and vPvB assessment Regulation (EC) No. 1907/2006 [REACH]

Date of issue/Date of revision : 14/03/2025 Date of previous issue : 14/11/2023 Version :7 15/22 Label No : 96283

# **SECTION 12: Ecological information**

Product/ingredient name	PBT	P	В	T	vPvB	νP	νB	
titanium dioxide	No	No	No	No	No	No	No	
(Z)-9-Octadecen-1-ol ethoxylated	No	No	No	No	No	No	No	
3-iodo-2-propynyl-butyl carbamate	No	No	No	No	No	No	No	
1,2-benzisothiazol-3(2H)-one	No	No	No	No	No	No	No	
reaction mass of: 5-chloro- 2-methyl-4-isothiazolin- 3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol- 3-one [EC no. 220-239-6] (3: 1)	No	No	No	No	No	No	No	

#### **Regulation (EC) No. 1272/2008 [CLP]**

Product/ingredient name	PBT	P	В	T	vPvB	vP	vB	
titanium dioxide	No	No	No	No	No	No	No	
(Z)-9-Octadecen-1-ol ethoxylated	No	No	No	No	No	No	No	
3-iodo-2-propynyl-butyl carbamate	No	No	No	No	No	No	No	
1,2-benzisothiazol-3(2H)-one	No	No	No	No	No	No	No	
reaction mass of: 5-chloro- 2-methyl-4-isothiazolin- 3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol- 3-one [EC no. 220-239-6] (3: 1)	No	No	No	No	No	No	No	

**Conclusion/Summary Regulation (EC) No. 1272/2008** [CLP]

: The product does not meet the criteria to be considered as a PBT or vPvB.

#### 12.6 Endocrine disrupting properties

Not available.

**Conclusion/Summary [Product]** 

: The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

#### 12.7 Other adverse effects

No known significant effects or critical hazards.

# **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

#### **Product**

**Methods of disposal** 

: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

Risk of self-ignition of used cleaning rags, paper wipes etc. Contaminated materials should be soaked in water and placed in a closed metal container before disposal.

**European waste** catalogue (EWC)

**Packaging** 

**: 0**80112, 200128

Date of issue/Date of revision : 14/03/2025 : 14/11/2023 Version: 7 16/22 Date of previous issue Label No : 96283

# **SECTION 13: Disposal considerations**

**Methods of disposal** 

: The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

**Special precautions** 

This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

# **SECTION 14: Transport information**

	ADR/RID	ADN	IMDG	IATA
14.1 UN number or ID number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-	-
14.3 Transport hazard class(es)	-	-	-	-
14.4 Packing group	-	-	-	-
14.5 Environmental hazards	No.	No.	No.	No.

14.6 Special precautions for

: Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Maritime transport in bulk according to IMO instruments

: Not relevant/applicable due to nature of the product.

# **SECTION 15: Regulatory information**

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

**Annex XIV** 

None of the components are listed.

Substances of very high concern

None of the components are listed.

#### Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Product/ingredient name	%	Designation [Usage]
WOODEX AQUA WOOD OIL	≥90	3

Labelling

Other EU regulations

**Industrial emissions** : Not listed

(integrated pollution prevention and control) -

**Air** 

Date of issue/Date of revision : 14/11/2023 Version :7 17/22 : 14/03/2025 Date of previous issue Label No: 96283

# **SECTION 15: Regulatory information**

: Not listed

Industrial emissions (integrated pollution

prevention and control) -

Water

Explosive precursors : Not applicable.

Ozone depleting substances (EU 2024/590)

Not listed.

Prior Informed Consent (PIC) (649/2012/EU)

Not listed.

**Persistent Organic Pollutants** 

Not listed.

**Seveso Directive** 

This product is not controlled under the Seveso Directive.

**National regulations** 

<u>Austria</u>

Limitation of the use of

: Permitted.

organic solvents

**Belgium** 

Book VI carcinogenic agents annex VI.2-1 - VI.2-3

Ingredient name	Status
Noirs de charbon	Listed
Silice	Listed

#### **Czech Republic**

**Denmark** 

**Executive Order No. 1795/2015** 

Ingredient name	Annex I Section A	Annex I Section B
tranium dioxide	Listed	-

MAL-code : 00-1

**Protection based on MAL** 

: According to the regulations on work involving coded products, the following stipulations apply to the use of personal protective equipment:

**General:** Gloves must be worn for all work that may result in soiling. Apron/coveralls/protective clothing must be worn when soiling is so great that regular work clothes do not adequately protect skin against contact with the product. A face shield must be worn in work involving spattering if a full mask is not required. In this case, other recommended use of eye protection is not required.

In all spraying operations in which there is return spray, the following must be worn: respiratory protection and arm protectors/apron/coveralls/protective clothing as appropriate or as instructed.

MAL-code: 00-1

**Application:** When spraying in existing\* spray booths, if the operator is outside the spray zone.

- Arm protectors must be worn.

During all spraying where atomisation occurs in cabins or spray booths where the operator is inside the spray zone and during spraying outside a closed facility, cabin or booth.

Label No : 96283

- Full mask with combined filter, coveralls and hood must be worn.

Date of issue/Date of revision: 14/03/2025Date of previous issue: 14/11/2023Version: 718/22

# SECTION 15: Regulatory information

Drying: Items for drying/drying ovens that are temporarily placed on such things as rack trolleys, etc, must be equipped with a mechanical exhaust system to prevent fumes from wet items from passing through workers' inhalation zone.

**Polishing:** When polishing treated surfaces, a mask with dust filter must be worn. When machine grinding, eye protection must be worn. Work gloves must always be

**Caution** The regulations contain other stipulations in addition to the above.

\*See Regulations.

**Restrictions on use** : Not to be used by professional users below 18 years of age. See the National

Working Environment Authorities Executive Order regarding Young People At Work.

List of undesirable

substances

Not listed

Carcinogenic waste

: Waste containers must be labeled: Contains a substance or substances regulated

by Danish working environment legislation on cancer risks.

**Finland** 

**France** 

Reinforced medical surveillance

: Act of July 11, 1977 determining the list of activities which require reinforced

medical surveillance: not applicable

Germany

Storage class (TRGS 510) : 12 **Hazardous incident ordinance** 

This product is not controlled under the Germany Hazardous Incident Ordinance.

Hazard class for water : 2

Technical instruction on air quality control (TA Luft)

Number [Class]	Description	%
<b>5</b> .2.1	Total dust	13.9
5.2.5	Organic substances	4.3
5.2.5 [I]	Organic substances	0.94
5.2.7.2	Poorly degradable, easily accumulating and highly toxic organic substances	0.22

**AOX** The product contains organically bound halogens and can contribute to the AOX

value in waste water.

Italy

D.Lgs. 152/06 : Not determined.

**Netherlands** 

**Water Discharge Policy** 

(ABM)

: A(3) Hazardous for aquatic organisms, may have long-term hazardous effects in

aquatic environment. Decontamination effort: A

**Norway Sweden** 

**Switzerland** 

**VOC** content : Exempt.

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

**Montreal Protocol** 

Not listed.

**Stockholm Convention on Persistent Organic Pollutants** 

Not listed.

Date of issue/Date of revision : 14/03/2025 : 14/11/2023 Version: 7 19/22 Date of previous issue

WOODEX AQUA WOOD OIL - GREY

Label No: 96283

# **SECTION 15: Regulatory information**

**Rotterdam Convention on Prior Informed Consent (PIC)** 

Not listed.

#### **UNECE Aarhus Protocol on POPs and Heavy Metals**

Not listed.

15.2 Chemical safety assessment

 This product contains substances for which Chemical Safety Assessments are still required.

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No.

#### **SECTION 16: Other information**

Indicates information that has changed from previously issued version.

Abbreviations and acronyms

: ATE = Acute Toxicity Estimate

1272/2008]
DMEL = Derived Minimal Effect Level

DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level

EUH statement = CLP-specific Hazard statement

N/A = Not available

PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration RRN = REACH Registration Number

SGG = Segregation Group

vPvB = Very Persistent and Very Bioaccumulative

#### Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification	
Aquatic Chronic 3, H412	Calculation method	

#### **Full text of abbreviated H statements**

ge.
nged or repeated exposure.
effects.
fects.
1

### Full text of classifications [CLP/GHS]

Acute Tox. 2	ACUTE TOXICITY - Category 2
Acute Tox. 3	ACUTE TOXICITY - Category 3
Acute Tox. 4	ACUTE TOXICITY - Category 4
Aquatic Acute 1	SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1
Aquatic Chronic 1	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1
Aquatic Chronic 3	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3
Carc. 2	CARCINOGENICITY - Category 2
Eye Dam. 1	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1
Skin Corr. 1C	SKIN CORROSION/IRRITATION - Category 1C
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2
Skin Sens. 1	SKIN SENSITISATION - Category 1
Skin Sens. 1A	SKIN SENSITISATION - Category 1A
STOT RE 1	SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 1

Date of issue/ Date of : 14/03/2025

revision

Date of issue/Date of revision : 14/03/2025 Date of previous issue : 14/11/2023 Version : 7 20/22

WOODEX AQUA WOOD OIL - GREY

Label No : 96283

### **SECTION 16: Other information**

: 14/11/2023 Date of previous issue

**Version** : 7

#### **Notice to reader**

The information in this SDS is based on the present state of our knowledge and on current laws. The product is not to be used for purposes other than those specified under section 1 without first obtaining written handling instructions. It is always the responsibility of the user to take all necessary steps to fulfil the demands set out in the local rules and legislation. The information in this SDS is meant to be a description of the safety requirements for our product. It is not to be considered a guarantee of the product's properties.

Version :7 Date of issue/Date of revision : 14/03/2025 Date of previous issue : 14/11/2023 21/22 Label No : 96283

Version :7 Date of issue/Date of revision : 14/03/2025 Date of previous issue : 14/11/2023 22/22 **Label No :9**6283