#### Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2020/878 - Malta

# SAFETY DATA SHEET



WOODEX BIOLEUM - All variants

## SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1	Product identifier	
Pr	roduct name	

: WOODEX BIOLEUM - All variants

1.2 Relevant identified uses of the substance or mixture and uses advised against **Product use** : Paint.

#### 1.3 Details of the supplier of the safety data sheet

Teknos Group Oy, Takkatie 3, FI-00370 HELSINKI, FINLAND. Tel. +358 9 506 091.

e-mail address of person : Prod-safe@teknos.com responsible for this SDS

## **National contact**

Teknos Group Oy, Takkatie 3, FI-00370 HELSINKI, FINLAND. Tel. +358 9 506 091.

#### 1.4 Emergency telephone number

#### National advisory body/Poison Centre

**Telephone number** : Malta Competition and Consumer Affairs Authority (MCCAA): +356 2395 2000

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture Product definition : Mixture Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Aquatic Chronic 3, H412

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements		
Signal word	:	No signal word.
Hazard statements	:	H412 - Harmful to aquatic life with long lasting effects.
Precautionary statements		
Prevention	:	P273 - Avoid release to the environment.
Response	:	Not applicable.
Storage	:	Not applicable.
Disposal	:	P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.
Supplemental label elements	:	Contains 3-iodo-2-propynyl-butyl carbamate and 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction. Contains biocidal products for dry film and in-can preservation: IPBC and BIT. Risk of skin sensitisation.Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist. Safety data sheet available on request.
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	:	
Date of issue/Date of revision		: 28/02/2025 Date of previous issue : 15/09/2023 Version : 4 1/17

### **SECTION 2: Hazards identification**

#### 2.3 Other hazards

Product meets the criteria	: This mixture does not contain any substances that are assessed to be a PBT or a
for PBT or vPvB according	
to Regulation (EC) No.	

to Regulation (EC) No. 1907/2006, Annex XIII Other hazards which do : None known. not result in classification

### **SECTION 3: Composition/information on ingredients**

3.2 Mixtures : Mixture					
Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Туре
2-Butoxyethanol	REACH #: 01-2119475108-36 EC: 203-905-0 CAS: 111-76-2 Index: 603-014-00-0	<10	Acute Tox. 4, H302 Acute Tox. 3, H331 Skin Irrit. 2, H315 Eye Irrit. 2, H319	ATE [Oral] = 1200 mg/kg ATE [Inhalation (vapours)] = 3 mg/l	[1] [2]
3-iodo-2-propynyl-butyl carbamate	EC: 259-627-5 CAS: 55406-53-6 Index: 616-212-00-7	≤0.3	Acute Tox. 4, H302 Acute Tox. 3, H331 Eye Dam. 1, H318 Skin Sens. 1, H317 STOT RE 1, H372 (larynx) Aquatic Acute 1, H400 Aquatic Chronic 1, H410	ATE [Oral] = 400 mg/kg ATE [Inhalation (dusts and mists)] = 0.67 mg/l M [Acute] = 10 M [Chronic] = 1	[1]
1,2-benzisothiazol-3(2H)- one	EC: 220-120-9 CAS: 2634-33-5 Index: 613-088-00-6	<0.036	Acute Tox. 4, H302 Acute Tox. 2, H330 Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410	ATE [Oral] = 450 mg/kg ATE [Inhalation (dusts and mists)] = $0.21$ mg/l Skin Sens. 1, H317: $C \ge 0.036\%$ M [Acute] = 1 M [Chronic] = 1	[1]
			See Section 16 for the full text of the H statements declared above.		

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Contains: > 1 % TiO2

Туре

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

### **SECTION 4: First aid measures**

#### 4.1 Description of first aid measures

Eye contact		<ul> <li>Immediately flush eyes with p eyelids. Check for and remo- occurs.</li> </ul>		
Inhalation		Remove victim to fresh air an	ld keep at rest in a position	comfortable for breathing.
Skin contact		: Flush contaminated skin with shoes. Get medical attention		contaminated clothing and
Date of issue/Date of revision		: 28/02/2025 Date of previous is	ssue : 15/09/2023	Version : 4 2/17
WOODEX BIOLEUM - All va	arian	ts		Label No : <mark>8</mark> 5459

Ingestion	: Wash out mouth with water. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Do not induce vomiting unless directed to do so by medical personnel.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training.
4.2 Most important sympton	ns and effects, both acute and delayed
Over-exposure signs/symp	i <u>toms</u>
Eye contact	: No specific data.
Inhalation	: No specific data.
Skin contact	: No specific data.
Ingestion	: No specific data.
4.3 Indication of any immedi	ate medical attention and special treatment needed
Notes to physician	<ul> <li>Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.</li> </ul>
Specific treatments	: No specific treatment.
SECTION 5: Firefigh	ting measures
5.1 Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
5.2 Special hazards arising f	from the substance or mixture
Hazards from the substance or mixture	: In a fire or if heated, a pressure increase will occur and the container may burst. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
Hazardous combustion products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide
5.3 Advice for firefighters	
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident i there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for the mined incidente.
	chemical incidents.

6.1 Personal precautions, protective equipment and emergency procedures			
For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Put on appropriate personal protective equipment.	
For emergency responders	:	If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".	

: 28/02/2025 Date of previous issue

### **SECTION 6: Accidental release measures**

6.2 Environmental precautions	: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.	
6.3 Methods and materia	for containment and cleaning up	
Small spill	<ul> <li>Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.</li> </ul>	
Large spill	: Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.	
6.4 Reference to other sections	<ul> <li>See Section 1 for emergency contact information.</li> <li>See Section 8 for information on appropriate personal protective equipment.</li> <li>See Section 13 for additional waste treatment information.</li> </ul>	

### SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

#### 7.1 Precautions for safe handling

Protective measures	<ul> <li>Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapour or mist. Avoid release to the environment. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.</li> <li>Risk of self-ignition of used cleaning rags, paper wipes etc. Contaminated materials should be soaked in water and placed in a closed metal container before disposal.</li> </ul>
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

#### 7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)
Recommendations
Industrial sector specific solutions

- : Not available.
- : Not available.

### **SECTION 8: Exposure controls/personal protection**

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

### 8.1 Control parameters

Occupational exposure limits

Product/ingredient name	Exposure limit values
₽-Butoxyethanol	<b>EU OEL (Europe, 1/2022)</b> Absorbed through skin. TWA 8 hours: 20 ppm. TWA 8 hours: 98 mg/m <sup>3</sup> . STEL 15 minutes: 50 ppm. STEL 15 minutes: 246 mg/m <sup>3</sup> .

#### **Biological exposure indices**

Product/ingredient name	Exposure indices
No exposure indices known.	
procedures European S assessmen values and atmosphere of exposure (Workplace for the mea	should be made to monitoring standards, such as the following: Standard EN 689 (Workplace atmospheres - Guidance for the t of exposure by inhalation to chemical agents for comparison with limit measurement strategy) European Standard EN 14042 (Workplace es - Guide for the application and use of procedures for the assessment to chemical and biological agents) European Standard EN 482 atmospheres - General requirements for the performance of procedures surement of chemical agents) Reference to national guidance for methods for the determination of hazardous substances will also be
DNELs/DMELs	
Product/ingredient name	Result
2-Butoxyethanol	<b>DNEL - General population - Long term - Oral</b> 6.3 mg/kg bw/day <u>Effects</u> : Systemic
	<b>DNEL - General population - Short term - Oral</b> 26.7 mg/kg bw/day <u>Effects</u> : Systemic
	<b>DNEL - General population - Long term - Inhalation</b> 59 mg/m <sup>3</sup> <u>Effects</u> : Systemic
	DNEL - Workers - Long term - Inhalation 98 mg/m <sup>3</sup> Effects: Systemic
	DNEL - General population - Short term - Inhalation 147 mg/m³ <u>Effects</u> : Local
	<b>DNEL - Workers - Short term - Inhalation</b> 246 mg/m³ <u>Effects</u> : Local
	<b>DNEL - General population - Short term - Inhalation</b> 426 mg/m <sup>3</sup> <u>Effects</u> : Systemic
	DNEL - Workers - Short term - Inhalation 1091 mg/m³ <u>Effects</u> : Systemic
3-iodo-2-propynyl-butyl carbamate	<b>DNEL - Workers - Long term - Inhalation</b> 0.023 mg/m <sup>3</sup>
ate of issue/Date of revision : 28/02/2025	Date of previous issue: 15/09/2023Version: 45/17
VOODEX BIOLEUM - All variants	Label No : <mark>Ø</mark> 5459

### **SECTION 8: Exposure controls/personal protection**

Effects: Systemic

**DNEL - Workers - Short term - Inhalation** 0.07 mg/m<sup>3</sup> <u>Effects</u>: Systemic

**DNEL - Workers - Short term - Inhalation** 1.16 mg/m<sup>3</sup> <u>Effects</u>: Local

**DNEL - Workers - Long term - Inhalation** 1.16 mg/m<sup>3</sup> <u>Effects</u>: Local

**DNEL - Workers - Long term - Dermal** 2 mg/kg bw/day <u>Effects</u>: Systemic

**DNEL - General population - Long term - Dermal** 0.345 mg/kg bw/day <u>Effects</u>: Systemic

**DNEL - Workers - Long term - Dermal** 0.966 mg/kg bw/day <u>Effects</u>: Systemic

**DNEL - General population - Long term - Inhalation** 1.2 mg/m<sup>3</sup> <u>Effects</u>: Systemic

**DNEL - Workers - Long term - Inhalation** 6.81 mg/m<sup>3</sup> <u>Effects</u>: Systemic

#### **PNECs**

Not available.

od general ventilation should be sufficient to control worker exposure to airborne ntaminants. Ash hands, forearms and face thoroughly after handling chemical products, fore eating, smoking and using the lavatory and at the end of the working period. propriate techniques should be used to remove potentially contaminated clothing. ash contaminated clothing before reusing. Ensure that eyewash stations and fety showers are close to the workstation location. fety eyewear complying with an approved standard should be used when a risk
Fore eating, smoking and using the lavatory and at the end of the working period. propriate techniques should be used to remove potentially contaminated clothing. ash contaminated clothing before reusing. Ensure that eyewash stations and ety showers are close to the workstation location. fety eyewear complying with an approved standard should be used when a risk
Fore eating, smoking and using the lavatory and at the end of the working period. propriate techniques should be used to remove potentially contaminated clothing. ash contaminated clothing before reusing. Ensure that eyewash stations and ety showers are close to the workstation location. fety eyewear complying with an approved standard should be used when a risk
sessment indicates this is necessary to avoid exposure to liquid splashes, mists, ses or dusts. If contact is possible, the following protection should be worn, ess the assessment indicates a higher degree of protection: safety glasses with e-shields.
emical-resistant, impervious gloves complying with an approved standard should worn at all times when handling chemical products if a risk assessment indicates is is necessary. Considering the parameters specified by the glove manufacturer, eck during use that the gloves are still retaining their protective properties. It puld be noted that the time to breakthrough for any glove material may be erent for different glove manufacturers. In the case of mixtures, consisting of veral substances, the protection time of the gloves cannot be accurately imated.

Date of issue/Date of revision	: 28/02/2025	Date of previous issue	: 15/09/2023	Version	:4	6/17
WOODEX BIOLEUM - All variants				Label No	8545	9

1,2-benzisothiazol-3(2H)-one

### **SECTION 8: Exposure controls/personal protection**

•		• •
		Recommendations : Wear suitable gloves tested to EN374.
		> 8 hours (breakthrough time): Nitrile gloves. thickness > 0.3 mm
		Not recommended polyvinyl alcohol (PVA) gloves
Body protection	:	Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	:	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	:	Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.
		Filter type (spray application): A P
Environmental exposure controls	:	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

## **SECTION 9: Physical and chemical properties**

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

#### 9.1 Information on basic physical and chemical properties

Physical state: Liquid.Colour: VariousOdour: SlightOdour threshold: Not available.Melting point/freezing point: Not available.Initial boiling point and:	Appearance	
Odour: SlightOdour threshold: Not available.Melting point/freezing point: Not available.Initial boiling point and:	Physical state	: Liquid.
Odour threshold: Not available.Melting point/freezing point: Not available.Initial boiling point and:	Colour	: Various
Melting point/freezing point: Not available.Initial boiling point and:	Odour	: Slight
Initial boiling point and :	Odour threshold	: Not available.
	Melting point/freezing point	: Not available.
	Initial boiling point and	1 C
boiling range	boiling range	

Ingredient name	°C	°F	Method
water	100	212	
2-Butoxyethanol	171 to 171.5	339.8 to 340.7	IP 123-93

Flammability	: Not available.
Lower and upper explosion	: Lower: Not applicable.
limit	Upper: Not applicable.
Flash point	

÷.

#### **Flash point**

	Closed cup			Open cup		
Ingredient name	°C	°F	Method	°C	°F	Method
2-Butoxyethanol	67	152.6	DIN 51758	61.85	143.3	
MODIFIED LINSEED OIL POLYMER	>100	>212				

#### **Auto-ignition temperature**

Ingredient name	°C	°F	Method
2-Butoxyethanol	230	446	DIN 51794

#### **Decomposition temperature** : Not available. : 8.4 to 9.1 pН : Not available. Viscosity Solubility(ies) ŝ

Not available.

## SECTION 9: Physical and chemical properties

1

Solubility in water : Not available.

Partition coefficient: n-octanol/ : Not applicable. water

### Vapour pressure

	Vapour Pressure at 20°C			Vapour pressure at 50°		
Ingredient name	mm Hg	kPa	Method	mm Hg	kPa	Method
water	17.5	2.3				
2-Butoxyethanol	0.75006	0.1				
Relative density	: Not	available.	<b>I</b>			
Density	: 1 g/cm <sup>3</sup>					
/apour density	: Not	available.				
Particle characteristics						
Median particle size	: Not	applicable.				

#### 9.2 Other information

9.2.1 Information with regard to physical hazard classes					
Explosive properties	:	Not available.			
Oxidising properties	:	Not available.			
9.2.2 Other safety characteristics					

## 9.2.2 Other safety characteristics

Not applicable.

## **SECTION 10: Stability and reactivity**

10.1 Reactivity	No specific test data related to reactivity available for this product or its ing	redients.
10.2 Chemical stability	The product is stable.	
10.3 Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not c	occur.
10.4 Conditions to avoid	No specific data.	
10.5 Incompatible materials	No specific data.	
10.6 Hazardous decomposition products	Under normal conditions of storage and use, hazardous decomposition pro should not be produced.	oducts

## **SECTION 11: Toxicological information**

11.1 Information on hazard classes as de	afined in Regulation (EC) No 1272/2008
Acute toxicity	
Product/ingredient name	Result
3-iodo-2-propynyl-butyl carbamate	Rat - Oral - LD50
	400 mg/kg
	Rat - Dermal - LD50
	>2000 mg/kg
	Rat - Inhalation - LC50 Dusts and mists
	0.763 mg/l [4 hours]
	Rat - Inhalation - LC50 Dusts and mists
	0.67 g/m³ [4 hours]
1,2-benzisothiazol-3(2H)-one	Rat - Oral - LD50
	1020 mg/kg
Date of issue/Date of revision : 28/02/20	D25Date of previous issue: 15/09/2023Version: 48/17
WOODEX BIOLEUM - All variants	Label No : <mark>8</mark> 5459

# **SECTION 11: Toxicological information**

Conclusion/Summary [Product] : Not available.

#### Acute toxicity estimates

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
	14023.9	N/A	N/A	35.1	225.3
2-Butoxyethanol	1200	N/A	N/A	3	N/A
3-iodo-2-propynyl-butyl carbamate	400	N/A	N/A	N/A	0.67
1,2-benzisothiazol-3(2H)-one	450	N/A	N/A	N/A	0.21

Skin corrosion/irritation		
Product/ingredient name		Result
2-Butoxyethanol		Rabbit - Skin - Mild irritant Amount/concentration applied: 500 mg
1,2-benzisothiazol-3(2H)-one		Human - Skin - Mild irritant Duration of treatment/exposure: 48 hours Amount/concentration applied: 5 %
Conclusion/Summary [Product]	: Not available.	
Serious eye damage/eye irritation		
Product/ingredient name		Result
₽-Butoxyethanol		Rabbit - Eyes - Moderate irritant Duration of treatment/exposure: 24 hours Amount/concentration applied: 100 mg
		Rabbit - Eyes - Severe irritant Amount/concentration applied: 100 mg
3-iodo-2-propynyl-butyl carbamate		Rabbit - Eyes - Severe irritant
Conclusion/Summary [Product]	: Not available.	
Respiratory corrosion/irritation Not available.		
Conclusion/Summary [Product]	: Not available.	
Respiratory or skin sensitization		
Product/ingredient name		Result
3-iodo-2-propynyl-butyl carbamate		Guinea pig - skin <u>Result</u> : Not sensitizing
Skin		
Conclusion/Summary [Product]	: Not available.	
Respiratory		
Conclusion/Summary [Product]	: Not available.	
Germ cell mutagenicity		
Product/ingredient name		Result
	/22/2225	
Date of issue/Date of revision : 28/	/02/2025 Date of p	previous issue : 15/09/2023 Version : 4

### **SECTION 11: Toxicological information**

3-iodo-2-propynyl-butyl carbamate

In vitro - Bacteria Result: Negative

Conclusion/Summary [Product] : Not available.

#### Carcinogenicity

Not available.

Conclusion/Summary [Product] : Not available.

#### **Reproductive toxicity**

**Product/ingredient name** 

3-iodo-2-propynyl-butyl carbamate

#### Result

Rabbit - Female - Oral 50 mg/kg [7 days per week] [13 days] Maternal toxicity: Positive Developmental: Negative

Rabbit - Female - Oral 20 mg/kg [7 days per week] [13 days] Maternal toxicity: Negative **Developmental:** Negative

**Conclusion/Summary [Product]** : Not available.

# Specific target organ toxicity (single exposure)

Not available.

#### Specific target organ toxicity (repeated exposure) . . . ... ....

Product/ingredient name	Result
3-iodo-2-propynyl-butyl carbamate	STOT RE 1, H372 (larynx)

#### **Aspiration hazard**

Not available.

NUL avaliable.	
Information on likely routes	of exposure
Not available.	
Potential acute health effect	<u>s</u>
Eye contact	: No known significant effects or critical hazards.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: No known significant effects or critical hazards.
Ingestion	: No known significant effects or critical hazards.
Symptoms related to the ph	ysical, chemical and toxicological characteristics
Eye contact	: No specific data.
Inhalation	: No specific data.
Skin contact	: No specific data.
Ingestion	: No specific data.
Delayed and immediate effe	cts as well as chronic effects from short and long-term exposure
Short term exposure	
Potential immediate	: Not available.
effects	
Potential delayed effects	: Not available.
Long term exposure	
Potential immediate effects	: Not available.

Date of issue/Date of revision WOODEX BIOLEUM - All variants : 28/02/2025 Date of previous issue

### **SECTION 11: Toxicological information**

Potential delayed effects	Not available.
Potential chronic health e	ifects
Not available.	
Conclusion/Summary [P	roduct] : Not available.
General	: No known significant effects or critical hazards.
Carcinogenicity	: No known significant effects or critical hazards.
Mutagenicity	: No known significant effects or critical hazards.
Reproductive toxicity	: No known significant effects or critical hazards.
11.2 Information on other h	azards

#### **11.2.1 Endocrine disrupting properties**

Not available.

Conclusion/Summary [Product]

: The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

#### 11.2.2 Other information

Not available.

### SECTION 12: Ecological information

#### 12.1 Toxicity

### **Product/ingredient name**

3-iodo-2-propynyl-butyl carbamate

2-Butoxyethanol

#### Result

Acute - LC50 - Marine water Fish - Inland silverside - Menidia beryllina Size: 40 to 100 mm 1250000 µg/l [96 hours] Effect: Mortality

#### Acute - LC50 - Marine water

Crustaceans - Common shrimp, sand shrimp - Crangon crangon 800000 µg/l [48 hours] Effect: Mortality

#### Acute - LC50 - Fresh water

EU Fish - Trout - Oncorhynchus mykiss 0.067 mg/l [96 hours]

#### Acute - NOEC - Fresh water

EU Fish - Trout - Oncorhynchus mykiss 0.049 mg/l [96 hours]

#### Acute - EC50 - Fresh water

FU Daphnia - Daphnia - Daphnia magna 0.16 mg/l [48 hours]

#### **Chronic - NOEC - Fresh water** EU Daphnia - Daphnia - Daphnia Magna 0.05 mg/l [21 days]

### Acute - EC50 - Fresh water EU

Algae - Algae - Scenedemus subspicatus 0.022 mg/l [72 hours]

Acute - LC50 - Fresh water

1,2-benzisothiazol-3(2H)-one

OECD [Fish, Acute Toxicity Test]

Date of issue/Date of revision WOODEX BIOLEUM - All variants : 28/02/2025 Date of previous issue

### **SECTION 12: Ecological information**

Fish - Trout - *Onorhynchus Mykiss* 1.9 mg/l [96 hours]

#### Acute - EC50

OECD 202 [Daphnia sp. Acute Immobilization Test and Reproduction Test] Daphnia - Daphnia - *Daphnia Magna* 3.7 mg/l [48 hours]

#### Acute - EC50 - Marine water

OECD 201 [Alga, Growth Inhibition Test] Algae - Algae - *Skeletonema Costatum* 0.36 mg/l [72 hours]

#### Acute - NOEC - Marine water

OECD 201 [Alga, Growth Inhibition Test] Algae - Algae - *Skeletonema Costatum* 0.15 mg/l [72 hours]

**Conclusion/Summary [Product]** : Not available.

#### 12.2 Persistence and degradability

#### **Product/ingredient name**

1,2-benzisothiazol-3(2H)-one

Result EU 24% [28 days]

Conclusion/Summary [Product] : Not available.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
riodo-2-propynyl-butyl carbamate	-	-	Not readily
1,2-benzisothiazol-3(2H)-one	-	-	Inherent

#### 12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
2-Butoxyethanol	0.81	-	Low
3-iodo-2-propynyl-butyl carbamate	>1	-	Low
1,2-benzisothiazol-3(2H)-one	-	3.2	Low

#### 12.4 Mobility in soil

#### Soil/water partition coefficient

Product/ingredient name	logKoc	Кос
2-Butoxyethanol	1.83	67.3685
3-iodo-2-propynyl-butyl carbamate	1.13	13.4558
1,2-benzisothiazol-3(2H)-one	1.86	73.142

#### Results of PMT and vPvM assessment

Product/ingredient name	PMT	Р	Μ	Т	vPvM	vP	vM
P-Butoxyethanol 3-iodo-2-propynyl-butyl	No No						
carbamate 1,2-benzisothiazol-3(2H)-one	No						

Mobility

: Not available.

: The product does not meet the criteria to be considered as a PMT or vPvM.

: 15/09/2023

### 12.5 Results of PBT and vPvB assessment Regulation (EC) No. 1907/2006 [REACH]

Date of issue/Date of revision

WOODEX BIOLEUM - All variants

**Conclusion/Summary** 

: 28/02/2025 Date of previous issue

Version :4

12/17

Product/ingredient name	PBT	Р	В	т	vPvB	vP	vB
2-Butoxyethanol	No	No	No	No	No	No	No
3-iodo-2-propynyl-butyl carbamate	No	No	No	No	No	No	No
1,2-benzisothiazol-3(2H)-one	No	No	No	No	No	No	No
Regulation (EC) No. 1272/20	08 [CLP]						
Product/ingredient name	PBT	Р	В	т	vPvB	vP	vB
2-Butoxyethanol	No	No	No	No	No	No	No
3-iodo-2-propynyl-butyl carbamate	No	No	No	No	No	No	No
1,2-benzisothiazol-3(2H)-one	No	No	No	No	No	No	No

[CLP]

#### 12.6 Endocrine disrupting properties

Not available.

Conclusion/Summary [Product]

: The product does not meet the criteria to be considered as having endocrine disrupting properties according to the criteria set out in either Regulation (EC) No. 1907/2006 or Regulation (EC) No 1272/2008.

### 12.7 Other adverse effects

No known significant effects or critical hazards.

### **SECTION 13: Disposal considerations**

13.1	Waste	treatment	methods

Product	
Methods of disposal	<ul> <li>The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.</li> <li>Risk of self-ignition of used cleaning rags, paper wipes etc. Contaminated materials should be soaked in water and placed in a closed metal container before disposal.</li> </ul>
European waste catalogue (EWC)	: 080111*, 200127*
Packaging	
Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.
Special precautions	: This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

## **SECTION 14: Transport information**

SECTION 14: Transport information				
	ADR/RID	ADN	IMDG	IATA
14.1 UN number or ID number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-	-
14.3 Transport hazard class(es)	-	-	-	-
14.4 Packing group	-	-	-	-
14.5 Environmental hazards	No.	No.	No.	No.

: Not relevant/applicable due to nature of the product.

user

**14.6 Special precautions for** : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Maritime transport in bulk according to IMO instruments

### **SECTION 15: Regulatory information**

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

**Annex XIV** 

None of the components are listed.

#### Substances of very high concern

None of the components are listed.

#### Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

		%	Designation [Usage]	
WOODEX BIOLEUM		≥90	3	
Labelling	:	4		
Other EU regulations				
Industrial emissions (integrated pollution prevention and control) - Air	: Not listed			
Industrial emissions (integrated pollution prevention and control) - Water	: Not listed			
Explosive precursors	: Not applicat	ole.		
Ozone depleting substances	s (EU 2024/59	<u>0)</u>		
Not listed.				

### **SECTION 15: Regulatory information**

Persistent Organic Pollutants Not listed.

#### **Seveso Directive**

This product is not controlled under the Seveso Directive.

#### International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals Not listed.

#### Montreal Protocol

Not listed.

### Stockholm Convention on Persistent Organic Pollutants

Not listed.

### Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

#### **UNECE Aarhus Protocol on POPs and Heavy Metals**

Not listed.

#### **15.2 Chemical safety assessment** : This product contains substances for which Chemical Safety Assessments are still required.

### **SECTION 16: Other information**

Indicates information that has changed from previously issued version.

Abbreviations and	: ATE = Acute Toxicity Estimate
acronyms	CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No.
	1272/2008]
	DMEL = Derived Minimal Effect Level
	DNEL = Derived No Effect Level
	EUH statement = CLP-specific Hazard statement
	N/A = Not available
	PBT = Persistent, Bioaccumulative and Toxic
	PNEC = Predicted No Effect Concentration
	RRN = REACH Registration Number
	SGG = Segregation Group
	vPvB = Very Persistent and Very Bioaccumulative

#### Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification	
Aquatic Chronic 3, H412	Calculation method	

#### Full text of abbreviated H statements

<b>H</b> 302	Harmful if swallowed.	
H315	Causes skin irritation.	
H317	May cause an allergic skin reaction.	
H318	Causes serious eye damage.	
H319	Causes serious eye irritation.	
H330	Fatal if inhaled.	
H331	Toxic if inhaled.	
H372	Causes damage to organs through prolonged or repeated exposure.	
H400	Very toxic to aquatic life.	
H410	Very toxic to aquatic life with long lasting effects.	
H412	Harmful to aquatic life with long lasting effects.	

Full text of classifications [CLP/GHS]

: 28/02/2025 Date of previous issue

### **SECTION 16: Other information**

Cute Tox. 2	ACUTE TOXICITY - Category 2
Acute Tox. 3	ACUTE TOXICITY - Category 3
Acute Tox. 4	ACUTE TOXICITY - Category 4
Aquatic Acute 1	SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1
Aquatic Chronic 1	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1
Aquatic Chronic 3	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3
Eye Dam. 1	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1
Eye Irrit. 2	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2
Skin Sens. 1	SKIN SENSITISATION - Category 1
Skin Sens. 1A	SKIN SENSITISATION - Category 1A
STOT RE 1	SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 1
Date of issue/ Date of revision	: 28/02/2025
Date of previous issue	: 15/09/2023
Version	: 4
	WOODEX BIOLELIM All variants

#### Notice to reader

The information in this SDS is based on the present state of our knowledge and on current laws. The product is not to be used for purposes other than those specified under section 1 without first obtaining written handling instructions. It is always the responsibility of the user to take all necessary steps to fulfil the demands set out in the local rules and legislation. The information in this SDS is meant to be a description of the safety requirements for our product. It is not to be considered a guarantee of the product's properties.

Date of issue/Date of revision WOODEX BIOLEUM - All variants

: 28/02/2025 Date of previous issue