

BASEMENT

Basement paint

Water-borne, matt paint for ceilings and walls in basic indoor areas e.g. basements, garages and car parks.



For painting of new plaster, concrete, sprayed concrete, building board, brick and gypsum board surfaces, as well as for previously painted ceilings and walls when a matt surface is needed.



TECHNICAL DATA

Certificates, approvals and classification	Finnish Key Flag
Fields of application	Ceilings, Indoor wall
Recommended substrate	Building board, Clay brick, Concrete, Filler, Gypsum board, Mineral boards
Solids	Approx. 35% by volume
Volatile organic compound (VOC)	EU VOC limit value (cat A/a): 30 g/l. The product's VOC: max. 30 g/l.
Practical spreading rate	Previously painted surface: 7 - 10 m ² /l. Filler and wood fibre board: 5 - 8 m ² /l. Concrete and plastered surface: 4 - 7 m ² /l.
Colours	White.
Gloss (60°)	Matt
Thinner	Water.
Density	Approx. 1.6 g/ml
Storage	Must not freeze.
Packaging	White: 10 l.

DIRECTION FOR USE

Surface preparation	Clean new surfaces from dust and dirt. Wash previously painted surfaces with RENSA SUPER paint cleaner. For smoothing of irregularities in the surface choose a suitable filler from the SILORA series. The dried filler is sanded down and the dust removed.
Priming	Surface can be painted with BASEMENT without a primer.
Application method	Brush, Roller, Spray
Application	Stir thoroughly before use. Apply once or twice.

Application conditions	The surface to be treated must be dry. During the application and drying period the temperature of the ambient air, the surface and the product shall be above +5°C and the relative air humidity below 80%. Good ventilation during the application and drying period quickens the drying process.
Drying time	+23°C / 50% RH
- dust free	½ h
- overcoatable	2 h
	The drying process will be slower in cold and/or damp.
Washability and wear resistance	Wet scrub resistance: class 4, according to EN 13300 (ISO 11998).
Cleaning	Warm water and RENSA BRUSH brush cleaner. Wash the equipment immediately after use.

HEALTH AND SAFETY

Safety and precaution measures See safety data sheet.

Teknos Group Oy Takkatie 3, P.O.Box 107 FI-00371 Helsinki, Finland Tel. +358 9 506 091

The above information is normative and based on laboratory tests and practical experiences. The information is noncommittal, and we cannot accept liability for the results obtained under working conditions beyond our control, and consequently the buyer or the user is not released from the obligation to test the suitability of our products for specific means and application methods under the actual application conditions. Our liability covers only damage caused directly by defects in the products supplied by Teknos. This implies that the user possesses sufficient knowledge for using the product correctly with regard to technical and working safety aspects. The latest versions of Teknos' Technical Data Sheets and Safety Data Sheets are available from our homepage www.teknos.com. All trademarks displayed on this document are the exclusive property of Teknos Group or its affiliated companies.