

ETERNO 2102-15

Solvent-based, 1C top coat for interior and exterior use

ETERNO 2102 is a solvent-based, aromatics-free, well-filling and hard-wearing 1C top coat. The product has a good resistance to water, oil, grease and alcohol as well as very good weather resistance.



TECHNICAL DATA

Solids	Approx. 46% by weight
Volatile organic compound (VOC)	Approx. 483 g/l (DIRECTIVE 2010/75/EU) The VOC value provided is the average value for factory produced products, and consequently it will be subject to variations between individual products covered by this Technical Data Sheet.
Theoretical spreading rate	100 g/m ² ; 10 m ² /kg
Colours	Colourless.
Gloss (60°)	15
Thinner	TERPENTINERSATZ 4214-98
Density	Approx. 0.903 g/ml
Storage	Storage temperature is +5°C - +30°C. Store in a tightly closed container.

DIRECTION FOR USE

Surface preparation	Every substrate must be well-cleaned, dry and free from grease and oil. Coating removal: Sand
----------------------------	---

Application

Stir or shake the product well for several minutes before use, if necessary by machine.

APPLICATION ADVICE					
Wood substrate raw					
	Product			Applied Quantity	
Presanding	With grain 100-150				
Primer	TURVANOL BIP 2075 on all sides				
Drying	at least 48 hours				
Intermediate sanding	With grain 180-220				
Recoating	ETERNO 2102			1-2x 100 g/m ²	
For further application proposals please ask our representative.					
APPLICATION					
	Viscosity DIN 4 mm	Dilution	Nozzle in mm	Pressure in bar	Spray Cycles
Gravity Feed Gun	18"	10-25%	1.5-1.8	2.5-3.5	1-2x 100 g/m ²

Application conditions

Recommended temperature for surroundings and product: +15°C-25°C. Do not apply below +10°C. Avoid application in direct sunlight.

Drying time

+23°C / 65% RH

- dust free

after 60 minutes

- touch dry

after 16 hours

- overcoatable

after 1 day

- fit for sanding

after 16 hours

- through dry

after 7 days

Cleaning

Wash the equipment immediately after use. TERPENTINERSATZ 4214-98

HEALTH AND SAFETY

Safety and precaution measures

See safety data sheet.

First aid

We recommend wearing personal protective clothing even in cases where no local regulations are in force.

CH: The precautions according to local regulations (SUVA) with respect to hygiene and equipment must be observed.

Teknos Group Oy Takkatie 3, P.O.Box 107 FI-00371 Helsinki, Finland Tel. +358 9 506 091

The above information is normative and based on laboratory tests and practical experiences. The information is noncommittal, and we cannot accept liability for the results obtained under working conditions beyond our control, and consequently the buyer or the user is not released from the obligation to test the suitability of our products for specific means and application methods under the actual application conditions. Our liability covers only damage caused directly by defects in the products supplied by Teknos. This product is intended for professional use only. This implies that the user possesses sufficient knowledge for using the product correctly with regard to technical and working safety aspects. The latest versions of Teknos' Technical Data Sheets and Safety Data Sheets are available from our homepage www.teknos.com. All trademarks displayed on this document are the exclusive property of Teknos Group or its affiliated companies.