

GLANZÖL 1410-80

Solvent-based, high-quality preservative oil for wood substrates for interior use



GLANZÖL 1410 is a low-viscosity, glossy preservative oil based on natural raw materials. The products have a good mechanical strength.

Parquet floors: For treating the surfaces of wooden floors, stairs and cork floors.

Carpenter application: For surface treatment of wooden doors, tables, chairs and stairs.



TECHNICAL DATA

Certificates, approvals and classification	Swiss environmental label UE II, class F
Fields of application	Furniture, Floors
Solids	Approx. 53% by weight
Theoretical spreading rate	75 g/m ² ; 13.3 m ² /kg
Colours	Colourless.
Gloss (60°)	80
Thinner	TERPENTINERSATZ 4214-98
Density	Approx. 0.9 g/ml
Storage	Storage temperature is +5°C - +30°C. Store in a tightly closed container.

DIRECTION FOR USE

Surface preparation	Every substrate must be well-cleaned, dry and free from grease and oil. Coating removal: Sand
Application method	Cloth, Smooth roller Hazard warning: Pads and cloths soaked in oil can spontaneously combust under certain conditions and should therefore be kept in a metal bin with a lid until they are disposed of correctly.

Application	Stir or shake the product well for several minutes before use, if necessary by machine.		
	APPLICATION ADVICE		
	Wood substrate raw - Parquet		
		Product	Applied Quantity
	Primer	GLANZÖL 1410	depending on the type of wood 60-70 g/m ²
		Apply lengthwise and across the fibre, allow to soak in only briefly and massage in with beige pad when wet.	
	Recoating	GLANZÖL 1410	depending on the type of wood 30-40 g/m ²
		Apply lengthwise and across the fibre, allow to soak in only briefly and massage in with beige pad when wet.	
	Wood substrate raw - Carpentry application		
		Product	Applied Quantity
Primer	GLANZÖL 1410	75 g/m ²	
	Apply lengthwise and across the fibre, allow to soak in only briefly and massage in with beige pad when wet.		
Intermediate sanding	Carefully sand with 280-320 lacquer sandpaper or a beige pad		
Recoating	GLANZÖL 1410	40 g/m ²	
	Apply lengthwise and across the fibre, allow to soak in only briefly and massage in with beige pad when wet.		
	For further application proposals please ask our representative.		

Application conditions Recommended temperature for surroundings and product: +15°C-25°C. Do not apply below +10°C. Ideal surface and object temperature for application: +18°C-22°C. Avoid application in direct sunlight. Underfloor heating systems must be adjusted well in advance.

Drying time	+23°C / 65% RH
- dust free	after 2-3 hours
- overcoatable	after 8-10 hours
- through dry	after 7 days

Cleaning Wash the equipment immediately after use. TERPENTINERSATZ 4214-98

HEALTH AND SAFETY

Safety and precaution measures	See safety data sheet.
First aid	We recommend wearing personal protective clothing even in cases where no local regulations are in force. CH: The precautions according to local regulations (SUVA) with respect to hygiene and equipment must be observed.

ADDITIONAL INFORMATION

Maintenance instructions

Parquet floors:

Maintenance: After at least 3 weeks curing time with RENSA WOOD OIL POLISH 4584-00. Re-impregnate with RENSA WOOD CARE OIL 1413.

Carpenter application:

Maintenance: After a minimum period of 3 weeks by wiping surfaces with a damp cloth (not wet). As required, e.g. weekly, add approx. 1% RENSA WOOD OIL POLISH 4584-00 to the cleaning water (2 caps to 1l of water). Cleans and nourishes the oiled surface. Re-impregnate with RENSA WOOD CARE OIL 1413.

For further information on products for treating the surfaces of wooden floors and their use please visit www.parkett-verband.ch

Teknos Group Oy Takkatie 3, P.O.Box 107 FI-00371 Helsinki, Finland Tel. +358 9 506 091

The above information is normative and based on laboratory tests and practical experiences. The information is noncommittal, and we cannot accept liability for the results obtained under working conditions beyond our control, and consequently the buyer or the user is not released from the obligation to test the suitability of our products for specific means and application methods under the actual application conditions. Our liability covers only damage caused directly by defects in the products supplied by Teknos. This product is intended for professional use only. This implies that the user possesses sufficient knowledge for using the product correctly with regard to technical and working safety aspects. The latest versions of Teknos' Technical Data Sheets and Safety Data Sheets are available from our homepage www.teknos.com. All trademarks displayed on this document are the exclusive property of Teknos Group or its affiliated companies.