

# HARTÖL 1394-50

Solvent-based, oxidatively drying oil for the industrial surface treatment of wood substrates for interior use



HARTÖL 1394 is a low-viscosity, oxidatively drying oil for industrial surface treatment of parquet floors with roller application.



## TECHNICAL DATA

|                              |   |
|------------------------------|---|
| <b>Fields of application</b> | Furniture, Floors   |
| <b>Solids</b>                | Approx. 47% by weight   |
| <b>Colours</b>               | Colourless.   |
| <b>Gloss (60°)</b>           | 50  |
| <b>Density</b>               | Approx. 0.88 g/ml   |
| <b>Storage</b>               | Storage temperature is +5°C - +30°C. Store in a tightly closed container. |

## DIRECTION FOR USE

|                               |  |
|-------------------------------|--|
| <b>Surface preparation</b>    | Every substrate must be well-cleaned, dry and free from grease and oil. Coating removal: Sand  |
| <b>Application method</b>     | Cloth, Smooth roller<br>Hazard warning:<br>Pads and cloths soaked in oil can spontaneously combust under certain conditions and should therefore be kept in a metal bin with a lid until they are disposed of correctly. |
| <b>Application</b>            | Stir or shake the product well for several minutes before use, if necessary by machine.  |
| <b>Application conditions</b> | Recommended temperature for surroundings and product: +15°C-25°C. Do not apply below +10°C.  |
| <b>Drying time</b>            | At 30°C and 65% rel. humidity.   |
| - dust free                   | after 10 minutes   |
| - overcoatable                | after 10 minutes   |
| - fit for sanding             | after 10 minutes   |
| - through dry                 | after 7 days   |
| <b>Cleaning</b>               | Wash the equipment immediately after use. TERPENTINERSATZ 4214-98  |

## HEALTH AND SAFETY

|                                       |                        |
|---------------------------------------|------------------------|
| <b>Safety and precaution measures</b> | See safety data sheet. |
|---------------------------------------|------------------------|

**First aid**

We recommend wearing personal protective clothing even in cases where no local regulations are in force.

CH: The precautions according to local regulations (SUVA) with respect to hygiene and equipment must be observed.

**ADDITIONAL INFORMATION****Maintenance instructions**

Parquet floors:

Maintenance: After at least 3 weeks curing time with RENSA WOOD OIL POLISH 4584-00. Re-impregnate with RENSA WOOD CARE OIL 1413.

Carpenter application:

Maintenance: After a minimum period of 3 weeks by wiping surfaces with a damp cloth (not wet). As required, e.g. weekly, add approx. 1% RENSA WOOD OIL POLISH 4584-00 to the cleaning water (2 caps to 1l of water). Cleans and nourishes the oiled surface. Re-impregnate with RENSA WOOD CARE OIL 1413.

For further information on products for treating the surfaces of wooden floors and their use please visit [www.parkett-verband.ch](http://www.parkett-verband.ch)

**Teknos Group Oy Takkatie 3, P.O.Box 107 FI-00371 Helsinki, Finland Tel. +358 9 506 091**

The above information is normative and based on laboratory tests and practical experiences. The information is noncommittal, and we cannot accept liability for the results obtained under working conditions beyond our control, and consequently the buyer or the user is not released from the obligation to test the suitability of our products for specific means and application methods under the actual application conditions. Our liability covers only damage caused directly by defects in the products supplied by Teknos. This product is intended for professional use only. This implies that the user possesses sufficient knowledge for using the product correctly with regard to technical and working safety aspects. The latest versions of Teknos' Technical Data Sheets and Safety Data Sheets are available from our homepage [www.teknos.com](http://www.teknos.com). All trademarks displayed on this document are the exclusive property of Teknos Group or its affiliated companies.