

HARTÖL 6448-15

Solvent-based, oxidatively drying oil for the industrial surface treatment of wood substrates for interior use

HARTÖL 6448-15 is a fast drying, high solid oil based on natural raw materials for the industrial surface treatment of parquet floors.



TECHNICAL DATA

Solids	Approx. 93% by weight
Colours	Colourless.
Gloss (60°)	15
Density	Approx. 0.93 g/ml
Storage	Storage temperature is +5°C - +30°C. Store in a tightly closed container.

DIRECTION FOR USE

Surface preparation	Every substrate must be well-cleaned, dry and free from grease and oil. Coating removal: Sand
Application method	Hazard warning: Pads and cloths soaked in oil can spontaneously combust under certain conditions and should therefore be kept in a metal bin with a lid until they are disposed of correctly.
Application	Stir or shake the product well for several minutes before use, if necessary by machine.
Application conditions	Recommended temperature for surroundings and product: +15°C-25°C. Do not apply below +10°C.
Drying time	At 40-50°C and a relative humidity of 65%.
- overcoatable	after 4 hours
- fit for sanding	after 4 hours
Cleaning	Wash the equipment immediately after use. TERPENTINERSATZ 4214-98

HEALTH AND SAFETY

Safety and precaution measures	See safety data sheet.
First aid	We recommend wearing personal protective clothing even in cases where no local regulations are in force. CH: The precautions according to local regulations (SUVA) with respect to hygiene and equipment must be observed.

ADDITIONAL INFORMATION

Maintenance instructions

Parquet floors:

Maintenance: After at least 3 weeks curing time with RENSA WOOD OIL POLISH 4584-00. Re-impregnate with RENSA WOOD CARE OIL 1413.

Carpenter application:

Maintenance: After a minimum period of 3 weeks by wiping surfaces with a damp cloth (not wet). As required, e.g. weekly, add approx. 1% RENSA WOOD OIL POLISH 4584-00 to the cleaning water (2 caps to 1l of water). Cleans and nourishes the oiled surface. Re-impregnate with RENSA WOOD CARE OIL 1413.

For more information on wood floor surface treatments and their use, visit www.parkett-verband.ch.

Teknos Group Oy Takkatie 3, P.O.Box 107 FI-00371 Helsinki, Finland Tel. +358 9 506 091

The above information is normative and based on laboratory tests and practical experiences. The information is noncommittal, and we cannot accept liability for the results obtained under working conditions beyond our control, and consequently the buyer or the user is not released from the obligation to test the suitability of our products for specific means and application methods under the actual application conditions. Our liability covers only damage caused directly by defects in the products supplied by Teknos. This product is intended for professional use only. This implies that the user possesses sufficient knowledge for using the product correctly with regard to technical and working safety aspects. The latest versions of Teknos' Technical Data Sheets and Safety Data Sheets are available from our homepage www.teknos.com. All trademarks displayed on this document are the exclusive property of Teknos Group or its affiliated companies.