

NATURÖL FINISH 1391-05

Solvent-based, oxidatively drying oil for the surface treatment of wood substrates for interior use

NATURÖL FINISH 1391 is a low-viscosity oxidative drying oil for surface treatment of parquet floors, stairs and furniture.



TECHNICAL DATA

Fields of application	Furniture, Floors
Binder	Polyurethane
Solids	Approx. 48% by weight
Volatile organic compound (VOC)	Approx. 453 g/l (DIRECTIVE 2010/75/EU) The VOC value provided is the average value for factory produced products, and consequently it will be subject to variations between individual products covered by this Technical Data Sheet.
Colours	Colourless.
Tinting system	Largo
Gloss (60°)	5
Density	Approx. 0.9 g/ml
Storage	Storage temperature is +5°C - +30°C. Store in a tightly closed container.

DIRECTION FOR USE

Surface preparation	Every substrate must be well-cleaned, dry and free from grease and oil.
----------------------------	---

Application

Stir or shake the product well for several minutes before use, if necessary by machine.

APPLICATION ADVICE		
Manual Application		
	Product	Applied Quantity
Impregnation	NATURÖL-FINISH 1391	ca. 60 g/m ²
	Uniformly spread a thin coat with a brush, sponge or applicator and rub in with a beige (tan) pad.	
Drying	Overnight	
Repeat treatment	NATURÖL-FINISH 1391	ca. 50 g/m ²
Machine Application		
	Product	Applied Quantity
Primer	NATURÖL-FINISH 1391	1-2x 12-15 g/m ²
	Rolling Steamrolling	
	Ejector brush	
Drying	Circulating air dryer 40-50°C Drying before packing: 5 min at room temperature To speed up drying, additional UV lamps (extra heat) can be used.	
Care		
	Product	Applied Quantity
Care	RENSA WOOD CARE OIL 1413	
For further application proposals please ask our representative.		

Application conditions

Recommended temperature for surroundings and product: +15°C-25°C. Do not apply below +10°C.

Drying time

+23°C / 50% RH (dry film 20 µm)

Cleaning

Wash the equipment immediately after use. ACETON 8000-98, OWECCELL D 1500-98, TERPENTINERSATZ 4214-98.

HEALTH AND SAFETY

Safety and precaution measures

See safety data sheet.

First aid

We recommend wearing personal protective clothing even in cases where no local regulations are in force.

CH: The precautions according to local regulations (SUVA) with respect to hygiene and equipment must be observed.

Teknos Group Oy Takkatie 3, P.O.Box 107 FI-00371 Helsinki, Finland Tel. +358 9 506 091

The above information is normative and based on laboratory tests and practical experiences. The information is noncommittal, and we cannot accept liability for the results obtained under working conditions beyond our control, and consequently the buyer or the user is not released from the obligation to test the suitability of our products for specific means and application methods under the actual application conditions. Our liability covers only damage caused directly by defects in the products supplied by Teknos. This product is intended for professional use only. This implies that the user possesses sufficient knowledge for using the product correctly with regard to technical and working safety aspects. The latest versions of Teknos' Technical Data Sheets and Safety Data Sheets are available from our homepage www.teknos.com. All trademarks displayed on this document are the exclusive property of Teknos Group or its affiliated companies.