

# PREMIUM TEAK OIL 6151-00

Impregnating wood oil for the care and preservation of tropical woods

PREMIUM TEAK OIL 6151-00 is a high-quality, preservative wood oil for the care and maintenance of all tropical wood species such as teak, bangkirai, massaranduba, ipé and mahogany. The coating is suitable for terrace decking, planking, tables, chairs, boat decking etc., for exterior applications. PREMIUM TEAK OIL 6151-00 enhances the intensity of the wood colour and has high penetrating properties



## TECHNICAL DATA

<b>Fields of application</b>	Exterior doors, Decking
<b>Solids</b>	Approx. 27% by weight
<b>Volatile organic compound (VOC)</b>	Approx. 628 g/l (DIRECTIVE 2010/75/EU) The VOC value provided is the average value for factory produced products, and consequently it will be subject to variations between individual products covered by this Technical Data Sheet.
<b>Theoretical spreading rate</b>	75 g/m <sup>2</sup> ; 13.3 m <sup>2</sup> /kg
<b>Colours</b>	Colourless.
<b>Density</b>	Approx. 0.85 g/ml
<b>Storage</b>	Storage temperature is +5°C - +30°C. Store in a tightly closed container.

## DIRECTION FOR USE

<b>Surface preparation</b>	Every substrate must be well-cleaned, dry and free from grease and oil. Coating removal: Sand
----------------------------	---

**Application method**

Cloth, Smooth roller

Apply generously with a clean cloth 1 to 2 times at a 15 minute interval, leave to soak in and wipe off any excess oil while still wet.

When used on domestic coniferous woods such as fir, spruce or larch, previous application of TEKNOL 6005 to prevent blue staining is necessary or recommended. (For outdoor use only!)

Hazard warning:

Pads and cloths soaked in oil can spontaneously combust under certain conditions and should therefore be kept in a metal bin with a lid until they are disposed of correctly.

Do not permit the product to come into contact with the soil, groundwater, rivers or lakes.

**Application**

Stir or shake the product well for several minutes before use, if necessary by machine.

APPLICATION ADVICE		
Wood substrate raw		
	Product	Applied Quantity
Impregnation	PREMIUM TEAK OIL 6151	1-3x 75 g/m <sup>2</sup>
	1-3 times at intervals of 15 minutes, rub in generously	
For further application proposals please ask our representative.		

**Application conditions**

Recommended temperature for surroundings and product: +15°C-25°C. Do not apply below +10°C.

**Drying time**

+23°C / 65% RH

**- dust free**

after 2 hours

**- overcoatable**

after 8 hours

**- fit for sanding**

after 8 hours

**- through dry**

after 7 days

**Cleaning**

Wash the equipment immediately after use. TERPENTINERSATZ 4214-98

**HEALTH AND SAFETY****Safety and precaution measures**

See safety data sheet.

**First aid**

We recommend wearing personal protective clothing even in cases where no local regulations are in force.

CH: The precautions according to local regulations (SUVA) with respect to hygiene and equipment must be observed.

## ADDITIONAL INFORMATION

### Maintenance instructions

Depending on the exposure to the weather, we recommend regular maintenance with PREMIUM TEAK OIL 6151-00. Apply 1 to 4 times annually.

Clear, non-pigmented products do not have any active UV protection.

For more information on wood floor surface treatments and their use, visit [www.parkett-verband.ch](http://www.parkett-verband.ch).

**Teknos Group Oy Takkatie 3, P.O.Box 107 FI-00371 Helsinki, Finland Tel. +358 9 506 091**

The above information is normative and based on laboratory tests and practical experiences. The information is noncommittal, and we cannot accept liability for the results obtained under working conditions beyond our control, and consequently the buyer or the user is not released from the obligation to test the suitability of our products for specific means and application methods under the actual application conditions. Our liability covers only damage caused directly by defects in the products supplied by Teknos. This product is intended for professional use only. This implies that the user possesses sufficient knowledge for using the product correctly with regard to technical and working safety aspects. The latest versions of Teknos' Technical Data Sheets and Safety Data Sheets are available from our homepage [www.teknos.com](http://www.teknos.com). All trademarks displayed on this document are the exclusive property of Teknos Group or its affiliated companies.