

RENSA WOOD OIL POLISH 4584-00

Gentle, concentrated maintenance cleaner

RENSA WOOD OIL POLISH 4584 is a gentle, concentrated maintenance cleaner with natural jojoba oil conditioner for the care and maintenance of all oiled wood, cork, linoleum and parquet floors. The product is suitable for light and dark woods. Slightly enhances the natural grain of the floor and can intensify its colour.

pH value: approx. 6.5 (concentrate)

Information on contained substances (according to EU recommendations):

5-15 % anionic surfactants, below 5 % non-ionic surfactants (biologically degradable). Additional ingredients: Jojoba oil.



TECHNICAL DATA

Fields of application	Furniture, Floors
Solids	Approx. 94% by weight
Volatile organic compound (VOC)	Approx. 5 g/l (DIRECTIVE 2010/75/EU) The VOC value provided is the average value for factory produced products, and consequently it will be subject to variations between individual products covered by this Technical Data Sheet.
Colours	Colourless. White. Black. Can be adjusted individually for customers by agreement.
Tinting system	Largo
Density	Approx. 1 g/ml
Storage	Storage temperature is +5°C - +30°C. Store in a tightly closed container. Store in a cool, dry place, locked away and out of the reach of children (with safety lock).

DIRECTION FOR USE

Surface preparation	Every substrate must be well-cleaned, dry and free from grease and oil.
----------------------------	---

Application method

Cloth, Smooth roller

The product can slightly accentuate the natural grain of the floor and can intensify its colour.

Spot test at an inconspicuous place as a precaution.

Hazard warning:

Pads and cloths soaked in oil can spontaneously combust under certain circumstances and should therefore be kept in a metal bin with a lid until they are disposed of.

Application

Stir or shake the product well for several minutes before use, if necessary by machine.

APPLICATION ADVICE		
Oxidatively oiled wood, cork and linoleum floors		
	Product	Applied Quantity
Care	RENSA WOOD OIL POLISH 4584 (1% in mop water)	25 g/m ²
For further application proposals please ask our representative.		

Application conditions

Recommended temperature for surroundings and product: +15°C-25°C. Do not apply below +10°C. Ideal surface and object temperature for application: +18°C-22°C. Avoid application in direct sunlight. Underfloor heating systems must be adjusted well in advance.

Drying time

+23°C / 50% RH (dry film 20 µm)

- dust free

after 30 minutes

- through dry

after 30 minutes

Can be walked on after: 30 minutes

Cleaning

Wash the equipment immediately after use. Water.

HEALTH AND SAFETY

Safety and precaution measures

See safety data sheet.

First aid

We recommend wearing personal protective clothing even in cases where no local regulations are in force.

CH: The precautions according to local regulations (SUVA) with respect to hygiene and equipment must be observed.

ADDITIONAL INFORMATION

Maintenance instructions

Add 1 part (1%) to 5 l of cleaning water. Wipe the cleaned floor with a damp, lint-free mop. Leave to dry for at least 30 minutes. Wait for at least three weeks before treating newly oiled floors. In the event of heavy soiling, touch up locally with a cloth moistened with RENSA WOOD OIL POLISH 4584-00. Wipe off with water.

Refreshing older floors: Clean the floor thoroughly with RENSA PRO CLEAN 4582-00 (diluted 1:1 with water) and immediately wipe up the dissolved dirt with a damp cloth. After drying, re-oil with preservative oil, RENSA WOOD CARE OIL 1413.

Also refer to our brochure "Perfect parquet floor care".

For further information on products for treating the surfaces of wooden floors and their use please visit www.parkett-verband.ch.

Teknos Group Oy Takkatie 3, P.O.Box 107 FI-00371 Helsinki, Finland Tel. +358 9 506 091

The above information is normative and based on laboratory tests and practical experiences. The information is noncommittal, and we cannot accept liability for the results obtained under working conditions beyond our control, and consequently the buyer or the user is not released from the obligation to test the suitability of our products for specific means and application methods under the actual application conditions. Our liability covers only damage caused directly by defects in the products supplied by Teknos. This product is intended for professional use only. This implies that the user possesses sufficient knowledge for using the product correctly with regard to technical and working safety aspects. The latest versions of Teknos' Technical Data Sheets and Safety Data Sheets are available from our homepage www.teknos.com. All trademarks displayed on this document are the exclusive property of Teknos Group or its affiliated companies.