

SPRITZSPACHTEL 0841-00

Solvent-based 1C spray filler for interior use

SPRITZSPACHTEL 0841-00 is a solvent-based 1C spray filler with good filling properties and sandability. The coating is ideal for wetrooms due to its isolating effect.



TECHNICAL DATA

Fields of application	Furniture, Fixed furniture, Interior doors
Binder	Alkyd
Solids	Approx. 51% by weight
Theoretical spreading rate	175 g/m ² ; 5.7 m ² /kg
Colours	White.
Thinner	VERDÜNNER 1000-98
Density	Approx. 1.25 g/ml
Storage	Storage temperature is +5°C - +30°C. Store in a tightly closed container.

DIRECTION FOR USE

Surface preparation	Every substrate must be well-cleaned, dry and free from grease and oil. Coating removal: Sand, strip
Application method	Conventional spraying, Airless spraying, Air-assisted airless spraying

APPLICATION ADVICE					
Wood substrate					
	Product		Applied Quantity		
Presanding	SPRITZSPACHTEL 841SP		150-200 g/m ²		
Primer	With grain 180-220				
Intermediate sanding	SPRITZSPACHTEL 841SP		150-200 g/m ²		
Recoating	Colour lacquer of your choice				
MDF/HDF raw					
	Product		Applied Quantity		
Primer	SPRITZSPACHTEL 841SP		150-180 g/m ²		
Intermediate sanding	With grain 180-240				
Primer	SPRITZSPACHTEL 841SP		150-200 g/m ²		
Recoating	Colour lacquer of your choice				
For further application proposals please ask our representative.					
APPLICATION					
	Viscosity DIN 4 mm	Dilution	Nozzle in mm	Pressure in bar	Spray Cycles
Gravity Feed Gun	25-30"	10-15%	1.8-2.5	3-4	1-2
Suction Cup Gun	25-30"	10-15%	1.8-2.5	3-4	1-2
Airless / Airmix Spray Application	30-40"	5-10%	0.28-0.33		1-2
HVLP-Pistol	25-30"	15%	1.8-2.5	3-4	1-2

Application conditions Recommended temperature for surroundings and product: +15°C-25°C. Do not apply below +10°C.

Drying time	+23°C / 65% RH
- dust free	after 60 minutes
- touch dry	after 50 minutes
- overcoatable	after 8 hours
- fit for sanding	after 5-6 hours
- through dry	after 10 hours

Cleaning Wash the equipment immediately after use. VERDÜNNER 1000-98

HEALTH AND SAFETY

Safety and precaution measures See safety data sheet.

First aid We recommend wearing personal protective clothing even in cases where no local regulations are in force.
CH: The precautions according to local regulations (SUVA) with respect to hygiene and equipment must be observed.

Teknos Group Oy Takkatie 3, P.O.Box 107 FI-00371 Helsinki, Finland Tel. +358 9 506 091

The above information is normative and based on laboratory tests and practical experiences. The information is noncommittal, and we cannot accept liability for the results obtained under working conditions beyond our control, and consequently the buyer or the user is not released from the obligation to test the suitability of our products for specific means and application methods under the actual application conditions. Our liability covers only damage caused directly by defects in the products supplied by Teknos. This product is intended for professional use only. This implies that the user possesses sufficient knowledge for using the product correctly with regard to technical and working safety aspects. The latest versions of Teknos' Technical Data Sheets and Safety Data Sheets are available from our homepage www.teknos.com. All trademarks displayed on this document are the exclusive property of Teknos Group or its affiliated companies.