

# TEKNOSPRO STOP

## Stain-blocking primer

Powerful coverage for tough stains such as grease, ink, nicotine, soot and water damage. This hard-working primer has impressive hiding power and can be used on previously painted filler, concrete, building board, brick, plaster, wood and metal. It is easy to apply and dries fast, which means it can be overcoated on the same day.



TEKNOSPRO STOP comes in white with a full-matt finish for priming and blocking stains on all surfaces, it can also be used as a stain-blocking topcoat on ceilings. May also be used for blocking wallpapered surfaces before overcoating.



## TECHNICAL DATA

<b>Certificates, approvals and classification</b>	M1 classification, Finnish Key Flag
<b>Fields of application</b>	Ceilings, Indoor wall
<b>Recommended substrate</b>	Building board, Clay brick, Concrete, Filler, Metal, Plaster, Wood
<b>Solids</b>	Approx. 50% by volume
<b>Volatile organic compound (VOC)</b>	1 g/l. EU VOC limit value (kat A/g): 30 g/l. The VOC value provided is the average value for factory produced products, and consequently it will be subject to variations between individual products covered by this TDS.
<b>Practical spreading rate</b>	7 - 10 m <sup>2</sup> /l.
<b>Colours</b>	White.
<b>Gloss (60°)</b>	Full-matt
<b>Thinner</b>	Water.
<b>Density</b>	Approx. 1.45 g/ml
<b>Storage</b>	Must not freeze.
<b>Packaging</b>	1 l, 3 l, 10 l, 20 l. Availability varies by country.

## DIRECTION FOR USE

<b>Surface preparation</b>	<p>Clean the surface from dirt and dust as well as possible. Wash water-resistant dirty surfaces with RENSA SUPER paint cleaner. Remove loose and poorly adhered coats of old paint. Matt down hard or gloss surfaces by sanding and thereafter remove the dust. For smoothing of irregularities in the surface choose a suitable filler from the SILORA series. The dried filler is sanded down and the dust removed.</p> <p>TEKNOSPRO STOP is a water-borne paint. Coatings, which are not waterproof, such as old unpainted ceiling filler or glue paint coats, must be removed before applying TEKNOSPRO STOP.</p>
<b>Application method</b>	Brush, Roller, Spray
<b>Application</b>	<p>Stir thoroughly before use. Suitable airless nozzle size 0.017 - 0.021". Apply once. In the rare occasion that the stain is still visible in the first coat, paint a second coat after 4 hours. Top coating with a separate top coat after 4 hours.</p> <p>Please note, that it is important during larger projects or longer pauses in the painting work to stir the paint every once in a while or close the lid of the can. Otherwise there is a risk of a minor film formation on the surface of the paint due to the fast drying time of the paint.</p>
<b>Application conditions</b>	<p>The surface to be treated must be dry. During the application and drying period the temperature of the ambient air, the surface and the product shall be above +5°C and the relative air humidity below 80%. Drying is faster in low air humidity and/or above + 21°C. Application will be easier if air is humidified and/or temperature is lowered in the working space. Ventilation after the painting will quicken the drying.</p>
<b>Thinning</b>	The paint can be diluted with water, if required, but dilution may impair the insulation capability and the coverage of the paint.
<b>Drying time</b>	+23°C / 50% RH
<b>- dust free</b>	1 h
<b>- overcoatable</b>	4 h
	The drying process will be slower in cold and/or damp.
<b>Top coating and suitable top coats</b>	Surfaces insulation primed with TEKNOSPRO STOP can be top coated with all Teknos interior paints which otherwise suit the object in question.
<b>Resistance</b>	Wet scrub resistance, class 1 according to EN 13300 (ISO 11998).
<b>Cleaning</b>	Warm water and RENSA BRUSH brush cleaner. Wash the equipment immediately after use.

## HEALTH AND SAFETY

**Safety and precaution measures** See safety data sheet.

**Teknos Group Oy Takkatie 3, P.O.Box 107 FI-00371 Helsinki, Finland Tel. +358 9 506 091**

The above information is normative and based on laboratory tests and practical experiences. The information is noncommittal, and we cannot accept liability for the results obtained under working conditions beyond our control, and consequently the buyer or the user is not released from the obligation to test the suitability of our products for specific means and application methods under the actual application conditions. Our liability covers only damage caused directly by defects in the products supplied by Teknos. This product is intended for professional use only. This implies that the user possesses sufficient knowledge for using the product correctly with regard to technical and working safety aspects. The latest versions of Teknos' Technical Data Sheets and Safety Data Sheets are available from our homepage [www.teknos.com](http://www.teknos.com). All trademarks displayed on this document are the exclusive property of Teknos Group or its affiliated companies.