

HYDROPUR MERO 2595

Water-based 2C PUR Coating

NATURAL WOOD

This water-soluble coating offers a luxurious, naturally matt surface. The coated surface gives an untreated look and has excellent scratch resistance. The combination of possibilities using HYDROPUR MERO 2595 with other coatings offers unlimited scope for creativity.

SUITABLE FOR ALL TYPES OF WOOD

The product can be used on all types of wood, including: interior (e.g. wall coverings); decorative models; furniture; kitchen equipment and store fittings. In addition, HYDROPUR MERO 2595 contains UV protection, so that the natural yellowing effect of wood is actively reduced.

CONTACT US

Calling Teknos is a quick and easy way to get expert advice on the use of HYDROPUR MERO 2595 or other Teknos coating products. Our technical customer service is always ready to help when it comes to developing optimum coating solutions and systems.



MAIN FEATURES

- Natural wood effect
- Anti-fingerprint properties
- Easy-to-use
- · High scratch resistance
- · High UV resistance
- · Low emissions





PRODUCT DATA

GLOSS LEVEL • Dull matt 02

APPLICATION • Gravity feed gun

• Airless (airmix) spraying

CONTAINER SIZE • Paint: 1 kg, 5 kg, 10 kg

• Hardener: 0.5 l, 1 l

MIXING RATIO • 10:1

DRYING TIMES

DUST DRY AFTER 30 minutes

TOUCH DRY AFTER 2 hours

SANDABLE AFTER 4 hours

FULLY DRY AFTER 3 days

COATING RECOMMENDATION / INTERIORS

	NATURAL WOOD LOOK	ACCENTUATES THE GRAIN OF UNTREATED WOOD	LIGHTENS UNTREATED WOOD
PRE-SANDING	Grain 150-180	Grain 150-180	Grain 150-180
PRIMER	HYDROPUR MERO 2595	MOTIVO KLARLACK 2080	MOTIVO CHIARO 2083
OR		MOTIVO KLARLACK 2080	
INTERMEDIATE SANDING	Grain 280-320	Grain 220-280	Grain 220-280
RECOATING	HYDROPUR MERO 2595	HYDROPUR MERO 2595	HYDROPUR MERO 2595

For further technical information refer to data sheet no. 2595

TEKNOS GBI
7 LONGLANDS RD
BICESTER
OXON 0X26 5AH
T 01869 208005

TEKNOS IRELAND 54 BALLYMOUGHAN RD MAGHERAFELT BT45 6HN T 02879 301472

teknos.co.uk sales@teknos.co.uk

